

Package ‘gggroups’

September 2, 2018

Type Package

Title Genetic group contributions

Version 0.1.1

Author Mohammad Ali Nilforooshan

Maintainer Mohammad Ali Nilforooshan <m.a.nilforooshan@gmail.com>

Description Genetic group contributions to individuals in a pedigree.

License GPL (>= 2)

URL <https://github.com/nilforooshan/gggroups>

Encoding UTF-8

LazyData true

Imports pedigreemm

RoxygenNote 6.1.0

Repository GitHub

Installation devtools::install_github('nilforooshan/gggroups')

R topics documented:

gggroups-package	2
gghead	2
Qgpu	3
qmat	4
sampleped	4
samplesol	5
Index	6

gggroups-package

Genetic Group Contribution

Description

This package contains functions related to calculating the matrix of genetic group contributions to individuals in a pedigree, and adding genetic group contributions to genetic merit of animals in a pedigree.

Details

The concept of genetic groups or phantom parent groups is based on the fact that unknown parents do not belong to the same base population and they might come from different genetic levels. With \mathbf{Q} , $\hat{\mathbf{g}}$, and $\hat{\mathbf{u}}$ being the matrix of genetic group contributions to individuals in the pedigree, the vector of predicted additive genetic merit of animals, and the vector of predicted genetic group effects, respectively, the contribution of genetic groups should be added to the predicted genetic merit of animals ($\mathbf{Q}\hat{\mathbf{g}} + \hat{\mathbf{u}}$).

Forming Mixed Model Equations corresponding to the model, $\hat{\mathbf{u}}$ and $\hat{\mathbf{g}}$ are predicted (Quaas, 1988: Eq. [3]). However, using Quaas and Pollak (1981) transformation, $\mathbf{Q}\hat{\mathbf{g}} + \hat{\mathbf{u}}$ can be obtained directly (Quaas, 1988: Eq. [4]).

Some solver packages obtain $\mathbf{Q}\hat{\mathbf{g}} + \hat{\mathbf{u}}$ directly, some not. The aim of this package is to find the genetic contribution of each genetic group on each individual in the pedigree (matrix \mathbf{Q}), and also calculating $\mathbf{Q}\hat{\mathbf{g}} + \hat{\mathbf{u}}$, given the pedigree and a vector of $[\hat{\mathbf{g}}, \hat{\mathbf{u}}]$.

Author(s)

Mohammad Ali Nilforooshan <m.a.nilforooshan@gmail.com>

References

- Quaas, R. L. 1988. Additive Genetic Model with Groups and Relationships. J. Dairy Sci., 71:1338-1345.
- Quaas, R. L., and E. J. Pollak. 1981. Modified equations for sire models with groups. J. Dairy Sci., 64:1868-1872.

gghead

Pedigree processing

Description

Does specific pedigree checks; adds genetic groups to the head of the pedigree and sorts it.

Usage

```
gghead(ped)
```

Arguments

ped : A data.frame with 3 integer columns corresponding to ID, SIRE, DAM

Details

Consider this simple pedigree:

3 0 0
4 3 0
6 4 5
5 0 0

First, unknown parents are replaced with the corresponding genetic groups.

Please note that unknown parent IDs should be smaller than animal IDs.

3 1 2
4 3 2
6 4 5
5 1 2

This pedigree is provided as a sample data (sampleped) by the package, with columns corresponding to ID, SIRE, DAM.

Value

ped2 : A processed pedigree data.frame

Examples

gghead(sampleped)

Qgpu	$Qg + u$
------	----------

Description

Add genetic group contributions to genetic merit of animals in a pedigree.

Usage

Qgpu(Qmat, sol)

Arguments

Qmat : The output matrix from qmat; for more details: ?qmat
sol : A data.frame with 2 numeric columns corresponding to ID, EBV (\hat{g}, \hat{u}).
A sample data for solutions is provided (samplesol) by the package, with columns corresponding to ID, EBV (\hat{g}, \hat{u}).

Value

uhatplus : Vector of $Q\hat{g} + \hat{u}$

Examples

```
Qgpu(qmat(gghead(sampleped)), samplesol)
```

qmat	Create matrix Q
------	------------------------

Description

Creates the genetic group contribution matrix.

Usage

```
qmat(ped2)
```

Arguments

ped2 : The output of gghead; for more details: ?gghead

Value

Qmat : Matrix **Q**

Examples

```
qmat(gghead(sampleped))
```

sampleped	Sample pedigree data
-----------	----------------------

Description

Sample data for ped

Usage

```
sampleped
```

Format

An object of class data.frame with 4 rows and 3 columns.

samplesol	<i>Sample solution data</i>
-----------	-----------------------------

Description

Sample data for sol

Usage

samplesol

Format

An object of class `data.frame` with 6 rows and 2 columns.

Index

*Topic **datasets**

sampleped, [4](#)

samplesol, [5](#)

gghead, [2](#)

gggroups-package, [2](#)

Qgpu, [3](#)

qmat, [4](#)

sampleped, [4](#)

samplesol, [5](#)