

Topic 03:

2


Stereo triangulation

4

if we know the camera centers & corresponding pixels (in homogeneous coordinates) we can compute the homogeneous coordinates of \hat{P}

Two-View Geometry

- epipolar lines & epipolar planes
- the fundamental matrix (F-matrix)
- geometric interpretation of the F-matrix
- the essential matrix
- fundamental matrix estimation:
the normalized 8-point algorithm
- algorithms & applications of stereo reconstruction
- image homographies
- stereo image rectification



The stereo correspondence problem: Given x_1 , find x_2

a stereo image pair

3

Piazza : Please enroll

(or monitor it)

Office hours this week:

12:30 - 2pm tomorrow



Left

Right

(Prince, 2011)



Left

Right

(Prince, 2011)

two-view geometry



Goal: Explore basic geometry of multiple images to support the inference of 3D scene structure from two or more images of the scene.

Consider two perspective images of a scene as taken from a stereo pair of cameras (or equivalently, assume the scene is rigid and imaged with a single camera from two different locations).

- Given a scene point \vec{X}^p which is imaged in the “left” camera at \vec{p}^L , where could the image of the same point be in the right camera?
- The relationship between such *corresponding image points* turns out to be both simple and useful; i.e., the corresponding point in the “right” camera, \vec{p}^R , is constrained to lie on a line.

The Epipolar Constraint

(Prince, 2011)





\Rightarrow correspondence-finding between two (rand) views is a 1D problem
 \Rightarrow if allows us to infer relative camera motion

the epipolar constraint

The Epipolar Constraint

(Prince, 2011)




For every pair of perspective photos, there exists a line-to-line mapping between them such that scene points projecting to one line will also project to the other

Topic 03:

Two-View Geometry


- epipolar lines & epipolar planes
- the fundamental matrix (F-matrix)
- geometric interpretation of the F-matrix
- the essential matrix
- fundamental matrix estimation: the normalized 8-point algorithm
- algorithms & applications of stereo reconstruction
- image homographies
- stereo image rectification



10

epipolar lines & epipolar planes

*3x4 projection
matrix of camera 1*



12

Topic 03:

- epipolar lines & epipolar planes
- the fundamental matrix (F-matrix)
- geometric interpretation of the F-matrix
- the essential matrix
- fundamental matrix estimation: the normalized 8-point algorithm
- algorithms & applications of stereo reconstruction
- image homographies
- stereo image rectification

geometry of the epipolar constraint

15

- ② Assume that \hat{x}_1, \hat{c}_1 are 4D vectors whose 4th coordinate is the same



$$x_2 = \Pi_2 \hat{p}$$



- ① Typical point on this ray


$$\hat{p} = \lambda \hat{c}_1 + (1-\lambda) \hat{x}_1$$

homogeneous 3D coordinates of image point x_1

geometry of the epipolar constraint

14

- ③ $x_2 = \lambda \Pi_2 \hat{c}_1 + (1-\lambda) \Pi_2 \hat{x}_1$
- projection along camera 2 of camera 1's center of projection




$$\Pi_2(\lambda \hat{c}_1 + (1-\lambda) \hat{x}_1)$$

geometry of the epipolar constraint

16

- ④ Its projection in image 2:



$$\hat{p} = \lambda \hat{c}_1 + (1-\lambda) \hat{x}_1$$

homogeneous 3D coordinates of image point x_1


geometry of the epipolar constraint

17

geometry of the epipolar constraint

derivation of the epipolar constraint

19



Key observation: we can compute this line knowing just P_1, P_2 and (image point) x_1

18

geometry of the epipolar constraint

$$\textcircled{3} \quad x_2 = \lambda P_2 \hat{x}_1 + (1-\lambda) P_2 \hat{x}_1$$


projection along camera 2 of camera 1's center

projection along camera 2 of x-hat1

of projection


This is always a line, called the epipolar line

1. P_1 maps world points to image points
Question: How do we go from image point x_1 ?



20

derivation of the epipolar constraint



21


derivation of the epipolar constraint

derivation of the epipolar constraint

23

$$x_2 = \lambda \hat{\Pi}_2 \hat{c}_1 + (1-\lambda) \hat{\Pi}_2 \hat{x}_1$$

projection along
camera 2 of
camera 1's center
of projection




1. Question: How do we go $\overset{\text{from}}{\text{to world point}}$ $\overset{\text{image point}}{\text{x-hat_1}}$ *
- Ans: $x_1 = \hat{\Pi}_1 \hat{x}_1$ so define $\hat{x}_1 = (\Pi_1^\top \Pi_1)^{-1} \Pi_1^\top x_1$

derivation of the epipolar constraint

22

$$x_2 = \lambda \hat{\Pi}_2 \hat{c}_1 + (1-\lambda) \hat{\Pi}_2 \hat{x}_1$$

projection along
camera 2 of
camera 1's center
of projection




2. Question: What is \hat{c}_1 ?
- The projection of \hat{c}_1 along camera 1 is degenerate

derivation of the epipolar constraint

24

$$x_2 = \lambda \hat{\Pi}_2 \hat{c}_1 + (1-\lambda) \hat{\Pi}_2 \hat{x}_1$$

projection along
camera 2 of
camera 1's center
of projection




2. Question: What is \hat{c}_1 ?
- Can we use the pseudo-inverse here?
- Ans: No, \hat{c}_1 is not on the image plane

derivation of the epipolar constraint

25

derivation of the epipolar constraint

27





derivation of the epipolar constraint *

26

- a point on the ray containing \hat{x}_1 and \hat{c}_1 :
 $\lambda \hat{c}_1 + (1-\lambda) \hat{x}_1$
- its projection is . $\Pi_1(\lambda \hat{c}_1 + (1-\lambda) \hat{x}_1) \stackrel{\approx}{=} x_1$
 $(*) \quad \Delta(\Pi_1 \hat{c}_1) + (1-\lambda) (\Pi_1 \hat{x}_1) \stackrel{\approx}{=} x_1$
- but we also know that by construction
 $\Pi_1 \hat{x}_1 \stackrel{\approx}{=} x_1$
- since (*) holds for all points x_1, \hat{x}_1
- it follows that $\Pi_1 \hat{c}_1 = 0 \Rightarrow \hat{c}_1$ is in Π_1 's null space

derivation of the epipolar constraint *

28



Topic 03:

Two-View Geometry

- epipolar lines & epipolar planes
- the fundamental matrix (F -matrix)
- geometric interpretation of the F -matrix
- the essential matrix
- fundamental matrix estimation: the normalized 8-point algorithm
- algorithms & applications of stereo reconstruction
- image homographies
- stereo image rectification

the fundamental matrix

4. So $\times_2^\top (\Pi_2 w \wedge \Pi_2 (\Pi_1^\top \Pi_1)^{-1} \Pi_1^\top \times_1) = 0$

$$\Leftrightarrow \times_2^\top [\underbrace{\Pi_2 w}_\text{cross-product}] \Pi_2 (\Pi_1^\top \Pi_1)^{-1} \Pi_1^\top \times_1 = 0$$

$$\alpha \wedge b = \begin{bmatrix} 0 & -\alpha_3 & \alpha_2 \\ \alpha_3 & 0 & -\alpha_1 \\ -\alpha_2 & \alpha_1 & 0 \end{bmatrix} b$$


$$\boxed{\times_2^\top F \times_1 = 0}$$

F is a 3×3 matrix called the Fundamental Matrix

geometric interpretation of the F -matrix: epipoles


$$\times_2^\top F \times_1 = 0 \quad \times_2 = \lambda \hat{\Pi}_2 \hat{C}_1 + (1-\lambda) \hat{\Pi}_2 \hat{x}_1$$

$$\text{does not depend on } x_1 \quad \text{so all epipolar lines pass through it}$$





geometric interpretation of the F -matrix

$$\times_2^\top F \times_1 = 0 \quad \text{3x3 matrix}$$





the epipoles



Question: Where are the epipoles?

What does this tell you about the cameras' motion between views?

the epipoles



(Prince, 2011)

Question: Where are the epipoles?

What does this tell you about the cameras' motion between views?

35

geometric interpretation of the F-matrix: epipoles

$$x_2^T F x_1 = 0 \quad x_2 = \lambda \hat{e}_2 + (1-\lambda) \hat{e}_1 x_1$$

does not depend on x_1

so all epipolar lines pass through it

\star $x_2^T F e_1 = 0$ for all x_2 e_1 is its (right) null vector


If F has rank 2 and e_1 is its (right) null vector

$x_2^T F e_1 = 0$ for all x_2 e_1 is its (right) null vector

$x_2 = \lambda \hat{e}_2 + (1-\lambda) \hat{e}_1 x_1$

\curvearrowleft does not depend on x_1

so all epipolar lines pass through it



36


geometric interpretation of the F-matrix: epipoles

37

how many degrees of freedom does F have?

39


- a 3×3 matrix has 9 - $\text{rank}(F) = 2$ means defined up to scale
- $\Rightarrow F$ has at most 7 $\det(F) = 0 \Rightarrow$ removes another DOF



- ① $\text{rank}(F) = 2$
- ② null vectors are the epipoles
- ③ defined up to scale

38

basic properties of the fundamental matrix *




- ① $\text{rank}(F) = 2$
- ② null vectors are the epipoles
- ③ defined up to scale

projective invariance of the F-matrix

40

- The previous derivation was based on purely projective quantities (no metric information needed)
- if we multiply both Π_1 and Π_2 by T , nothing changes (it cancels out in the formula for F)
- Invertible 4x4 homogeneous transform



41

Topic 03:


Two-View Geometry

- epipolar lines & epipolar planes
- the fundamental matrix (F-matrix)
- geometric interpretation of the F-matrix
- the essential matrix
- fundamental matrix estimation: the normalized 8-point algorithm
- algorithms & applications of stereo reconstruction
- image homographies
- stereo image rectification

the Essential matrix

$$x_2^\top \begin{bmatrix} [\bar{c}]_x & \bar{\Omega} \end{bmatrix} x_1 = 0$$

* The Essential Matrix



Epipolar line passes through x_2 and \bar{c} and $\begin{bmatrix} \bar{\Omega} & \bar{c} \end{bmatrix} \begin{bmatrix} x_1 \\ 1 \end{bmatrix} = \bar{\Omega}x_1 + \bar{c}$
Line coordinates are $\Pi_2 = \begin{bmatrix} \bar{\Omega} & \bar{c} \end{bmatrix}$ 3×1 vector
 $\Pi_2 = \begin{bmatrix} \bar{\Omega} & \bar{c} \end{bmatrix}$ 3×3 matrix

the epipolar constraint with metric camera info

E.g. assume square pixels of unit size for both images

and focal length l

Let us write Π_2 as


$$\Pi_2 = \begin{bmatrix} \bar{\Omega} & \bar{c} \end{bmatrix} \quad 3 \times 1 \text{ vector}$$

$\Pi_2 = \begin{bmatrix} \bar{\Omega} & \bar{c} \end{bmatrix}$ 3×3 matrix

$$\begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{bmatrix} = \Pi_1$$

$\hat{x}_1 = \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$

$\hat{x}_1 = \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$ def




R Epipolar line passes through x_2 and \bar{c} and $\begin{bmatrix} \bar{\Omega} & \bar{c} \end{bmatrix} \begin{bmatrix} x_1 \\ 1 \end{bmatrix} = \bar{\Omega}x_1 + \bar{c}$
Line coordinates are $\Pi_2 = \begin{bmatrix} \bar{\Omega} & \bar{c} \end{bmatrix}$ 3×1 vector
 $\Pi_2 = \begin{bmatrix} \bar{\Omega} & \bar{c} \end{bmatrix}$ 3×3 matrix

the Relative Orientation Problem

$$x_2^\top \begin{bmatrix} [\bar{c}]_x & \bar{\Omega} \end{bmatrix} x_1 = 0$$

* The Essential Matrix E




Once we know E , we can compute $\bar{\Omega}$ and \bar{c}
This is known as the relative orientation problem
details in (P:431 in Prince)

the Essential matrix

$$x_2^\top \begin{bmatrix} [\bar{c}]_x & \bar{\Omega} \end{bmatrix} x_1 = 0$$

* The Essential Matrix E



Unlike F , E has 5 degrees of freedom
(3 translation + 3 rotation - 1 rank)

Topic 03:

47


Two-View Geometry

- epipolar lines & epipolar planes
- the fundamental matrix (F -matrix)
- geometric interpretation of the F -matrix
- the essential matrix

- **fundamental matrix estimation:**
the normalized 8-point algorithm

- algorithms & applications of stereo reconstruction
- image homographies
- stereo image rectification


the Relative Orientation Problem



46

estimating the fundamental matrix

Since F (and E) are relations strictly between image points, we can estimate them from image correspondences




(Prince, 2011)

48

⇒ just from knowing E , we can establish a 3D coordinate system in which the 3D position and orientation of both cameras is known.

Since F (and E) are relations strictly between image points, we can estimate them from image correspondences




49

estimating the fundamental matrix

F-matrix estimation: gold-standard algorithm

Gold Standard Approach: Suppose the noise in the point positions \vec{x}_k^μ , for $\mu = L, R$ is additive, independent and normally distributed with mean zero and covariance Σ_k^μ :

$$\vec{x}_k^\mu = \vec{m}_k^\mu + \vec{n}_k^\mu, \quad (15)$$



where \vec{m}_k^μ is the true position and \vec{n}_k^μ is the noise. Note: there is no noise in the third component of \vec{x}_k^μ in homogeneous coordinates.


Then the (maximum likelihood) problem is to find $F \in \mathbb{R}^{3 \times 3}$ and \vec{m}_k^μ , for $k = 1, \dots, K$ and $\mu = L, R$, such that the following objective function is minimized:

$$* \quad \mathcal{O} \equiv \sum_{\mu \in \{L, R\}} \sum_{k=1}^K (\vec{x}_k^\mu - \vec{m}_k^\mu)^T (\Sigma_k^\mu)^{\dagger} (\vec{x}_k^\mu - \vec{m}_k^\mu) \quad (16)$$

where $(\Sigma_k^\mu)^{\dagger}$ denotes the pseudo-inverse.

minimum # of point correspondences

What is the minimum number of correspondences to estimate F and E ?



gold standard: minimizing "reprojection error"

Gold Standard Approach: Suppose the noise in the point positions \vec{x}_k^μ , for $\mu = L, R$ is additive, independent and normally distributed with mean zero and covariance Σ_k^μ :

$$\vec{x}_k^\mu = \vec{m}_k^\mu + \vec{n}_k^\mu, \quad (15)$$

where \vec{m}_k^μ is the true position and \vec{n}_k^μ is the noise. Note: there is no noise in the third component of \vec{x}_k^μ in homogeneous coordinates.

- * F has 7 DOFs \Rightarrow minimum 7 *
- * E has 5 DOFs \Rightarrow minimum 5 *
- * Each correspondence gives 1 constraint equation $x_2^T F x_1 = 0$

easier alternative: minimizing algebraic error

Going back to the epipolar constraint

$$x_2^\top \begin{bmatrix} f_{11} & f_{12} & f_{13} \\ f_{21} & f_{22} & f_{23} \\ f_{31} & f_{32} & f_{33} \end{bmatrix} x_1 = 0$$

- Ignoring noise, this constraint is linear in the elements of F

$$\mathbb{A} \begin{bmatrix} f_{11} \\ f_{12} \\ \vdots \\ f_{33} \end{bmatrix} = 0$$

... but scaling is poor because typically pixels have (x, y) , $\begin{pmatrix} 0, 100 \\ 0, 100 \end{pmatrix}$ always 1

F -matrix estimation: gold-standard algorithm

54

subject to

$$(\vec{m}_k^L)^T F \vec{m}_k^R = 0, \quad k = 1, \dots, K, \quad (17)$$

$$\text{rank}(F) = 2 \quad (18)$$

Thus, \mathcal{O} is a quadratic objective function for the \vec{m}_k^μ 's, with nonlinear constraints (17) and (18).

We have a matrix \mathbb{A} determined from the point correspondences

$$\mathbb{A} \begin{bmatrix} f_{11} \\ f_{12} \\ \vdots \\ f_{33} \end{bmatrix} = 0$$

- Ignoring noise, this constraint is linear in the elements of F

Then the (maximum likelihood) problem is to find $F \in \mathbb{R}^{3 \times 3}$ and \vec{m}_k^μ , for $k = 1, \dots, K$ and $\mu = L, R$, such that the following objective function is minimized:

$$\mathcal{O} \equiv \sum_{\mu \in \{L, R\}} \sum_{k=1}^K (\vec{x}_k^\mu - \vec{m}_k^\mu)^T (\Sigma_k^\mu)^\dagger (\vec{x}_k^\mu - \vec{m}_k^\mu) \quad (16)$$

where $(\Sigma_k^\mu)^\dagger$ denotes the pseudo-inverse.



This is a nonlinear problem

the 8-point algorithm

We have a matrix \mathbb{A} determined from the point correspondences

$$\mathbb{A} \begin{bmatrix} f_{11} \\ f_{12} \\ \vdots \\ f_{33} \end{bmatrix} = 0$$

the 8-point algorithm

55

- Ignoring noise, this constraint is linear in the elements of F

Then the (maximum likelihood) problem is to find $F \in \mathbb{R}^{3 \times 3}$ and \vec{m}_k^μ , for $k = 1, \dots, K$ and $\mu = L, R$, such that the following objective function is minimized:

$$\mathcal{O} \equiv \sum_{\mu \in \{L, R\}} \sum_{k=1}^K (\vec{x}_k^\mu - \vec{m}_k^\mu)^T (\Sigma_k^\mu)^\dagger (\vec{x}_k^\mu - \vec{m}_k^\mu) \quad (16)$$

56

the normalized 8-point algorithm

2. Minimize the objective function $\mathcal{O}(\hat{F})$

$$\mathcal{O}(\hat{F}) \equiv \sum_{k=1}^K \left[(\vec{r}_k^L)^T \hat{F} \vec{r}_k^R \right]^2. \quad (27)$$

Note this is a linear least squares problem for the elements of \hat{F} .




FIG. 4. (a), (b) First two images of chapel sequence, (c) matches, (d) basis supplied by MLESAC, (e) the inliers, and (f) outliers.

From Tom & Zissermann MLESAC CVIU v.78, n.1, 2000
(we will discuss this method later in the course)

the normalized 8-point algorithm *

Hartley (PAMI, 1997) introduced the following algorithm. Given corresponding points $\{(\vec{x}_k^L, \vec{x}_k^R)\}_{k=1}^K$ with $K \geq 8$,

1. Recenter and rescale the image points using M^μ , $\mu = L, R$, such that

$$M^\mu = \begin{pmatrix} s^\mu & 0 & b_1^\mu \\ 0 & s^\mu & b_2^\mu \\ 0 & 0 & 1 \end{pmatrix}, \quad (24)$$

with

$$\frac{1}{K} \sum_{k=1}^K M^\mu \vec{x}_k^\mu = (0, 0, 1)^T, \quad (25)$$

$$\frac{1}{K} \sum_{k=1}^K [M^\mu \vec{x}_k^\mu - (0, 0, 1)^T]_*^2 = (\sigma_1^2, \sigma_2^2, 0)^T, \quad (26)$$

where $\sigma_1^2 + \sigma_2^2 = 2$. Here $[...]_*$ denotes the square of each element.

Define $\vec{r}_k^\mu = M^\mu \vec{x}_k^\mu$ for $k = 1, \dots, K$ and $\mu = L, R$.

$$F = (M^L)^T \hat{F} M^R \quad (28)$$

58

the normalized 8-point algorithm

2. Minimize the objective function $\mathcal{O}(\hat{F})$


$$\mathcal{O}(\hat{F}) \equiv \sum_{k=1}^K \left[(\vec{r}_k^L)^T \hat{F} \vec{r}_k^R \right]^2. \quad (27)$$

Note this is a linear least squares problem for the elements of \hat{F} .

3. Project \hat{F} to the nearest rank 2 matrix (with the error measured in the Frobenius norm):

- (a) Form the SVD of $\hat{F} = U \Sigma V^T$. In general $\Sigma = \text{diag}[\sigma_1^2, \sigma_2^2, \sigma_3^2]$ with $\sigma_i^2 \geq \sigma_{i+1}^2$ for $i = 1, 2$.
- (b) Reset $\sigma_3 = 0$.
- (c) Assign \hat{F} to be $U \Sigma V^T$.


4. Undo the normalization of the image points,



K F-matrices for every image pair (one per object)
static camera + K rigidly-moving objects

62

Topic 03:




Ch. 4 of Szeliski's book discusses
many techniques (not required reading)

64

Two-View Geometry

image points
consistent with
rigid-body
3D motion



(Delong et al., IJCV12)

one
F-matrix
applies to
one pair
of images


- epipolar lines & epipolar planes
- the fundamental matrix (F-matrix)
- geometric interpretation of the F-matrix
- the essential matrix
- fundamental matrix estimation:
the normalized 8-point algorithm

- algorithms & applications of stereo reconstruction

Static scene + moving camera
Static camera + one rigidly-moving object

one
F-matrix
applies to
one pair
of images

- image homographies
- stereo image rectification





Topic 03:

Two-View Geometry


- epipolar lines & epipolar planes
- the fundamental matrix (F-matrix)
- geometric interpretation of the F-matrix
- the essential matrix
- fundamental matrix estimation: the normalized 8-point algorithm
- algorithms & applications of stereo reconstruction
- **image homographies**
- stereo image rectification

Special case: geometry of two views of a plane



Special case: geometry of two views of a plane

③ \hat{p} also satisfies a plane equation: $(\hat{m})^T \hat{p} = 0$



③ More generally:

$$\hat{P} = \hat{\mathcal{M}}\hat{\mathcal{C}}_1 + \Pi_1^* X_1$$

pseudo-inverse
of Π_1

vector in nullspace of Π_1

④ Combining relations:


$$(\hat{m})^T (\hat{\mathcal{M}}\hat{\mathcal{C}}_1 + \Pi_1^* X_1) = 0$$

$$\Rightarrow \lambda = (\hat{m})^T \Pi_1^* X_1 / (\hat{m})^T \hat{\mathcal{C}}_1$$

Special case: geometry of two views of a plane

$$\hat{P} = \frac{1}{(\hat{m})^T \hat{C}_1} (\hat{m})^T \Pi_1^* x_1 \hat{C}_1 + \Pi_1^* x_1 = \left(I - \frac{1}{(\hat{m})^T \hat{C}_1} \cdot \hat{C}_1 (\hat{m})^T \right) \Pi_1^* x_1$$

$\underbrace{\quad\quad\quad}_{3 \times 4 \text{ Matrix}}$



(2) More generally:
 $\hat{P} = \lambda \hat{C}_1 + \Pi_1^* X_1$

pseudo inverse of Π_1


vector in null space of Π_1

(3) typical point on this manifold
 $\hat{P} = \lambda \hat{C}_1 +$
 homogeneous 3D coordinates
 of image point X_1

Special case: geometry of two views of a plane


$$\hat{P} = \frac{\hat{C}_1}{(\hat{m})^T \hat{C}_1} (\hat{m})^T P_1^* x_1 \hat{C}_1 + P_1^* x_1 = \left(I - \frac{1}{(\hat{m})^T \hat{C}_1} \cdot \hat{C}_1 (\hat{m})^T \right) P_1^* x_1$$

$\underbrace{\quad\quad\quad}_{3 \times 4 \text{ Matrix}}$




The image of a plane point in a second camera

75



The image-to-3D-plane transformation

This 3×4 matrix maps homogeneous image coordinates to the homogeneous 3D coordinates of a unique point on the 3D plane



The homography between two views of a plane

The matrix H defines an invertible linear mapping from the projection of plane points in image 1 to their projection in image 2.

76

The homography between two views of a plane

The matrix H defines an invertible linear mapping from the projection of plane points in image 1 to their projection in image 2.

77

Example: creating an image mosaic

79

a stereo image pair




78

Computing the homography matrix

Corollary (Prove it!): we can compute H by solving a linear system if we know the projection of at least 4 points on the plane in the two views.

π_2



Topic 03: Two-View Geometry

80

homogeneous words
of
projection
image 2

$X_2 = \mathcal{H} X_1$

Homogeneous 2D
coordinates of
projection
image 1

3×3 homography
matrix

- epipolar lines & epipolar planes
- the fundamental matrix (F-matrix)
- geometric interpretation of the F-matrix
- the essential matrix
- fundamental matrix estimation: the normalized 8-point algorithm
- algorithms & applications of stereo reconstruction
- image homographies
- stereo image rectification



81





Figure 16.9 Planar rectification. The images from figures 16.6 and 16.7 have been rectified by applying homographies. After rectification, each point induces an epipolar line in the other image that is horizontal and on the same scanline (compare to figure 16.7a). This means that the match is guaranteed to be on the same scanline. In this figure, the red dotted line is the superimposed outline of the other image.





Once F (or E) are known, we can warp the images so that corresponding epipolar lines line up

82

→ the warp sends both epipoles to infinity
see 16.5.1 in Prince for details.

84

stereo image rectification



The Epipolar Constraint

For every pair of perspective photos, there exists a line-to-line mapping between them such that scene points projecting to one line will also project to the other

(Prince, 2011)

→ the warp sends both epipoles to infinity

Idea: find homographies H_1, H_2 such that $H_2^T F H_1 = \begin{bmatrix} 0 & 0 & 0 \\ 0 & 0 & 0 \\ 0 & -1 & 0 \end{bmatrix}$