

MASTER'S THESIS IN PHYSICS

---

# Development of an Interface between an SiPM-based Scintillation Detector and the CMS Drift Tube Read-Out System using the lpGBT ASIC

---

written by

Nils Jonathan Esper

presented to

The Faculty of Mathematics, Computer Science and Natural  
Sciences of RWTH Aachen University

Institute of Physics IIIA

supervised by

Univ.-Prof. Dr. rer. nat. Alexander Schmidt

and as second reviewer

Univ.-Prof. Dr. rer. nat. Oliver Pooth

Aachen, December 2025

# Abstract

Abstract.

# Contents

|          |                                                          |          |
|----------|----------------------------------------------------------|----------|
| <b>1</b> | <b>Introduction</b>                                      | <b>1</b> |
| 1.1      | Idea . . . . .                                           | 1        |
| 1.2      | Standard model of particle physics . . . . .             | 1        |
| 1.3      | Cosmic particles . . . . .                               | 1        |
| 1.3.1    | Cosmic radiation . . . . .                               | 1        |
| 1.3.2    | Atmospheric creation of muons . . . . .                  | 1        |
| 1.4      | Principles of particle detection . . . . .               | 1        |
| 1.4.1    | Interactions of particles and matter . . . . .           | 1        |
| 1.4.2    | Scintillators . . . . .                                  | 1        |
| 1.4.3    | Gaseous detectors . . . . .                              | 1        |
| 1.5      | Modern read-out electronics . . . . .                    | 1        |
| 1.5.1    | Requirements for detector read-out . . . . .             | 1        |
| 1.5.2    | Field Programmable Gate Array devices . . . . .          | 1        |
| 1.5.3    | Basics of logic development . . . . .                    | 1        |
| <b>2</b> | <b>CMS Drift Tube system</b>                             | <b>2</b> |
| 2.1      | Compact Muon Solenoid experiment . . . . .               | 2        |
| 2.1.1    | Large Hadron Collider . . . . .                          | 2        |
| 2.1.2    | Experimental setup . . . . .                             | 2        |
| 2.2      | Drift Tube system . . . . .                              | 2        |
| 2.2.1    | Subsystem setup . . . . .                                | 2        |
| 2.2.2    | Detector impact and performance . . . . .                | 2        |
| 2.3      | Phase-2 DT read-out electronics . . . . .                | 2        |
| 2.3.1    | Motivation for upgrade . . . . .                         | 2        |
| 2.3.2    | Phase-2 DT system overview . . . . .                     | 2        |
| 2.3.3    | Minicrate electronics . . . . .                          | 2        |
| 2.4      | Cosmic test stand in Aachen . . . . .                    | 2        |
| <b>3</b> | <b>SiPM-based scintillation detector</b>                 | <b>3</b> |
| 3.1      | Detector setup . . . . .                                 | 3        |
| 3.2      | FPGA read-out system . . . . .                           | 3        |
| 3.2.1    | Signal sampling with FPGA-internal comparators . . . . . | 3        |
| 3.2.2    | Timestamp assignment . . . . .                           | 3        |
| 3.2.3    | Online coincidence evaluation . . . . .                  | 3        |
| 3.2.4    | Data funneling . . . . .                                 | 3        |
| 3.3      | Calibration procedures . . . . .                         | 3        |
| 3.3.1    | Comparator threshold calibration . . . . .               | 3        |
| 3.3.2    | Intra-channel timing calibration . . . . .               | 3        |

|          |                                                      |           |
|----------|------------------------------------------------------|-----------|
| <b>4</b> | <b>lpGBT detector interface</b>                      | <b>4</b>  |
| 4.1      | lpGBT ASIC . . . . .                                 | 4         |
| 4.2      | lpGBT Mezzanine PCB . . . . .                        | 4         |
| 4.3      | Data interface to FPGA . . . . .                     | 4         |
| <b>5</b> | <b>Unified backend electronics</b>                   | <b>5</b>  |
| 5.1      | HTG-940 prototype backend . . . . .                  | 5         |
| 5.2      | Backend firmware . . . . .                           | 5         |
| 5.2.1    | Functionalities for OBDTs . . . . .                  | 5         |
| 5.2.2    | Modifications to interface lpGBT Mezzanine . . . . . | 5         |
| 5.3      | Data path to computer . . . . .                      | 5         |
| <b>6</b> | <b>Detector synchronization</b>                      | <b>6</b>  |
| 6.1      | Testpulse theta board . . . . .                      | 6         |
| 6.2      | Synchronization with test pulses . . . . .           | 6         |
| <b>7</b> | <b>First combined measurements</b>                   | <b>7</b>  |
| 7.1      | Cosmic muon coincidence . . . . .                    | 7         |
| 7.2      | Recovering DT-specific distributions . . . . .       | 7         |
| <b>8</b> | <b>Summary and outlook</b>                           | <b>8</b>  |
|          | <b>Appendix A Additional details</b>                 | <b>9</b>  |
|          | <b>Bibliography</b>                                  | <b>10</b> |
|          | <b>List of Figures</b>                               | <b>11</b> |
|          | <b>List of Tables</b>                                | <b>12</b> |
|          | <b>List of Acronyms</b>                              | <b>13</b> |

# 1 Introduction

## 1.1 Idea

## 1.2 Standard model of particle physics

## 1.3 Cosmic particles

### 1.3.1 Cosmic radiation

### 1.3.2 Atmospheric creation of muons

## 1.4 Principles of particle detection

### 1.4.1 Interactions of particles and matter

### 1.4.2 Scintillators

### 1.4.3 Gaseous detectors

## 1.5 Modern read-out electronics

### 1.5.1 Requirements for detector read-out

### 1.5.2 Field Programmable Gate Array devices

### 1.5.3 Basics of logic development

## 2 CMS Drift Tube system

### 2.1 Compact Muon Solenoid experiment

#### 2.1.1 Large Hadron Collider

#### 2.1.2 Experimental setup

### 2.2 Drift Tube system

#### 2.2.1 Subsystem setup

#### 2.2.2 Detector impact and performance

### 2.3 Phase-2 DT read-out electronics

#### 2.3.1 Motivation for upgrade

#### 2.3.2 Phase-2 DT system overview

#### 2.3.3 Minicrate electronics

### 2.4 Cosmic test stand in Aachen

# **3 SiPM-based scintillation detector**

## **3.1 Detector setup**

## **3.2 FPGA read-out system**

### **3.2.1 Signal sampling with FPGA-internal comparators**

### **3.2.2 Timestamp assignment**

### **3.2.3 Online coincidence evaluation**

### **3.2.4 Data funneling**

## **3.3 Calibration procedures**

### **3.3.1 Comparator threshold calibration**

### **3.3.2 Intra-channel timing calibration**

## 4 lpGBT detector interface

### 4.1 lpGBT ASIC

### 4.2 lpGBT Mezzanine PCB

### 4.3 Data interface to FPGA

# 5 Unified backend electronics

## 5.1 HTG-940 prototype backend

## 5.2 Backend firmware

### 5.2.1 Functionalities for OBDTs

### 5.2.2 Modifications to interface lpGBT Mezzanine

## 5.3 Data path to computer

## 6 Detector synchronization

### 6.1 Testpulse theta board

### 6.2 Synchronization with test pulses

# 7 First combined measurements

## 7.1 Cosmic muon coincidence

## 7.2 Recovering DT-specific distributions

## 8 Summary and outlook

# Appendix

## A Additional details

# Bibliography

# List of Figures

## List of Tables

# List of Acronyms

# Acknowledgements

Acknowledgements.