AGENTIC AI IN BUSINESS

Context Engineering for AI Agents

From Context to Memory

Context engineering · Agent Skills · User Memory · Retrieval

PART ONE

What the model sees each round

PART TWO

How to control cost and behavior


PART THREE

How knowledge persists across sessions

OUTLINE

Course Map

Four parts, one information supply chain



- What is context
- API-level Context Structure
- Context Design

- KV Cache
- Prompt engineering

- Prompt engineering
- Agentic skill

- User memory
- Basic RAG

From “what the model sees in this round” to “what the system knows in the long run.”

OUTCOMES

Learning Outcomes

By the end, you should be able to make these engineering decisions

Read Trajectories

Identify system, user, assistant, tool messages, and differences between tool definitions and tool results

Understand the Information Flow

Know static prefixes, dynamic states, skills, long-term memory, and retrieved evidence

Explain the Trade-offs

Describe the costs and risks between cache hits, retrieval quality, status updates, and long-term maintenance

PART 1

Context

What is actually in the window, and who put it there

CONTEXT

Context Sets the Performance Ceiling

Question: Plan my trip from Heilbronn to Frankfurt Airport. My flight departs at 19:00.

Context 1

Only user goal: flight at **19:00**

“You should leave early enough to arrive at the airport around 16:30–17:00.”

Context 2

User goal + **DB timetable / planned route**

“Take the 14:30 train via Mannheim and arrive at Frankfurt Airport at 16:25.”

Context 3

User goal + timetable + **DB might delay**

“The original route is now too risky. Choose an alternative connection or leave earlier.**”**

Same model. Same question. Different context → Different decisions.

CONTEXT

Information in Context

Deliver the structured background information an agent needs to the model.

The task
Goal · Limits · what counts as done

The rules
Policy · Order · What to check

Right now
Live data · What changed

Without the task

It answers a reasonable question rather than yours: a route that arrives on time, to the wrong airport.

Without the rules

It takes the cheapest connection and never checks the delay, because nothing said checking was part of the job.

Without the current situation

It recommends a train that left an hour ago. Its timetable was right in training and is wrong today.

Context tells the model what is happening out there.

CONTEXT

Every Decision Depends on the Last One

The next action depends on what has already happened.



The API remembers nothing for you.

Each round is a fresh call. Nothing carries over on its own.

The simplest approach is to resend the entire message history.

Production systems compress it — but whatever the next decision depends on must survive the compression.

So the question for the rest of today: how do you keep it informative and stop it getting expensive?

CONTEXT IN API

Where does context enter the API call

System Prompt — Who you are · How you should act · What rules to follow · What steps to take

Tool Definition — What the tool is called · What it does · What inputs it needs

Interaction [Conversation history / trajectory (grows with interaction →)]

user › assistant › tool › assistant

Context Composition Each Time the Agent Calls the Model

CONTEXT IN API

system — Developers Define Identities, Constraints, and Processes

user — End-User Requests and Supplemental Inputs

assistant — Model Previous Text Reply or Tool Call Request

tool — Framework Results Returned After Tool Execution


Role structure helps the model judge who is speaking, what is instruction, and what is just data.

```
“messages”: [
  {
    "role": "system",
    "content": "You are a travel assistant. Always check real-time train status before recommending a route."
  },
  {
    "role": "user",
    "content": "Plan my trip from Heilbronn to Frankfurt Airport. My flight departs at 19:00."
  },
  {
    "role": "assistant",
    "content": "I will check the available train connections first."
  },
  {
    "role": "tool",
    "content": "ICE 123 arrives at Frankfurt Airport at 16:30 and is currently delayed by 70 minutes."
  },
  {
    "role": "assistant",
    "content": "The original connection is now risky. I recommend checking an alternative route."
  }
]
```

CONTEXT IN API

Single-Turn Call

One API call: provide the required context, get one model response



system

You are a travel assistant.

User

“Plan my trip to Frankfurt Airport.”


assistant

Here is a recommended route...

Multi-Turn Interaction with Tool Calls

A tool call usually requires another model API call after the tool result is returned.

Question "What's the current time and weather in Vancouver?"



The model decides what to call; the framework executes the tools; the results are added to the context and sent back to the model.

CONTEXT IN API

Tool Calls

```
    {
      "role": "assistant",                              // ← Model output from 1st call,
      ↪  included verbatim
      "content": null,
      "tool_calls": [
        { "id": "call_abc123", "function": { "name": "get_current_time", "arguments":
↪   "{\"timezone\": \"America/Vancouver\"}" } },
        { "id": "call_def456", "function": { "name": "get_weather", "arguments":
↪   "{\"city\": \"Vancouver\", \"unit\": \"celsius\"}" } }
      ]
    },
```

Parallel execution

get_current_time (timezone)
get_weather (city)

Independent tool calls can run in parallel; dependent calls must wait for earlier results.

Tool ID

tool_call_id

tells the framework which result belongs to which tool call

CONTEXT IN API

Message History Grows with Each Round

Round 0	system + user
Round 1	+ assistant tool_calls + tool results
Round 2	+ assistant final response

Trajectory = the agent's step-by-step work history.

CONTEXT IN API

Context Composition

Stable Prefix — **System Prompt + Core Tool Definitions**

Dynamic Trajectory

user · assistant · tool result · …


appended every round, compressed if necessary

Conversation history, *i.e.,* the trajectory, grows with each interaction

PART 2

Caching and Prompt Design

Chat Template





- Use standard message roles, the chat template converts them into the model's expected format
- This formatting happens before tokenization

KV CACHE

Attention

Each token forms a Query, Key, and Value. A new token uses its Query to find relevant information from previous tokens.





- Each token produces a Query, Key, and Value.
- The new token compares its Query with the Keys of previous tokens, and gets a weighted sum of the Values.
- Each token can only attend to current and previous tokens.

KV CACHE

What the cache actually stores

The model is decoding one token at a time. It has finished t1 to t4 and is about to place t5. Ask what genuinely changes at this step.

Token positions

t1	t2	t3	t4	new t5
past — already computed				current position

Recomputed at this step

one new column, and nothing else

q5 k5 v5

The Query is fresh every step, because the thing doing the looking is new.

Read back from the cache

everything to the left of it

k1 … k4 v1 … v4

These were computed from tokens that have not changed — and, by the causal mask, cannot change.

q5 → compare with k1 … k5 → weights → weighted sum of v1 … v5 → z5 *one step*

The past does not change, so its Keys and Values do not change. Store them once, append one column per step. That is the entire idea — and the reason a stable prefix is worth money.

KV CACHE

KV Cache

Without KV cache

Every decoding step forwards the whole prefix again.

step 1	compute K_1 V_1
step 2	recompute K_1 V_1 + compute K_2 V_2
step 3	recompute K_1 V_1 K_2 V_2 + compute K_3 V_3
step 4	recompute all earlier K/V + compute K_4 V_4

With KV cache

Read the stored history and append one new K/V pair.


step 1	compute and store K_1 V_1
step 2	read cache + append K_2 V_2
step 3	read cache + append K_3 V_3
step 4	read cache + append K_4 V_4

KV cache removes repeated projection work

A context-design rule: keep the prefix stable so the cached prefix states remain reusable

https://huggingface.co/blog/not-lain/kv-caching

Stable Prefix




- A token's K/V depends not only on the token itself, but also on the prefix before it.
- Modify the prefix → invalidate the cache from the point of change onward.

KV Cache vs. Prompt Cache


KV Cache

Caches K/V during a single generation (one request)



Prompt Cache

Caches model states for the same prefix across multiple requests



	KV Cache	Prompt Cache
Scope	Single request (one generation)	Multiple requests (same prefix)
What is cached	Key and Value states of past tokens	Model intermediate states for a fixed prefix
When it helps	During autoregressive generation	When many requests share the same prefix
Managed by	Typically on the model server (transparent to users)	Provided by the service provider (e.g., API-level feature)
Typical benefit	Faster token generation, lower per-token latency	Lower latency and cost for repeated prefixes across requests

KV CACHE

Common Context Patterns

Anti-pattern	What people do, and why it hurts	Do this instead
Dynamic System Prompt	Some developers embed timestamps in the system prompt (e.g., “Current time: 2025-09-14 10:30:45.123456”)	**Put the time at the end,**
Dynamic Rearrangement Tool	Dynamically reorder tools based on usage frequency	**Fixed Sequence**
Sliding Window	Keeping only the last N messages drops the oldest one on every turn — which is the start of the prefix. With a window of 10, message 11 drop message 1 and the cache restarts from the top.	**Compress old turns**
Hand-rolled text formatting	Flattening roles into “USER: … ASSISTANT: …” by hand produces a string the model was never trained on.	**Using Standard Message Structure**

Cache-Friendly Design Principles

1 **Fixed Early Content**

Once the system prompt, the tool definitions and their order are set, leave them alone for as long as you can.

2 **Append dynamic information**

Time, status and task progress belong at the end of the message list, never at the top.

3 **Keep the standard structure**

Let the chat template render roles, boundaries and tool results. Hand-formatting saves nothing and breaks the cache.

PROMPT ENGINEERING: Prompt Format

Reduce content ambiguity and put the power of the model into what really needs reasoning.

Format

- **Markdown** organizes the content for human and machine readers
- **XML tags** precise, machine-parseable semantics

```
# Tool Usage Guidelines

## File Operations
<file_operation>
- Check whether the path exists before reading a file
- Create a backup before writing a file
</file_operation>

## Network Requests
<network_request>
- Set the timeout to 30 seconds
- Retry at most 3 times after a failure
</network_request>
```

Organization

Process-Driven vs. Rule Stacking

Rule stacking

Dozens of independent rules.

The model has to work out the priority on the spot, and when it goes wrong there is no step to point at.

Process Driven

Validation → Classification → Preprocessing → Execution → Validation

The model knows which stage it is in, what that stage is for, and what comes next. So do you, when it fails.

When to show examples, and when not to

Writing rules

- Tasks the model already knows how to do
- Clear judgment conditions
- Simple output structure


Provide examples

- Writing style
- Complex Report Format
- Customer Service Tone and Boundaries Cases

Engineering notes

- 2–3 high-quality examples of coverage boundaries, often outperforming 10 near-repeat examples.
- Once the example is selected, the prefix should also be kept stable.

Prompt Injection



Defenses: Multiple Layers of Protection

Combine prompt-level protections with runtime safeguards.

1 Tag Source

Clearly mark external content (e.g., external_content) so the model knows it is data, not a directive.

external_content

2 Keep Role

Preserve correct message roles (tool ≠ user). Tool outputs and web content should stay in the tool role.

```
role: tool
<web content ...>
```

3 Restrict Permissions

Limit what the agent can do (e.g., sandbox, allow-list, read-only access).

- ✓ Read only
- ✓ Allow-list
- ✓ Sandbox

4 High Risk Confirmation

Require explicit confirmation for high-risk actions (write / send / pay).

Write to /tmp/leaked.txt ?

Cancel | Confirm

Context-level protection reduces attack rates, but is not a substitute for permission controls and action-level safeguards.

PROMPT ENGINEERING

Tool Definitions

Keep tool discovery lightweight, and load detailed tool definitions only when needed.

1 Load All Tools Upfront

Every request carries every definition, used or not.

System prompt
(instructions, rules)

Tool A full definition
(name, purpose, inputs)

Tool B full definition
(name, purpose, inputs)

Many more tool definitions ...

- Long stable prefix
- All tools sent every time
- More tokens and cost

Simple, but expensive

2 Progressive Tool Loading

A catalog upfront; full definitions on demand.

System prompt
(instructions, rules)

Tool catalog
(names + short descriptions)
e.g., search_route, get_weather

1. Model selects a tool
"I should use get_weather."

2. Load selected tool definition
(inputs, types, examples, usage rules)

3. Append to conversation once
It stays in the same position; later messages are added after it.

PART 3

Skills and Agent Status

What is Skill

Objective Modularize the Agent's capabilities into independent, loadable knowledge packages

Information Domain knowledge

Collection of prompts and files

Format

- SKILL.md file
  - YAML frontmatter
  - Description
    - "Use when"
    - "Do not use when"

name	template-skill
description	Replace with description of the skill and when Claude should use it.

Insert instructions below


https://github.com/anthropics/skills/blob/main/template/SKILL.md

What a Useful Skill Contains


1	**Who**	Who it serves, which tasks it covers, and what a good output looks like
2	**core**	Step-by-step instructions, The most important principle, matching examples and counterexamples
3	**common mistakes**	Forbidden actions, out-of-scope actions, and the exceptions that are allowed
4	**completion standard**	Stop conditions, confirmation points, and how to verify the result
5	**Reference resource**	Glossary, templates, worked examples, detailed sub-documents


https://github.com/agentskills/agentskills/blob/main/docs/specification.mdx?utm_source=chatgpt.com

Workflow


User-triggered
User types an explicit command (e.g., /pptx).
User types /pptx
Client intercepts and expands locally
Load full SKILL.md
Model-triggered
Model reads the catalog and decides a skill is needed.
Model reads metadata catalog
Decides a Skill is needed
Call Skill tool
Tool result: skill is launching
Load full SKILL.md
Same landing point
Append full SKILL.md at the invocation point in the current trajectory.
Loaded once. Later messages are appended after it.

Skills vs Tools






a skill supplies the knowledge of how to proceed; a tool supplies the ability to act.

AGENT STATUS BAR: Hidden State in Long Trajectories

Managing Trajectories How the Agent can keep the model aware of task progress, environment changes, and tool-call counts

Without Status Bar




Model must scan the full history and recount: xfinity_calls = 3

With Status Bar

Agent Status Bar


```
xfinity_calls: 3 / 3
deal_search: completed
account_checked: yes
next_action: do_not_call_again
```

current state is explicit




Composition

- **Task Planning**
  - TODO List
- **Current Environment Observation Summary**
  - Dynamic environment information
  - Abnormal operation alerts (“This tool has been called N times repeatedly”)
- **Side-channel Information for Events**
  - Events tool-ID, file-ID etc


messages: [
{ role: "system", content: "You are a telecom customer service agent..." }
tools: [cancel_plan, query_records, ...]
fixed
(KV Cache)
{ role: "user", content: "Help me cancel my plan" }
{ role: "assistant", tool_calls: [cancel_plan(...)] }
{ role: "tool", content: "This plan has a contract period..." }
{ role: "assistant", content: "Your plan is within the contract period..." }
... more conversation turns ...
{ role: "user", content: "Then help me check my call records" }
user follow-up
{ role: "user", content: "<agent_status>
Called 3/3 times · TODO: Cancel plan (in progress)</agent_status>"
Agent framework insertion
agent status bar
model starts generating from here
← adjacent to model generation start, receives highest attention weight

Update

Replace each round



Persistent appending



all previous messages stay in place

Update

Can you decide which update strategy should be used? 🤔

From the perspective of cache pricing

Replace each round

status is large

status updates are frequent

Persistent appending

status is small

many messages are produced between updates

Maintain

- **Maintain the status bar with code whenever possible**

If an LLM is unavoidable, extract items one by one and aggregate them with code; never ask it to perform a batch count in one shot

- **Do not delete the original context**

The status bar is a lossy projection of the trajectory. The moment a question falls outside the fields you chose, the answer collapses — so keep the original underneath it.

PART 4

User Memory and RAG

USER MEMORY

Personalized service across sessions

```
User: Help me book a flight to Tokyo next Friday. I prefer window seats
      and I'm vegetarian, so I'll need a special meal.
Agent: I'll search for flights to Tokyo for next Friday...
       [calls flight_search tool, returns 3 options]
Agent: Here are your options. Based on your preference, I've filtered for
       window seat availability. Shall I book the ANA direct flight?
User: Yes, and use my United MileagePlus number 12345678.
```

```
Extracted memories:
- User prefers window seats (preference)
- User is vegetarian, needs special meals on flights (dietary restriction)
- User's United MileagePlus number: 12345678 (loyalty program)
- User has travel plans to Tokyo (recent activity)
```

Three rules for what you extract Selective Abstraction Structured

USER MEMORY

Three Levels of Memory Capability

Level 1

Basic Memories

Accurately save and return clear facts

Level 2

Retrieve

associated entities, time, channels and composite events across sessions

Level 3

Proactive services

synthesizes old information to identify risks and backlogs ahead of time

LoCoMo (https://aclanthology.org/2024.acl-long.747.pdf)

USER MEMORY

Where, how, and what to store

1 Where does it live?

Trajectory — this run, append-only
User long-term memory — across sessions

2 How is it written?

Simple notes → enhanced notes → JSON cards → advanced JSON cards
Cheap and lossy, or expressive and costly.
the next slide

3 What kind of thing to write?

Episodic — a specific event
Semantic — a stable fact
Procedural — a reusable routine

Episodic

what happened — one event, with a time

PERSON
dinner with a colleague at that Italian place, last Wednesday

AGENT
the user booked the ANA flight to Tokyo for next Friday

Semantic

what is true — distilled from many Episodic

PERSON
the capital of Italy is Rome

AGENT

the user is vegetarian;
prefers window seats


Procedural

how it is done — learned by repetition

PERSON
riding a bicycle

AGENT
search direct flights → confirm the seat → use the frequent-flyer number

Storage Formats



USER MEMORY

Compression

Keep memory useful without letting storage and retrieval cost grow without bound.

Stage 1

Importance filter

Score memories

- Access frequency
- Time decay
- Emotional intensity
- Information uniqueness

↓

Keep high-score memories

Low score → compress / archive / delete

Stage 2

Cluster & Summarize

Merge similar memories

- "Asked about rain"
- "Checked weekend weather"
- "Asked if an umbrella is needed"

Representative summary

"Often checks weather before outdoor plans"

Stage 3

Abstract & generalize

Repeated episodes --> stable rules

- episode A
- episode B
- episode C

Extract recurring pattern

Semantic memory


"Prefers cost-effective products."

Procedural memory

"Check reviews before recommending a product."

Retrieval-Augmented Generation

Without retrieval, the model answers from a snapshot that stopped at training time




https://dl.acm.org/doi/epdf/10.1145/3637528.3671470

RAG

Retrieval-Augmented Generation

The pipeline



https://dl.acm.org/doi/epdf/10.1145/3637528.3671470

Embeddings

- Dense vector (list of numbers)
- Token Embeddings
  - One vector per token

    "What does this specific word mean in this exact context?"
- Sentence Embedding
  - One vector for the entire sentence


    "What is the overall meaning of the entire sentence?"

RAG

Chunking

Cut long documents into fragments (chunks)

Fixed-size




Equal token windows
Fast, but may cut meaning

Structure-aware



Natural document boundaries
A strong production default

Semantic



Cuts where meaning changes
Coherent, but costs more

- The choice of chunk size and overlap is a trade-off

Evaluation

Recall@k	Is the correct evidence inside the top k results at all?
MRR	First relevant result ranked first
nDCG	Overall sort quality of all relevant results

Evaluate whether the search found evidence before discussing whether the generated answer is well written.

SUMMARY

Course Summary

1	**Context**	The model acts on information visible in the current call
2	**KV Cache**	A stable prefix reduces repeated computation and cost
3	**Prompt & Skills**	Clear rules and expert knowledge loaded on demand
4	**Status Bar**	The framework converts hidden progress into explicit state
5	**Memory & RAG**	Cross-session facts and shared knowledge return to context on demand

THE LAB

This afternoon: build the context

Understand the supplied scripts, then choose your own modifications. Explain how your changes affect the model's context and responses.

1. Understand and modify the tool-use conversation. Print each request and identify the system prompt, tool definitions, assistant tool calls, and tool results.
   - Change the contents of tool to addition.
2. Compare a stable prompt prefix with one that changes every turn. Move dynamic information to the end and measure prompt-processing time across repeated runs.
   - Explain the code
3. Understand and modify a Skill with explicit trigger conditions and load it on demand. Maintain an agent status record with code and inspect how both enter the next request.
   - Change the skill to translation: for example, translate text into German or Chinese.
4. Understand how persistent facts are extracted and saved as structured memory. Start a new session and compare responses with and without reloading that memory.