KernelMix reference manual

Nilson Chapagain

Contents

1 KernelMix **2**
1.1 Install . . . 3
1.2 Example . . . 3
1.3 Documentation . . . 4
1.4 References and license . . . 4

2 Model and interpretation **4**
2.1 Continuous outcomes . . . 4
2.2 Binary outcomes . . . 5
2.3 Count outcomes . . . 5
2.4 Survival outcomes . . . 5
2.5 Random intercepts . . . 6
2.6 Priors and exposure selection . . . 6
2.7 Inputs and computation . . . 7
2.8 Prediction and contrasts . . . 8
2.9 Diagnostics and scope . . . 8

3 An exposure-mixture analysis **9**
3.1 Define the data . . . 9
3.2 Fit and inspect a continuous outcome . . . 9
3.3 Predict at exposure profiles . . . 10
3.4 Summarize exposure associations . . . 10
3.5 Fit a binary outcome . . . 11
3.6 Fit counts and include observation time . . . 11
3.7 Fit right-censored survival times . . . 11
3.8 Account for clustered observations . . . 13
3.9 Plot the results . . . 13
3.10 Save and load a fit . . . 13

4 Ozone and weather in New York **14**
4.1 Data and question . . . 14
4.2 Model and run . . . 14
4.3 Results and checks . . . 16
4.4 Reuse and limits . . . 17

5 Structured models and Gaussian process approximations **19**
5.1 Choose an exposure kernel . . . 19
5.2 Reduce GP matrix size . . . 20
5.3 Model random intercepts and slopes . . . 20
5.4 Separate Gaussian variance and correlation . . . 21
5.5 Encode delayed entry and competing events . . . 22
5.6 Record left or interval censoring . . . 23
5.7 Supply known covariate paths . . . 24
5.8 Set starting values . . . 24

6 API reference **25**
6.1 Fitting . . . 25
6.2 Structured model results . . . 27
6.3 Fit results and diagnostics . . . 27
6.4 Prediction . . . 28
6.5 Cluster and survival results . . . 29
6.6 Exposure contrasts and curves . . . 30
6.7 Plotting . . . 31
6.8 Kernel helper . . . 32
6.9 Method sources . . . 32

7 Verified results and open gaps **32**
7.1 Evidence status . . . 32
7.2 Original-paper targets . . . 33
7.3 Platform evidence . . . 33

8 Checks and development **33**
8.1 Run checks . . . 33
8.2 Numerical evidence . . . 34
8.3 Observed data and original studies . . . 35
8.4 Build the manual . . . 35

1 KernelMix

Bayesian kernel machine regression (BKMR) for exposure mixtures in Python. KernelMix estimates how an outcome varies with several exposures together. The exposure–response function can describe curved relationships and interactions: the association with one exposure can depend on another. Other measured variables, called adjustment covariates, enter as linear terms. It supports continuous, binary, count and survival outcomes. NumPy and SciPy handle fitting and prediction; R is not required.

Analysis	Functions
Fit outcomes	`fit`, `Prior`: Gaussian, probit, Poisson, negative binomial and piecewise-exponential survival
Cluster observations	Random intercepts/slopes; Gaussian AR1, exponential or supplied residual correlations
Model unequal residual variance	Gaussian variance regression and residual-variance prediction
Choose how to represent the exposure function	Gaussian, Matérn 3/2 or rational-quadratic kernels; dense, predictive-process or random-Fourier bases
Model survival records	Delayed entry, competing causes, known predictor histories and left/interval censoring
Select exposures or exposure groups	`selection="component"` or `"group"`, posterior inclusion probabilities
Inspect results	`summary`, `diagnostics`, `posterior_samples`
Predict	`predict_h`, `predict`, `predict_survival`, `posterior_moments_h`
Describe exposure associations	Overall, single-exposure and interaction contrasts; response curves and surfaces
Plot	Chains, inclusion probabilities, exposure curves, survival curves, contrasts and surfaces

1.1 Install

With access to this repository:

```
python -m pip install "kernelmix[plots] @ git+https://github.com/nilson01/kernelmix.git@main"
```

Or, from a downloaded source folder:

```
python -m pip install ".[plots]"
```

Python 3.10 or later is required. Omit `[plots]` if plots are not needed.

1.2 Example

```
import numpy as np
from kernelmix import fit, univariate_response, plot_response

rng = np.random.default_rng(17)
Z = rng.normal(size=(24, 2))
y = np.sin(Z[:, 0]) + 0.3 * Z[:, 1] + rng.normal(0, 0.5, 24)
result = fit(y, Z, draws=200, warmup=200, chains=2, seed=17)
print(result.summary())
curve = univariate_response(result, variable=0, points=25, seed=17)
ax = plot_response(curve)
```

Example output (first rows):

```
BKMRFit(family='gaussian', n=24, exposures=2, chains=2, draws=200)
95% pointwise credible intervals
Parameter             Mean         SD      Lower      Upper
lambda               16.93      9.047      4.145      38.61
sigma2              0.2159    0.08346     0.1142     0.4188
```

These short sampling runs, called chains, trigger mixing warnings: they may not explore the fitted distribution well enough. For an analysis, use longer runs and inspect agreement between chains and effective sample size, which accounts for dependence between saved draws.




Figure 1: Exposure response curve with pointwise 95% credible intervals

The curve changes the first exposure while holding the second at its sample median. It shows the difference from the fitted exposure function when both exposures are at their medians. It shows an association, not an identified causal effect.

1.3 Documentation

Need	Guide
Run an analysis	Tutorial, observed ozone example
Choose a model	Equations and assumptions, structured models
Find a function	API reference
Check the evidence	Verified results and open gaps, development checks
Read offline	Reference manual

The full Gaussian process (GP) model describes how exposure-function values vary together. Its dense matrix calculations limit practical sample size. Finite GP bases represent the function with fewer terms; they approximate the full model and can change uncertainty estimates. Group selection permits at most one active exposure per group. Survival uses a piecewise-exponential likelihood. Priors differ between default and structured fits; consult the model guides. Diagnostics cannot prove convergence or validate assumptions.

1.4 References and license

The method is due to Bobb et al. (2015). The software and binary-outcome extension are described by Bobb et al. (2018). KernelMix is a separate Python implementation. Selected Gaussian/probit calculations, including random intercepts, are checked at fixed parameter values against R `bkmr` 0.2.2. See NOTICE for attribution and LICENSE for GPL-2.0-only terms.

Count and survival models use additional standard likelihoods documented in the model guide.

2 Model and interpretation

2.1 Continuous outcomes

Following Bobb et al. (2015), we separate the exposure function from linear adjustment for other measured variables:

$$Y_i = h(\mathbf{z}_i) + \mathbf{x}_i^{\mathsf{T}}\boldsymbol{\beta} + \epsilon_i, \qquad \epsilon_i \overset{\text{iid}}{\sim} N(0, \sigma^2).$$

Here, Y_i is the outcome, $\mathbf{z}_i$ contains the M exposures, $\mathbf{x}_i$ contains adjustment covariates, and $\boldsymbol{\beta}$ contains their coefficients. The error ϵ_i is independent normal noise with variance σ^2. The function h allows curved exposure associations and interactions, where the association with one exposure depends on another. An exposure profile is a row of exposure values. A Gaussian process (GP) prior describes how values of h vary together across profiles before using the outcome data. At the observed profiles, this prior is

$$\mathbf{h} = (h_1, \ldots, h_n)^{\mathsf{T}} \sim N(\mathbf{0}, \tau\mathbf{K}_{Z,\mathbf{r}}), \qquad K(\mathbf{z}, \mathbf{z}'; \mathbf{r}) = \exp\left\{-\sum_{m=1}^{M} r_m (z_m - z'_m)^2\right\}.$$

Here $h_i = h(\mathbf{z}_i)$, n is the observation count, τ controls prior variation in h, and $\mathbf{K}_{Z,\mathbf{r}}$ is the matrix of kernel values between observed profiles. The kernel measures similarity between profiles. The relevance parameters $r_m \geq 0$ determine how strongly each exposure changes that similarity. An exposure with $r_m = 0$ does not affect h. In the default marginalized Gaussian sampler, `lambda` is $\lambda = \tau/\sigma^2$. Integrating out $\mathbf{h}$ gives covariance $\sigma^2(\mathbf{I} + \lambda\mathbf{K}_{Z,\mathbf{r}})$. Here $\mathbf{I}$ is the identity matrix. Integrating out $\mathbf{h}$ means accounting for its distribution without sampling each of its values during parameter fitting.

The code uses the following names for the paper's quantities. The meaning of `lambda` depends on the fitting route.

Paper quantity	Meaning	API name
$\mathbf{z}_i$, $\mathbf{x}_i$	Exposure and adjustment rows	Rows of `Z` and `X`
h, $\boldsymbol{\beta}$	Exposure function and adjustment coefficients	`predict_h`, `beta`
σ^2, r_m	Residual variance and exposure relevance	`sigma2`, `r`
τ	GP covariance amplitude	Default Gaussian/probit: `lambda` stores τ/σ^2; structured and default count/survival: it stores τ directly

The structured guide defines its separate priors. Equal numerical values of `lambda` need not describe the same covariance across these routes.

2.2 Binary outcomes

With `family="binomial"`, the model uses a probit link:

$$\Pr(Y_i = 1 \mid h, \boldsymbol{\beta}) = \Phi\{h(\mathbf{z}_i) + \mathbf{x}_i^\top \boldsymbol{\beta}\}.$$

Here Φ is the standard normal cumulative distribution function. The latent normal scale is the underlying normal variable whose threshold determines the binary outcome. Its residual variance is fixed at one. This extension follows Bobb et al. (2018). Probability contrasts depend on both exposure profiles and adjustment covariates. They are not odds ratios. The default sampler rejects complete or quasi-complete separation: adjustment covariates that separate the outcome classes, possibly with some observations on the separating boundary. With a flat coefficient prior, the posterior can then fail to have finite total probability. Structured fits use a proper normal coefficient prior, a distribution with total probability one.

2.3 Count outcomes

For Poisson and NB2 outcomes, define

$$\eta_i = h(\mathbf{z}_i) + \mathbf{x}_i^\top \boldsymbol{\beta} + u_{c(i)}, \qquad \mu_i = \exp(\eta_i + o_i).$$

The known log offset o_i accounts for observation time or exposure amount. Without clustering, $u_{c(i)} = 0$. The Poisson model has conditional mean and variance μ_i. The NB2 model has

$$E(Y_i \mid \mu_i, \phi) = \mu_i, \qquad \mathrm{Var}(Y_i \mid \mu_i, \phi) = \mu_i + \mu_i^2/\phi, \qquad \phi > 0.$$

`dispersion` stores ϕ. Larger values approach Poisson variation. These likelihoods follow the standard Poisson and NB2 parameterizations. R `bkmr` 0.2.2 does not implement these count likelihoods.

2.4 Survival outcomes

For positive observed time t_i and event indicator d_i, the model is

$$\lambda_i(t) = \lambda_0(t)\exp(\eta_i), \qquad S_i(t) = \exp\{-\Lambda_0(t)\exp(\eta_i)\}.$$

A hazard is the instantaneous event rate among subjects still event-free. Here $\lambda_0(t)$ is the baseline hazard, $\Lambda_0(t)$ is its integral, and $S_i(t)$ is the probability of remaining event-free through time t. The linear predictor η_i is defined above without a count offset. The indicator d_i is one for an observed event and zero when follow-up ends first (right censoring). Under independent right censoring, the likelihood contribution is $\{\lambda_i(t_i)\}^{d_i} S_i(t_i)$. The model uses constant baseline rates λ_{0j} within fixed, right-closed intervals. If D_{ij} is subject i's time in interval j, $j(i)$ contains its event time, and d_j counts events in interval j, then

$$\ell = \sum_i d_i \{\log \lambda_{0,j(i)} + \eta_i\} - \sum_i e^{\eta_i} \sum_j D_{ij} \lambda_{0j}.$$

An event at a cut belongs to the interval on its left. Every event then has positive time at risk in its event interval. With independent $\lambda_{0j} \sim \text{Gamma}(a_0, b_0)$ priors, the conditional update is

$$\lambda_{0j} \mid \cdots \sim \text{Gamma}\left(a_0 + d_j,\ b_0 + \sum_i D_{ij} e^{\eta_i}\right).$$

This is a full piecewise-exponential event-time likelihood, not Cox partial likelihood. See the INLA manual, section 3.15 for the model form and the Stan survival guide for censoring contributions. KernelMix uses its own independent gamma baseline prior. Once selected, the time cutpoints are held fixed. The model does not include uncertainty from choosing them. Defaults use event-time deciles, so assess sensitivity to their number and placement. Baseline priors depend on the chosen time unit.

The likelihood above describes the default right-censored model. The structured survival interface also supports delayed entry, competing causes, predictor histories and left/interval censoring. All-censored data are accepted with a warning: the posterior then depends strongly on the priors. A fitted intercept and the baseline hazard share a scale. Separate estimates are anchored by their priors; `intercept=False` avoids adding that redundant coefficient.

2.5 Random intercepts

For the default random-intercept route, with observation-cluster index $c(i)$, independent Gaussian intercepts satisfy $u_g \sim N(0, \sigma_u^2)$. Exposures in `groups` and observations in `cluster` serve different purposes. Conditional on h, covariates and random intercepts, observations are independent under the selected outcome likelihood.

For default Gaussian/probit fits, `lambda_cluster` is σ_u^2/σ^2, with probit $\sigma^2 = 1$. The marginalized covariance is

$$\sigma^2\{\mathbf{I} + \lambda \mathbf{K}_{Z,\mathbf{r}} + \lambda_u \mathbf{J}\}, \qquad J_{ij} = 1\{c(i) = c(j)\}.$$

For count/survival fits there is no residual Gaussian variance parameter: `lambda` and `lambda_cluster` are the GP and random-intercept variances directly. The random-intercept model follows the Gaussian/probit extension described by Bobb et al. (2018). KernelMix also combines these intercepts with count and survival likelihoods.

Prediction for a known cluster uses its fitted random intercept. Equal unseen labels share a new Gaussian draw. Omitted labels fix $u = 0$; this differs from averaging predictions over the distribution of cluster effects. Random intercepts do not provide arbitrary serial correlation or cluster-robust inference. The data may provide little information to distinguish GP variation from cluster variation, particularly for constant kernels or clusters with only one observation.

2.6 Priors and exposure selection

Default Gaussian/probit priors follow R `bkmr` 0.2.2. The structured guide defines its separate priors. A prior describes parameter values before using the outcome data. Gamma distributions below use shape and **rate**. The inverse-gamma density is proportional to $(\sigma^2)^{-a-1} \exp(-b/\sigma^2)$ for shape a and parameter b.

Quantity	Default
λ and λ_u, when clustered	Gamma(1, 0.1)
σ^2, continuous outcome	Inverse-gamma(0.001, 0.001)
Active r_m	$1/r_m \sim$ Uniform$(0, 100)$
Inclusion probability π	Beta(1,1)
$\boldsymbol{\beta}$	Flat prior

Count/survival `fit(..., prior=None)` instead uses $\lambda, \lambda_u \sim \text{Gamma}(4, 4)$, independent $\boldsymbol{\beta} \sim N(\mathbf{0}, 25\mathbf{I})$, $\phi \sim \text{Gamma}(2, 0.1)$ for NB2, and $\lambda_{0j} \sim \text{Gamma}(0.1, 0.1)$ for survival. At fixed finite predictor values, the resulting prior distributions of the count mean and relative hazard have finite means and second moments. A supplied `Prior` is used as specified. A partial dictionary overlays the selected family's defaults, for example `prior={"r_distribution": "gamma"}`. Warnings identify supplied amplitude or dispersion priors for which these moment guarantees do not hold. Assess prior sensitivity; large finite moments can still be numerically unstable. `sigma2=1` is a storage convention for count/survival fits and is omitted from their summaries.

The inverse-uniform relevance prior has an unbounded upper tail. An average from a finite sampling run can be calculated even when the posterior mean of r_m does not exist. Inspect quantiles and mixing; assess prior sensitivity for the application. `Prior(r_distribution="gamma")` and `"unif"` provide other positive priors. The gamma parameters use mean and standard deviation. Uniform bounds apply to r_m for `"unif"` and to $1/r_m$ for `"invunif"`.

With component selection, $\delta_m \sim \text{Bernoulli}(\pi)$ indicates whether $r_m > 0$. Excluded exposures have $r_m = 0$. Group selection uses the groups S_g and indicator ω_g from Bobb et al. (2015): each active group contains **one** selected exposure, chosen uniformly within that group. KernelMix does not offer unequal within-group prior probabilities. A group PIP is its posterior inclusion probability; a conditional PIP is an exposure's inclusion probability given that its group is active. A never-selected group has an undefined conditional PIP. PIPs depend on the model and priors; they do not measure causal importance.

2.7 Inputs and computation

`fit` adds an intercept and standardizes exposures by default. Standardization uses the retained training mean and sample standard deviation. Prediction reuses these values. Pass `intercept=False` or `standardize=False` to disable either. Do not include a constant adjustment column when adding an intercept. R `bkmr` does not automatically apply these Python preprocessing defaults.

`missing="raise"` rejects missing data. `missing="drop"` removes rows jointly across required inputs, including applicable cluster labels, offsets and survival inputs. For recorded subject histories, it removes the whole affected history; see structured survival. Retained original row indices are stored in `result.data["rows"]`. Complete-case fitting does not correct bias caused by missing data. Covariates must be numeric; categorical encoding is the caller's responsibility.

A chain is one sampling run through the posterior distribution, which combines the data and priors. Chains run sequentially with separate random streams. `draws` counts saved draws per chain after `warmup`; `thin` controls the spacing of saved draws. Proposals are fixed during sampling. `sampling_info` records acceptance counts and runtime. The default Gaussian sampler integrates out h during parameter sampling. The default binary sampler also samples underlying normal outcomes constrained to be positive or negative according to the observed binary response. Predictions use those saved normal outcomes.

Default count/survival fits sample a noncentered GP with elliptical slice sampling, log-scale Metropolis updates and conjugate baseline updates. Eigenvalues at most $100n\epsilon \max(1, \lambda_{\max}(\mathbf{K}))$, where ϵ is machine precision, are treated as zero in numerical calculations. Eigenvalues measure variation along matrix directions; very small ones cannot be distinguished reliably from zero at machine precision. No small constant is added to the kernel diagonal (diagonal jitter). Prediction uses the same rank rule and the saved latent function. Saved auxiliary white coordinates are internal, standardized sampling variables. Their eigenvector signs can differ across platforms without changing the represented function. Archive validation checks that values lie in the supported matrix directions rather than requiring identical signs.

Structured fits instead sample the GP and other normal-prior coordinates jointly by elliptical slice sampling, with log-scale Metropolis updates for amplitudes, relevance, dispersion and survival baseline rates. Gaussian residual variance has a conditional inverse-gamma update. Their priors and covariance options are defined in the structured guide.

Dense matrix factorization requires roughly cubic work in n per parameter update: doubling the observation count can multiply this work by about eight. Working-memory checks reject oversized fitting or prediction requests; they are protective estimates, not a promise about peak process memory.

2.8 Prediction and contrasts

`predict_h` draws h jointly over requested profiles. `predict(kind="mean")` returns outcome means, binary probabilities, or relative hazards for survival. `predict_survival` gives survival probabilities or hazards on a time grid. `predict(kind="observation")` also includes new observation variation for Gaussian, binary and response-scale count predictions. Survival observation sampling is not implemented. The latent binary scale is the underlying normal scale.

A contrast is a difference between fitted values. Contrasts subtract **joint** posterior draws, which contain predictions at all compared profiles together. This preserves how their uncertainty varies together. `overall_effect` compares all-exposure quantile profiles with a reference profile. `single_exposure_effects` changes one exposure while holding the others fixed. `interaction_effects` returns a difference of two single-exposure contrasts. Curves and surfaces vary one or two exposures; others are held fixed. Their equal-tailed intervals leave the same posterior probability below and above each interval. They describe uncertainty at individual points, not a simultaneous band for a whole curve. On the response scale, adjustment covariates default to their retained training means unless `X` supplies a different profile.

A quantile profile combines a percentile chosen separately for each exposure. That combination may be uncommon when exposures are correlated. Check whether observed exposure rows are close to the requested combinations before interpreting contrasts. Causal interpretation requires additional identification assumptions; fitting a model does not supply them.

2.9 Diagnostics and scope

`diagnostics()` reports rank-normalized/folded split $\widehat{R}$, bulk effective sample size and tail effective sample size. R-hat compares sampled distributions across parts of the chains; values near one are desirable. Effective sample size accounts for dependence between draws, in the main part (bulk) or extremes (tails) of the distribution. Large $\widehat{R}$, small effective sample sizes, or constant sampled traces need investigation. Fixed parameters are excluded from these diagnostics. Trace plots and sensitivity checks remain necessary; favorable diagnostics do not prove convergence.

KernelMix supports Gaussian, probit, Poisson, NB2 and right-censored piecewise-exponential survival models with independent Gaussian random intercepts. The structured interface adds alternative kernels, finite GP bases, random slopes, Gaussian residual correlation and variance regression. It also supports delayed entry, competing causes, known covariate paths and left/interval censoring, with separate proper priors and a direct GP amplitude. See verified results and open gaps for the limits of the numerical checks and original-study reproduction.

3 An exposure-mixture analysis

KernelMix fits Bayesian kernel machine regression (BKMR) for continuous, binary, count and right-censored survival outcomes. The exposure-response function, called `h`, describes how the outcome varies with the exposures together. It can describe curved relationships and interactions, where the association with one exposure depends on another. Adjustment covariates are other measured variables included as linear terms.

This tutorial uses small, deterministic example data. Run its Python blocks in order after installing the source package as described in the README. The chains illustrate the workflow; they are too short for inference. For an analysis, use longer runs and check whether chains explore similar values (mixing). Inspect effective sample sizes, which account for dependence between draws, and whether conclusions change under other reasonable prior distributions. A prior describes parameter values before using the outcome data.

3.1 Define the data

Each row is an observation. Columns of `Z` are exposures; columns of `X` are adjustment covariates. Keep `Z` in its original units. The fit stores the training means and sample standard deviations and reuses them for prediction.

```
import numpy as np
import kernelmix as km

t = np.linspace(-1.0, 1.0, 12)
Z = np.column_stack((1.5 + t, 2.0 + np.sin(3 * t), 10.0 + np.cos(5 * t)))
X = t[:, None]
y = 0.3 + np.sin(2 * t) + 0.2 * t**2
names = ["Exposure A", "Exposure B", "Exposure C"]
```

The default adds an intercept, so `X` should not include a constant column. Missing values raise an error. Use `missing="drop"` only when analysis of complete rows is appropriate. It drops a row if its outcome, exposure or adjustment value is missing. Dropping rows does not correct bias caused by missing data.

3.2 Fit and inspect a continuous outcome

Component selection allows each exposure to enter or leave the model. Its posterior inclusion probability (PIP) is the proportion of saved draws in which that exposure is included.

```
gaussian = km.fit(
    y, Z, X,
    family="gaussian", selection="component",
    exposure_names=names, covariate_names=["Adjustment"],
    draws=12, warmup=12, chains=2, seed=19,
)
print(gaussian.summary())
parameter_rows = gaussian.summary_table()
pip_rows = gaussian.inclusion_probabilities()
checks = gaussian.diagnostics()
```

The summary describes the posterior distribution, which combines the data and priors. It gives means, standard deviations and credible intervals. A 95% credible interval contains 95% of the posterior probability for the reported quantity. Split R-hat compares the sampled distributions across parts of the chains; values near one are desirable. Effective sample sizes account for dependence between draws. These diagnostics detect some sampling problems but cannot validate the model. PIPs depend on selection priors and do not measure causal importance.

3.3 Predict at exposure profiles

An exposure profile is one row of exposure values, such as the values for one person or day. Supply new exposures in the training column order and their original units. New adjustment rows contain the raw `X` columns, without an intercept. They are required when adjustments were fitted.

```
Znew = Z[:3].copy()
Xnew = X[:3].copy()
mean_prediction = gaussian.predict(Znew, Xnew, seed=20)
observation_prediction = gaussian.predict(
    Znew, Xnew, kind="observation", seed=20,
)
h_prediction = gaussian.predict_h(Znew, seed=20)
prediction_rows = mean_prediction.to_records()
```

The default predicts outcome means. Observation predictions add residual noise and describe new outcomes. `predict_h` returns only the exposure function, without the intercept or adjustment contribution. Prediction objects retain joint draws: each saved draw contains values for all requested rows together. They also store intervals for each row and the covariance, which describes how predictions vary together. Calling `predict()` without new data uses the retained training rows and their adjustments.

3.4 Summarize exposure associations

A contrast is a difference between fitted values. Overall contrasts set every exposure to a chosen percentile of its own observed distribution, then compare that combination with a reference combination. Single-exposure contrasts change one exposure while fixing the others. These describe associations with the specified values held fixed. A causal interpretation needs additional scientific assumptions.

```
overall = km.overall_effect(gaussian, reference=0.5, seed=21)
single = km.single_exposure_effects(gaussian, seed=21)
interaction = km.interaction_effects(
    gaussian, variables=["Exposure A", "Exposure B"], seed=21,
)
curve = km.univariate_response(
    gaussian, variable="Exposure A", points=7, seed=21,
)
surface = km.bivariate_response(
    gaussian, variables=("Exposure A", "Exposure B"), points=4, seed=21,
)
overall_rows = overall.to_records()
```

By default, these summaries describe changes in `h`. Curves and surfaces hold other exposures at their medians and subtract a common all-median reference profile. A centered value of zero means no change from that reference. `center=False` returns the uncentered curve or surface. Each interval describes posterior uncertainty at one point. The collection of intervals is not a band with the same probability for the whole curve at once.

Each contrast uses joint prediction draws for the profiles being compared. This retains their covariance. A profile compared with itself has exactly zero contrast. Combining percentiles chosen separately for each exposure can create a combination rarely seen in the data, especially when exposures are correlated. Check how close the requested combinations are to observed rows before interpreting them.

3.5 Fit a binary outcome

For a binary outcome, use `family="binomial"`. The probit link converts an underlying normal-scale predictor to a probability using the standard normal cumulative distribution function. Outcomes must be zero or one.

```
y_binary = np.array([0, 1, 0, 1, 0, 1, 0, 1, 0, 1, 0, 1])
binary = km.fit(
    y_binary, Z, X,
    family="binomial", exposure_names=names,
    covariate_names=["Adjustment"],
    draws=12, warmup=12, chains=2, seed=22,
)
probability_prediction = binary.predict(Znew, Xnew, seed=23)
probability_contrast = km.overall_effect(
    binary, scale="response", X=[0.0], seed=23,
)
```

Binary mean predictions are probabilities. With `kind="observation"`, predictions are zero-or-one outcomes. A response-scale contrast subtracts predicted probabilities after applying the probit transformation to each joint draw. It is not an odds ratio. In exposure summaries, `X` is one raw adjustment vector held constant at every profile. If it is omitted, response-scale summaries use the retained training covariate means. The API calls summaries of `h` alone "latent-scale" summaries; they exclude adjustment terms and do not accept `X`.

3.6 Fit counts and include observation time

Use `"poisson"` when the count variance equals its mean after accounting for predictors and any cluster effects. Use `"negative_binomial"` to allow additional variation. An offset is the log observation time or another known exposure amount. It enters with coefficient one.

```
counts = np.array([0, 1, 0, 2, 1, 3, 1, 2, 4, 3, 5, 2])
observation_time = np.array([1, 1, 2, 1, 2, 1, 1, 3, 1, 2, 1, 1])
count_fit = km.fit(
    counts, Z, family="negative_binomial", offset=np.log(observation_time),
    draws=12, warmup=12, chains=2, seed=24,
)
count_mean = count_fit.predict(Z[:3], offset=np.log(observation_time[:3]), seed=25)
count_observation = count_fit.predict(
    Z[:3], offset=np.log(observation_time[:3]), kind="observation", seed=25,
)
```

`count_mean` describes expected counts for the supplied observation times. Observation predictions are nonnegative integer counts. Set `family="poisson"` to use the Poisson model. The negative-binomial `dispersion` parameter controls extra variation; it is separate from variation due to exposures or clusters. Response-scale exposure summaries use an offset of zero, so they compare counts per unit observation exposure. Their latent scale describes changes in `h`, which enter the log mean. These models use proper coefficient priors: distributions with total probability one. See the model guide for the defaults.

3.7 Fit right-censored survival times

Each observation supplies a positive observed time and an event indicator: `1` means the event occurred; `0` means follow-up ended first. The model uses proportional hazards: predictor effects multiply the event rate by a factor that does not change with time. The baseline hazard is the reference event rate; it is constant within each specified time interval.

```
observed_time = np.array([1.0, 1.4, 2.0, 2.6, 3.0, 3.8, 4.0, 4.7, 5.2, 6.0, 6.4, 7.0])
event = np.array([1, 0, 1, 1, 0, 1, 0, 1, 1, 0, 1, 0])
survival_fit = km.fit(
    observed_time, Z, family="survival", event=event,
    baseline_breaks=[2.0, 4.0], intercept=False,
    draws=12, warmup=12, chains=2, seed=26,
)
survival = survival_fit.predict_survival(
    Z[:2], times=np.linspace(0, 7, 30), seed=27,
)
survival_ax = km.plot_survival(survival)
log_hr = km.overall_effect(survival_fit, quantiles=[0.75], reference=0.25, seed=27)
hr_draws = np.exp(log_hr.draws)
hr_interval = np.quantile(hr_draws, [0.025, 0.975], axis=(0, 1))
```

The baseline intervals are $(0, 2]$, $(2, 4]$ and $(4, \infty)$ in this example. An event exactly at a cut belongs to the interval on its left. The model assumes independent right censoring and proportional hazards. For delayed entry, competing causes or known covariate paths, use the structured interface. Beyond observed follow-up, predictions extend the final constant baseline hazard. Such extrapolation needs scientific justification.

`predict_survival` returns survival probabilities, or hazards with `kind="hazard"`. Ordinary `predict` returns relative hazards for this family. Response-scale exposure contrasts therefore subtract relative hazards; they do not subtract survival probabilities. For hazard ratios, exponentiate each latent `h` contrast before summarizing it. The baseline and a fitted intercept share a scale, so this example omits the intercept.




Figure 2: Count response and survival probabilities. (a) Negative-binomial mean counts as z_1 varies, with offset zero. (b) Survival probabilities at the first exposure's 25th and 75th percentiles. Other exposures are fixed at their medians and $u = 0$. Shading shows pointwise 95% credible intervals.

The figure uses the data above, 200 warmup and 200 saved draws per chain, two chains, and the same seeds. Predictions use 100 draws per chain. These short fits have mixing warnings and illustrate the outputs; they do not support inference or show whether the intervals achieve their stated coverage across repeated datasets. Figure values.

3.8 Account for clustered observations

`cluster` labels observations that share a Gaussian random intercept. It is separate from `groups`, which groups exposures for selection. All five families accept `cluster`.

```
cluster = ["A"] * 3 + ["B"] * 3 + ["C"] * 3 + ["D"] * 3
clustered_fit = km.fit(
    counts, Z, family="poisson", cluster=cluster,
    draws=12, warmup=12, chains=2, seed=28,
)
intercepts = clustered_fit.random_intercepts(seed=29)
cluster_prediction = clustered_fit.predict(
    Z[:3], cluster_new=["A", "new", "new"], seed=29,
)
```

Known prediction labels use their posterior random intercept. Repeated unseen labels share one new intercept per posterior draw. Omitting `cluster_new` fixes the prediction random intercept to zero; this is not an average over clusters. The exposure summaries also use a zero random intercept. This model captures shared intercept variation. For random slopes and Gaussian residual correlation, see structured models.

3.9 Plot the results

Plotting requires Matplotlib (`[plots]`). Each function returns an axes object; the caller controls display and export.

```
trace_ax = km.plot_trace(gaussian)
pip_ax = km.plot_pips(gaussian)
curve_ax = km.plot_response(curve)
overall_ax = km.plot_overall(overall)
surface_ax = km.plot_surface(surface)

# Optional: display the figures in an interactive session.
# import matplotlib.pyplot as plt
# plt.show()
```

Curve and overall plots include pointwise posterior intervals. The surface plot displays the posterior mean only; its result object also retains lower and upper limits. Plot exposures separately when their units differ. The trace excludes warmup draws.

3.10 Save and load a fit

A fit includes its retained training data as well as saved draws. Store and share it with the same care as the input data. The archive uses a non-pickle format.

```
from pathlib import Path
from tempfile import TemporaryDirectory

with TemporaryDirectory() as directory:
    path = Path(directory) / "mixture-fit.npz"
    gaussian.save(path)
    restored = km.BKMRFit.load(path)
    restored_prediction = restored.predict(Znew, Xnew, seed=20)
```

See the API reference for argument defaults and result fields. The method is described by Bobb et al. (2015); Bobb et al. (2018) describes exposure summaries and the probit extension. KernelMix's pairwise interaction summary and median-reference curve centering are specified in the API reference.

4 Ozone and weather in New York

This exploratory example models observed ozone using solar radiation, wind and temperature. It includes source data, saved results and sampling checks. It is separate from the applications in Bobb et al. (2015).

4.1 Data and question

The R airquality data contain 153 daily records from New York, May–September 1973. Ozone was measured at Roosevelt Island, solar radiation at Central Park, and wind and temperature at LaGuardia Airport. Their measurement times also differ. These are daily environmental measurements, not personal exposures.

Variable	Role	Unit
`Ozone`	Outcome, transformed with the natural logarithm	Parts per billion
`Solar.R`	Exposure function	Langleys
`Wind`	Exposure function	Miles per hour
`Temp`	Exposure function	Degrees Fahrenheit
`Month`	Linear adjustment, May as reference	Four indicators

There are 37 missing ozone values and seven missing solar-radiation values. Keeping only rows with all required values retains 111 days and excludes 42. No missing values are filled in. The source CSV preserves all 153 records. Its provenance records the R version, hash, units and excluded row numbers.

Month	Recorded days	Complete days
May	31	24
June	30	9
July	31	26
August	31	23
September	30	29

Ozone medians are 31 ppb in complete rows and 35 ppb in the five rows missing solar radiation. Missingness is uneven across months, and ozone is unknown on 37 days. These observed ozone values do not show whether excluding incomplete days leaves the analysis unbiased.

4.2 Model and run

We use the Gaussian BKMR model with $Y_i = \log(\text{Ozone}_i)$, $\mathbf{z}_i$ containing solar radiation, wind and temperature, and $\mathbf{x}_i$ containing an intercept and four month indicators:

$$Y_i = h(\mathbf{z}_i) + \mathbf{x}_i^{\mathsf{T}}\boldsymbol{\beta} + \epsilon_i, \qquad \epsilon_i \overset{\text{iid}}{\sim} N(0, \sigma^2).$$

Exposure standardization subtracts each exposure's mean and divides by its sample standard deviation, using the 111 retained days. The Gaussian kernel uses independent $r_m \sim \text{Gamma}(1, 1)$ priors, with shape and rate equal to one. Residual variance has an inverse-gamma(2,1) prior. Priors describe parameter values before using the outcome data. Other default Gaussian priors remain in force, including the flat adjustment-coefficient prior and $\lambda = \tau/\sigma^2 \sim \text{Gamma}(1, 0.1)$. Exposure selection is disabled. Month adjustment handles coarse seasonality; independent errors are a working assumption, not a verified property of the daily series.

From the source folder, with KernelMix and its plotting extra installed:




Figure 3: Availability of all 153 daily records. (a) Recorded measurements and missing values, marked by crosses. (b) Recorded and complete days by month; 111 days have all four variables.




Figure 4: Observed ozone against solar radiation, wind and temperature for the 111 complete days. Each point is one day, without smoothing or adjustment for month.

```
python tools/analyze_airquality.py --draws 20000 --warmup 5000 --output ozone-results
python tools/plot_airquality.py --results ozone-results --output ozone-figure
```

Four chains run sequentially with seed 73. Each has 5,000 warmup iterations and 20,000 saved draws. An initial 4,000-draw run had maximum $\widehat{R} = 1.0142$; one longer run was made to improve sampling, with the model, prior and data unchanged. This is an exploratory workflow, not a prospectively fixed study.

4.3 Results and checks

Check	Recorded result
Maximum rank/folded split $\widehat{R}$	1.0053
Minimum bulk effective sample size	885
Minimum tail effective sample size	1,193
Consecutive-day residual pairs	92
Correlation of consecutive-day fitted residuals	0.0136
Fitting time on the recorded local environment	72.6 seconds

Diagnostics cover ten individual parameters using all saved draws. R-hat compares chains, and effective sample size accounts for dependence between draws. These checks do not prove convergence of every curve. Curves and fitted residuals use 400 evenly spaced states per chain. The residual correlation cannot establish independence. Fitted-versus-observed values use training data, not held-out observations.




Figure 5: Ozone example: (a–c) posterior means and 95% pointwise credible intervals for $h(\mathbf{z}) - h(\mathbf{z}_{0.5})$, with other exposures fixed at their sample medians and $\mathbf{z}_{0.5}$ the all-median profile; (d) fitted and observed log ozone; (e) residuals by date, with missing dates unconnected; (f) residual pairs one calendar day apart. Intervals assume independent Gaussian working errors.

Each displayed curve changes one weather variable while holding the others at their medians. The fitted differences increase with solar radiation and temperature and decrease with wind over much of the plotted range. These are associations on the log scale with the other variables fixed. Curve points use distinct percentiles of each variable

between the 5th and 95th percentiles. Combining these values with the other variables' medians can still give combinations rarely observed in the data. The curve table includes distance to the nearest observed combination of weather values after standardization. Exponentiating a log-scale difference gives a ratio of fitted ozone medians under this model, at the specified weather and month values. It does not give a difference in arithmetic means.

4.3.1 Parameter estimates

The relevance parameters r_m enter the kernel; β contains adjustment coefficients. Their scales and meanings differ. Points below are posterior means; bars are 95% equal-tailed credible intervals under the fitted model.




Figure 6: Posterior means and 95% equal-tailed credible intervals. (a) Exposure relevance r_m. (b) Month coefficients in β, relative to May, on the log-ozone scale. The intercept is omitted. Relevance does not measure causal importance.

4.3.2 Sampling checks

Bulk effective sample size concerns the main posterior distribution; tail effective sample size concerns its tails. The figure shows all ten parameters rather than only the least favorable summary.

4.3.3 Distance from observed exposure combinations

A curve point can combine an exposure value with medians of other exposures that were rarely recorded together. The distance below measures how far that combination is from the nearest observed combination. It uses training standard deviations to put the exposure axes on a common scale; no cutoff declares a prediction reliable.

The plotting script regenerates these five additional figures from saved tables without refitting:

```
python tools/plot_airquality_details.py
```

4.4 Reuse and limits

The results record, parameter summaries, diagnostics, curve values and dated observations/residuals accompany the runnable scripts. R is not required to run the analysis. Maintainers can regenerate the source CSV with `Rscript tools/export_airquality.R destination.csv`; the recorded export uses R 4.5.0.

Missingness, measurement differences, priors and serial dependence limit interpretation. This example establishes neither causal effects nor time-series interval coverage. Original-study reproduction and external research use remain separate evidence gaps; see reference studies.




Figure 7: Sampling diagnostics from four chains, each with 20,000 saved draws. (a) Rank-normalized/folded split $\widehat{R}$. (b) Bulk effective sample size. (c) Tail effective sample size. These checks do not establish convergence or validate the model.




Figure 8: Nearest observed-combination distance along each saved curve grid, after standardizing exposures. Other exposures remain at their medians. There are 21 solar-radiation, 17 wind and 21 temperature locations; tied percentile values were removed. Distance describes data proximity, not model validity.

5 Structured models and Gaussian process approximations

These options change how the exposure function, cluster effects, residual errors or survival records are modeled. A Gaussian process (GP) describes how exposure-function values vary together. A finite GP basis represents that function with a limited set of terms. Selecting one returns a `StructuredFit`, with the priors defined below. A prior describes parameter values before using the outcome data. The exposure model follows Bobb et al. (2015) and the 2018 extension; the additional structures have separate definitions.

Run these blocks in order. Their eight observations and four warmup/saved draws per chain illustrate the interface. For inference, use longer runs, sampling diagnostics, checks with other reasonable priors, and checks that requested exposure combinations are represented in the data.

```
import numpy as np
import kernelmix as km

x = np.linspace(-1.0, 1.0, 8)
visit = np.tile(np.arange(4), 2)
cluster = np.array(["a"] * 4 + ["b"] * 4)
Z = np.column_stack((2 + x, 5 + np.sin(np.arange(8))))
X = np.cos(np.arange(8))[:, None]
y = 0.3 + x + 0.2 * np.sin(2 * np.arange(8))
slope = x[:, None]
V = (x - x.mean())[:, None]
demo = dict(draws=4, warmup=4, chains=2, seed=47)
```

Supply exposures and knots in original units. Prediction reuses training standardization. Adjustment and random-slope inputs exclude the added intercept.

5.1 Choose an exposure kernel

An exposure profile is one row of exposure values. For two profiles $\mathbf{z}$ and $\mathbf{z}'$, with M exposures and relevance parameters r_m, define

$$q(\mathbf{z}, \mathbf{z}') = \sum_{m=1}^{M} r_m (z_m - z'_m)^2, \qquad r_m \geq 0.$$

The profiles use the fitted standardization when enabled. Setting $r_m = 0$ removes exposure m from the kernel.

`kernel`	Kernel at weighted squared distance q
`"gaussian"`	$\exp(-q)$
`"matern32"`	$(1 + \sqrt{6q})\exp(-\sqrt{6q})$
`"rational_quadratic"`	$(1 + q/\alpha)^{-\alpha}$

The fixed $\alpha > 0$ (`kernel_alpha`) defaults to one; changing it requires `kernel="rational_quadratic"`. As α increases, this kernel approaches the Gaussian kernel. These definitions follow GPML, Chapter 4 with KernelMix relevance parameters.

```
matern = km.fit(y, Z, X, kernel="matern32", **demo)
rq = km.fit(y, Z, X, kernel="rational_quadratic", kernel_alpha=1.5, **demo)
curve = km.univariate_response(matern, variable=0, points=5, seed=48)
```

Structured fits store `lambda` as the **direct GP covariance amplitude**, corresponding to Bobb's τ: $\mathbf{h} \sim N(\mathbf{0}, \tau\mathbf{K})$. This also applies to structured Gaussian fits. The default Gaussian sampler instead stores the ratio τ/σ^2. Selecting a structured model therefore changes its prior specification as well as its covariance options. Exposure contrasts describe conditional associations; causal interpretation requires additional assumptions.

5.1.1 Structured priors

Quantity	Default
Adjustment coefficients, including the intercept	Independent $N(0, 25)$; SD set by `prior.beta_sd`
Direct GP amplitude τ	Gamma(shape 4, rate 4)
Gaussian residual variance σ^2	Inverse-gamma(shape 2, rate 1)
Random-coefficient covariance	Defined in the random-effects section

A `prior` dictionary overrides supplied fields; a `Prior` object supplies every field. Check `fit.settings["prior"]` when comparing models. The `cluster_lambda_mean` and `cluster_lambda_sd` fields apply to default random intercepts, not structured random coefficients.

5.2 Reduce GP matrix size

`approximation="dense"` uses the full kernel. `"pp"` uses a predictive process: it represents the function through values at a smaller set of exposure profiles called knots. `"rff"` uses random Fourier features, a fixed set of sine and cosine terms that approximate the kernel.

```
pp = km.fit(y, Z, X, kernel="matern32", approximation="pp",
            n_components=4, **demo)
rff = km.fit(y, Z, X, kernel="matern32", approximation="rff",
             n_components=8, **demo)
pp_prediction = pp.predict(Z[:2], X[:2], seed=48)
```

For the predictive process (PP), `n_components` caps the number of automatically chosen knots, which are spread across observed exposure profiles; explicit knots can instead be supplied as `knots=Z[[0, 3, 5, 7]]`. Its covariance is $\tau \mathbf{K}_{ZU} \mathbf{K}_{UU}^{+} \mathbf{K}_{UZ}$, where U denotes the knots and $+$ is the numerical pseudoinverse, an inverse restricted to matrix directions distinguishable from zero. This representation omits the full GP's remaining variation after its knot values are known. Uncertainty can therefore be much smaller away from knots; this is the projected model described by Banerjee and colleagues, not an exact dense-GP uncertainty calculation.

For random Fourier features (RFF), `n_components` counts frequency pairs, giving twice as many features. Paired sine/cosine features follow Rahimi and Recht. Frequencies are Gaussian for the Gaussian kernel, multivariate Student-t with three degrees of freedom for Matérn, and a Gaussian/Gamma scale mixture for RQ. Each mixture scale is shared across all coordinates of one frequency vector. Base draws stay fixed throughout sampling and are saved with the fit. Inference treats this saved set of features as fixed. It does not include uncertainty from choosing a different feature set, and a fixed feature count does not establish approximation accuracy.

During fitting, PP/RFF use observation-by-feature and feature-by-feature matrices. Joint predictions and exposure contrasts still return dense matrices over the requested prediction rows; keep these requests small or use suitable batches. Large correlated Gaussian residual blocks can still require dense calculations. Dense/PP eigensystems treat eigenvalues at most `100 * dimension * machine_epsilon * largest_eigenvalue` as zero for numerical calculations. Eigenvalues measure variation along matrix directions; this threshold removes directions too small to distinguish reliably from zero. Saved dense training values and PP knot values preserve prediction coordinates across reloads.

5.3 Model random intercepts and slopes

`cluster` identifies observation groups; exposure-selection `groups` has a separate meaning. `random_slopes` adds columns after the random intercept. All five outcome families support these coefficients.

```
slopes = km.fit(y, Z, X, cluster=cluster, random_slopes=slope, **demo)
coefficients = slopes.random_effects(["a", "new"], seed=49)
intercepts = slopes.random_intercepts(["a", "new"], seed=49)
prediction = slopes.predict(
    Z[:2], X[:2], cluster_new=["a", "new"], random_slopes_new=slope[:2], seed=49,
)
fixed_slopes = km.fit(
    y, Z, X, cluster=cluster, random_slopes=slope,
    random_covariance=[[0.5, 0.1], [0.1, 0.3]], **demo,
)
```

`random_effects()` returns joint coefficient draws; `predict` combines them with the new slope design. A fixed covariance must be positive definite (every nonzero linear combination has positive variance) and match `[intercept, slopes]`. Otherwise, the full covariance is estimated.

Each standard deviation is `random_scale * Phi(raw)`, where `raw` is standard normal and `Phi` is the standard normal cumulative distribution function. Thus SDs are uniform between zero and `random_scale`, default two. Correlations are constructed from a lower-triangular matrix with normal off-diagonal entries, then normalized. This gives a proper prior, with total probability one. It is neither the named LKJ prior nor a uniform distribution over correlation matrices.

Known labels use saved coefficients. Each distinct new label receives one fresh vector per draw, shared across its rows. Omitting `cluster_new` sets random effects to zero; on nonlinear links this differs from averaging over new clusters. Supply `random_slopes_new` when predicting their contribution at new rows. Redundant random-design columns are rejected, but few clusters or little slope variation can still leave covariance estimates strongly dependent on priors.

Count/probit inputs retain their usual meanings. For example, an NB2 model can use the same slope workflow:

```
counts = np.array([0, 1, 2, 1, 0, 2, 1, 3])
nb = km.fit(counts, Z, X, family="negative_binomial", cluster=cluster,
            random_slopes=slope, approximation="rff", n_components=8, **demo)
count_means = nb.predict(Z[:2], X[:2], seed=50)
```

Count `offset` remains a log observation-exposure offset. Response predictions are count means or, with `kind="observation"`, sampled counts. Response-scale exposure contrasts use zero offset and zero random effects. Survival contrasts describe differences in relative hazards; they are not hazard ratios or survival-probability differences.

5.4 Separate Gaussian variance and correlation

With `variance_design=V`, $\mathrm{Var}(\epsilon_i \mid \sigma^2, \boldsymbol{\gamma}) = \sigma^2 \exp(\mathbf{v}_i^\mathsf{T}\boldsymbol{\gamma})$, where $\mathbf{v}_i$ is row i of V and $\boldsymbol{\gamma} \sim N(\mathbf{0}, \mathbf{I})$. No intercept is added to `V`. Its columns must be linearly independent, and no linear combination of them may produce a nonzero constant column, because `sigma2` already controls the baseline variance. This is an exponential variance model with the package's own parameterization; compare nlme's variance-function definition.

```
ar = km.fit(
    y, Z, X, cluster=cluster, variance_design=V,
    correlation="ar1", observation_time=visit, correlation_parameter=0.4, **demo,
)
future_rows = np.array([3, 7])
future_mean = ar.predict(
    Z[future_rows], X[future_rows], cluster_new=["a", "b"],
    observation_time_new=[4, 4], variance_design_new=V[future_rows], seed=51,
)
residual_variance = ar.predict_residual_variance(
    Z[future_rows], variance_design_new=V[future_rows],
)
exponential = km.fit(
    y, Z, X, cluster=cluster, correlation="exponential",
    observation_time=visit / 2, **demo,
)
```

Residual correlation requires Gaussian outcomes and clusters. Within each cluster, AR1 times must be distinct integers and exponential times distinct finite values. AR1 uses `rho**gap`, with `-1 < rho < 1`; exponential uses `exp(-gap/range)`, with positive range. See nlme's AR1 definition and exponential definition. A supplied `correlation_parameter` is fixed. Otherwise, AR1 uses `rho=tanh(raw)` and exponential uses `range=exp(raw)`, each with a standard-normal prior on `raw`.

For known clusters, mean prediction uses the fitted training residuals to predict the new residual component. Observation prediction also includes uncertainty in that component. Supply original `cluster_new` labels to condition training-row predictions; their times and slope rows are reused. Unseen or omitted labels have no training residual cross-correlation. `predict_h` and exposure contrasts do not use training residuals to predict that component.

A fixed correlation matrix must cover all original rows, have unit diagonal, be positive definite, and be zero between clusters. Supply new-by-training and new-by-new correlations to condition new residuals:

```
R = np.where(cluster[:, None] == cluster[None, :],
             0.3 ** np.abs(visit[:, None] - visit[None, :]), 0.0)
fixed = km.fit(y, Z, X, cluster=cluster, correlation=R, **demo)
cross = np.array([
    np.where(cluster == label, 0.3 ** (4 - visit), 0.0)
    for label in ("a", "b")
])
fixed_prediction = fixed.predict(
    Z[future_rows], X[future_rows], cluster_new=["a", "b"],
    correlation_cross=cross, correlation_new=np.eye(2), seed=52,
)
```

With fixed correlation and no custom cross matrix, new residuals are independent of training residuals. The combined training/new correlation must be positive semidefinite: no linear combination may have negative variance. Residual variance predictions exclude uncertainty in the GP and random coefficients. Random effects and long-range residual correlation can be hard to distinguish with sparse repeated measurements.

5.5 Encode delayed entry and competing events

Delayed entry means observation starts after the time origin; the subject must remain event-free until entry to be included. Competing causes are different types of first event. For survival, `y` is an exact event time, a right-censoring time, or an interval lower bound. `event=0` means right censoring; positive integers `1..n_causes` identify causes. The first terminal event is modeled; recurrent events and general state transitions are excluded. Baseline intervals are right closed, so an event exactly at a cut belongs to its left interval.

```
time = np.array([0.8, 1.4, 2.2, 3.2, 1.1, 1.9, 2.8, 3.6])
event = np.array([1, 0, 2, 1, 0, 2, 0, 1])
entry = np.array([0.0, 0.2, 0.5, 0.4, 0.1, 0.3, 0.6, 0.2])
survival = km.fit(
    time, Z, X, family="survival", event=event, entry=entry, n_causes=2,
    baseline_breaks=[1.5, 2.5], intercept=False, **demo,
)
times = np.array([0.0, 1.0, 2.0, 3.0, 4.0])
s = survival.predict_survival(Z[:2], X[:2], times=times, entry=0.2, seed=53)
cif = survival.predict_cumulative_incidence(Z[:2], X[:2], times=times, entry=0.2, seed=53)
cause_two = survival.predict_cumulative_incidence(
    Z[:2], X[:2], times=times, cause=2, entry=0.2, seed=53,
)
hazard_two = survival.for_cause(2).predict_survival(
    Z[:2], X[:2], times=times, kind="hazard", entry=0.2, seed=53,
)
cause_contrast = km.overall_effect(survival.for_cause(2), seed=53)
```

For cause k, the hazard is $\lambda_k(t \mid \mathbf{z}_i, \mathbf{x}_i) = \lambda_{0k}(t) \exp\{h_k(\mathbf{z}_i) + \mathbf{x}_i^\top \boldsymbol{\beta}_k\}$, with random-coefficient terms added when supplied. Cause-specific functions and parameters have independent priors conditional on shared exposure relevance and selection. Posterior dependence can remain through shared parameters and interval-censored likelihoods.

Survival is the probability of no event of any cause. A cumulative incidence function (CIF) is the probability of a particular cause occurring by a time, accounting for all competing causes. Joint draws satisfy survival plus the sum of CIFs equals one. This distinction is explained in the R survival competing-risk guide. `cif` retains all causes; `cif.for_cause(2)` selects one. A fit's `for_cause(2)` view instead selects its exposure function, relative-hazard predictions and contrasts. `km.plot_survival(cause_two)` plots a selected CIF with pointwise intervals when Matplotlib is installed.

Prediction `entry` describes subjects known to be event-free through that time; before it, survival is one and CIFs are zero. Static-profile prediction extends the final baseline hazard beyond follow-up. Baseline cuts are held fixed; their selection uncertainty is excluded. A survival intercept and baseline share a scale, so `intercept=False` is useful unless their separate prior-dependent roles are intended.

Delayed-entry fits describe subjects included after surviving to their recorded entry times, at their recorded predictor values. They do not recover risk among people who were never observed before entry, or correct for how survival to entry changes who is included. New-cluster predictions use this same model for included subjects.

5.6 Record left or interval censoring

Interval censoring means the event is known to occur between two times. Supply `upper > y` for a finite event interval. Left censoring means the event occurred before the first observation; such a record has lower bound zero and entry zero. An exact event uses `upper == y` or omits `upper`; right censoring uses `event=0` and may use infinite upper bound. Unknown cause `event=-1` is allowed only for a finite interval. Set `n_causes` explicitly when all observed interval causes are unknown. These inputs use explicit KernelMix codes rather than the alternative status codes of R's Surv.

```
lower = np.array([0.0, 1.4, 1.8, 3.2, 1.1, 1.5, 2.8, 3.0])
upper = np.array([0.8, np.inf, 2.2, 3.2, np.inf, 1.9, np.inf, 3.6])
interval_event = np.array([1, 0, 2, 1, 0, -1, 0, 1])
interval = km.fit(
    lower, Z, X, family="survival", event=interval_event, upper=upper,
    entry=np.zeros(8), subject=np.arange(8), n_causes=2,
    baseline_breaks=[1.5, 2.5], intercept=False, **demo,
)
```

The likelihood assumes that censoring and inspection times provide no further information about event risk after accounting for modeled information. It also assumes that missing cause labels are ignorable after that information is considered. Summing over unknown causes does not model a recording process that depends on the cause itself. An interval row assumes its supplied predictors apply throughout the uncertain event interval.

5.7 Supply known covariate paths

Repeated `subject` labels identify successive `(entry, y]` risk intervals. Rows must follow time order, meet without gaps, and not overlap within a subject; only its last row may have an event or a finite censoring interval. Later row starts split an existing history rather than representing new cohort entry. Known subject histories with missing required values are dropped as a whole under `missing="drop"`; this preserves recorded histories but does not remove missing-data bias.

```
subject = np.repeat(np.arange(4), 2)
start = np.tile([0.0, 1.0], 4)
stop = np.tile([1.0, 3.0], 4)
path_event = np.array([0, 1, 0, 0, 0, 2, 0, 1])
path_fit = km.fit(
    stop, Z, X, family="survival", event=path_event, entry=start,
    subject=subject, n_causes=2, baseline_breaks=[1.5, 2.5],
    intercept=False, **demo,
)
path_inputs = dict(start=start, stop=stop, subject_new=subject,
                   times=[0.0, 1.0, 2.0, 3.0], seed=54)
path_survival = path_fit.predict_survival_path(Z, X, **path_inputs)
path_cif = path_fit.predict_survival_path(
    Z, X, kind="cumulative_incidence", **path_inputs,
)
path_cause_two = path_fit.predict_survival_path(
    Z, X, kind="cumulative_incidence", cause=2, **path_inputs,
)
```

Paths must cover requested times; the final row is never extended. `kind="hazard"` returns cause-specific hazards. Output follows first occurrence of `subject_new`. Repeated cluster labels share a random vector across intervals.

Predictors must be known before their risk interval. Do not copy event-time or later measurements backward. Paths are neither interpolated nor forecast. Draws are joint across times and causes; credible intervals are pointwise.

5.8 Set starting values

Structured `initial` dictionaries accept `beta`, `gp_weight`, `r`, `delta`, `pi`, `lambda` and `sigma2`; NB2 adds `dispersion` and survival adds `baseline_hazard`. Omitted values receive defaults. With K causes (one for nonsurvival models; this dimension label is distinct from the kernel matrix $\mathbf{K}$), p adjustment coefficients including the intercept, and b retained basis coordinates:

Key	Required shape and restriction
`beta`	(K, p); a length-p vector is also accepted when $K = 1$
`gp_weight`	(K, b); a length-b vector is also accepted when $K = 1$
`r`, `delta`	One value per exposure; relevance and zero/one inclusion must agree
`lambda`	Positive scalar or length-K vector of direct amplitudes
`sigma2`	Positive scalar; fixed at one outside Gaussian models
`pi`	Inclusion probability; one without selection
`dispersion`	Positive scalar for NB2
`baseline_hazard`	Positive (K, J) array for J baseline intervals

Random coefficients, covariance coordinates, variance coefficients and inferred residual-correlation coordinates start at their internal defaults. Those internal sampling variables cannot be set through `initial`. Dense basis dimension is the retained observation count, PP dimension is the knot count, and RFF dimension is twice `n_components`; numerical null columns are retained. Omit `gp_weight` to use zero starting coordinates.

Saved structured arrays have leading `(chain, draw)` axes. They include cause-indexed `beta`, `lambda` and `gp_weight`, shared `r`, `delta` and `pi`, and Gaussian `sigma2`. Dense/PP fits retain coordinate-independent `gp_anchor` values; RFF fits retain their frozen feature map. Applicable models also save `random_coeff`, `random_covariance`,

gamma, correlation_parameter, dispersion and baseline_hazard. Use result methods for prediction rather than interpreting internal coordinates as exposure effects.

6 API reference

Import the public API with import kernelmix as km. Arrays are NumPy arrays; pandas is not required. Examples that connect these functions are in the tutorial. An exposure profile means one row of exposure values. A posterior draw is one sampled set of values from the fitted distribution, which combines data and priors. See the model guide for equations and the mapping between paper symbols and API names.

6.1 Fitting

```
km.fit(
    y, Z, X=None, *, family="gaussian", draws=1000, warmup=1000,
    chains=4, thin=1, seed=None, standardize=True, intercept=True,
    selection="none", groups=None, prior=None, r_fixed=None, missing="raise",
    exposure_names=None, covariate_names=None, initial=None, proposal_scales=None,
    cluster=None, offset=None, event=None, baseline_breaks=None,
    kernel="gaussian", kernel_alpha=1, approximation="dense", n_components=32,
    knots=None, random_slopes=None, random_covariance=None, random_scale=2,
    correlation=None, observation_time=None, correlation_parameter=None,
    variance_design=None, entry=None, upper=None, subject=None, n_causes=None,
)
```

Returns BKMRFit, or its StructuredFit subclass when a structured option is selected. Structured models defines the additional inputs, priors, shapes and predictions.

Family	Required outcome inputs	Mean or probability
Gaussian	Numeric y	Continuous outcome mean
Binomial	y equal to 0 or 1	Probit probability
Poisson / negative binomial	Nonnegative integer y; offset when needed	Count mean, including the log offset
Survival	Default: positive observed times and binary event; structured: cause codes, entry and censoring bounds	Relative hazard from predict; survival/hazard from predict_survival

cluster supplies one string or integer label per observation. Missing labels participate in missing="drop". Integer 1 and string "1" are distinct. offset is a finite vector of log observation exposures for count families. event is required only for survival; baseline_breaks supplies internal positive, strictly increasing cuts. Omit cuts to use event-time deciles, or pass [] for a constant baseline hazard. Family-specific arguments are rejected elsewhere.

Input	Meaning
y, Z, X	Outcome vector, exposure matrix and optional adjustment matrix, with matching rows. Supply raw adjustment columns without an intercept when intercept=True.
family	"gaussian", "binomial" (probit), "poisson", "negative_binomial" (NB2) or "survival" (piecewise-exponential proportional hazards).
draws, warmup, chains, thin	Saved draws per chain, discarded iterations, sequential chains and spacing between saved draws. Total iterations per chain are warmup + draws * thin. At least two saved draws are required.

Input	Meaning
`seed`	Nonnegative integer or `None`; uses local random generators without changing NumPy's global random state.
`standardize`	Center exposures and divide by retained-training sample standard deviations. Constant exposures are invalid when this is enabled.
`selection`	`"none"`, `"component"` or `"group"`. Group selection requires one `groups` label per exposure and permits at most one active exposure in each included group.
`prior`	`Prior`, a dictionary of its fields, or `None` for defaults.
`r_fixed`	Finite nonnegative vector fixing exposure relevance values; disallows variable selection.
`missing`	`"raise"` or joint complete-case `"drop"`. Infinity remains invalid except for right-censoring upper bounds.
Names	Optional unique names for exposure and raw adjustment columns. Otherwise use input DataFrame columns, or generated names.
`initial`	Shared starting values; omitted entries use defaults. See initialization.
`proposal_scales`	Fixed positive log-scale proposal SDs, default `0.3`. All routes accept `r` and `lambda`; default clustered fits add `cluster_lambda`, NB2 adds `dispersion`, and structured survival adds `baseline_hazard`.

The adjustment columns must be linearly independent, with fewer columns than retained rows. Default probit fits reject complete or quasi-complete separation, where adjustment covariates separate the binary classes, possibly with some observations on the separating boundary. A flat coefficient prior can then give a posterior without finite total probability; structured fits use a proper normal prior, with total probability one. Dense fitting uses $O(n^2)$ memory and $O(n^3)$ matrix operations, where n is the retained observation count. Finite GP bases reduce that cost, but correlated residual blocks may remain dense.

6.1.1 Initialization

Fitting route	`initial` keys
Default Gaussian/probit	`beta`, `r`, `lambda`, `delta`, `pi`, `sigma2`; probit adds `ystar`
Default count/survival	`beta`, `r`, `lambda`, `delta`, `pi`, `latent_white`; NB2 adds `dispersion`, survival adds `baseline_hazard`
Default clustered fits	Add `lambda_cluster`; count/survival also add `u_white`
Structured	Cause-indexed coefficients and `gp_weight`; see shapes and restrictions

Inapplicable keys raise errors.

6.1.2 Prior configuration

```
km.Prior(
    r_distribution="invunif", r_mean=5.0, r_sd=5.0,
    r_lower=0.0, r_upper=100.0, lambda_mean=10.0, lambda_sd=10.0,
    sigma2_shape=0.001, sigma2_rate=0.001,
    inclusion_alpha=1.0, inclusion_beta=1.0,
    cluster_lambda_mean=10.0, cluster_lambda_sd=10.0, beta_sd=5.0,
    dispersion_shape=2.0, dispersion_rate=0.1,
    baseline_shape=0.1, baseline_rate=0.1,
)
```

`r_distribution` accepts `"gamma"`, `"unif"` and `"invunif"`. The inverse-uniform option places the uniform distribution on `1/r`, so its bounds apply to the reciprocal of an active relevance value. Excluded exposures have relevance zero. Relevance and amplitude gamma priors use mean/standard-deviation (SD) fields. Dispersion and baseline gamma priors use shape/rate fields; Gaussian residual variance uses inverse-gamma shape/rate. Inclusion probabilities use a beta-distribution prior. A prior describes parameter values before using the outcome data. The model guide defines these distributions and their parameters.

For the default count/survival sampler, `prior=None` uses `lambda_mean=1`, `lambda_sd=.5`, `cluster_lambda_mean=1`, `cluster_lambda_sd=.5`; the other fields retain their listed defaults. A dictionary overlays family defaults. A `Prior` object supplies all its values explicitly, including its listed amplitude defaults. `beta_sd` controls the proper coefficient prior for count/survival. Dispersion and baseline parameters use gamma shape/rate. Structured priors use a direct GP amplitude and separate Gaussian residual-variance defaults.

6.2 Structured model results

Task	Method or helper
Exact alternative kernels	`kernel_matrix(Z1, Z2=None, r=None, *, kernel="gaussian", alpha=1)`
Intercept/slope coefficient draws	`fit.random_effects(cluster_new=None, ...)`
Gaussian residual variances	`fit.predict_residual_variance(Znew=None, variance_design_new=None, ...)`
Cause-specific h and effect summaries	`fit.for_cause(cause)`
Competing-risk probabilities	`fit.predict_cumulative_incidence(..., times=..., cause=None)`
Time-varying predictor paths	`fit.predict_survival_path(..., start=..., stop=..., subject_new=..., times=...)`

`StructuredFit` retains the shared summary, sample, diagnostic, contrast and save/load methods. `RandomCoefficientPrediction` stores coefficient draws; `CompetingRiskPrediction.for_cause(k)` returns a curve accepted by `plot_survival`. Additional inputs, initialization shapes and runnable examples are in the structured guide.

6.3 Fit results and diagnostics

`BKMRFit` stores `data`, `samples`, `settings` and `sampling_info`, with `family`, `exposure_names` and `covariate_names` properties. Stored arrays are read-only; extracted samples are independent copies.

Method	Return and use
`fit.summary(probability=0.95)`	Text summary of parameter means, SDs, equal-tailed intervals, available posterior inclusion probabilities (PIPs) and diagnostic messages.
`fit.summary_table(probability=0.95)`	List of dictionaries with `parameter`, `mean`, `sd`, `lower`, `upper`.

Method	Return and use
`fit.posterior_samples(parameter=None, combine_chains=False)`	Dictionary of arrays, or one named parameter array. Leading axes are chain and retained draw; combining chains merges those axes.
`fit.inclusion_probabilities()`	Exposure names and PIPs for selection fits. Group fits also return group PIP and within-group conditional PIP; the conditional value is undefined (`NaN`) if a group was never selected. Raises without selection.
`fit.diagnostics()`	Parameter diagnostics and messages. Uses rank-normalized/folded split R-hat and bulk/tail effective sample sizes.
`fit.save(path)`	Save training data, settings and states in a compressed non-pickle archive. Replaces the destination atomically.
`km.BKMRFit.load(path, *, max_bytes=512 * 1024 * 1024)`	Load and validate an archive, limiting total uncompressed member size.
`km.diagnose(values)`	Diagnostics for one finite scalar-parameter array shaped `(chains, draws)`.

An equal-tailed interval leaves the same posterior probability below and above it. A PIP is the fraction of saved draws in which an exposure or group is included. R-hat compares chains; bulk and tail effective sample sizes account for dependence between draws in the main part and extremes of the distribution.

Default-route saved parameters include `beta`, `r`, `lambda`, `sigma2`, `delta` and `pi`; its binary fits also retain `ystar`. Structured arrays are described in the structured guide. `delta` records exposure inclusion. `beta` includes the added intercept when fitted. No-selection fits store `pi=1`. Diagnostics cannot establish model validity; R-hat requires multiple chains and short or constant sequences can yield undefined diagnostics.

6.4 Prediction

```
fit.predict_h(Znew=None, *, probability=0.95, max_draws=None, seed=None)
fit.predict(
    Znew=None, Xnew=None, *, kind="mean", scale="response",
    probability=0.95, max_draws=None, seed=None, offset=None, cluster_new=None,
)
fit.posterior_moments_h(Znew=None, max_draws=None)
```

Supply exposures in original units and training column order; named columns must match. Prediction reuses training standardization. New profiles require `Xnew` when adjustments were fitted, without the added intercept. Omitting new data uses retained training rows.

Call	Quantity
`predict_h`	Joint draws of `h`, excluding linear adjustment and all random effects.
`predict(..., kind="mean", scale="response")`	Gaussian/count means, binary probabilities, or survival relative hazards.
`predict(..., kind="observation", scale="response")`	Gaussian, binary or count future observations; survival is unsupported.
`predict(..., kind="mean", scale="latent")`	`h` plus linear adjustment and requested random effects, before link transformation; count offsets are included. Correlated Gaussian means also condition on training residuals.
`predict(..., kind="observation", scale="latent")`	Gaussian outcomes or binary latent outcomes including residual noise; binary residual variance is one. Count/survival latent observation draws are unsupported.
`posterior_moments_h`	Dictionary with deterministic integrated `mean` and `covariance` for `h`, averaging conditional moments over saved draws.

`max_draws` selects evenly spaced states **per chain** (at least two), without refitting. `seed` controls prediction draws. A `Prediction` stores `draws` shaped `(chains, selected_draws, rows)`, `mean`, `sd`, `lower`, `upper`, joint `covariance`, `probability`, `scale` and `kind`. `to_records()` gives one summary per row. Intervals are equal-tailed and pointwise: each describes uncertainty for one row, rather than for all rows at once. Observation intervals also include new outcome variation.

6.5 Cluster and survival results

```
fit.random_intercepts(cluster_new=None, *, probability=.95, max_draws=None, seed=None)
fit.predict_survival(
    Znew=None, Xnew=None, *, times, kind="survival", cluster_new=None,
    probability=.95, max_draws=None, seed=None,
)
km.plot_survival(prediction, row=0, ax=None)
```

`random_intercepts` returns a `Prediction` in training-cluster order, or supplied label order. Known and unseen labels follow the policy below.

Survival result	Meaning
`times`	Finite, nonnegative, strictly increasing prediction times
`draws`	Array with axes `(chain, draw, row, time)`
`mean`, `sd`, `lower`, `upper`	Arrays shaped `(row, time)`
`probability`, `kind`	Interval probability and survival/hazard scale
`to_records()`	One summary per profile/time pair

`kind="hazard"` evaluates hazards on the grid. Plots use survival curves or hazard points with intervals; they do not invent hazard steps between times.

`predict` additionally accepts `offset=None` and `cluster_new=None`. For training count prediction, omitted offsets reuse retained offsets. For new rows, offsets are required if they were supplied during fitting. Response-scale count observations are Poisson or NB2 draws. Latent count observations and survival observation draws are unsupported and raise an error.

Omitted `cluster_new` sets random effects to zero, including for training predictions. Known labels use their fitted cluster coefficients; unseen labels receive new Gaussian coefficients. Equal labels share a draw. `predict_h`

excludes random effects. For slopes and residual conditioning, see structured prediction. Default Gaussian/probit prediction samples `h + u` jointly when labels are supplied, preserving posterior covariance.

For the default count/survival route, samples include `h` and auxiliary `latent_white`; negative-binomial fits also include `dispersion`; survival fits include `baseline_hazard`. Default-route clustered fits include `lambda_cluster`, and count/survival fits also retain `u`. Default Gaussian/probit random intercepts are integrated out while fitting and drawn conditionally by `random_intercepts`. `sigma2=1` is only a shared latent convention for count/survival and is omitted from their summaries. Saved white coordinates are internal standardized sampling variables tied to a matrix decomposition. Use saved `h` for prediction that can be transferred across platforms.

6.6 Exposure contrasts and curves

A contrast is a difference between predictions. A quantile profile combines a chosen percentile of each exposure's own observed distribution. For example, the all-median profile sets each exposure to its own median. Such a combination need not be common in the observed rows.

```
km.overall_effect(
    fit, quantiles=(0.25, 0.5, 0.75), reference=0.5, scale="latent",
    X=None, probability=0.95, max_draws=None, seed=None,
)

km.univariate_response(
    fit, variable=None, grid=None, points=50, fixed_quantile=0.5,
    center=True, scale="latent", X=None, probability=0.95,
    max_draws=None, seed=None,
)

km.bivariate_response(
    fit, variables=(0, 1), grids=None, points=20, fixed_quantile=0.5,
    center=True, scale="latent", X=None, probability=0.95,
    max_draws=None, seed=None,
)

km.single_exposure_effects(
    fit, quantiles=(0.25, 0.75), fixed_quantiles=(0.25, 0.5, 0.75),
    scale="latent", X=None, probability=0.95, max_draws=None, seed=None,
)

km.interaction_effects(
    fit, variables=None, quantiles=(0.25, 0.75), fixed_quantile=0.5,
    scale="latent", X=None, probability=0.95, max_draws=None, seed=None,
)
```

Function	Quantity and result
`overall_effect`	Each all-exposure quantile profile minus the all-exposure `reference` profile. Returns `EffectResult`.
`univariate_response`	One named or zero-based indexed exposure, or all exposures with `variable=None`. Other exposures stay at `fixed_quantile`. Returns one joint `CurveResult`.
`bivariate_response`	Every combination of the supplied grid values for two distinct exposures. Other exposures stay at `fixed_quantile`. Returns `SurfaceResult`.
`single_exposure_effects`	High-minus-low quantile contrast for each exposure at every background `fixed_quantiles` value. Returns `EffectResult`.
`interaction_effects`	All unordered pairs from the selected names/indices, or all exposures by default. Returns `EffectResult`. For each pair the contrast is high/high - low/high - high/low + low/low, with other exposures fixed.

Quantiles use retained original training exposures and lie in `[0, 1]`. Default grids span the observed range; explicit grids must be finite, nonempty and strictly increasing. An all-variable curve shares one supplied `grid`; a surface uses one sequence per axis in `grids`. Dense joint calculations limit calls to 4096 output locations.

With `center=True`, curves and surfaces subtract the **all-median** reference profile, even if `fixed_quantile` is changed. This differs from R `bkmr` curve centering by the average fitted grid value. The pairwise interaction above also differs from the R summary that changes all background exposures together. These definitions should be specified when comparing results between packages.

Summary scale	Target
Latent	Contrasts of `h`; `X` is rejected
Response	Gaussian/count means, binary probabilities or survival relative hazards; random effects are zero
Count response	Zero log offset, representing unit observation exposure
Survival response	Differences in relative hazards, not hazard ratios or survival-probability differences

For response summaries, `X` is one raw adjustment vector and defaults to training covariate means. For each draw, predictions are transformed to the requested scale before subtraction. Joint draws keep all compared profiles together, preserving how their uncertainty varies together and exactly canceling identical profiles.

Results store `draws` shaped `(chains, selected_draws, locations)`, `mean`, `sd`, `lower`, `upper`, `scale`, `probability`, `kind` and `metadata`. `locations` labels outputs; `profiles` holds distinct original-unit rows; `coefficients` maps joint profile draws to summaries. `to_records()` combines locations and summaries. `SurfaceResult` adds `variables`, `grids` and `shape`; reshape summaries to `shape` with the second grid changing fastest.

These summaries describe associations at the specified values of the other variables. Check that nearby exposure combinations occur in the data. The intervals do not account for unmeasured confounding or a wrongly specified model.

6.7 Plotting

Matplotlib is an optional dependency and is imported only when a plot is requested.

```
km.plot_trace(fit, parameter="lambda", indices=None, ax=None)
km.plot_pips(fit, ax=None)
km.plot_response(curve, ax=None)
km.plot_overall(effect, ax=None)
km.plot_surface(surface, ax=None)
km.plot_survival(prediction, row=0, ax=None)
```

Each function returns axes, creating them when `ax=None`. The caller controls display, export and styles. Trace `indices` selects a vector component, such as `indices=0` for the first `beta`. Traces exclude warmup. PIP plots require selection.

`plot_response` accepts a univariate curve; `plot_overall` accepts an overall effect; `plot_surface` accepts a bivariate surface with at least two values on each grid. Curve and overall plots show pointwise posterior intervals. A surface shows the posterior mean only, with zero-centered colors when centered. Result objects retain its uncertainty. Request separate curves for exposures with different units.

6.8 Kernel helper

`km.gaussian_kernel(Z1, Z2=None, r=None)`

Returns the Gaussian kernel between supplied rows. `Z2=None` reuses `Z1` and `r=None` uses unit relevance. Relevance must be nonnegative. Inputs are used directly, without a fitted training transform.

6.9 Method sources

- Bobb et al. (2015), Bayesian kernel machine regression for estimating the health effects of multi-pollutant mixtures.
- Bobb et al. (2018), Statistical software for analyzing the health effects of multiple concurrent exposures via Bayesian kernel machine regression.
- Murray et al. (2010), Elliptical slice sampling.
- Stan count-distribution definitions.
- INLA manual, piecewise-constant proportional hazards (§3.15).

7 Verified results and open gaps

KernelMix implements the BKMR exposure model described by Bobb et al. (2015), with the probit and software extension described by Bobb et al. (2018). Three checks answer different questions: whether software calculations agree, whether intervals achieve their stated coverage across repeated datasets (calibration), and whether the original studies can be reproduced.

7.1 Evidence status

Check	Result and limit
Installed R bkmr 0.2.2 fixed-state comparisons	Selected Gaussian/probit means and covariances at fixed parameter values, kernel/prior calculations and inclusion summaries agree under documented conventions
Independent likelihood and conditional-posterior checks	Small examples with independently calculated answers agree within their test tolerances
Observed ozone example	A reproducible exploratory workflow on public environmental measurements
Repeated-dataset calibration	Open: systematic estimation error, interval coverage and exposure-selection performance need a separate study
Original-paper numerical reproduction	Blocked by missing original study assets and incomplete settings

The saved R comparison files use constructed parameter values, not matched sampling runs fitted in both packages. Markov chain Monte Carlo (MCMC) is the repeated sampling used to approximate the posterior. Different samplers do not produce matching chains from equal seeds. See numerical evidence for exact software versions and comparison limits.

7.2 Original-paper targets

The 2015 paper describes the following designs:

Target	Recorded design	Unresolved input
Main simulations	300 datasets per scenario; $n = 100$; three Bangladesh or 13 Boston exposure components; 10,000 iterations, last 5,000 retained	Original empirical exposure rows; complete response/noise, prior, grouping and fitting settings
Bangladesh application	375 children; log cord-blood As/Mn/Pb; motor score and specified covariate adjustment	Original analysis rows, preprocessing and full fitting settings
Dog crossover application	142 exposure records from 13 dogs; 13 elements; dog random intercepts	Original outcomes/exposures, dog IDs, exclusions, complete groups and settings

The application chains use 25,000 warmup iterations followed by 25,000 iterations, retaining every fifth draw. Original seeds remain unknown. The inspected author repository does not contain these data assets. Full supplementary settings were not recovered.

The default normal and "realistic" modes of R `SimData` generate Gaussian exposures; the latter uses a rounded covariance. The helper also offers uniform exposures. The original study instead sampled rows from observed exposure data. Substituting that generator would change the experiment and must not be labeled an exact reproduction. The NIEHS and binary examples linked from the 2018 software paper are simulated; they are not observed-data applications.

Exact reproduction needs the missing inputs and settings. The ozone example cannot replace the original studies.

7.3 Platform evidence

Environment	Evidence for the 0.3.0 runtime
Local Python 3.14, current dependencies	484 tests passed from an installed wheel
Local Python 3.11, minimum dependencies	484 tests passed from an installed wheel
Hosted Linux/Python 3.10 and 3.14; Windows/Python 3.13	Blocked before runner startup by account billing/spending limits

The main-branch check records the startup blocker. No hosted platform passed. Python 3.10 and Windows runtime compatibility remain unverified; configuration is not test evidence.

8 Checks and development

8.1 Run checks

```
python -m pip install -e ".[dev]"
python -m pytest
python -m ruff check src tests tools
python tools/check_public.py --history
python -m build
python -m twine check dist/*
```

The continuous integration (CI) configuration builds an installable wheel and tests it outside the source checkout on Linux with Python 3.10 and 3.14, and Windows with Python 3.13. The minimum-dependency job pins NumPy 1.24.0, SciPy 1.10.0 and Matplotlib 3.7.0. See the repository's Actions results for the outcome on each commit; configuration alone does not establish that a platform passed.

8.2 Numerical evidence

Check	Purpose and limit
Independent kernel and conditional-normal calculations	Check covariance, prediction and joint contrasts
Installed R `bkmr` 0.2.2	Compare constructed parameter states for Gaussian and probit models: means/covariances with those states fixed, with/without clusters, posterior inclusion probabilities (PIPs) and prior densities
Integrated Gaussian posterior	Compare sampled amplitude percentiles with numerical integration over one variable, after accounting analytically for residual variance
Probit orthant posterior	Compare sampled amplitude percentiles with an analytic likelihood for the signs of two underlying normal outcomes
Uninformative selection case	Check the beta-binomial count distribution when exposure selection cannot change the kernel
Count and survival likelihoods	Compare Poisson/NB2 mass with SciPy and survival density/censoring terms with independent arithmetic and interval splitting
Elliptical slice posterior	Check a normal posterior with a known exact answer
Poisson scalar posterior	Compare the posterior of a constant exposure function with numerical integration over one variable
NB2 dispersion / survival baseline	Check one-parameter/Gamma posterior distributions while other underlying model variables are held fixed; these do not check the full joint posterior
Seeded compatibility with 0.1.0	Saved arrays agree bitwise with 0.1.0 in six Gaussian/probit selection cases
Diagnostic examples	Detect shifted chains, autocorrelation and constant traces
Structured likelihoods	Independently check kernel and frequency calculations, joint Gaussian densities, residual predictions, censoring, cumulative incidence functions (CIFs) and predictor paths
Structured posterior targets	Constant-GP Gaussian, Poisson and delayed-entry survival targets against independent integration; amplitude held fixed for these checks
Finite-basis storage	Instrumented PP/RFF operations avoid training-size square matrices; this is not a large-dataset benchmark
Package and input checks	Exercise saved objects, preprocessing, errors, distribution contents and installed examples

The posterior tests compare sampling results with independently calculated answers. They use fixed seeds and tolerances that allow for sampling error based on effective sample size. These small checks do not establish performance across repeated datasets, general interval coverage, reproduction of the paper's studies or complete equivalence with the R API.

8.2.1 Reproduce the R fixtures

R is needed only to regenerate fixtures. Use an isolated R library with `bkmr` **0.2.2**, `jsonlite` and the dependencies declared by that version of `bkmr` (including `fields`, `truncnorm` and `tmvtnorm`). Its CRAN archive has SHA256 `7ed29f74c4c78f3b8c663eac5ec417b4ea9bc586d789e8049e3ddc51541af9af`. Set `R_LIBS` to that library, then run:

```
Rscript tools/export_reference.R tests/fixtures/r_reference.json
Rscript tools/export_cluster_reference.R tests/fixtures/r_cluster_reference.json
python -m pytest tests/test_reference.py tests/test_clusters.py
```

The exporters verify and record R/package versions. They call installed `ComputePostmeanHnew`, `ExtractPIPs`, and internal kernel/prior/covariance helpers. These fixture files contain **constructed parameter states, not fitted R sampling chains**, with explicit preprocessing and intercept columns. The R public summary API does not accept arbitrary new-cluster labels; Python h+u prediction is checked with an independent block-normal calculation. Count and survival inference has no corresponding R `bkmr` family; its evidence is separate.

The elementwise tolerance is `rtol=2e-11, atol=2e-12`. R's exact summary uses sample covariance between conditional means (denominator $S-1$); Python's finite empirical mixture uses denominator S, where S is the retained state count. The comparison adjusts this convention explicitly. Sampling proposals and random-number streams differ; equal seeds do not produce matching chains.

8.3 Observed data and original studies

The ozone example supplies data, scripts, tables and residual checks. Reference studies records its limits, original-study gaps and unresolved platform checks.

8.4 Build the manual

The editable sources are the README and Markdown pages in `docs`. Install the documentation extra and a local `pdflatex` distribution:

```
python -m pip install ".[docs]"
python tools/build_manual.py
```

Pandoc and LaTeX build the PDF; intermediate TeX is temporary. The README figure uses short illustrative chains, with values in `docs/figures/response.csv`. Its intervals describe uncertainty at individual curve points. They do not show whether the intervals achieve their stated coverage across repeated datasets.