Tutorial III.I: Recap with Caching

Programming: Everyday Decision-Making Algorithms

LECTURER
Dr. Nils Roemer, External Lecturer

AFFILIATION
Planningio GmbH

Introduction

Throughout our previous tutorials, we've explored fundamental programming concepts through the lens of everyday decision-making. Now, let's connect these concepts to another important algorithmic idea: caching.

The concepts we've learned map directly to caching principles:

- **Variables** → Like cache entries (storing specific pieces of information)
- **Comparisons** → Like cache eviction policies (what we keep/remove)
- **Lists** → Like cache storage (what we remember)
- **Loops** → Like cache maintenance (how we update our knowledge)

Throughout the three tutorials of this week, we build our **own LRU cache** step by step: today with lists and loops, in the next tutorial as functions, and in the last one we compare it with random eviction using Python packages.

> ℹ What is Caching?
>
> Remember today's lecture. Think of caching for example like your brain's short-term memory. When you frequently need certain information (like your friend's phone number), you keep it readily available instead of looking it up each time.

Section 1 - Variables and Datatypes

Just as a cache stores different types of data, Python variables can hold various datatypes. Let's explore this through a simple caching system for a coffee shop.

```
# Basic cache for coffee orders
last_order = "Latte" # String cache
drink_temperature = 75.5 # Float cache
is_favorite = True # Boolean cache
num_orders = 3 # Integer cache
```

Cache Types in Real Life

- **Strings**: Names, orders, preferences
- **Floats**: Prices, ratings, temperatures
- **Booleans**: Membership status, availability
- **Integers**: Visit counts, inventory levels

Exercise 1.1: Create a simple cache system for your favorite restaurant orders

1. Create a variable `last_meal` for the last meal you ordered (as a string)
2. Store its price in a variable `price` (as a float)
3. Whether you would order it again in a variable `would_order_again` (as a boolean)
4. How many times you've ordered it in the last month in a variable `num_orders` (as an integer)

```
# YOUR CODE BELOW
```

```
# Assertions to verify your solution
assert isinstance(last_meal, str), "last_meal should be a string"
assert isinstance(price, float), "price should be a float"
assert isinstance(would_order_again, bool), "would_order_again should be a
boolean"
assert isinstance(num_orders, int), "num_orders should be an integer"
print(f"Last meal: {last_meal}, price: {price}, would order again:
{would_order_again}, number of orders in the last month: {num_orders}")
```

Section 2 – Comparisons

Cache systems need to make decisions about what data to keep or remove. This is similar to how we use comparisons in Python. For example, the following code checks a simple eviction policy: items that were rarely used and not used for a while are removed. This is the idea behind **Least Recently Used (LRU)** from the lecture.

```
# Simple cache eviction policy
access_count = 2
last_accessed_minutes = 45

evict = False
if access_count < 5 and last_accessed_minutes > 30:
    evict = True
```

```
print(f"Based on {access_count} accesses and the last access
{last_accessed_minutes} minutes ago, should we evict? {evict}")
```

```
Based on 2 accesses and the last access 45 minutes ago, should we evict? True
```

> ⚠️ Cache Eviction
>
> Just like deciding what to remove from your phone when storage is full, cache eviction policies help determine what data to keep or remove based on usage patterns.

Exercise 2.1: Create a decision system for your favorite song

1. Write a small decision system for your **cached favorite song** `favorite_song`
2. Use at least **two conditions** based on the song's play count and last played time (`play_count` and `last_played_minutes_ago`)
3. You can set the parameters for the conditions yourself
4. Save the result of the decision in a variable `should_evict`
5. Print the result of whether we should evict the song or not

```
# YOUR CODE BELOW
```

```
# Assertions to verify your solution
assert isinstance(favorite_song, str), "favorite_song should be a string"
assert isinstance(play_count, int), "play_count should be an integer"
assert isinstance(last_played_minutes_ago, int), "last_played_minutes_ago should
be an integer"
assert isinstance(should_evict, bool), "should_evict should be a boolean"
print(f"Favorite song: {favorite_song}, play count: {play_count}, last played
minutes ago: {last_played_minutes_ago}, should evict: {should_evict}")
```

Section 3 – Lists and Tuples

Lists work like a cache's storage system, holding multiple items that we might need later. For an LRU cache, we keep the list **ordered by use**: the most recently used item at the front, the least recently used item at the end. Tuples are similar, but they are immutable. This means that once a tuple is created, its contents cannot be changed. To measure the size of a list or tuple, we can use the `len()` function.

! Think about the following code yourself!

Before running the code below, try to predict:

1. What will be in the cache after adding “Carnival of Rust”?
2. Which song will be removed?

```
# Recently played songs cache
recent_songs = ["Lithonia", "Leon", "WHEN THE MUSIC STOPS", "Chop Suey", "Rain of
Fire"]
max_cache_size = 5
new_song = "Carnival of Rust"

# Cache maintenance
if len(recent_songs) >= max_cache_size:
    popped_song = recent_songs.pop() # Remove the least recently used song
    print(f"Removed '{popped_song}' from cache")

if len(recent_songs) < max_cache_size:
    recent_songs.insert(0, new_song) # Add new song at beginning
    print(f"Added '{new_song}' to cache")

print(f"Current cache: {recent_songs}")
```

Tip

This behavior would **not have been possible with a tuple**, as we cannot change the contents of a tuple once it is created!

What if we play a song that is **already in the cache**? This is called a **cache hit**. Then we do not add it again, but move it to the front, because it is now the most recently used song:

```
recent_songs = ["Carnival of Rust", "Lithonia", "Leon", "WHEN THE MUSIC STOPS",
"Chop Suey"]
song = "Leon"

if song in recent_songs:  # cache hit
    recent_songs.remove(song)
    recent_songs.insert(0, song)

print(f"Current cache: {recent_songs}")
```

```
Current cache: ['Leon', 'Carnival of Rust', 'Lithonia', 'WHEN THE MUSIC STOPS',
'Chop Suey']
```

We can also use **lists to store tuples**, which is useful for storing multiple items with different properties. For example, we can store the name and price of items in a shopping cart.

```
# Shopping cart cache of a very expensive trip to the Apple store
shopping = [("MacBook Pro", 1999.99), ("AirPods", 159.99), ("Apple Watch",
399.99)]

print(f"Current shopping cart: {shopping}")
```

```
Current shopping cart: [('MacBook Pro', 1999.99), ('AirPods', 159.99), ('Apple
Watch', 399.99)]
```

Exercise 3.1: Create a shopping cart cache

1. Make a list `shopping_cart` of **five recently viewed items** in your shopping cart
2. Create tuples for the item details (name and price) and add them to the list
3. Ensure that the **name is a string** and the **price is a float**

> Tip
>
> First, create a list. Inside the list, the entries should be tuples of the item name and price.

```
# YOUR CODE BELOW
```

```
# Assertions to verify your solution
assert len(shopping_cart) == 5, "shopping_cart should have 5 items"
assert isinstance(shopping_cart, list), "shopping_cart should be a list"
assert all(isinstance(item, tuple) for item in shopping_cart), "All items in
shopping_cart should be tuples"
assert all(isinstance(item[0], str) and isinstance(item[1], (int, float)) for item
in shopping_cart), "All items in shopping_cart should be tuples with a string and
a number"
print("Great job! Your shopping cart is ready.")
```

Exercise 3.2: One step of an LRU cache

Your phone keeps the three most recently used apps ready in memory. The list `cache` is ordered from most to least recently used. Now you open `requested_app`. Update the cache like an LRU cache:

1. If the app is already in the cache (hit), move it to the front
2. If not (miss) and the cache is full, remove the least recently used app
3. On a miss, add the requested app at the front
4. Store whether it was a hit in a boolean variable `is_hit`

```
cache = ["Spotify", "WhatsApp", "Maps"]  # most recently used first
max_cache_size = 3
requested_app = "Camera"
# YOUR CODE BELOW
```

```
# Assertions to verify your solution
assert is_hit == False, "Camera was not in the cache, so this is a miss"
assert cache == ["Camera", "Spotify", "WhatsApp"], "Camera should be at the front
and Maps should be evicted"
print("Great job! Your cache works like an LRU cache.")
```

Section 4 - Loops

Loops are essential for cache maintenance and updates, just like how we periodically clean up our browser cache. We know two types of loops: `for` and `while`. The `for` loop is used when we know the number of iterations beforehand, while the `while` loop is used when we don't.

```
# Cache cleanup process
cached_items = [("fork", 5), ("spoon", 0), ("knife", 12)] # (item, access_count)
min_access_count = 10 # Minimum access count to keep an item

items_to_remove = []
for item, count in cached_items:
    if count < min_access_count:
        items_to_remove.append((item, count))

print(f"Items to remove: {items_to_remove}")

for item in items_to_remove:
    cached_items.remove(item)

print(f"Cached items after cleanup: {cached_items}")
```

```
Items to remove: [('fork', 5), ('spoon', 0)]
Cached items after cleanup: [('knife', 12)]
```

Exercise 4.1: Clean up a browser history cache

1. Write a loop to remove sites with low visit counts
2. If the site has been visited **less than 6 times**, remove it from the cache
3. Print the browser history after cleanup

> **Tip**
>
> Be careful with the loop. You need to iterate over the list and remove items from it. If you remove items directly from the list while iterating over it, you won't get the correct answer, as the list will change size while you iterate over it. Thus, you **first need to create a list of items to keep** and at the end replace the old list with the new one.

```
browser_history = [
    ("google.com", 10),
    ("youtube.de", 5),
    ("amazon.de", 1),
    ("netflix.de", 2),
    ("github.com", 15)
]
# YOUR CODE BELOW
```

```
# Assertions to verify your solution
assert len(browser_history) == 2, "browser_history should have 2 items"
assert isinstance(browser_history, list), "browser_history should be a list"
assert all(isinstance(item, tuple) for item in browser_history), "All items in
browser_history should be tuples"
```

Exercise 4.2: Count cache hits

Now let's run a whole sequence of app requests through our LRU cache with a loop. For every request, update the cache as in Exercise 3.2 and count the hits in `hits` and the misses in `misses`.

```
requests = ["Maps", "Spotify", "Maps", "Mail", "Camera", "Maps", "Spotify",
"Mail"]
cache = []  # start with an empty cache
max_cache_size = 3
hits = 0
misses = 0
# YOUR CODE BELOW
```

```
# Assertions to verify your solution
assert hits == 2, "There should be 2 cache hits"
assert misses == 6, "There should be 6 cache misses"
assert cache == ["Mail", "Spotify", "Maps"], "Check the order of your cache"
print(f"Great job! {hits} hits and {misses} misses, the hit rate is {hits /
len(requests):.0%}.")
```

Conclusion

Understanding these programming fundamentals through the lens of caching helps us see how computers and human decision-making often follow similar patterns. Whether we're deciding which restaurant to visit or which data to keep in memory, the principles remain surprisingly similar.

In the next tutorial, we'll turn our LRU cache into reusable functions!