Tutorial III.III: Package Management

Programming: Everyday Decision-Making Algorithms

LECTURER
Dr. Nils Roemer, External Lecturer

AFFILIATION
Planningio GmbH

Introduction

Welcome to this guided tutorial on understanding packages and package management in Python! We'll explore this concept through the lens of library management - how libraries organize, maintain, and share their resources.

Think of Python as your local library's main building. Just like a library has:

- A main collection (Python's standard library)
- Different sections (third-party packages)
- A catalog system (a package manager, in our case `uv`)
- Multiple branches (virtual environments / project folders)

In more detail

Let's break this down:

1. **Standard Library**: Like the core collection every library branch has:
   - Python comes with essential tools built-in
   - Data structures (lists, dictionaries, etc.)
   - Mathematical functions (sin, cos, sqrt, etc.)
   - Random numbers (random, choice, etc.)
2. **Third-Party Packages**: Similar to specialized sections in a library:
   - Data analysis packages (pandas, numpy) → Research section
   - Visualization packages (matplotlib, seaborn) → Art books
   - Web frameworks (Django, Flask) → Technical manuals
   - Machine learning packages (scikit-learn) → Advanced studies section
3. **Package Manager (`uv`)**: Works like the library's catalog:
   - Installing packages → Ordering new books
   - Updating packages → Replacing with newer editions
   - Uninstalling packages → Removing outdated books
   - Dependencies → "You must read Book A before Book B"
4. **Project Environments** (managed automatically by `uv`): Like different library branches:
   - Each branch can have its own collection of books (packages)
   - Different editions of the same book (package versions)
   - Specialized sections for different purposes (project-specific dependencies)

The best part? Most Python packages are free to use, thanks to the open-source community!

> **i** Note
>
> We use `uv` in this course for Python version management, virtual environments, and packages. See the separate guide for more details: uv setup.

Section 1 - Using Standard Libraries

Before we start using external packages, let's take a look at Python's standard libraries. Python comes with a set of **standard libraries that are always available**. You can use these libraries by simply importing them. For example, the `math` library provides mathematical functions like `sqrt` and `sin` and the `random` library provides functions to generate random numbers. You can import these libraries using the following syntax:

```
import math
import random
```

You can then use the functions provided by these libraries by calling them with the library name as a prefix. For example, the following code calculates the square root of 16.

```
a_square_root = math.sqrt(16)
print(f"The square root of 16 is {a_square_root}!")
```

```
The square root of 16 is 4.0!
```

The following code generates a random number between 0 and 1.

```
a_random_number = random.random()
print(f"A random number is {a_random_number}!")
```

```
A random number is 0.5739296265650886!
```

We can also use the library to choose a random element from a list. For example, the following code chooses a random element from the list `['book1', 'book2', 'book3']`. Try it out by executing the cell multiple times.

```
random_choice = random.choice(['book1', 'book2', 'book3'])
print(f"We chose {random_choice}!")
```

```
We chose book1!
```

Sometimes, we only need one function from a library. In this case, we can use the `from` keyword to import only the specific function we need. For example, the following code imports only the `randint` function from the `random` library and uses it to generate a random integer between 1 and 10.

```
from random import randint
a_random_integer = randint(1, 10)
print(f"A random integer between 1 and 10 is {a_random_integer}!")
```

```
A random integer between 1 and 10 is 6!
```

Other times, we might need to work with a library that has a rather long name. In this case, we can use the `as` keyword to give the library a shorter name. For example, the following code imports the `random` library and gives it the shorter name `rd`.

```
import random as rd
a_random_integer = rd.randint(1, 100)
print(f"Now, a random integer between 1 and 100 is {a_random_integer}!")
```

```
Now, a random integer between 1 and 100 is 57!
```

Exercise 1.1 - Use the math library

Use the `math` library to calculate the square root of 256. Call the result `square_root`.

```
# YOUR CODE BELOW
```

```
assert square_root == 16
print(f"Great job! The square root of 256 is {square_root}!")
```

Exercise 1.2 - Use the random library

Use the `random` library to generate a random number between 1 and 25. Call the result `random_number`.

```
# YOUR CODE BELOW
```

```
assert random_number >= 1 and random_number <= 25
print(f"Good! You generated a random integer {random_number} between 1 and 25!")
```

Section 2 – LRU or Random?

Now we can use the `random` package to answer a question from the lecture: is LRU really better than throwing out a random item? Here is the LRU function from the last tutorial:

```
def lru_access(cache, item, max_size):
    if item in cache:            # hit: move to the front
        cache.remove(item)
        cache.insert(0, item)
        return True
    if len(cache) >= max_size:   # miss and full: evict least recently used
        cache.pop()
    cache.insert(0, item)
    return False
```

To test both strategies, we need many requests. Real usage has **temporal locality**: for a while, we use a few apps again and again. The following code simulates 1000 app requests like this:

```
random.seed(42)  # makes the random numbers reproducible
apps = ["Mail", "Maps", "Spotify", "Camera", "Notes", "Banking", "Weather",
"News"]
requests = []
for i in range(1000):
    if i % 100 == 0:
        current_apps = random.sample(apps, 3)  # every 100 requests, we focus on 3
other apps
    if random.random() < 0.8:
        requests.append(random.choice(current_apps))
    else:
        requests.append(random.choice(apps))
print(requests[:10])
```

```
['Maps', 'Maps', 'Banking', 'Mail', 'Maps', 'Banking', 'Banking', 'Banking',
'Mail', 'Banking']
```

Exercise 2.1 – Random Eviction

Create a function `random_access(cache, item, max_size)` that works like `lru_access()`, but:

- On a hit, it leaves the cache unchanged and returns `True`
- On a miss with a full cache, it removes a **random** item with `random.choice()` before inserting the new item

```
# YOUR CODE BELOW
```

```
random.seed(1)
test_cache = ["A", "B", "C"]
assert random_access(test_cache, "B", 3) == True and test_cache == ["A", "B",
"C"], "A hit should not change the cache"
assert random_access(test_cache, "D", 3) == False and len(test_cache) == 3 and "D"
in test_cache, "A miss should replace one item"
print("Good! Your random eviction works.")
```

Exercise 2.2 - Compare the Strategies

Send all `requests` through a cache with 3 slots, once with `lru_access()` and once with `random_access()`. Store the hit rates (hits divided by the number of requests) in `lru_rate` and `random_rate`. Which strategy wins?

```
# YOUR CODE BELOW
```

```
assert round(lru_rate, 3) == 0.719, "Check your LRU hit rate"
assert 0 < random_rate < 1, "The random hit rate should be between 0 and 1"
print(f"LRU: {lru_rate:.1%} hits, random: {random_rate:.1%} hits")
```

> **Python ships an LRU cache**
>
> The standard library already contains an LRU cache: `functools.lru_cache`. It remembers the results of a function, so repeated calls with the same input are answered from the cache instead of being computed again.

```
from functools import lru_cache

@lru_cache(maxsize=3)  # keep the results of the 3 most recent inputs
def slow_square(n):
    print(f"Computing {n} * {n} ...")
    return n * n

slow_square(4)  # computed
slow_square(4)  # answered from the cache, no "Computing" message
```

```
Computing 4 * 4 ...
```

```
16
```

Section 3 – Using a package manager (`uv`)

Just as a library needs a system to track books (checkout system, catalog, etc.), Python projects need a tool to manage versions and dependencies. We use `uv` because it:

- Keeps track of what's available (like searching the catalog)
- Handles "checkouts" (installing packages)
- Manages "returns" (uninstalling packages)
- Ensures you have the right "edition" (version management)

Exercise 3.1 – Check your `uv` installation

Open a terminal (not the Python REPL) and run:

```
uv --version
```

You should see a version number.

Then confirm your Python version (after installing one via `uv` if needed):

```
uv run python --version
```

Section 4 – Installing Packages

Installing packages is like ordering new books for your library branch. With `uv` you typically:

- Initialize a project once (`uv init`)
- Add dependencies (`uv add packagename`)
- Remove them if not needed (`uv remove packagename`)
- Sync a project copied from elsewhere (`uv sync`)
- Update dependencies (`uv lock --upgrade`, then `uv sync`)

Under the hood `uv` creates (and reuses) a virtual environment for the project. Luckily most of that is handled for you and not that important in this basic introduction to Python.

Exercise 4.1 – Add `pandas`

Inside a `uv`-initialized project directory, run:

```
uv add pandas
```

This: - Resolves dependencies - Adds `pandas` to `pyproject.toml` - Installs it into the project's virtual environment

You can test if the installation was successful by running:

```
# Test your answer
try:
    import pandas
    print("pandas installed successfully!")
except ImportError:
    print("pandas was not installed correctly")
```

(If you see an import error, verify you are inside the project folder you initialized with `uv init`.)

Virtual environments are like having different library branches. Each branch can have:

- Its own collection of books (packages)
- Different editions of the same book (package versions)
- Specialized sections for different purposes (project-specific dependencies)

This separation ensures that:

- Changes in one branch don't affect others (project isolation)
- Each branch can be optimized for its community (project-specific dependencies)
- You can experiment without affecting the main collection (development safety)

For now, you don't need to worry about virtual environments except for the one we created now. This is more advanced and thus not necessary for this tutorial (or lecture). But it's good to know that they exist and that you can use them to manage your packages.

Conclusion

Great work! You learned how Python projects organize and access code via:

- The standard library, for example `random` to test our LRU cache
- Third-party packages
- A modern package & environment manager (`uv`)
- Isolated project environments for reliability

Treat each project like its own library branch: well-labeled, independent, and easy to maintain.

That's it for this week! Next week, we'll work with dictionaries and tabular data with pandas!