


DATA AND ARTIFICIAL INTELLIGENCE



simplilearn

P PURDUE
UNIVERSITY®

Data Science With Python

DATA AND ARTIFICIAL INTELLIGENCE




Mathematical Computing with Python (NumPy)

Learning Objectives

By the end of this lesson, you will be able to:

- Explain NumPy and its importance
- Discuss the basics of NumPy, including its fundamental objects
- Demonstrate how to create and print a NumPy array
- Analyze and perform basic operations in NumPy
- Utilize shape manipulation and copying methods
- Demonstrate how to execute linear algebraic functions
- Build basic programs using NumPy



DATA AND ARTIFICIAL INTELLIGENCE

Numpy

Quick Recap: Lists

Below are some of the properties of lists:

List

```
distance=[10,15,17,26]  
time=[.30,.47,.55,1.20]
```

Collection of values

Multiple types (heterogeneous)

Add, remove, update

Limitations of Lists

You can change individual values in a list, but you cannot apply a mathematical operation over the entire list.

```
distance=[10,15,17,26]
time=[.30,.47,.55,1.20]
```

```
speed=distance/time
```

 ← Mathematical operation over the entire “distance” and “time” lists


```
-----
TypeError                                Traceback (most recent call last)
<ipython-input-37-b779bad68500> in <module>()
----> 1 speed=distance/time
```

```
TypeError: unsupported operand type(s) for /: 'list' and 'list'
```

 ← Error

Why NumPy

Numerical Python (NumPy) supports multidimensional arrays over which you can easily apply mathematical operations.



```
distance=[10,15,17,26]  
time=[.30,.47,.55,1.20]
```

```
import numpy as np
```

 ← Import NumPy

```
np_distance = np.array(distance)  
np_time=np.array(time)  
speed=np_distance/np_time
```

 } Create “distance” and “time” NumPy arrays
← Mathematical function applied over the entire “distance” and “time” arrays

```
speed
```


```
array([ 33.33333333,  31.91489362,  30.90909091,  21.66666667])
```

 ← Output

NumPy Overview


NumPy is the foundational package for mathematical computing in Python.

It has the following properties:




Properties of ndarray

An array in NumPy has the following properties:



Purpose of ndarray

The ndarray in Python is used as the primary container to exchange data between algorithms.



Types of Arrays

Arrays can be one -dimensional, two -dimensional, three -dimensional, or multi -dimensional.

One-Dimensional Array

Printed as rows

`array([5, 7, 9])`

1 axis
rank 1

Length = 3

5	7	9
0	1	2

x axis

Two-Dimensional Array

Printed as matrices (2x3)

`array([[0, 1, 2],
[5, 6, 7]])`

2 axes
rank 2

Length = 3

y axis ↑	0 (0,0)	1 (0,1)	2 (0,2)
	5 (1,0)	6 (1,1)	7 (1,2)
	x axis →		

Three-Dimensional Array

Printed as list of matrices (3x3x3)


`array([[[0, 1, 2],
[3, 4, 5],
[6, 7, 8]],`

3 axes
rank 3

`[[9, 10, 11],
[12, 13, 14],
[15, 16, 17]],`

`[[18, 19, 20],
[21, 22, 23],
[24, 25, 26]]])`

Length = 3



Activity: Sequence it Right!

The code here is buggy. You must correct its sequence to debug it.

1

```
distance=[10,15,17,26]  
time=[.30,.47,.55,1.20]
```

2

```
np_distance = np.array(distance)  
np_time=np.array(time)
```

3

```
import numpy as np
```

4

```
speed=np_distance/np_time  
  
speed  
  
array([ 33.33333333,  31.91489362,  30.90909091,  21.66666667])
```


Activity: Sequence it Right!

1

```
distance=[10,15,17,26]  
time=[.30,.47,.55,1.20]
```

2

```
import numpy as np
```

3

```
np_distance = np.array(distance)  
np_time=np.array(time)
```

4

```
speed=np_distance/np_time
```

```
speed
```

```
array([ 33.33333333,  31.91489362,  30.90909091,  21.66666667])
```

Creating and Printing an ndarray



Demonstrate how to create and print a ndarray .

ASSISTED PRACTICE


Classes and Attributes of ndarray: .ndim

Numpy's array class is `ndarray` , also referred to as `numpy.ndarray` . The attributes of ndarray are:

`ndarray.ndim`


This refers to the number of axes (dimensions) of the array. It is also called the rank of the array.

`ndarray.shape`



Two axes or 2D array

`ndarray.size`



Three axes or 3D array

`ndarray.dtype`

Concept

Example

Classes and Attributes of ndarray: .ndim

ndarray.ndim

The array **np_city** is one-dimensional, while the array **np_city_with_state** is two-dimensional.

ndarray.shape

```
In [108]: np_city = np.array(['NYC', 'LA', 'Miami', 'Houston'])
```

```
In [109]: np_city.ndim
```

```
Out[109]: 1
```

ndarray.size

```
In [110]: np_city_with_state = np.array([[ 'NYC', 'LA', 'Miami', 'Houston'], [ 'NY', 'CA', 'FL', 'TX']])
```

```
In [111]: np_city_with_state.ndim
```

```
Out[111]: 2
```

ndarray.dtype

Concept


Example

Classes and Attributes of ndarray: .shape

Numpy's array class is `ndarray` , also referred to as `numpy.ndarray` . The attributes of ndarray are:


- `ndarray.ndim`
- `ndarray.shape`
- `ndarray.size`
- `ndarray.dtype`

This consists of a tuple of integers showing the size of the array in each dimension. The length of the **shape tuple** is the rank or ndim.



2 rows, 3 columns

Shape: (2, 3)



2 rows, 3 columns, 2 ranks

Shape: (2, 3, 2)

Concept Example

Classes and Attributes of ndarray: .shape

Numpy's array class is `ndarray` , also referred to as `numpy.ndarray` . The attributes of `ndarray` are:

`ndarray.ndim`

`ndarray.shape`

`ndarray.size`

`ndarray.dtype`

The shape tuple of both the arrays indicate their size along each dimension.

```
In [108]: np_city = np.array(['NYC', 'LA', 'Miami', 'Houston'])
```

```
In [110]: np_city_with_state = np.array([[ 'NYC', 'LA', 'Miami', 'Houston'], [ 'NY', 'CA', 'FL', 'TX']])
```

```
In [112]: np_city.shape
```

```
Out[112]: (4L,)
```

```
In [113]: np_city_with_state.shape
```

```
Out[113]: (2L, 4L)
```

Concept

Example

Classes and Attributes of ndarray: .size

Numpy's array class is `ndarray` , also referred to as `numpy.ndarray` . The attributes of `ndarray` are:


`ndarray.ndim`

`ndarray.shape`

`ndarray.size`


`ndarray.dtype`

It gives the total number of elements in the array. It is equal to the product of the elements of the shape tuple.



Array contains 6 elements

Array a = (2, 3)
Size = 6



Array contains 12 elements

Array b = (2, 3, 2)
Size = 12

Concept

Example

Classes and Attributes of ndarray: .size

Numpy's array class is `ndarray` , also referred to as `numpy.ndarray` . The attributes of `ndarray` are:

`ndarray.ndim`

`ndarray.shape`

`ndarray.size`

`ndarray.dtype`

Look at the examples to see how the shape tuples of the arrays are used to calculate their size.

```
In [112]: np_city.shape
```

```
Out[112]: (4L,)
```

```
In [113]: np_city_with_state.shape
```

```
Out[113]: (2L, 4L)
```

```
In [114]: np_city.size
```

```
Out[114]: 4
```

```
In [115]: np_city_with_state.size
```

```
Out[115]: 8
```

Concept

Example

Classes and Attributes of ndarray: .dtype

Numpy's array class is `ndarray` , also referred to as `numpy.ndarray` . The attributes of `ndarray` are:

`ndarray.ndim`

`ndarray.shape`


`ndarray.size`

`ndarray.dtype`

It's an object that describes the type of the elements in the array. It can be created or specified using Python.

Array contains integers

Array a = [3, 7, 4]
[2, 1, 0]



Array contains floats

Array b = [1.3, 5.2, 6.7]
[0.2, 8.1, 9.4]

[2.6, 4.2, 3.9]
[7.8, 3.4, 0.8]

Concept

Example

Classes and Attributes of ndarray: .dtype

Numpy's array class is `ndarray` , also referred to as `numpy.ndarray` . The attributes of `ndarray` are:

`ndarray.ndim`

`ndarray.shape`

`ndarray.size`

`ndarray.dtype`

Both the arrays are of **string** data type (dtype) and the longest string is of length 7, which is **Houston** .

```
In [116]: np_city
```

```
Out[116]: array(['NYC', 'LA', 'Miami', 'Houston'],  
               dtype='<S7')
```

```
In [117]: np_city_with_state
```

```
Out[117]: array([[ 'NYC', 'LA', 'Miami', 'Houston'],  
                [ 'NY', 'CA', 'FL', 'TX']],  
               dtype='<S7')
```

```
In [118]: np_city_with_state.dtype
```

```
Out[118]: dtype('<S7')
```

Concept

Example

Operations

Basic Operations

Using the following operands, you can easily apply various mathematical, logical, and comparison operations on an array.

Mathematical Operations

Addition	+
Subtraction	-
Multiplication	*
Division	/
Exponentiation	**

Logical Operations

And	&
Or	
Not	~

Comparison Operations

Greater	>
Greater or equal	>=
Less	<
Less or equal	<=
Equal	==
Not equal	!=

Executing Basic Operations




Demonstrate how to apply some basic operations on an array.

ASSISTED PRACTICE

Basic Operations: Example

NumPy uses the indices of the elements in each array to carry out basic operations. In this case, where we are looking at a dataset of four cyclists during two trials, vector addition of the arrays gives the required output.

```
In [99]: first_trial_cyclist = [10, 15, 17, 26] ← First trial
In [100]: second_trial_cyclist = [12, 11, 21, 24] ← Second trial
In [101]: np_first_trial_cyclist = np.array(first_trial_cyclist)
In [102]: np_second_trial_cyclist = np.array(second_trial_cyclist)
In [103]: np_first_trial_cyclist + np_second_trial_cyclist ← Total distance
Out[103]: array([22, 26, 38, 50])
```



Accessing Array Elements: Indexing

You can access an entire row of an array by referencing its axis index.

1st set data 2nd set data

```
In [117]: cyclist_trials = np.array([[10, 15, 17, 26], [12, 11, 21, 24]])
```

 ← Create 2D array using cyclist trial data shown earlier

```
In [118]: first_trial = cyclist_trials[0]
```

 ← First trial data

```
In [119]: first_trial
```

```
Out[119]: array([10, 15, 17, 26])
```

```
In [120]: second_trial = cyclist_trials[1]
```

 ← Second trial data

```
In [121]: second_trial
```

```
Out[121]: array([12, 11, 21, 24])
```

2D array containing cyclists' data

10	15	17	26
12	11	21	24

← First trial (axis 0)

← Second trial (axis 1)

Accessing Array Elements: Indexing

You can refer the indices of the elements in an array to access them. You can also select a particular index of more than one axis at a time.

```
In [122]: first_cyclist_firstTrial = cyclist_trials[0][0] ← First cyclist: first trial data
```

```
In [123]: first_cyclist_firstTrial
```

```
Out[123]: 10
```

```
In [124]: first_cyclist_all_trials = cyclist_trials[:,0] ← First cyclist: all trial data  
(Use : to select all the rows of an array)
```

```
In [125]: first_cyclist_all_trials
```

```
Out[125]: array([10, 12])
```

Cyclist 1, first trial data →

(0, 0)	(0, 1)	(0, 2)	(0, 3)
10	15	17	26
12	11	21	24
(1, 0)	(1, 1)	(1, 2)	(1, 3)

Cyclist 1, all trials data

(0, 0)	(0, 1)	(0, 2)	(0, 3)
10	15	17	26
12	11	21	24
(1, 0)	(1, 1)	(1, 2)	(1, 3)

Accessing Array Elements: Slicing

Use the slicing method to access a range of values within an array.

Shape of the array

```
In [152]: cyclist_trials.shape
Out[152]: (2L, 4L)
```

In [153]: `two_cyclist_trial_data=cyclist_trials[:,1:3]`

In [154]: `two_cyclist_trial_data`

```
Out[154]: array([[15, 17],
                [11, 21]])
```

Slicing the array data `[:, 1 : 3]`
where 1 is inclusive but 3 is not

Shape of the array

10	15	17	26
12	11	21	24

2 rows

4 columns

Slicing the array

10	15	17	26
12	11	21	24

Use ':' to select all rows

0 1 2 3

Starting index (1) Ending index (2)

Activity: Slice It!

Select any two elements from the array to see how the statement required to slice the range changes.

Rules of the Game

- Choose the first element of the range. Then, choose the element that ends the range.
- See how the values in the statement change according to your choices.
- Refresh to try again.

5	8	10	21
---	---	----	----

```
example_array[1:3]
```

Select any two elements from the array.

Accessing Array Elements: Iteration

Use the iteration method to go through each data element present in the dataset.

```
In [117]: cyclist_trials = np.array([[10,15,17,26],[12,11,21,24]])
```

```
In [153]: two_cyclist_trial_data=cyclist_trials[:,1:3]
```

```
In [154]: two_cyclist_trial_data
```

```
Out[154]: array([[15, 17],  
                [11, 21]])
```

```
In [159]: for iterate_cyclist_trials_data in cyclist_trials:  
           print (iterate_cyclist_trials_data)
```

```
[10 15 17 26]  
[12 11 21 24]
```

```
In [160]: for iterate_two_cyclist_trial_data in two_cyclist_trial_data:  
           print (iterate_two_cyclist_trial_data)
```

```
[15 17]  
[11 21]
```

Iterate with **for loop** through entire dataset

Iterate with **for loop** through the **two cyclist** datasets

Indexing with Boolean Arrays


Boolean arrays are useful when you need to select a dataset according to set criteria.

True False



Indexing with Boolean Arrays

Here, the original dataset contains test scores of two students. You can use a Boolean array to choose only the scores that are above a given value.



```
In [234]: test_scores = np.array([[83, 71, 57, 63], [54, 68, 81, 45]])
```

```
In [235]: passing_score = test_scores > 60
```

Setting the passing score

```
In [236]: passing_score
```

```
Out[236]: array([[ True,  True, False,  True],
                [False,  True,  True, False]], dtype=bool)
```

Shows data elements which fit the criteria (Boolean array)

```
In [237]: test_scores[passing_score]
```

Send passing score as an argument to test scores object

```
Out[237]: array([83, 71, 63, 68, 81])
```

Copy and Views

When working with arrays, data is copied into new arrays only in some cases. Following are the three possible scenarios:



Simple Assignments

In this method, a variable is directly assigned the value of another variable. No new copy is made.

```
In [303]: NYC_Borough = np.array(['Manhattan', 'Bronx', 'Brooklyn', 'Staten Island', 'Queens'])
```

```
In [294]: NYC_Borough
```

```
Out[294]: array(['Manhattan', 'Bronx', 'Brooklyn', 'Staten Island', 'Queens'],  
              dtype='<S13')
```

← Original dataset

```
In [295]: Boroughs_in_NYC = NYC_Borough
```

```
In [296]: Boroughs_in_NYC
```

```
Out[296]: array(['Manhattan', 'Bronx', 'Brooklyn', 'Staten Island', 'Queens'],  
              dtype='<S13')
```

← Assigned dataset

```
In [297]: Boroughs_in_NYC is NYC_Borough
```

```
Out[297]: True ← Shows both objects are the same
```



View/Shallow Copy



Deep Copy

Copy and Views



Simple Assignments



View/Shallow Copy



Deep Copy

A view, also referred to as a shallow copy, creates a new array object.

```
In [296]: Boroughs_in_NYC
```

```
Out[296]: array(['Manhattan', 'Bronx', 'Brooklyn', 'Staten Island', 'Queens'],  
              dtype='<S13')
```

← Original dataset

```
In [298]: View_of_Borough_in_NYC = Boroughs_in_NYC.view()
```

```
In [299]: len(View_of_Borough_in_NYC)
```

```
Out[299]: 5
```

```
In [300]: View_of_Borough_in_NYC[4] = 'Central Park' ← Change value in view object
```

```
In [301]: View_of_Borough_in_NYC
```

```
Out[301]: array(['Manhattan', 'Bronx', 'Brooklyn', 'Staten Island', 'Central Park'],  
              dtype='<S13')
```

```
In [302]: Boroughs_in_NYC
```

```
Out[302]: array(['Manhattan', 'Bronx', 'Brooklyn', 'Staten Island', 'Central Park'],  
              dtype='<S13')
```

← Original dataset
changed

Copy and Views



Simple Assignments



View/Shallow Copy



Deep Copy

Copy is also called **deep copy** because it entirely copies the original dataset. Any change in the copy will not affect the original dataset.

```
In [304]: Copy_of_NYC_Borough = NYC_Borough.copy()
```

```
In [305]: Copy_of_NYC_Borough is NYC_Borough
```

◀ Shows **copy** and original object are different

```
Out[305]: False
```

```
In [306]: Copy_of_NYC_Borough.base is NYC_Borough
```

◀ Shows **copy** object data is not owned by the original dataset

```
Out[306]: False
```

```
In [307]: Copy_of_NYC_Borough[4]='Central Park'
```

◀ Change value in **copy**

```
In [308]: NYC_Borough
```

```
Out[308]: array(['Manhattan', 'Bronx', 'Brooklyn', 'Staten Island', 'Queens'],  
              dtype='<S13')
```

◀ **Copy** object changed

```
In [309]: Copy_of_NYC_Borough
```

```
Out[309]: array(['Manhattan', 'Bronx', 'Brooklyn', 'Staten Island', 'Central Park'],  
              dtype='<S13')
```

◀ Original dataset retained

Universal Functions (ufunc)

NumPy provides useful mathematical functions called Universal Functions. These functions operate element-wise on an array, producing another array as output. Some of these functions are:

sqrt function provides the square root of every element in the array.

sqrt

cos function gives cosine values for all elements in the array.

cos

floor function returns the largest integer value of every element in the array.

floor

exp function performs exponentiation on each element.

exp

Ufunc: Examples

In [186]: `np_sqrt = np.sqrt([2,4,9,16])` ← Numbers for which square root will be calculated

In [187]: `np_sqrt`

Out[187]: `array([1.41421356, 2. , 3. , 4.])` ← Square root values

In [188]: `from numpy import pi` ← Import pi*
`np.cos(0)` ←

Out[188]: `1.0`

In [189]: `np.sin(pi/2)` ← Trigonometric functions

Out[189]: `1.0`

In [190]: `np.cos(pi)` ← Trigonometric functions

Out[190]: `-1.0`

In [191]: `np.floor([1.5,1.6,2.7,3.3,1.1,-0.3,-1.4])` ← Return the floor of the input element wise

Out[191]: `array([1., 1., 2., 3., 1., -1., -2.])`


In [192]: `np.exp([0,1,5])` ← Exponential functions for complex mathematical calculations

Out[192]: `array([1. , 2.71828183, 148.4131591])`

Shape Manipulation

You can use certain functions to manipulate the shape of an array.

The shape of an array can be changed according to the requirement using the NumPy library functions.




Array shape
manipulation
methods

Data
Wrangling

Shape Manipulation

Some common methods for manipulating shapes are:



Shape Manipulation: Example

You can use certain functions to manipulate the shape of an array to do the following:

```
In [383]: new_cyclist_trials = np.array([[10,15,17,26,13,19],[12,11,21,24,14,23]])
```

```
In [384]: new_cyclist_trials.ravel()
```

 ← **Flattens the dataset**

```
Out[384]: array([10, 15, 17, 26, 13, 19, 12, 11, 21, 24, 14, 23])
```

```
In [385]: new_cyclist_trials.reshape(3,4)
```

 ← **Changes or reshapes the dataset to 3 rows and 4 columns**

```
Out[385]: array([[10, 15, 17, 26],
                [13, 19, 12, 11],
                [21, 24, 14, 23]])
```

```
In [386]: new_cyclist_trials.resize(2,6)
```

 ← **Resizes again to 2 rows and 6 columns**

```
In [387]: new_cyclist_trials
```

```
Out[387]: array([[10, 15, 17, 26, 13, 19],
                [12, 11, 21, 24, 14, 23]])
```

```
In [388]: np.hsplit(new_cyclist_trials,2)
```

 ← **Splits the array into two**

```
Out[388]: [array([[10, 15, 17],
                [12, 11, 21]]), array([[26, 13, 19],
                [24, 14, 23]])]
```

```
In [389]: new_cyclist_1 = np.array([10,15,17,26,13,19])
```

```
In [390]: new_cyclist_2 = np.array([12,11,21,24,14,23])
```

```
In [391]: np.hstack((new_cyclist_1,new_cyclist_2))
```

 ← **Stacks the arrays together**

```
Out[391]: array([10, 15, 17, 26, 13, 19, 12, 11, 21, 24, 14, 23])
```

Broadcasting

NumPy uses broadcasting to carry out arithmetic operations between arrays of different shapes. In this method, NumPy automatically broadcasts the smaller array over the larger array.

```
In [9]: import numpy as np

In [10]: #Create two arrays of the same shape
array_a = np.array([2, 3, 5, 8])
array_b = np.array([.3, .3, .3, .3])

In [11]: #Multiply arrays
array_a * array_b


Out[11]: array([ 0.6,  0.9,  1.5,  2.4])

In [12]: #Create a variable with a scalar value
scalar_c = .3


In [13]: #Multiply 1D array with a scalar value
array_a * scalar_c

Out[13]: array([ 0.6,  0.9,  1.5,  2.4])
```

Element-wise
multiplication



Broadcasting



If the shape doesn't match with array_a, numpy doesn't have to create copies of scalar value. Instead, broadcast scalar value over the entire array to find the product.

Broadcasting: Constraints

Though broadcasting can help carry out mathematical operations between different -shaped arrays, they are subject to certain constraints as listed below:

```
In [9]: import numpy as np
```

```
In [10]: #Create two arrays of the same shape
array_a = np.array([2, 3, 5, 8])
array_b = np.array([.3, .3, .3, .3])
```

```
In [11]: #Multiply arrays
array_a * array_b
```

```
Out[11]: array([ 0.6,  0.9,  1.5,  2.4])
```

```
In [14]: #Create array of a different shape
array_d = np.array([4, 3])
```

```
In [15]: array_a * array_d
```

```
-----
ValueError                                Traceback (most recent call last)
<ipython-input-15-43adcf6f7a54> in <module>()
----> 1 array_a * array_d

ValueError: operands could not be broadcast together with shapes (4,) (2,)
```

- When NumPy operates on two arrays, it compares their shapes element -wise. It finds these shapes compatible only if:
 - Their dimensions are the same or
 - One of them has a dimension of size 1.
- If these conditions are not met, a **ValueError** is thrown, indicating that the arrays have incompatible shapes.

Broadcasting: Example

Let's look at an example to see how broadcasting works to calculate the number of working hours of a worker per day in a certain week.

```
In [246]: np_week_one = np.array([105, 135, 195, 120, 165])  
np_week_two = np.array([123, 156, 230, 200, 147])
```

← Week one earnings
← Week two earnings

```
In [247]: total_earning = np_week_one + np_week_two
```

```
In [248]: total_earning
```

```
Out[248]: array([228, 291, 425, 320, 312])
```

← Total earning for 2 weeks

```
In [249]: np_week_one_hrs = np_week_one / 15
```

← Calculate week one hours

```
In [250]: np_week_one_hrs
```



```
Out[250]: array([ 7,  9, 13,  8, 11])
```

← Number of working hours per day in week one

Linear Algebra: Transpose

NumPy can carry out linear algebraic functions as well. The `transpose()` function can help you interchange rows as columns, and vice -versa.

transpose()			
83	71	57	63
54	68	81	45



```
In [397]: test_scores = np.array([[83, 71, 57, 63], [54, 68, 81, 45]])
```

```
In [398]: test_scores.transpose()
```

```
Out[398]: array([[83, 54],  
                [71, 68],  
                [57, 81],  
                [63, 45]])
```

Linear Algebra: Inverse and Trace Functions

Using NumPy, you can also find the inverse of an array and add its diagonal data elements.

np.linalg.inv()

```
In [411]: inverse_array = np.array([[10, 20], [15, 25]])
```

```
In [412]: np.linalg.inv(inverse_array)
```

```
Out[412]: array([[ -0.5,  0.4],  
                [ 0.3, -0.2]])
```

Inverse of the given array

* Can be applied **only** on a square matrix

np.trace()

```
In [420]: trace_array = np.array([[10, 20], [22, 31]])
```

```
In [421]: np.trace(trace_array)
```

```
Out[421]: 41
```

Sum of diagonal elements **10** and **31**

Country GDP



Evaluate the dataset containing the GDPs of different countries to:

- Find and print the name of the country with the highest GDP
- Find and print the name of the country with the lowest GDP
- Print out text and input values iteratively
- Print out the entire list of the countries with their GDPs
- Print the highest GDP value, lowest GDP value, mean GDP value, standardized GDP value, and the sum of all the GDPs

UNASSISTED PRACTICE

Olympic 2012 Medal Tally



Evaluate the dataset of the Summer Olympics, London 2012 to:

- Find and print the name of the country that won maximum gold medals
- Find and print the countries who won more than 20 gold medals
- Print the medal tally
- Print each country name with the corresponding number of gold medals
- Print each country name with the total number of medals won

UNASSISTED PRACTICE

DATA AND ARTIFICIAL INTELLIGENCE



Knowledge Check

Knowledge Check

1

Which of the following arrays is valid?

- a. [1, 0.3, 8, 6.4]
- b. ["Lucy", 16, "Susan", 23, "Carrie", 37]
- c. [True, False, "False", True]
- d. [3.14j, 7.3j, 5.1j, 2j]



Knowledge Check

1

Which of the following arrays is valid?

- a. [1, 0.3, 8, 6.4]
- b. ["Lucy", 16, "Susan", 23, "Carrie", 37]
- c. [True, False, "False", True]
- d. [3.14j, 7.3j, 5.1j, 2j]



The correct answer is **d**

A NumPy ndarray can hold only a single data type, which makes it homogenous. NumPy supports integers, floats, Booleans, and even complex numbers. Of all the options provided, only the array containing complex numbers is homogenous. All the other options contain more than one data type.

Knowledge
Check

2

Which function is most useful to convert a multidimensional array into a one dimensional array?

-

- a. `ravel()`
- b. `reshape()`
- c. `resize()` and `reshape()`
- d. All of the above



Knowledge
Check

2

Which function is most useful to convert a multidimensional array into a one-dimensional array?

- a. `ravel()`
- b. `reshape()`
- c. `resize()` and `reshape()`
- d. All of the above



The correct answer is **a**

The function `ravel()` is used to convert a multidimensional array into a one-dimensional array. Though `reshape()` also functions in a similar way, it creates a new array instead of transforming the input array.

Knowledge
Check

3

The `np.trace()` method gives the sum of _____.

- a. the entire array
- b. the diagonal elements from left to right
- c. the diagonal elements from right to left
- d. consecutive rows of an array



Knowledge Check

3

The `np.trace()` method gives the sum of _____.

- a. the entire array
- b. the diagonal elements from left to right
- c. the diagonal elements from right to left
- d. consecutive rows of an array



The correct answer is **b**

The `trace()` function is used to find the sum of the diagonal elements in an array. It is carried out in an incremental order of the indices. Therefore, it can only add diagonal values from left to right and not vice versa.

of the

Knowledge
Check

4

The function `np.transpose()` when applied on a one dimensional array gives _____.

- a. a reverse array
- b. an unchanged original array
- c. an inverse array
- d. all elements with zeroes



Knowledge
Check

4

The function `np.transpose()` when applied on a one dimensional array gives _____.

- a. a reverse array
- b. an unchanged original array
- c. an inverse array
- d. all elements with zeroes



The correct answer is **b**

Transposing a one -dimensional array does not change it in any way. It returns an unchanged view of the original array.

Key Takeaways

You are now able to:

- 🔗 Explain NumPy and its importance
- 🔗 Discuss the basics of NumPy, including its fundamental objects
- 🔗 Demonstrate how to create and print a NumPy array
- 🔗 Analyze and perform basic operations in NumPy
- 🔗 Utilize shape manipulation and copying methods
- 🔗 Demonstrate how to execute linear algebraic functions
- 🔗 Build basic programs using NumPy



Thank You