Alexy G26 User Manual

Models: G26, G26 Lite, G26 Pro, G26 Fold

Release Date: March 28, 2026

Status: Internal/Confidential

1. Getting Started

Initial Setup

1. **Power On:** Press and hold the power button located on the titanium chassis.
2. **Biometric Enrollment:** Follow the on-screen prompts to register your "Vein-Scan." Ensure your finger is placed firmly on the lower section of the display.
3. **OS Integration:** The **"Fluid" OS** will ask to sync your existing accounts. Due to its microkernel architecture, it offers 100% app compatibility with both Android and iOS environments.
4. **Connectivity:** Connect to Wi-Fi or utilize the **6G Ready** modem for high-speed cellular data.

---

2. Using the "Fluid" OS

The Alexy G26 runs on a proprietary ecosystem designed for seamless integration.

- **App Compatibility:** You can install apps from various ecosystems without performance loss.
- **AI Features:** The Helios G1 Neural Chip provides an AI processing score of 98/100, enabling real-time optimization and advanced task handling.
- **Satellite SOS:** In areas without cellular coverage, access the Satellite SOS feature via the connectivity menu for emergency assistance.

---

3. Maintenance & Sustainability

The Alexy G26 is built with longevity and environmental responsibility in mind.

Durability & Cleaning

- **IP69 Rating:** The device is completely dust-tight and can withstand high-pressure, high-temperature water jets.
- **Internal Protection:** The **Hydro-Guard** internal seal uses a proprietary nanocoating to protect components even if the outer shell is compromised.
- **Thermal Care:** The liquid-cooling system maintains 92% efficiency under heavy load; however, avoid leaving the device in direct sunlight for extended periods.

4. Battery Management

The Alexy G26 is designed with a Sustainability focus, featuring a user-replaceable **battery** and a **93% recycled titanium chassis**. Follow these steps to safely maintain or repair your device.

4.1. Preparation and Safety

- **Power Down: Completely shut down the Alexy G26 before beginning any repair** to protect the **Helios G1M Neural Chip** and internal circuitry.
- **Environment:** Work on a flat, anti-static surface. While the phone has an **IP69 Rating** and **Hydro-Guard nanocoating**, repairs should always be performed in a dry environment to prevent moisture from entering the internal seal during the process.

4.2. Battery Replacement Process

Unlike traditional sealed flagships, the G26 is engineered for hardware accessibility.

1. **Chassis Access:** Locate the recessed security toggles on the **titanium chassis**.
2. **Disengage Seals:** Carefully release the rear panel. Note that the **Hydro-Guard Internal Seal** provides a proprietary nanocoating layer that may offer slight resistance; do not force the panel.
3. **Remove Old Battery:** Disconnect the localized power ribbon from the **5,500 mAh battery** unit.
4. **Insert New Unit:** Align the new high-capacity cell. The **Adaptive Hardware** system will automatically calibrate the new battery to maintain the **95/100 Battery Life** benchmark.
5. **Reseal:** Press the rear panel firmly until the **IP69-rated** seals click into place, ensuring the device remains waterproof against high-pressure jets.

4.3. Post-Repair Calibration

- **Rapid Charge Test:** Connect the device to a **60W Rapid Charger** to verify the connection.
- **System Check:** Upon rebooting **"Fluid" OS**, navigate to "Hardware Health" to ensure the **Thermal Efficiency** remains at the target **92%**.
- **Security Sync:** Ensure the **Quantum-Safe Encryption** and **Vein-Scan** biometric systems are functioning correctly after the power cycle.

---

5. Troubleshooting

Issue	Potential Solution
Weak Signal	The 6G-ready modem is optimized for weak areas. Ensure "Signal Stability" mode is active in settings.
Overheating	The titanium chassis and liquid cooling should manage heat. Close heavy AI processing apps if the device feels excessively warm.
Biometric Failure	Ensure the display is clean. The "Vein-Scan" requires a clear view of the under-display sensor.
App Crashes	Verify that the "Fluid" OS microkernel is up to date to maintain Android/iOS compatibility.

- End of Document -