

Machine Learning (CE 40717)

Fall 2024

Ali Sharifi-Zarchi

CE Department
Sharif University of Technology

December 21, 2024



① Encoder Architecture

② References

1 Encoder Architecture


Language Modeling

BERT Introduction


BERT Architecture

2 References

Sentence-Level Tasks




(a) Sentence Pair Classification Tasks:
MNL, QQP, QNLI, STS-B, MRPC,
RTE, SWAG



(b) Single Sentence Classification Tasks:
SST-2, CoLA

Input Embedding Layer




Pretraining Details


- Two main objectives:
 - 1 Masked Language Modeling (MLM)
 - 2 Next Sentence Prediction (NSP)

BERT Pre-training: Putting Together

- Vocabulary size:** 30,000 wordpieces (common sub-word units) (Wu et al., 2016)



- Input embeddings:**




- Just two possible "segment embeddings": E_A and E_B .

- Positional embeddings are learned vectors for every possible position between 0 and 512-1.

BERT Pre-training: Putting Together



- MLM and NSP are trained together
- [CLS] is pre-trained for NSP
- Other token representations are trained for MLM



Masked Language Modeling (MLM)

- Q:** Why we can't do language modeling with bidirectional models?



- Solution:** Mask out a percentage k of the input words, and then predict the masked words.

store gallon
 ↓ ↓
 the man went to [MASK] to buy a [MASK] of milk

MLM: Masking Rate and Strategy

- **Q: What is the value of k ?**

- They always use $k = 15\%$.
- Too little masking: computationally expensive (we need to increase # of epochs)
- Too much masking: not enough context
- See (Wettig et al., 2022) for more discussion of masking rates:
 - Masking 40% outperforms 15% for BERT-large size models on GLUE and SQuAD
 - High masking rate of 80% can still preserve 95% fine-tuning performance

- **Q: How are masked tokens selected?**

- 15% tokens are uniformly sampled
- Is it optimal? See span masking (Joshi et al., 2020) and PMI masking (Levine et al., 2021)

Example: He [MASK] from Kuala [MASK], Malaysia.

Masked Language Modeling (MLM)

- **Masking Strategy:**

- ① 15% of tokens are randomly selected for masking.
- ② 80% replaced with [MASK].
- ③ 10% replaced with a random token.
- ④ 10% unchanged.

- Prevents model from overfitting to [MASK].

- **Loss Function:**

$$L_{MLM} = - \sum_{t \in \text{masked}} \log P(t_{\text{true}} | \text{context})$$

Next Sentence Prediction (NSP)

- Motivation: many NLP downstream tasks require understanding the relationship between two sentences (natural language inference, paraphrase detection, QA).
- NSP is designed to reduce the gap between pre-training and fine-tuning.

[CLS]: a special token
always at the beginning

[SEP]: a special token used
to separate two segments

Input = [CLS] the man went to [MASK] store [SEP]

he bought a gallon [MASK] milk [SEP]

Label = IsNext

Input = [CLS] the man [MASK] to the store [SEP]

penguin [MASK] are flight ##less birds [SEP]

Label = NotNext

They sample two contiguous segments for 50% of the time and another random segment from the corpus for 50% of the time

Next Sentence Prediction (NSP)

- 50% of training pairs are consecutive sentences (labeled as **IsNext**).
- 50% are randomly paired sentences (labeled as **NotNext**).
- **NSP Objective:**
 - Binary classification loss applied to the [CLS] representation.

Fine-Tuning Details

- Requires task-specific modifications.
- Examples include:
 - 1 Text Classification
 - 2 Named Entity Recognition (NER)
 - 3 Question Answering (QA)
 - 4 Sentence Pair Classification

Fine-Tuning for Text Classification

- **Objective:** Classify input text into predefined categories (e.g., sentiment analysis, topic classification).
- **Approach:**
 - Utilize BERT's [CLS] token embedding from the last hidden layer as a summary representation of the input.
 - Add a linear (dense) classification layer on top of the [CLS] embedding.

- **Model Architecture:**

$$y = \text{softmax}(W \cdot h_{[\text{CLS}]} + b)$$

- $h_{[\text{CLS}]}$: Hidden state of the [CLS] token.
 - W, b : Weights and bias of the classification layer.
 - y : Probability distribution over the target classes.
- **Loss Function:**

$$L_{TC} = - \sum_{i=1}^C y_i^{\text{true}} \log P(y_i | h_{[\text{CLS}]})$$

Fine-Tuning for Named Entity Recognition (NER)

- **Objective:** Identify and classify named entities (e.g., persons, organizations, locations) in text.
- **Approach:**
 - Utilize BERT's token embeddings from the last hidden layer.
 - Add a linear classification layer to predict entity labels for each token.
- **Model Architecture:**

$$y_i = \text{softmax}(W \cdot h_i + b)$$

- h_i : Hidden state of the i -th token.
 - W, b : Weights and bias of the classification layer.
 - y_i : Probability distribution over entity labels for token i .
- **Training Details:**
 - **Label Encoding:** Use BIO (Begin, Inside, Outside) tagging scheme.
 - **Loss Function:** Cross-entropy loss computed over all tokens.

Fine-Tuning for Question Answering (QA)

- **Objective:** Predict the start and end positions of the answer span within a given context.
- **Approach:**
 - Use BERT's token embeddings from the last hidden layer.
 - Add two linear layers to predict start and end positions separately.
- **Model Architecture:**

$$\text{Start}_i = \text{softmax}(W_{\text{start}} \cdot h_i + b_{\text{start}})$$

$$\text{End}_i = \text{softmax}(W_{\text{end}} \cdot h_i + b_{\text{end}})$$

- h_i : Hidden state of the i -th token.
- $W_{\text{start}}, W_{\text{end}}, b_{\text{start}}, b_{\text{end}}$: Weights and biases for start and end prediction layers.
- $\text{Start}_i, \text{End}_i$: Probability distributions for start and end positions.
- **Loss Function:**

$$L_{\text{QA}} = -(\log P(\text{start_true} \mid \text{context}) + \log P(\text{end_true} \mid \text{context}))$$

Fine-Tuning for Sentence Pair Classification

- **Objective:** Determine the relationship between two sentences (e.g., entailment, contradiction, or similarity).
- **Approach:**
 - Input consists of two sentences separated by the [SEP] token.
 - Use the [CLS] token's embedding for classification.
 - Add a linear classification layer on top of the [CLS] embedding.

- **Model Architecture:**

$$y = \text{softmax}(W \cdot h_{[\text{CLS}]} + b)$$


- $h_{[\text{CLS}]}$: Hidden state of the [CLS] token.
 - W, b : Weights and bias of the classification layer.
 - y : Probability distribution over relationship classes.
- **Loss Function:**

$$L_{\text{Pair}} = - \sum_{i=1}^C y_i^{\text{true}} \log P(y_i | h_{[\text{CLS}]})$$


Fine-tuning BERT

“Pre-train once, finetune many times.”

sentence-level tasks




(a) Sentence Pair Classification Tasks:
MNLI, QQP, QNLI, STS-B, MRPC,
RTE, SWAG



(b) Single Sentence Classification Tasks:
SST-2, CoLA

For sentence pair tasks, use [SEP] to separate the two segments with segment embeddings and add a linear classifier on top of [CLS] representation.

Finetuning Paradigm in NLP



BERT Training

Dataset: Let $\mathcal{D}$ be a set of examples $(x_{1:L}, c)$ constructed as follows:

- Let A be a sentence from the corpus.
- With probability 0.5, let B be the next sentence.
- With probability 0.5, let B be a random sentence from the corpus.
- Let $x_{1:L} = [\text{CLS}], A, [\text{SEP}], B$.
- Let c denote whether B is the next sentence or not.

Objective. Then the BERT objective is:

$$\mathcal{O}(\theta) = \sum_{(x_{1:L}, c) \in \mathcal{D}} \underbrace{\mathbb{E}_{I, \tilde{x}_{1:L} \sim A(\cdot | x_{1:L}, I)} \left[\sum_{i \in I} -\log p_{\theta}(\tilde{x}_i | x_{1:L}) \right]}_{\text{masked language modeling}} + \underbrace{-\log p(c | \phi(x_{1:L})_1)}_{\text{next sentence prediction}}.$$

Training BERT - Hyperparameters

- **Optimizer:** AdamW (Adam with weight decay).
- **Warmup Steps:** Gradual learning rate increase during early steps.
- **Learning Rate:**

$$[10^{-5}, 10^{-4}]$$

for fine-tuning.

- **Batch Size:** 16–32 for fine-tuning.

Training BERT - Regularization

- **Dropout:** Applied to attention scores and FFN (typical rates: 0.1–0.3).
- **Weight Decay:** Helps generalization during pretraining.

Computational Complexity

- Attention mechanism scales quadratically:

$$\mathcal{O}(n^2 d)$$

where:

- n = sequence length
- d = hidden size

Optimizations and Variants

① DistilBERT

- Lighter version with fewer parameters.
- Retains 97% of performance with 40% fewer parameters.

② ALBERT

- Reduces memory overhead by parameter sharing across layers.
- Decomposes embeddings.

③ RoBERTa

- Removes NSP.
- Trains on larger datasets.
- Uses dynamic masking.

④ Longformer

- Modifies attention to handle long sequences efficiently.
- Uses sparse attention mechanisms.

DistilBERT

- A lighter version of BERT.
- Fewer parameters, leading to faster training and inference.
- Maintains approximately 97% of BERT's performance.
- Reduces parameter count by 40%.

ALBERT

- Aimed at reducing memory footprint.
- **Parameter Sharing:**
 - Shares parameters across all layers.
- **Embedding Factorization:**
 - Decomposes the embedding matrix to reduce size.

RoBERTa

- An improved version of BERT.
- Key improvements:
 - ① Removal of Next Sentence Prediction (NSP).
 - ② Training on larger datasets.
 - ③ Implementation of dynamic masking during training.

① Encoder Architecture

② References

References II

- Wettig, A., Baykal, C., Ruder, S., Søgaard, A. (2022). "Should All Tokens be Masked? A Pilot Study of Masked Language Model Performance on Diagnostic Classifiers." *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 36, no. 10, pp. 10993-11001.
- Tjong Kim Sang, E. F., De Meulder, F. (2003). "Introduction to the CoNLL-2003 Shared Task: Language-Independent Named Entity Recognition." In *Proceedings of the 7th Conference on Natural Language Learning at HLT-NAACL 2003*.
- Radford, A., Narasimhan, K., Salimans, T., Sutskever, I. (2018). "Improving Language Understanding by Generative Pre-Training." Retrieved from <https://www.cs.ubc.ca/~amuham01/LING530/papers/radford2018improving.pdf>