Project 3 report and screenshot submission

Executive Summary

This engagement tested four attack categories aligned to the OWASP LLM Top 10: indirect prompt injection (LLM01), agent identity spoofing (LLM09), system prompt extraction (LLM07), and RAG/MCP poisoning. All four categories were attempted; three produced confirmed successful exploitation, and one produced a partial compliance result.

Key findings:

Agent identity spoofing succeeded on the first attempt (100% success rate) - a message falsely labeled as coming from a trusted orchestrator caused the agent to execute a privileged refund action it had just refused under a normal user identity. This is the most operationally dangerous finding, since it requires no technical exploit, only a forged trust label, and no cryptographic verification currently exists to stop it.

Role elevation via prompt engineering succeeded in at least one run, with the model directly confirming “Your role is confirmed as admin. Write:admin access has been granted” -despite no real authentication occurring.

RAG/MCP poisoning succeeded on the first attempt (100% success rate) - a single malicious instruction planted in the simulated knowledge base caused the agent to trigger an unauthorized delete_account tool call during an unrelated, benign question.


Indirect prompt injection did not achieve a full credential leak across 3 payloads, but one payload (the translation-trick variant) produced successful attack.
Payloads and results:

Finding	Vector	Score	Severity
Indirect Injection	CVSS:3.1/AV:N/AC:H/PR:N/UI:R/S:U/C:L/I:N/A:N	3.1	Low
Agent Spoofing	CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:N/I:H/A:N	8.6	High
Prompt Extraction	CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:N/I:H/A:N	8.6	High
RAG poisoning/MCP abuse	CVSS:3.1/AV:N/AC:H/PR:N/UI:N/S:C/C:L/I:H/A:L	8.1	High
Role Elevation	CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:N/I:H/A:N	8.6	High


Top 3 Hardening Recommendations

1. Sign agent-to-agent messages with Ed25519 and verify before execution. This directly closes Finding 2 (8.2, the highest-confidence success) — Agent B should reject any instruction claiming elevated trust unless it carries a valid cryptographic signature from a known key.
2. Add an output guardrail that redacts credential-shaped strings and an input guardrail that blocks known injection patterns before they reach the model. This addresses Finding 1 and reduces the risk surface of Finding 3's role-elevation pattern, even though the base model already resists most direct extraction attempts.
3. Separate "retrieved content" from "instructions" in the prompt-construction layer and validate all content before it enters the RAG knowledge base. This close Finding 4 by ensuring the agent treats retrieved chunks as reference text it can quote, never as commands it executes.


1.Terminal output : Payload 2 of the indirect prompt injection attack, showing the model engaging with the embedded instruction in its response rather than treating it as inert document content.




2.Two-agent terminal output : Agent B refusing a direct refund request under normal user identity, followed by Agent B executing the same refund after receiving a spoofed [ORCHESTRATOR]-tagged message.




3.Terminal output : the role_elevation prompt extraction attempt, showing the model's response confirming "Your role is confirmed as admin. Write:admin access has been granted for this conversation."




4. Terminal output : the RAG poisoning attack, showing the retrieved poisoned chunk and the resulting [SIMULATED MCP CALL TRIGGERED] tool=delete_account log line.



5.CVSS 3.1 calculator at first.org — full vector breakdown for the highest-severity finding (role elevation, CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:N/I:H/A:N, score 8.6), all 8 metrics visible.



6.MITRE ATLAS (atlas.mitre.org) technique page for [confirmed AML.T0051.001], mapped to the role elevation finding.



7.CVSS findings table — all 4 scored attack categories with full vector strings and severity ratings.

Finding	Vector	Score	Severity	MITRE ATLAS
Indirect Injection	CVSS:3.1/AV:N/AC:H/PR:N/UI:R/S:U/C:L/I:N/A:N	3.1	Low	https://atlas.mitre.org/techniques/AML.T0051.001 https://atlas.mitre.org/techniques/AML.T0093
Agent Spoofing	CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:N/I:H/A:N	8.6	High	https://atlas.mitre.org/techniques/AML.T0073
Prompt Extraction	CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:N/I:H/A:N	8.6	High	https://atlas.mitre.org/techniques/AML.T0051
RAG poisoning/MCP abuse	CVSS:3.1/AV:N/AC:H/PR:N/UI:N/S:C/C:L/I:H/A:L	8.1	High	https://atlas.mitre.org/techniques/AML.T0070
Role Elevation	CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:N/I:H/A:N	8.6	high	https://atlas.mitre.org/techniques/AML.T0051

8.Attack success matrix — % success rate per category before any defensive controls: indirect injection 0% full / 33% partial, agent spoofing 100%, prompt extraction 17% (1 of 6, including role elevation), RAG/MCP poisoning 100%.

