WORKSHEET 7 SQL

1-B

2-B,C

3-C

4-C

5-C

6-C

7-C

8-B

9-B

10-A

11. What are joins in SQL?

Joins in SQL are used to combine data from two or more tables based on a common column or set of columns. Join operations are an essential part of querying relational databases, and allow us to extract meaningful insights by combining information from different tables.

12. What are the different types of joins in SQL?

Types of joins in SQL:

Inner join: An inner join returns only the rows from both tables where the join condition is true. In other words, it returns only the records that match in both tables based on the join condition.

Left join: A left join returns all the rows from the left table and the matched rows from the right table. If there is no match, the result will contain NULL values in the columns from the right table.

Right join: A right join returns all the rows from the right table and the matched rows from the left table. If there is no match, the result will contain NULL values in the columns from the left table.

Full outer join: A full outer join returns all the rows from both tables, with NULL values in the columns where there is no match in the other table.

13. What is SQL Server?
SQL Server is a relational database management system (RDBMS) .
It is used to store and manage data in a structured way, with support for tables, columns, and relationships between data.
SQL Server supports the SQL language, which is used to interact with the database and perform operations such as creating tables, inserting data, updating records, and querying data.

SQL Server is widely used in enterprise settings, where it is used to manage large amounts of data across multiple users and applications.

14. What is primary key in SQL?
In SQL, a primary key is a column or set of columns in a table that uniquely identifies each row in that table. It is a type of constraint that ensures that the values in the specified columns are unique and not null.

A primary key can be created when a table is first created, or added to an existing table using the ALTER TABLE statement. The primary key can be made up of one or more columns, depending on the requirements of the table.

Common examples of primary keys include ID columns, social security numbers, and email addresses, among others.

15. What is ETL in SQL?

ETL stands for Extract, Transform, and Load, and it refers to a process of integrating data from various sources, transforming the data to fit the requirements of the target system, and then loading the transformed data into a target database or data warehouse.

ETL is a crucial process in data integration, and it is used to consolidate data from disparate sources into a single, unified view.