National University of Computer and Emerging Sciences



Laboratory Manuals for **Computer Networks**

(CL - 307)

Department of Computer Science FAST-NU, Lahore, Pakistan

Lab Manual 02

Objectives:

• To learn basic commands of Linux related to Directory and File Manipulation, Process management and Network Management

In-lab Statement

1. Find out the purpose of the following commands and execute them on your system with different parameters. [1]

ls, cd, pwd, mkdir, rmdir, rm, cp, mv, touch

2. Some commands may be new for most of you. Practice these terms on your own: [9]

top	The top program provides a dynamic real-time view of a running	top
	system. It can display system summary information as well as a	
	list of tasks currently being managed by the Linux kernel.	
ps	ps displays status of a selection of the active/currently running	ps
	processes.	
kill pid	Kill is used to send a signal to a process. Where pid stands for	kill –SIGKILL
	process id	pid
	Default syntax for this is kill [-signal number or name)] pid	
	On your terminal to see the list of available signals. Kill -L	
	A PID of -1 is special; it indicates all processes except the kill	
	process itself and in it. It will terminate all programs and log	
	off. BEWARE!	
ah-ma d		
chmod	This command is used to grant or revert reading, writing, and	
	executing permissions from a user, group or others. Following	
	are the symbolic representation of three different roles:	
	You can check the details by typing	

	man chmod	
	chmod 400 lab1.txt	
	Check what happened to your file.	
	Now write	
	chmod 700 lab1.txt	
	What happened to your file?	
ifconfig	ifconfig is used to configure the kernel-resident network	ifconfig
	interfaces.	
	If no arguments are given, if config displays the status of the	ifconfig -a
	currently active interfaces. If a single interface argument is	
	given, it displays the status of the given interface only; if a single	ifconfig eth0
	-a argument is given, it displays the status of all interfaces, even	
	those that are down. Otherwise, it configures an interface.	
route	Route manipulates the kernel's IP routing tables. Its primary use	route
	is to set up static routes to specific hosts or networks via an	
	interface.	
SS	The command is used to investigate socket statistics.	
	Use ss-u for udp and ss-t for tcp sockets to analyze which sockets	
	are being used for which protocol.	
wget	wget stands for "web get". It is a command-line utility which	
	downloads files over a network. It supports HTTP, HTTPS, and	
	FTP protocols, as well as retrieval through HTTP proxies. wget	
	has been designed for robustness over slow or unstable network	
	connections; if a download fails due to a network problem, it will	
	keep retrying until the whole file has been retrieved. If the server	
	supports rejects permission, it will instruct the server to continue	
	the download from where it left off.	
	The simplest way to use wget is to simply provide it with the	

	location of a file to download over HTTP. For example, to
	download the file http://website.com/files/file.zip, this command:
	wget http://website.com/files/file.zip
	Where will this file be downloaded?
traceroute	traceroute prints the route that packets take to a network host.
	traceroute gives an insight to the entire path that a packet travels
	through, names and identity of routers and devices in your path,
	network latency (the time taken to send and receive data to each
	devices on the path). It's a tool that can be used to verify the path
	that your data will take to reach its destination, without actually
	sending your data.
	Write on your terminal
	traceroute nu.edu.pk
nslookup	nslookup is a network administration tool for querying the
	Domain Name System (DNS) to obtain domain name or IP
	address mapping or any other specific DNS record. It is also used
	to troubleshoot DNS related problems.
	Write on your terminal window
	nslookup <u>www.google.com</u>
host	It is an alternative of nslookup but with more details. Write up on
	your terminal window: host www.google.com

3. Ping command: [2]

Ping is a command that is used to check the connection and latency rate between two computers in a network. One network pings another in order to exchange data packets (Response) to calculate the latency and exchange rate.

Syntax for Pinging is:

ping [other network's ID (Domain/IP Address)]

Question - You are required to ping at least 5 other networks (including your own address i.e. 127.0.0.1) and compare the <u>latency rate</u> of all networks.

4. Python Question: [4]

Write a Python program to determine the byte ordering (little-endian or big-endian) of your machine. Your program should output the byte ordering of your machine and display how a short integer (2 bytes) is stored in memory, byte by byte.

You can store a hexadecimal number (e.g., `0x3412`) in a short integer and visualize how the data is stored in memory. Use Python's 'struct' module to pack and unpack the data and determine the system's byte order.

Hint:

- Use `sys.byteorder` to determine the system's byte ordering.
- The `struct` module can be used to pack and unpack binary data in Python.

5.Python Question: [4]

Write a Python program that reads a file containing a list of domain names, and for each domain, extract the top-level domain (TLD). A domain name's TLD is the last part of the domain name (e.g., .com, .org, etc.). Use regular expressions to identify and extract the TLD.

Create an input file with following content:

www.google.com

www.testbgp.online

www.python.123

www.fast.edu.pk

www.fast.edu

www.sixtotwo.or