

Frequencies and Offsets

Fundamental to these Pandas time series tools is the concept of a frequency or date offset. Just as we saw the D (day) and H (hour) codes previously, we can use such codes to specify any desired frequency spacing. [Table 3-7](#) summarizes the main codes available.

Table 3-7. Listing of Pandas frequency codes

Code	Description	Code	Description
D	Calendar day	B	Business day
W	Weekly		
M	Month end	BM	Business month end
Q	Quarter end	BQ	Business quarter end
A	Year end	BA	Business year end
H	Hours	BH	Business hours
T	Minutes		
S	Seconds		
L	Milliseconds		
U	Microseconds		
N	Nanoseconds		

The monthly, quarterly, and annual frequencies are all marked at the end of the specified period. Adding an S suffix to any of these marks it instead at the beginning ([Table 3-8](#)).

Table 3-8. Listing of start-indexed frequency codes

Code	Description
MS	Month start
BMS	Business month start
QS	Quarter start
BQS	Business quarter start
AS	Year start
BAS	Business year start

Additionally, you can change the month used to mark any quarterly or annual code by adding a three-letter month code as a suffix:

- Q - JAN, BQ - FEB, QS - MAR, BQS - APR, etc.
- A - JAN, BA - FEB, AS - MAR, BAS - APR, etc.

In the same way, you can modify the split-point of the weekly frequency by adding a three-letter weekday code:

- W - SUN, W - MON, W - TUE, W - WED, etc.

On top of this, codes can be combined with numbers to specify other frequencies. For example, for a frequency of 2 hours 30 minutes, we can combine the hour (H) and minute (T) codes as follows:

```
In[23]: pd.timedelta_range(0, periods=9, freq="2H30T")

Out[23]:
TimedeltaIndex(['00:00:00', '02:30:00', '05:00:00', '07:30:00', '10:00:00',
                '12:30:00', '15:00:00', '17:30:00', '20:00:00'],
              dtype='timedelta64[ns]', freq='150T')
```

All of these short codes refer to specific instances of Pandas time series offsets, which can be found in the `pd.tseries.offsets` module. For example, we can create a business day offset directly as follows:

```
In[24]: from pandas.tseries.offsets import BDay
        pd.date_range('2015-07-01', periods=5, freq=BDay())

Out[24]: DatetimeIndex(['2015-07-01', '2015-07-02', '2015-07-03', '2015-07-06',
                        '2015-07-07'],
                      dtype='datetime64[ns]', freq='B')
```

For more discussion of the use of frequencies and offsets, see the [“DateOffset objects” section of the Pandas online documentation](#).

Resampling, Shifting, and Windowing

The ability to use dates and times as indices to intuitively organize and access data is an important piece of the Pandas time series tools. The benefits of indexed data in general (automatic alignment during operations, intuitive data slicing and access, etc.) still apply, and Pandas provides several additional time series-specific operations.

We will take a look at a few of those here, using some stock price data as an example. Because Pandas was developed largely in a finance context, it includes some very specific tools for financial data. For example, the accompanying `pandas-datareader` package (installable via `conda install pandas-datareader`) knows how to import