

Profiling and Timing Code

In the process of developing code and creating data processing pipelines, there are often trade-offs you can make between various implementations. Early in developing your algorithm, it can be counterproductive to worry about such things. As Donald Knuth famously quipped, “We should forget about small efficiencies, say about 97% of the time: premature optimization is the root of all evil.”

But once you have your code working, it can be useful to dig into its efficiency a bit. Sometimes it’s useful to check the execution time of a given command or set of commands; other times it’s useful to dig into a multiline process and determine where the bottleneck lies in some complicated series of operations. IPython provides access to a wide array of functionality for this kind of timing and profiling of code. Here we’ll discuss the following IPython magic commands:

`%time`

Time the execution of a single statement

`%timeit`

Time repeated execution of a single statement for more accuracy

`%prun`

Run code with the profiler

`%lprun`

Run code with the line-by-line profiler

`%memit`

Measure the memory use of a single statement

`%mprun`

Run code with the line-by-line memory profiler

The last four commands are not bundled with IPython—you’ll need to install the `line_profiler` and `memory_profiler` extensions, which we will discuss in the following sections.

Timing Code Snippets: `%timeit` and `%time`

We saw the `%timeit` line magic and `%%timeit` cell magic in the introduction to magic functions in “IPython Magic Commands” on page 10; `%%timeit` can be used to time the repeated execution of snippets of code:

```
In[1]: %timeit sum(range(100))  
100000 loops, best of 3: 1.54 µs per loop
```

Note that because this operation is so fast, `%timeit` automatically does a large number of repetitions. For slower commands, `%timeit` will automatically adjust and perform fewer repetitions:

```
In[2]: %%timeit
      total = 0
      for i in range(1000):
          for j in range(1000):
              total += i * (-1) ** j
```

1 loops, best of 3: 407 ms per loop

Sometimes repeating an operation is not the best option. For example, if we have a list that we'd like to sort, we might be misled by a repeated operation. Sorting a pre-sorted list is much faster than sorting an unsorted list, so the repetition will skew the result:

```
In[3]: import random
      L = [random.random() for i in range(100000)]
      %timeit L.sort()
```

100 loops, best of 3: 1.9 ms per loop

For this, the `%time` magic function may be a better choice. It also is a good choice for longer-running commands, when short, system-related delays are unlikely to affect the result. Let's time the sorting of an unsorted and a presorted list:

```
In[4]: import random
      L = [random.random() for i in range(100000)]
      print("sorting an unsorted list:")
      %time L.sort()
```

sorting an unsorted list:

CPU times: user 40.6 ms, sys: 896 µs, total: 41.5 ms

Wall time: 41.5 ms

```
In[5]: print("sorting an already sorted list:")
      %time L.sort()
```

sorting an already sorted list:

CPU times: user 8.18 ms, sys: 10 µs, total: 8.19 ms

Wall time: 8.24 ms

Notice how much faster the presorted list is to sort, but notice also how much longer the timing takes with `%time` versus `%timeit`, even for the presorted list! This is a result of the fact that `%timeit` does some clever things under the hood to prevent system calls from interfering with the timing. For example, it prevents cleanup of unused Python objects (known as *garbage collection*) that might otherwise affect the timing. For this reason, `%timeit` results are usually noticeably faster than `%time` results.

For `%time` as with `%timeit`, using the double-percent-sign cell-magic syntax allows timing of multiline scripts:

```
In[6]: %%time
total = 0
for i in range(1000):
    for j in range(1000):
        total += i * (-1) ** j

CPU times: user 504 ms, sys: 979 µs, total: 505 ms
Wall time: 505 ms
```

For more information on `%time` and `%timeit`, as well as their available options, use the IPython help functionality (i.e., type `%time?` at the IPython prompt).

Profiling Full Scripts: `%prun`

A program is made of many single statements, and sometimes timing these statements in context is more important than timing them on their own. Python contains a built-in code profiler (which you can read about in the Python documentation), but IPython offers a much more convenient way to use this profiler, in the form of the magic function `%prun`.

By way of example, we'll define a simple function that does some calculations:

```
In[7]: def sum_of_lists(N):
total = 0
for i in range(5):
    L = [j ^ (j >> i) for j in range(N)]
    total += sum(L)
return total
```

Now we can call `%prun` with a function call to see the profiled results:

```
In[8]: %prun sum_of_lists(1000000)
```

In the notebook, the output is printed to the pager, and looks something like this:

```
14 function calls in 0.714 seconds

Ordered by: internal time
```

ncalls	tottime	percall	cumtime	percall	filename:lineno(function)
5	0.599	0.120	0.599	0.120	<ipython-input-19>:4(<listcomp>)
5	0.064	0.013	0.064	0.013	{built-in method sum}
1	0.036	0.036	0.699	0.699	<ipython-input-19>:1(sum_of_lists)
1	0.014	0.014	0.714	0.714	<string>:1(<module>)
1	0.000	0.000	0.714	0.714	{built-in method exec}

The result is a table that indicates, in order of total time on each function call, where the execution is spending the most time. In this case, the bulk of execution time is in the list comprehension inside `sum_of_lists`. From here, we could start thinking about what changes we might make to improve the performance in the algorithm.