



UNIVERSITY OF ENGINEERING AND TECHNOLOGY, TAXILA
FACULTY OF TELECOMMUNICATION AND INFORMATION ENGINEERING



COMPUTER ENGINEERING DEPARTMENT

Operating systems

SHELL PROGRAMMING

LAB MANUAL 2

Date:	
Name:	
Reg#:	Group:
Marks:	Signature:



UNIVERSITY OF ENGINEERING AND TECHNOLOGY, TAXILA

FACULTY OF TELECOMMUNICATION AND INFORMATION ENGINEERING



COMPUTER ENGINEERING DEPARTMENT

Operating systems

Lab Objective: This lab introduces few of the basic commands of Linux.

Getting Started with Linux

- The login prompt may be graphical or simple text
- If text, logging in will present a **shell**
- If graphical, logging in will present a **desktop**
 - Some combination of mouse and keystrokes will make a **terminal window** appear
 - A shell runs in the terminal window

Linux Command Line

- The shell is where commands are invoked
- A command is typed at a **shell prompt**
 - Prompt usually ends in a dollar sign (\$)
- After typing a command press Enter to invoke it
 - The shell will try to obey the command
 - Another prompt will appear
- Example:
\$ **date**
Sat March 01 11:59:05 BST 2008
\$
 - The dollar represents the prompt in this course, do not type it

Logging Out

- To exit from the shell, use the exit command
- Pressing Ctrl+D at the shell prompt will also quit the shell
 - Quitting all programs should log you out
 - If in a text-only single-shell environment, exiting the shell should be sufficient



UNIVERSITY OF ENGINEERING AND TECHNOLOGY, TAXILA

FACULTY OF TELECOMMUNICATION AND INFORMATION ENGINEERING



COMPUTER ENGINEERING DEPARTMENT

Operating systems

- ✚ In a window environment, the window manager should have a log out command for this purpose
- ✚ After logging out, a new login prompt should be displayed

Command Syntax

- ✚ Most commands take **parameters**
 - Some commands *require* them
 - Parameters are also known as **arguments**
 - For example, echo simply displays its arguments:
\$ echo
\$ echo Hello there
Hello there
- ✚ Commands are case-sensitive
 - Usually lower-case
\$ echo whisper
whisper
\$ ECHO SHOUT
bash: ECHO: command not found

Files

- ✚ Data can be stored in a **file**
- ✚ Each file has a **filename**
 - A label referring to a particular file
 - Permitted characters include letters, digits, hyphens (-), underscores (_), and dots (.)
 - Case-sensitive — *NewsCrew.mov* is a different file from *NewScrew.mov*
- ✚ The ls command lists the names of files



Operating systems

Creating Files with cat

- There are many ways of creating a file
- One of the simplest is with the cat command:

```
$ cat > shopping_list
```

```
cucumber
```

```
bread
```

```
yoghurts
```

```
fish fingers
```

- Note the greater-than sign (>) — this is necessary to create the file
- The text typed is written to a file with the specified name
- Press Ctrl+D after a line-break to denote the end of the file
 - The next shell prompt is displayed
- ls demonstrates the existence of the new file

Displaying Files' Contents with cat

- There are many ways of viewing the contents of a file
- One of the simplest is with the cat command:

```
$ cat shopping_list
```

```
cucumber
```

```
bread
```

```
yoghurts
```

```
fish fingers
```

- Note that no greater-than sign is used
- The text in the file is displayed immediately:
 - Starting on the line after the command
 - Before the next shell prompt



Operating systems

Deleting Files with rm

- ✚ To delete a file, use the rm ('remove') command
- ✚ Simply pass the name of the file to be deleted as an argument:
\$ rm shopping_list
- ✚ The file and its contents are removed
 - There is no recycle bin
 - There is no 'unrm' command
- ✚ The ls command can be used to confirm the deletion

UNIX Command Feedback

- ✚ Typically, successful commands do not give any output
- ✚ Messages are displayed in the case of errors
- ✚ The rm command is typical
 - If it manages to delete the specified file, it does so silently
 - There is no 'File shopping_list has been removed' message
 - But if the command fails for whatever reason, a message is displayed
- ✚ The silence can be off-putting for beginners
- ✚ It is standard behaviour, and doesn't take long to get used to

Copying and Renaming Files with cp and mv

- ✚ To copy the contents of a file into another file, use the cp command:
\$ cp CV.pdf old-CV.pdf
- ✚ To rename a file use the mv ('move') command:
\$ mv committee_minutes.txt committee_minutes.txt
 - Similar to using cp then rm
- ✚ For both commands, the existing name is specified as the first argument and the new name as the second
 - If a file with the new name already exists, it is overwritten



UNIVERSITY OF ENGINEERING AND TECHNOLOGY, TAXILA

FACULTY OF TELECOMMUNICATION AND INFORMATION ENGINEERING



COMPUTER ENGINEERING DEPARTMENT

Operating systems

Filename Completion

- ✚ The shell can making typing filenames easier
- ✚ Once an unambiguous prefix has been typed, pressing Tab will automatically ‘type’ the rest
- ✚ For example, after typing this:
`$ rm sho`
Pressing Tab may turn it into this:
`$ rm shopping_list`
- ✚ This also works with command names
 - For example, da may be completed to date if no other commands start ‘da’

Command History

- ✚ Often it is desired to repeat a previously-executed command
- ✚ The shell keeps a **command history** for this purpose
 - Use the *Up* and Down cursor keys to scroll through the list of previous commands
 - Press *Enter* to execute the displayed command
- ✚ Commands can also be edited before being run
 - Particularly useful for fixing a typo in the previous command
 - The Left and Right cursor keys navigate across a command
 - Extra characters can be typed at any point
 - Backspace deletes characters to the left of the cursor
 - Del and Ctrl+D delete characters to the right
 - Take care not to log out by holding down Ctrl+D too long

Skills Developed

By completing the second lab, one should have basic understanding of Linux environment and few Linux commands.



UNIVERSITY OF ENGINEERING AND TECHNOLOGY, TAXILA
FACULTY OF TELECOMMUNICATION AND INFORMATION ENGINEERING



COMPUTER ENGINEERING DEPARTMENT

Operating systems

Lab Exercises

(Note: you have to perform each lab exercise and submit them accordingly with snapshots and suitable commands with them. Submit lab exercises only, not whole manual)

Q1

- a. Log in. Open a terminal window, to start a shell.
- b. Exit from the shell; the terminal window will close.
- c. Start another shell. Enter each of the following commands in turn.
 - i. date
 - ii. whoami
 - iii. hostname
 - iv. uname
 - v. uptime

Q2

- a. Use the ls command to see if you have any files.
- b. Create a new file using the cat command as follows:
\$ cat > hello.txt
Hello world!
This is a text file.
- c. Press Enter at the end of the last line, then Ctrl+D to denote the end of the file.
- d. Use ls again to verify that the new file exists.
- e. Display the contents of the file.
- f. Display the file again, but use the cursor keys to execute the same command again without having to retype it.

Q3



UNIVERSITY OF ENGINEERING AND TECHNOLOGY, TAXILA
FACULTY OF TELECOMMUNICATION AND INFORMATION ENGINEERING



COMPUTER ENGINEERING DEPARTMENT

Operating systems

- a. Create a second file. Call it *secret-of-the-universe*, and put in whatever content you deem appropriate.
- b. Check its creation with `ls`.
- c. Display the contents of this file. Minimize the typing needed to do this:
 - i. Scroll back through the command history to the command you used to create the file.
 - ii. Change that command to display *secret-of-the-universe* instead of creating it.

Q4

After each of the following steps, use `ls` and `cat` to verify what has happened.

- a. Copy *secret-of-the-universe* to a new file called *answer.txt*. Use Tab to avoid typing the existing file's name in full.
- b. Now copy *hello.txt* to *answer.txt*. What's happened now?
- c. Delete the original file, *hello.txt*.
- d. Rename *answer.txt* to *message*.
- e. Try asking `rm` to delete a file called *missing*. What happens?
- f. Try copying *secret-of-the-universe* again, but don't specify a filename to which to copy. What happens now?