

# Introduction to Algorithms - Reading Notes & Selected Solutions

Nimrod Shneor

October 4, 2019

# Chapter 2

## Solutions to selected exercises:

2.1-1

$A = [31, 41, 59, 26, 41]$   
 $A = [31, 41, 59, 26, 41]$   
 $A = [31, 41, 26, 59, 41]$   
 $A = [31, 26, 41, 59, 41]$   
 $A = [26, 31, 41, 59, 41]$   
 $A = [26, 31, 41, 41, 59]$

2.1-4

---

**Algorithm 1** BinaryAddition( $A, B, n$ )

---

```

carry  $\leftarrow 0$ 
for  $i \leftarrow 1$  to  $n$ : do
     $C[i] \leftarrow (A[i] + B[i] + C[i]) \bmod 2$ 
     $carry \leftarrow A[i] * B[i]$ 
end for
 $C[i + 1] \leftarrow carry$ 
return  $C$ 

```

---

- Input: two  $n$ -bit numbers  $A, B$ .
- Output: the sum of  $A, B$  - an  $n + 1$ -bit number.

2.2-3      Define  $X$  = The number of elements checked in a “brute force” linear search.

Then  $X \in \{1 \dots n\}$  and the average number of elements checked in a linear search is exactly:

$$E[X] = \sum_{i=1}^n \frac{1}{n} i = \frac{1}{n} \sum_{i=1}^n i = \frac{n(n-1)}{2n} = \Theta(n)$$

The worst case is where the last element of the array is the one searched for - resulting in an  $\Theta(n)$  run time.

2.3-3

$$T(n) = \begin{cases} 2 & n = 2 \\ 2T(\frac{n}{2}) + n & n > 2 \end{cases}$$

Q: Proof by induction that if  $n$  is an exact power of two (that is  $n = 2^k$  for some constant  $k \geq 1$ ) then  $T(n) = n \log n$ .

Proof: By induction.

Base case: for  $k = 1$  than  $T(n) = 2 = 2\log 2 = n\log n$   
Assumption: Assume the above holds for all integers up to  $k > 1$ .  
Induction step: We now prove the statement for  $n = 2^{k+1}$ .  
Plugging in to the formula

$$\begin{aligned}
T(n) &= 2T\left(\frac{n}{2}\right) + n = 2T\left(\frac{2^{k+1}}{2}\right) + 2^{k+1} \\
&= 2T(2^k) + 2^{k+1} = 2 * 2^k \log 2^k + 2^{k+1} \\
&= k2^{k+1} + 2^{k+1} = (k+1)2^{k+1} = 2^{k+1} \log 2^{k+1} \\
&= n \log n
\end{aligned}$$

□

---

**Algorithm 2** BinarySearch(A,x)

---

2.3-5

```

 $l \leftarrow 0$ 
 $r \leftarrow \text{length}(A)$ 
while  $l < r - 1$  do
  if  $x = A[\frac{l+r}{2}]$  then
     $\frac{l+r}{2}$ 
  end if
  if  $x > A[\frac{l+r}{2}]$  then
     $l = A[\frac{l+r}{2}]$ 
  else
     $r = A[\frac{l+r}{2}]$ 
  end if
end while
return -1

```

---

At each iteration of the while loop the distance between the two pointers -  $l, r$  - is halved until the element is found or we return -1. The while loop will terminate once the two pointers are at distance two at which point either the element  $x$  is found or the loop will terminate. Thus the distance between the two pointers at each iteration  $i$  is percisly  $\frac{\text{length}(A)}{2^i} = \frac{n}{2^i}$

At the time of the termination the distance between the two pointers is two, thus -

$$\begin{aligned}
\frac{n}{2^i} &= 2 \\
n &= 2^{i+1} \\
\log(n) &= i + 1 \\
\log(n) - 1 &= i \\
\Theta(\log(n)) &= i
\end{aligned}$$

2.3-7

---

**Algorithm 3** FindSum(A,x)

---

```

 $B \leftarrow \text{MergeSort}(A)$ 
 $l \leftarrow 0$ 
 $r \leftarrow \text{length}(B)$ 
while  $l < r$  do
    if  $B[l] + B[r] == x$  then
        return true
    else if  $B[l] + B[r] < x$  then
         $l \leftarrow l + 1$ 
    else
         $r \leftarrow r - 1$ 
    end if
end while
return false

```

---

**Solutions to selected problems:**

2-1

- a            Given  $\frac{n}{k}$  lists each of size  $k$ . Applying *InsertionSort* to each list separately yields worst-case runtime of  $\Theta(k^2)$ . Doing this for all  $\frac{n}{k}$  lists yields an  $\Theta(\frac{n}{k}k^2) = \Theta(nk)$  runtime algorithm.

b

---

**Algorithm 4** ModifiedMergeSort(A)

---

```

Split  $A$  to form  $S = [A_1, \dots, A_{\frac{n}{k}}]$  array of sub-arrays of size  $k$ 
for  $i \leftarrow 1$  to  $\frac{n}{k}$  do
     $A_i \leftarrow \text{InsertionSort}(A_i)$ 
end for
while  $|S| > 1$  do
     $l \leftarrow 1$ 
     $r \leftarrow \text{length}(S)$ 
     $S' \leftarrow \Phi$ 
    while  $l < r$  do
         $S' \leftarrow S' \cup \text{Merge}(A_l, A_r)$ 
         $l \leftarrow l + 1$ 
         $r \leftarrow r - 1$ 
    end while
     $S \leftarrow S'$ 
end while

```

---

We prove that at each iteration of the outer while loop the size of  $|S|$  is  $\frac{n}{2^i k}$ .  
 Proof: By induction,

Base  $i = 1$ : In the first iteration we set  $l$  and  $r$  to hold the two opposite ends of  $S$ , at each iteration we merge two subsets and continue so on until  $l = r$  or  $l > r$  (depending on the number of subsets) because at each iteration we merged two subsets the number of iterations of the inner loop is precisely  $\frac{n}{2^i k}$ .

Step: Assume that the number of subsets in  $|S|$  is  $\frac{n}{2^i k}$  at iteration  $i$  next we prove that at iteration  $i + 1$  the above statement holds.

Again, from the same argument for the base case - at each iteration of the inner loop the number of elements decrease by two the number of iterations of the inner loop is  $\frac{n}{2^{i+1} k}$  yielding that number of subsets.

The outer loop will terminate once  $|S| = 1$ , that is -

$$\begin{aligned}\frac{n}{2^i k} &= 1 \\ \frac{n}{k} &= 2^i \\ \log\left(\frac{n}{k}\right) &= i\end{aligned}$$

At each iteration we perform  $\frac{n}{2^i k}$  merges each runs in  $\Theta(2^i k)$  for a total of  $\Theta(n)$ , Thus the total running time of the while loop is  $\Theta(n \log(\frac{n}{k}))$

All together we get  $\Theta(n \log(\frac{n}{k})) + \Theta(nk)$ .