Experiment 2: Demonstrate Git & GitHub for Source Code Management

MINGW64:/f/3rd Year/Internet Programming (P.E-1)/IP_Experiments

```
ninad@DESKTOP-I4UVVTO MINGW64 /f/3rd Year/Internet Programming (P.E-1)/IP_Experi
ments
$ git config --global user.name "ninadarondekar"

ninad@DESKTOP-I4UVVTO MINGW64 /f/3rd Year/Internet Programming (P.E-1)/IP_Experiments
$ git config --global user.email "ninadarondekar@gmail.com"

ninad@DESKTOP-I4UVVTO MINGW64 /f/3rd Year/Internet Programming (P.E-1)/IP_Experiments
$ git init
Initialized empty Git repository in F:/3rd Year/Internet Programming (P.E-1)/IP_Experiments/.git/

ninad@DESKTOP-I4UVVTO MINGW64 /f/3rd Year/Internet Programming (P.E-1)/IP_Experiments (main)
$ git add .
warning: in the working copy of 'Exp_3/script.js', LF will be replaced by CRLF the next time Git touches it

ninad@DESKTOP-I4UVVTO MINGW64 /f/3rd Year/Internet Programming (P.E-1)/IP_Experiments (main)
$ git commit -m "Added Experiment 3: Designing a calculator using Typescript"
[main (root-commit) 5b93445] Added Experiment 3: Designing a calculator using Typescript
 3 files changed, 220 insertions(+)
 create mode 100644 Exp_3/index.html
 create mode 100644 Exp_3/script.js
 create mode 100644 Exp_3/script.ts

ninad@DESKTOP-I4UVVTO MINGW64 /f/3rd Year/Internet Programming (P.E-1)/IP_Experiments (main)
$ git remote add origin https://github.com/ninadarondekar/IP_Experiments.git

ninad@DESKTOP-I4UVVTO MINGW64 /f/3rd Year/Internet Programming (P.E-1)/IP_Experiments (main)
$ git branch -M main

ninad@DESKTOP-I4UVVTO MINGW64 /f/3rd Year/Internet Programming (P.E-1)/IP_Experiments (main)
$ git push -u origin main
Enumerating objects: 6, done.
Counting objects: 100% (6/6), done.
Delta compression using up to 4 threads
Compressing objects: 100% (5/5), done.
Writing objects: 100% (6/6), 2.20 KiB | 751.00 KiB/s, done.
Total 6 (delta 1), reused 0 (delta 0), pack-reused 0 (from 0)
remote: Resolving deltas: 100% (1/1), done.
To https://github.com/ninadarondekar/IP_Experiments.git
 * [new branch]      main -> main
branch 'main' set up to track 'origin/main'.
```

