Program:

File name: server.js

```
const { MongoClient } = require("mongodb");

const url = "mongodb://localhost:27017/";
const client = new MongoClient(url);

async function con() {
   try {
      await client.connect();
      console.log("Connected!");

      // Accessing the database and the collection
      const db = client.db("collegeDB");
      const c = db.collection("student");

      // ---------- CREATE ----------
      await c.insertOne({ name: "Ninad", age: 20, class: "CSE" });
      await c.insertOne({ name: "Sahil", age: 22, class: "CSE" });

      await c.insertMany([
         { name: "Bob",     age: 21, class: "CE" },
         { name: "Charlie", age: 20, class: "EE" }
      ]);

      // ---------- READ ----------
      const student = await c.findOne({ name: "Ninad" });

      // ---------- UPDATE ----------
      await c.updateOne(
         { name: "Bob" },
         { $set: { age: 20 } }
      );

      // ---------- DELETE ----------
      await c.deleteOne({ name: "Charlie" });
      const finalData = await c.find().toArray();

   } catch (error) {
      console.log("Connection Failed!", error);
   } finally {
      // Closing the connection so the program exits cleanly
      await client.close();
   }
}

con();
```

Output:

1. MongoDB Compass connected to the local server



---

2. Connection established through Node.js

```
PS F:\3rd Year\Internet Programming (P.E-1)\IP_Experiments\Exp_6> node server.js
Connected!
```

---

3. Create operation – insertOne()

```
_id: ObjectId('6aba67833ffb3b4624b41a7c')
name: "Ninad"
age: 20
class: "CSE"
```

```
_id: ObjectId('6aba67833ffb3b4624b41a7d')
name: "Sahil"
age: 22
class: "CSE"
```

4. Create operation – insertMany()

```
_id: ObjectId('6ab7a368b73afa71935e84e5')
name : "Bob"
age : 21
class : "CE"
```

```
_id: ObjectId('6ab7a368b73afa71935e84e6')
name : "Charlie"
age : 20
class : "EE"
```

5. Read operation – findOne()

```
_id: ObjectId('6aba67833ffb3b4624b41a7c')
name: "Ninad"
age: 20
class: "CSE"
```

6. Update operation – updateOne()

```
_id: ObjectId('6aba67833ffb3b4624b41a7e')
name: "Bob"
age: 20
class: "CE"
```

7. Delete operation – deleteOne()

```
_id: ObjectId('6ab7a368b73afa71935e84e5')
name : "Bob"
age : 20
class : "CE"
```

```
_id: ObjectId('6ab7a368b73afa71935e84e3')
name : "Ninad"
age : 20
class : "CSE"
```

```
_id: ObjectId('6ab7a368b73afa71935e84e4')
name : "Sahil"
age : 22
class : "CSE"
```

```
_id: ObjectId('6ab7a368b73afa71935e84e5')
name : "Bob"
age : 20
class : "CE"
```