



```
Router>enable
Router#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Router(config) #ip dhcp excluded-address 192.168.2.100 192.168.2.101
Router(config) #ip dhcp pool net2
Router(dhcp-config) #network 192.168.2.0 255.255.255.0
Router (dhcp-config) #default-router 192.168.2.100
Router (dhcp-config) #dns-server 192.168.2.101
Router(dhcp-config) #int fa0/0
Router(config-if) #ip ad 192.168.2.100 255.255.255.0
Router(config-if) #no sh
Router(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up
Router(config-if) #int fal/0
Router(config-if) #ip ad 192.168.3.2 255.255.255.0
Router(config-if) #no sh
Router(config-if)#
%LINK-5-CHANGED: Interface FastEthernet1/0, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet1/0, changed state to up
Router(config-if) #ro rip
Router (config-router) #net 192.168.2.0
Router(config-router) #net 192.168.3.0\
% Invalid input detected at '^' marker.
Router (config-router) #net 192.168.3.0
Router(config-router)#
```

```
Physical
          Config Desktop Programming
                                         Attributes
 Command Prompt
                                                                                Χ
 C:\>ipconfig
 FastEthernet0 Connection: (default port)
    Connection-specific DNS Suffix..:
    Link-local IPv6 Address.....: FE80::2D0:97FF:FE9D:B03
    IPv6 Address....: ::
    IPv4 Address..... 192.168.2.1
    Subnet Mask..... 255.255.255.0
    Default Gateway....::::
                             192.168.2.100
 Bluetooth Connection:
    Connection-specific DNS Suffix..:
    Link-local IPv6 Address....::
   IPv6 Address....::::
    IPv4 Address..... 0.0.0.0
    Subnet Mask..... 0.0.0.0
    Default Gateway....:::
 C:\>ipconfig
 FastEthernet0 Connection: (default port)
    Connection-specific DNS Suffix..:
    Link-local IPv6 Address.....: FE80::2D0:97FF:FE9D:B03
   IPv6 Address....: ::
    IPv4 Address..... 192.168.2.1
    Subnet Mask..... 255.255.255.0
    Default Gateway....::
                              192.168.2.100
 Bluetooth Connection:
   Connection-specific DNS Suffix..:
    Link-local IPv6 Address....::
    IPv6 Address....:::
    IPv4 Address..... 0.0.0.0
    Subnet Mask..... 0.0.0.0
    Default Gateway....:::
                              0.0.0.0
 C:\>
□ Top
```

```
C:\>ping 192.168.2.1
Pinging 192.168.2.1 with 32 bytes of data:

Reply from 192.168.2.1: bytes=32 time=5ms TTL=128
Reply from 192.168.2.1: bytes=32 time=7ms TTL=128
Reply from 192.168.2.1: bytes=32 time=7ms TTL=128
Reply from 192.168.2.1: bytes=32 time=8ms TTL=128
Ping statistics for 192.168.2.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 5ms, Maximum = 8ms, Average = 6ms
C:\>
```