

## IR2110(-1-2)(S)PbF/IR2113(-1-2)(S)PbF

### HIGH AND LOW SIDE DRIVER


#### Features

- Floating channel designed for bootstrap operation  
Fully operational to +500V or +600V  
Tolerant to negative transient voltage  
dV/dt immune
- Gate drive supply range from 10 to 20V
- Undervoltage lockout for both channels
- 3.3V logic compatible  
Separate logic supply range from 3.3V to 20V  
Logic and power ground  $\pm 5V$  offset
- CMOS Schmitt-triggered inputs with pull-down
- Cycle by cycle edge-triggered shutdown logic
- Matched propagation delay for both channels
- Outputs in phase with inputs

#### Product Summary

$V_{\text{OFFSET}}$ (IR2110)	500V max.
(IR2113)	600V max.
$I_{\text{O+/-}}$	2A / 2A
$V_{\text{OUT}}$	10 - 20V
$t_{\text{on/off}}$ (typ.)	120 & 94 ns
Delay Matching (IR2110)	10 ns max.
(IR2113)	20ns max.


#### Packages



#### Description

The IR2110/IR2113 are high voltage, high speed power MOSFET and IGBT drivers with independent high and low side referenced output channels. Proprietary HVIC and latch immune CMOS technologies enable ruggedized monolithic construction. Logic inputs are compatible with standard CMOS or LSTTL output, down to 3.3V logic. The output drivers feature a high pulse current buffer stage designed for minimum driver cross-conduction. Propagation delays are matched to simplify use in high frequency applications. The floating channel can be used to drive an N-channel power MOSFET or IGBT in the high side configuration which operates up to 500 or 600 volts.

#### Typical Connection



## IR2110(-1-2)(S)PbF/IR2113(-1-2)(S)PbF

International  
IR Rectifier

## Absolute Maximum Ratings

Absolute maximum ratings indicate sustained limits beyond which damage to the device may occur. All voltage parameters are absolute voltages referenced to COM. The thermal resistance and power dissipation ratings are measured under board mounted and still air conditions. Additional information is shown in Figures 28 through 35.

Symbol	Definition	Min.	Max.	Units
$V_B$	High side floating supply voltage (IR2110)	-0.3	525	V
	(IR2113)	-0.3	625	
$V_S$	High side floating supply offset voltage	$V_B - 25$	$V_B + 0.3$	
$V_{HO}$	High side floating output voltage	$V_S - 0.3$	$V_B + 0.3$	
$V_{CC}$	Low side fixed supply voltage	-0.3	25	
$V_{LO}$	Low side output voltage	-0.3	$V_{CC} + 0.3$	
$V_{DD}$	Logic supply voltage	-0.3	$V_{SS} + 25$	
$V_{SS}$	Logic supply offset voltage	$V_{CC} - 25$	$V_{CC} + 0.3$	
$V_{IN}$	Logic input voltage (HIN, LIN & SD)	$V_{SS} - 0.3$	$V_{DD} + 0.3$	
$dV_S/dt$	Allowable offset supply voltage transient (figure 2)	—	50	V/ns
$P_D$	Package power dissipation @ $T_A \leq +25^\circ\text{C}$ (14 lead DIP)	—	1.6	W
	(16 lead SOIC)	—	1.25	
$R_{THJA}$	Thermal resistance, junction to ambient (14 lead DIP)	—	75	$^\circ\text{C}/\text{W}$
	(16 lead SOIC)	—	100	
$T_J$	Junction temperature	—	150	$^\circ\text{C}$
$T_S$	Storage temperature	-55	150	
$T_L$	Lead temperature (soldering, 10 seconds)	—	300	

## Recommended Operating Conditions

The input/output logic timing diagram is shown in figure 1. For proper operation the device should be used within the recommended conditions. The  $V_S$  and  $V_{SS}$  offset ratings are tested with all supplies biased at 15V differential. Typical ratings at other bias conditions are shown in figures 36 and 37.

Symbol	Definition	Min.	Max.	Units
$V_B$	High side floating supply absolute voltage	$V_S + 10$	$V_S + 20$	V
$V_S$	High side floating supply offset voltage (IR2110)	Note 1	500	
	(IR2113)	Note 1	600	
$V_{HO}$	High side floating output voltage	$V_S$	$V_B$	
$V_{CC}$	Low side fixed supply voltage	10	20	
$V_{LO}$	Low side output voltage	0	$V_{CC}$	
$V_{DD}$	Logic supply voltage	$V_{SS} + 3$	$V_{SS} + 20$	
$V_{SS}$	Logic supply offset voltage	-5 (Note 2)	5	
$V_{IN}$	Logic input voltage (HIN, LIN & SD)	$V_{SS}$	$V_{DD}$	$^\circ\text{C}$
$T_A$	Ambient temperature	-40	125	

Note 1: Logic operational for  $V_S$  of -4 to +500V. Logic state held for  $V_S$  of -4V to  $-V_{BS}$ . (Please refer to the Design Tip DT97-3 for more details).

Note 2: When  $V_{DD} < 5\text{V}$ , the minimum  $V_{SS}$  offset is limited to  $-V_{DD}$ .

**IR2110(-1-2)(S)PbF/IR2113(-1-2)(S)PbF****Dynamic Electrical Characteristics**

$V_{BIAS}$  ( $V_{CC}$ ,  $V_{BS}$ ,  $V_{DD}$ ) = 15V,  $C_L$  = 1000 pF,  $T_A$  = 25°C and  $V_{SS}$  = COM unless otherwise specified. The dynamic electrical characteristics are measured using the test circuit shown in Figure 3.

Symbol	Definition	Figure	Min.	Typ.	Max.	Units	Test Conditions
$t_{on}$	Turn-on propagation delay	7	—	120	150	ns	$V_S = 0V$
$t_{off}$	Turn-off propagation delay	8	—	94	125		$V_S = 500V/600V$
$t_{sd}$	Shutdown propagation delay	9	—	110	140		$V_S = 500V/600V$
$t_r$	Turn-on rise time	10	—	25	35		
$t_f$	Turn-off fall time	11	—	17	25		
MT	Delay matching, HS & LS turn-on/off	(IR2110) (IR2113)	—	—	—	10 20	

**Static Electrical Characteristics**

$V_{BIAS}$  ( $V_{CC}$ ,  $V_{BS}$ ,  $V_{DD}$ ) = 15V,  $T_A$  = 25°C and  $V_{SS}$  = COM unless otherwise specified. The  $V_{IN}$ ,  $V_{TH}$  and  $I_{IN}$  parameters are referenced to  $V_{SS}$  and are applicable to all three logic input leads: HIN, LIN and SD. The  $V_O$  and  $I_O$  parameters are referenced to COM and are applicable to the respective output leads: HO or LO.

Symbol	Definition	Figure	Min.	Typ.	Max.	Units	Test Conditions
$V_{IH}$	Logic "1" input voltage	12	9.5	—	—	V	
$V_{IL}$	Logic "0" input voltage	13	—	—	6.0		
$V_{OH}$	High level output voltage, $V_{BIAS} - V_O$	14	—	—	1.2		$I_O = 0A$
$V_{OL}$	Low level output voltage, $V_O$	15	—	—	0.1		$I_O = 0A$
$I_{LK}$	Offset supply leakage current	16	—	—	50	$\mu A$	$V_B = V_S = 500V/600V$
$I_{QBS}$	Quiescent $V_{BS}$ supply current	17	—	125	230		$V_{IN} = 0V$ or $V_{DD}$
$I_{QCC}$	Quiescent $V_{CC}$ supply current	18	—	180	340		$V_{IN} = 0V$ or $V_{DD}$
$I_{QDD}$	Quiescent $V_{DD}$ supply current	19	—	15	30		$V_{IN} = 0V$ or $V_{DD}$
$I_{IN+}$	Logic "1" input bias current	20	—	20	40		$V_{IN} = V_{DD}$
$I_{IN-}$	Logic "0" input bias current	21	—	—	1.0		$V_{IN} = 0V$
$V_{BSUV+}$	$V_{BS}$ supply undervoltage positive going threshold	22	7.5	8.6	9.7	V	
$V_{BSUV-}$	$V_{BS}$ supply undervoltage negative going threshold	23	7.0	8.2	9.4		
$V_{CCUV+}$	$V_{CC}$ supply undervoltage positive going threshold	24	7.4	8.5	9.6		
$V_{CCUV-}$	$V_{CC}$ supply undervoltage negative going threshold	25	7.0	8.2	9.4		
$I_{O+}$	Output high short circuit pulsed current	26	2.0	2.5	—	A	$V_O = 0V$ , $V_{IN} = V_{DD}$ $PW \leq 10 \mu s$
$I_{O-}$	Output low short circuit pulsed current	27	2.0	2.5	—		$V_O = 15V$ , $V_{IN} = 0V$ $PW \leq 10 \mu s$



## IR2110(-1-2)(S)PbF/IR2113(-1-2)(S)PbF

### Lead Assignments

<p>14 Lead PDIP <b>IR2110/IR2113</b></p>	<p>16 Lead SOIC (Wide Body) <b>IR2110S/IR2113S</b></p>
<p>14 Lead PDIP w/o lead 4 <b>IR2110-1/IR2113-1</b></p>	<p>14 Lead PDIP w/o leads 4 &amp; 5 <b>IR2110-2/IR2113-2</b></p>
Part Number	



International  
**IR** Rectifier

## IR2110(-1-2)(S)PbF/IR2113(-1-2)(S)PbF




Figure 7A. Turn-On Time vs. Temperature




Figure 7B. Turn-On Time vs. Vcc/Vbs Supply Voltage




Figure 7C. Turn-On Time vs. VDD Supply Voltage




Figure 8A. Turn-Off Time vs. Temperature




Figure 8B. Turn-Off Time vs. Vcc/Vbs Supply Voltage




Figure 8C. Turn-Off Time vs. VDD Supply Voltage

# IR2110(-1-2)(S)PbF/IR2113(-1-2)(S)PbF

International  
**IR** Rectifier




Figure 9A. Shutdown Time vs. Temperature




Figure 9B. Shutdown Time vs. Vcc/Vbs Supply Voltage




Figure 9C. Shutdown Time vs. VDD Supply Voltage




Figure 10A. Turn-On Rise Time vs. Temperature




Figure 10B. Turn-On Rise Time vs. Voltage




Figure 11A. Turn-Off Fall Time vs. Temperature






Figure 11B. Turn-Off Fall Time vs. Voltage




Figure 12A. Logic "1" Input Threshold vs. Temperature




Figure 12B. Logic "1" Input Threshold vs. Voltage




Figure 13A. Logic "0" Input Threshold vs. Temperature




Figure 13B. Logic "0" Input Threshold vs. Voltage




Figure 14A. High Level Output vs. Temperature

# IR2110(-1-2)(S)PbF/IR2113(-1-2)(S)PbF

International  
**IR** Rectifier




Figure 14B. High Level Output vs. Voltage




Figure 15A. Low Level Output vs. Temperature




Figure 15B. Low Level Output vs. Voltage




Figure 16A. Offset Supply Current vs. Temperature




Figure 16B. Offset Supply Current vs. Voltage




Figure 17A. V<sub>BS</sub> Supply Current vs. Temperature

International  
**IR** Rectifier

## IR2110(-1-2)(S)PbF/IR2113(-1-2)(S)PbF




Figure 17B.  $V_{BS}$  Supply Current vs. Voltage




Figure 18A.  $V_{CC}$  Supply Current vs. Temperature




Figure 18B.  $V_{CC}$  Supply Current vs. Voltage




Figure 19A.  $V_{DD}$  Supply Current vs. Temperature




Figure 19B.  $V_{DD}$  Supply Current vs.  $V_{DD}$  Voltage




Figure 20A. Logic "1" Input Current vs. Temperature

# IR2110(-1-2)(S)PbF/IR2113(-1-2)(S)PbF

International  
**IR** Rectifier




Figure 20B. Logic "1" Input Current vs. V<sub>DD</sub> Voltage




Figure 21A. Logic "0" Input Current vs. Temperature




Figure 21B. Logic "0" Input Current vs. V<sub>DD</sub> Voltage




Figure 22. V<sub>BS</sub> Undervoltage Lockout (+) vs. Temperature




Figure 23. V<sub>BS</sub> Undervoltage Lockout (-) vs. Temperature




Figure 24. V<sub>CC</sub> Undervoltage Lockout (+) vs. Temperature

International  
IR Rectifier

## IR2110(-1-2)(S)PbF/IR2113(-1-2)(S)PbF




Figure 25. Vcc Undervoltage (-) vs. Temperature




Figure 26A. Output Source Current vs. Temperature




Figure 26B. Output Source Current vs. Voltage




Figure 27A. Output Sink Current vs. Temperature




Figure 27B. Output Sink Current vs. Voltage






Figure 28. IR2110/IR2113  $T_J$  vs. Frequency  
(IRFBC20)  $R_{GATE} = 33\Omega$ ,  $V_{CC} = 15V$

# IR2110(-1-2)(S)PbF/IR2113(-1-2)(S)PbF


International  
**IR** Rectifier




**Figure 29. IR2110/IT2113  $T_j$  vs. Frequency (IRFBC30)  $R_{\text{GATE}} = 22\Omega$ ,  $V_{\text{CC}} = 15\text{V}$**




**Figure 30. IR2110/IR2113  $T_j$  vs. Frequency (IRFBC40)  $R_{\text{GATE}} = 15\Omega$ ,  $V_{\text{CC}} = 15\text{V}$**




**Figure 31. IR2110/IR2113  $T_j$  vs. Frequency (IRFPE50)  $R_{\text{GATE}} = 10\Omega$ ,  $V_{\text{CC}} = 15\text{V}$**



**Figure 32. IR2110S/IR2113S  $T_j$  vs. Frequency (IRFBC20)  $R_{\text{GATE}} = 33\Omega$ ,  $V_{\text{CC}} = 15\text{V}$**




**Figure 33. IR2110S/IR2113S  $T_j$  vs. Frequency (IRFBC30)  $R_{\text{GATE}} = 22\Omega$ ,  $V_{\text{CC}} = 15\text{V}$**




**Figure 34. IR2110S/IR2113S  $T_j$  vs. Frequency (IRFBC40)  $R_{\text{GATE}} = 15\Omega$ ,  $V_{\text{CC}} = 15\text{V}$**


## IR2110(-1-2)(S)PbF/IR2113(-1-2)(S)PbF



**Figure 35. IR2110S/IR2113S  $T_J$  vs. Frequency (IRFPE50)  $R_{GATE} = 10\Omega$ ,  $V_{CC} = 15V$**



**Figure 36. Maximum  $V_S$  Negative Offset vs.  $V_{BS}$  Supply Voltage**





**Figure 37. Maximum  $V_{SS}$  Positive Offset vs.  $V_{CC}$  Supply Voltage**

# IR2110(-1-2)(S)PbF/IR2113(-1-2)(S)PbF

International  
**IR** Rectifier



## Case Outlines






International  
**IR** Rectifier

## IR2110(-1-2)(S)PbF/IR2113(-1-2)(S)PbF



**IR2110(-1-2)(S)PbF/IR2113(-1-2)(S)PbF**International  
**IR** Rectifier**LEADFREE PART MARKING INFORMATION****ORDER INFORMATION****Part only available Lead Free**

14-Lead PDIP IR2110 order IR2110PbF  
 14-Lead PDIP IR2110-1 order IR2110-1PbF  
 14-Lead PDIP IR2110-2 order IR2110-2PbF  
 14-Lead PDIP IR2113 order IR2113PbF  
 14-Lead PDIP IR2113-1 order IR2113-1PbF  
 14-Lead PDIP IR2113-2 order IR2113-2PbF  
 16-Lead SOIC IR2110S order IR2110SPbF  
 16-Lead SOIC IR2113S order IR2113SPbF

International  
**IR** Rectifier**IR WORLD HEADQUARTERS:** 233 Kansas St., El Segundo, California 90245 Tel: (310) 252-7105**This product has been qualified per industrial level***Data and specifications subject to change without notice 3/23/2005*



**电查网** [www.ic5.cn](http://www.ic5.cn)

地球上最全的电子元器件资料查询网站，1500多万种型号，  
与主流厂商同步更新。没错，这就是电查网！！！！