

rGMAP

June 12, 2018

Type Package

Title Call hierarchical chromatin domains from HiC matrix by GMAP

Version 1.3

Date 06-11-2018

Author Wenbao Yu

Maintainer Wenbao Yu <yuw1@email.chop.edu>

Description Call hierarchical chromatin domains from HiC contact matrix by Gaussian Mixture model And Proportion test

License GPL (>= 2)

LazyData TRUE

Imports data.table,
ggplot2,
mclust,
EMD,
caTools,
Matrix,
Rcpp (>= 0.12.5)

LinkingTo Rcpp

RoxygenNote 6.0.1

R topics documented:

data_simu	2
hic_rao_IMR90_chr15	2
plotdom	3
rGMAP	3
Index	5

data_simu	<i>generate simulated hic_mat and true tads</i>
-----------	---

Description

generate simulated hic_mat and true tads

Usage

```
data_simu(stype = "poisson-dist", nratio = 2.5, mu0 = 20, resl = 1)
```

Arguments

stype	One of four types of simulated data in the manuscript: poisson-dist, poisson-dist-hier, nb-dist, nb-dist-hier; poisson- or nb- indicates poisson distribution or negative binomial distribution -hier indicated subtads are generated nestly
nratio	The effect size between intra- and inter domain, larger means higher intra-tad contacts
mu0	The mean parameter, default 20
resl	Resolution, default set to 1

Value

A list includes following elements:

hic_mat	n by n contact matrix
hierTads	True heirarchical domains
tads_true	True TADs

hic_rao_IMR90_chr15	<i>Normalized Hi-C data for IMR90, chr15 with resolution 10kb.</i>
---------------------	--

Description

Normalized Hi-C data for IMR90, chr15 with resolution 10kb.

Usage

```
hic_rao_IMR90_chr15
```

Format

A data table with 3 variables:

n1 bin 1

n2 bin 2

count normalized counts

Source

Rao et al., Cell 2014, A 3D map of the human genome at kilobase resolution reveals principles of chromatin looping

plotdom	<i>visualize hierarchical domains</i>
---------	---------------------------------------

Description

visualize hierarchical domains

Usage

```
plotdom(hic_dat, hiertads_gmap, start_bin, end_bin, cthr = 20, kb_resl = 10)
```

Arguments

hiertads_gmap	the hierarchical domains called by gmap
start_bin	the start bin of the genome
end_bin	the end bin of the genome
cth	the count threshold for color, default 20
kb_resl	reslution of Hi-C data in kb
hic_mat	hic_mat with 3 columns matrix or data.frame with columns: bin1, bin2, counts, in which bin1 and bin2, from 1 to m, are the bin

rGMAP	<i>Detect hierarchical choromotin domains by GMAP</i>
-------	---

Description

Detect hierarchical choromotin domains by GMAP

Usage

```
rGMAP(hic_mat, resl = 10 * 10^3, logt = T, dom_order = 2, min_d = 25,
      max_d = 100, min_dp = 5, max_dp = 10, maxDistInBin = min(200, 2 *
      10^6/resl), hthr = 0.95, tlthr = 0.5)
```

Arguments

<code>hic_mat</code>	Either a 3 columns Hi-C contact matrix for a given chromosome, with each row corresponding to the start bin, end bin and the contact number; or a n by n matrix, n is the number of bins for a given chromosom
<code>resl</code>	The resolution (bin size), default 10kb
<code>logt</code>	Do log-transformation or not, default TRUE
<code>dom_order</code>	Maximum level of hierarchical structures, default 2 (call TADs and subTADs)
<code>min_d</code>	The minimum d (d: window size), default 25
<code>max_d</code>	The maximum d (d: window size), default 100
<code>min_dp</code>	The minmum dp (dp: lower bound of tad size), default 5
<code>max_dp</code>	The maximum dp (dp: lower bound of tad size), default 10. <code>min_d</code> , <code>max_d</code> , <code>min_dp</code> and <code>max_dp</code> should be specified in number of bins
<code>maxDistInBin</code>	Only consider contact whose distance is not greater than <code>maxDistInBin</code> bins, default 200 bins (or 2Mb)
<code>hthr</code>	The lower bound cutoff for posterior probability, default 0.95
<code>t1thr</code>	Lower bound for t1 for calling TAD, default 0.5 quantile of test statistics of TADs, 0.9 of subTADs

Value

A list includes following elements:

<code>tads</code>	A data frame with columns start, end indicates the start and end coordinates of each domain, respectively
<code>hierTads</code>	A data frame with columns start, end, dom_order, where dom_order indicates the hierarchical status of a domain, 1 indicates tads, 2 indicates subtads, and so on
<code>params</code>	A data frame gives the final parameters for calling TADs

Index

*Topic **datasets**

hic_rao_IMR90_chr15, [2](#)

data_simu, [2](#)

hic_rao_IMR90_chr15, [2](#)

plotdom, [3](#)

rGMAP, [3](#)