

# Machine Learning

---

## Chap2

- The gradient of a function ::= a vector of partial derivatives

$$f([x^{(1)}, x^{(2)}]) = ax^{(1)} + bx^{(2)} + c, \quad \nabla f \text{ is given by the vector } \left[ \frac{\partial f}{\partial x^{(1)}}, \frac{\partial f}{\partial x^{(2)}} \right]$$

- Random variables
  - Usually expressed by italic capital letter
  - Expectation value

$$\begin{aligned} \mathbb{E}[X] &\stackrel{\text{def}}{=} \sum_{i=1}^k [x_i \cdot \Pr(X = x_i)] \\ &= x_1 \cdot \Pr(X = x_1) + x_2 \cdot \Pr(X = x_2) + \dots + x_k \cdot \Pr(X = x_k), \end{aligned}$$

- Hyperparameters -> set by data analysts
- Parameters -> directly modified by learning algorithms
- Classification ::= assign labels to unlabeled examples
- Regression ::= predicting real valued labels (target)
- Model based & Instrumental Based Learning
  - Model-based:
    - Creates models
    - Develops parameter
    - Like  $w^*$  &  $b^*$  of SVM
  - Instrumental Based Learning
    - K-Nearest Neighbors (KNN)
    - Look at the close neighborhood of the input, output the most often ones.