Ref. Ares(2025)7733636 - 16/09/2025

EUROPEAN
COMMISSION

Brussels, XXX
[…](2025) XXX draft

ANNEX

ANNEX

to the

Commission Delegated Regulation

supplementing Regulation (EU) 2023/1542 of the European Parliament and of the Council by establishing the methodology for the calculation and verification of the recycled content in batteries, and the format for the documentation.

DRAFT

Disclaimer

This draft is a working document supporting the development of a methodology for the calculation and verification of the recycled content in batteries, and the format for the documentation. It sets out an initial draft of the text to support the stakeholders' consultation process, in particular the Waste Expert Group meeting of 15 October 2025.

Please note that this draft has not been adopted nor endorsed by the European Commission. Any views expressed are the preliminary views of DG ENV and JRC staff and may not in any circumstances be regarded as stating an official position of the European Commission.

ANNEX

Methodology for the calculation and verification of the percentage share of cobalt, lithium or nickel that is present in active materials and that has been recovered from battery manufacturing waste or post-consumer waste, and the percentage share of lead that is present in the battery and that has been recovered from waste, and the format for the documentation.

*Note: this working document is presenting two possible options regarding the implementation of the chain of custody models to be chosen to implement the calculation and verification methodology. The parts specific to each option are indicated in brackets and identifiable by the labels **option 1** and **option 2**. The endings of the specific sections are also identified by the following markers: / for option 1, / for option 2. The rest of the text remain valid for both options. Choosing one option means retaining, throughout the text, all the text bracketed and identified by the label of this option while deleting the text bracketed and identified by the label of the other option.*

1. Definitions

For the purposes of this Annex the following definitions shall apply:

(1) "Recycled material" means materials obtained from eligible waste materials outlined in Article 8 of Regulation (EU) 2023/1542, following a recycling process, or derived materials thereof obtained after further transformation processes;

(2) "Recycled content" means the proportion, by mass of recycled to total cobalt, lithium or nickel in active materials of a battery or recycled to total lead in a battery;

(3) "plant" means the location with geographical boundaries at which defined activities under the control of an organisation are carried out [Note 1 to entry: Sites may be in one geographical area but need not be contiguous. For example, a road can separate two geographical areas that are operated as a single site];

(4) "Manufacturing plant" means a location where one or more of the following occur: synthesis, processing, and formulation of raw materials or intermediate components required for battery manufacturing.

(5) "Supply chain" means the series of processes or activities involved in the production and distribution of a material or product through which it passes from the source [Note 1 to entry: A supply chain is typically composed of a series of different organisations];

(6) "Supply chain actor" means an entity or group of people and facilities with an arrangement of responsibilities, authorities and relationships and identifiable objectives, that is part of the supply chain;

DRAFT

(7) "Input fraction" means the mass of any material or product that enters a production process of a supply chain actor [Note 1 to entry: Input fractions may be used at any step of the supply chain; Note 2 to entry: Input fractions may also include secondary materials; Note 3 to entry: Input fractions will have associated information].

(8) "Output fraction" means the mass of any material or product that leaves a production plant of a supply chain actor [Note 1 to entry: Output fractions can be created at any step of the supply chain; Note 2 to entry: Output fractions might include other products resulting from production processes; Note 3 to entry: Output fractions will have associated information];

(9) "process" Set of interrelated or interacting activities that use inputs to deliver an intended output [Note 1 to entry: A process can include services].

(10) "Traceability" means the ability to trace the history, application, location or source(s) of a material or product throughout the supply chain;

(11) "Chain of custody" means a process by which inputs and outputs and associated information are transferred, monitored and controlled as they move through each step in the relevant supply chain;

(12) "Accounting period" means a timeframe defined for bookkeeping purposes, to reconcile input and output materials and to reallocate volumes of recycled material;

(13) "Volume reconciliation" means the reconciliation of inputs and outputs through the production process within the accounting period;

(14) "Conversion factor" means a factor that describes the change in quantity of a specific material due to processing. It shall be calculated for each processing step and shall be based on actual data;

(15) "toll-treatment mechanism" means a business arrangement under which the treatment of waste and waste-derived materials is performed as a service for a specific operator or partner. In this context, the same entity serves as both the supplier of the input fraction and the receiver of the equivalent processed material as the output fraction.

2. Calculation rules

2.1. Recycled content in batteries placed on the Union market

Battery manufacturers shall calculate the mass percentage share of cobalt, lithium or nickel that is present in active materials and that has been recovered from battery manufacturing waste or post-consumer waste, and the mass percentage share of lead that is present in the battery and that has been recovered from waste, for each battery model per year and per manufacturing plant.

Battery manufacturers and their supply chain actors shall calculate the recycled content of their output fractions. To this end, the supplier of materials shall give information of recycled content based on calculations indicated in section 2.4. Calculations shall only be performed at supply steps that transform or mix materials.

2.2. Chain of custody model and system description

2.2.1 System boundary for calculation

The spatial system boundary for the calculation is the manufacturing plant. It includes all production lines and processes, storages of inputs and storages of outputs, including by-products and waste. Volume reconciliation is performed at manufacturing plant level over the accounting period (see sections 2.2.3 and 2.2.4.)

2.2.2 Chain of custody

The calculation and verification of recycled content shall rely on a traceability system, which ensures that recycled content can be tracked from the moment waste enters a recycling plant to the moment the derived secondary material is used in a battery model. The traceability system is based exclusively on documentation.

Battery manufacturers shall collect the evidence and information determining the input data for the recycled content calculations of the battery. Manufacturers shall collect information from preceding supply chain actors, starting with suppliers of secondary material. Each supply chain actor shall keep traceability data in their own local system, with data in accordance with section 2.3 shared between supply chain actors upstream and downstream.

The traceability of information shall be achieved through the implementation of a pre-defined chain of custody model.

[option 1- Plant-level mass balance with volume reconciliation and credit allocation for processing as a service: The chain of custody model shall correspond to plant-level mass balance with volume reconciliation and credit allocation for processing as a service. Recycled content is distributed proportionally across all plant output fractions during an accounting period, unless a toll-treatment mechanism applies. A toll-treatment mechanism allows supply chain actors to allocate a higher recycled content to specific outputs intended for battery manufacturing, provided that the supplier of the secondary material (containing Li, Co, Ni, or Pb) also purchases an equivalent quantity of processed material from the plant (e.g., through take-back agreements or strategic partnerships). If this condition is not fulfilled, it is not permissible to assign a recycled content higher than the average across all output fractions to any specific batch or production line.

The following specific requirements shall apply for all supply chain actors, including the battery manufacturer:

- Input-output reconciliation: The quantities received and supplied to customers shall be reconciled within a defined accounting period, to verify that recycled content in output fractions relate to the input fractions.
- Volume reconciliation: Volume reconciliation for recycled content allocation within an accounting period entails the possibility to re-distribute recycled content generated at a manufacturing plant over the accounting period.
- Proportional allocation of recycled content: Recycled content from all output fractions generated during an accounting period shall be proportionally

distributed across all plant-level process output fractions for materials outside the toll-treatment mechanism.

- Credit allocation for processing as a service: When a supplier of secondary input fractions also serves as the customer of the resulting output fractions, the recycled content in those output fractions—adjusted for process losses—may directly correspond to the recycled content in the supplied input fractions.
- No credit carryover: Recycled content credits shall not be carried over to the next accounting period, as any recycled content outside the toll-treatment mechanism is proportionally allocated across all outputs produced during the current accounting period.
- Recycled content credits shall not be transferred between different facilities of a company or between different companies. **/]**

[option 2 - Plant-level mass balance with volume reconciliation and credit allocation equitably distributed per economic area: The chain of custody model shall correspond to plant-level mass balance with volume reconciliation and credit allocation equitably distributed per economic area. Recycled content may be allocated to any output fraction during the accounting period, but when output fractions are directed to different markets (the Union market or third countries markets), the maximum credit allocation for each market is capped at the plant's average recycled content during the accounting period.

The following specific requirements shall apply for all supply chain actors, including the battery manufacturer:

- Input-output reconciliation: The quantities received and supplied to customers shall be reconciled within a defined accounting period, to verify that recycled content output fractions relate to the input fractions.
- Volume reconciliation: Volume reconciliation for recycled content allocation within an accounting period entails the possibility to re-distribute recycled content generated at a manufacturing plant over the accounting period.
- Market-specific cap: For output fractions directed to different markets (i.e. Union market and third country markets), the maximum credit allocation for output fractions in any specific market is capped by the plant's average recycled content during the accounting period.
- Unrestricted allocation: Recycled content from all output fractions destined for a specific market produced during the accounting period may be allocated to selected output fractions.
- Credit carryover: Positive recycled content credits may be carried forward to the next accounting period, while negative balances cannot be transferred beyond the period.
- Recycled content credits shall not be transferred between different facilities of a company or between different companies. **/]**

2.2.3. Accounting period

The battery manufacturer and the other supply chain actors shall choose the length of the accounting period. It shall not exceed the documentation period of 12 months. The accounting period shall be longer than the maximum possible residence time of metals in the production system **[*option 2:*** and its associated storage facilities. **/]**

In the case where input fractions have started to be processed during an accounting

period, but output fractions are only produced in a subsequent accounting period data relating to input fractions consumption and output fractions production shall be recorded in the accounting period where output fractions are produced.

For made-to-order production in a non-serial production process, the accounting period shall be determined by the total production time for the specific order. For new production lines where the chosen accounting period has not yet been completed at the time of calculation, the accounting period shall be set to the time elapsed since the production line started operating.

Accounting periods must be structured so that each accounting period's start and end dates fall within the year of documentation, allowing for multiple periods to be included as required.

2.2.4. Volume reconciliation in the accounting period

Volume reconciliation for recycled content allocation within an accounting period involves budgeting, distributing, and allocating recycled content to distinct output fractions produced during that timeframe. **[option1:** Recycled content is proportionally allocated to output fractions outside the toll-treatment mechanism. All input fractions under the toll-treatment mechanism are then assigned the same recycled content after processing, adjusted for process losses.

For assigning the recycled content of output fractions, a rolling average shall be used. The recycled content of each output fraction shall be based on the recycled content in output fractions produced over a time period equal to the length of the accounting period, including the batch to be assigned a documented recycled content. This ensures the recycled content reflects the average of all batches produced at the plant from the preceding period. A rolling average is a dynamic method that calculates the average recycled content over a fixed-length timeframe (e.g., 90 days) that shifts forward as new data is added. As new outputs are produced, the oldest data from the timeframe is dropped, and the newest data is included, creating a continuously updated average. This approach accounts for variations in recycled material usage (e.g., due to production changes or supply chain fluctuations) and avoids bias from isolated events, providing as such flexibility for supply chain management and material inventories. **/]**

[option 2: The recycled content shall be calculated based on unrestricted allocation rules that cap recycled content for outputs shipped to different markets based on the total recycled content of the outputs produced at the plant level. **/]**

For calculating the recycled content for each battery model per year and per manufacturing plant, battery manufacturers may have to take in consideration calculation results from different accounting periods that span the total time of 12 months required in accordance with point 2.5.

2.3. Data collection and processing

2.3.1. Data collection from upstream supply chain actors

Battery manufacturers shall collect the evidence and information determining the input data for the recycled content calculations of the battery by setting up a traceability system that spans the entire supply chain. To this end, battery manufacturers shall ensure that all supply chain actors involved:

- choose an accounting period as specified in point 2.2.3;
- collect and store dated certificates or proof of buying input fractions and selling output fractions (e.g. order slips, contracts) and certificates of proof that inputs originate from eligible waste materials as specified in Article 8 of Regulation (EU) 2023/1542;
- collect the data to perform the calculations as indicated in section 2.3.2. To avoid double-counting, digital records for a contiguous series of accounting periods that encompass a minimum total duration of one year prior to the date where outputs leave the plant shall be collected and stored for a period of at least 10 years;
- calculate correctly the recycled content of outputs using the methods specified in section 2.4;
- pass on the data indicated in point 2.3.2, including the recycled content as outcome of their calculations, to their direct downstream actor;
- provide the notified body access to the documentation that supports the data used for the calculation of the recycled content share, in an unrestrained manner and free of charge.

2.3.2 Data for the calculations

The following information and data are required for all transactions taking place at the manufacturing plant over the accounting period:

(I) A description of the materials, including:

a. Input / output fraction identifier
b. Trade name and type
c. Quantity of material received / shipped
d. Mass of cobalt, nickel, lead and lithium present
e. Recycled content of the cobalt, nickel, lead and lithium

(II) Transaction information:

f. Date(s) of shipment / receipt
g. Name and address of the supplier / customer, **[option 2:** including information on the region of origin and destination (EU/Third countries) **/]**.
h. **[option 1**: information on the existence of a toll-treatment mechanism, if applicable **/]**

2.3.3 Digital calculation tool

Calculations shall be done in a digital calculation tool, e.g. one or more spreadsheets or an accounting software. The digital calculation tool shall contain, in a digital database,

DRAFT

identifiers for all inputs and outputs to the manufacturing plants. These records shall at least include the data listed in point 2.3.2.

2.4. Calculations for output fractions produced during the accounting period

2.4.1 General

In the calculations, X is defined as the cobalt (Co), lithium (Li) or nickel (Ni) or lead (Pb), as defined in Article 8 of Regulation (EU) 2023/1542:

a) Recycled material X refers to cobalt, lithium or nickel that is destined for or present in active materials of the batteries in scope of Article 8, and that has been recovered from battery manufacturing waste or post-consumer waste, and the lead that is destined for or present in the battery and that has been recovered from waste, for each battery model per year and per manufacturing plant.

b) Primary material X refers to cobalt, lead, lithium or nickel that is destined for or present in active materials of the batteries in scope of Article 8, derived from primary raw materials, by-products or waste materials not listed under point a.

The recycled content of a material X (Li, Ni, Co or Pb) is expressed in mass percentage, [mass %]. This parameter shall be available and calculated for all input fractions, output fractions, and materials that are stored at the production plant. The mass of recycled material X used as an input to a production process at the production plant shall be recorded.

[Option 1:

2.4.2. Mass of recycled material of output fractions produced during an accounting period

The mass of recycled material at the output of production process(es) is calculated from the mass of recycled material at input as follows:

$$m(X)_{rec,output,no-toll} = m(X)_{rec,input,no-toll} * cf \quad (1a)$$

$$m(X)_{rec,output,toll} = m(X)_{rec,input,toll} * cf \quad (1b)$$

Where:

- $m(X)_{rec,output}$ is the mass of recycled material X, produced at the manufacturing plant during the rolling accounting period;
- $m(X)_{rec,input,no-toll}$ is the mass of recycled material X, not covered under the toll-treatment mechanism, serving as inputs for the production processes within the manufacturing plant during the rolling accounting period
- $m(X)_{rec,input,toll}$ is the mass of recycled material X, covered under the toll-treatment mechanism, serving as input for the production processes within the manufacturing plant during the rolling accounting period
- cf = conversion factor, for the target material X at the plant level over the accounting period. The conversion factor shall be established by subtracting the losses in the system due to leakage, processing efficiency, conversion efficiencies or any other factors which reduce the total pool of material available for accounting to plant outputs. It may also be calculated based on the product yields and metal contents of the inputs and outputs. The conversion factor is 1 in case

no process losses occur.

2.4.3. Recycled content of output fractions produced during the accounting period

The recycled content is then calculated for output fractions covered by the toll-treatment mechanism and remaining output fractions, as follows:

$$ReCo(X)_{o,no\text{-}toll} = \frac{\Sigma m(X)\ rec,output,no-toll}{\Sigma m(X) output,no-toll} * 100 \qquad (2a)$$

$$ReCo(X)_{o,toll} = \frac{\Sigma m(X)\ rec,output,toll}{\Sigma m(X) output,toll} * 100 \qquad (2b)$$

Where:

- $ReCo(X)_{o,no\text{-}toll}$ is the recycled content (expressed as %) of the target material X of an output fraction produced at the manufacturing plant during the rolling accounting period, not subject to the toll-treatment mechanism
- $\Sigma m(X)_{rec,output,no\text{-}toll}$ is the mass of recycled material X, produced at the manufacturing plant during the rolling accounting period, not subject to the toll-treatment mechanism
- $\Sigma m(X) output, no - toll$ is the total mass of, primary and recycled, material X of the output fraction produced at the manufactruring plant during the rolling accounting period, not subject to the toll-treatment mechanism
- $ReCo(X)_{o,toll}$ is the recycled content (expressed as %) of the target material X of an output fraction subject to the toll-treatment mechanism
- $\Sigma m(X)_{rec,output,toll}$ is the mass of recycled material X, produced at the manufacturing plant during an accounting period, subject to the toll-treatment mechanism
- $\Sigma m(X) output, toll$ is the total mass of, primary and recycled, material X of the output fraction subject to the toll-treatment mechanism

]

[option 2:

2.4.2. Mass of recycled material of output fractions produced during an accounting period

The mass of recycled material at the output of a manufacturing process is calculated from the mass of recycled material at input as follows:

$$m(X)_{rec,output} = m(X)_{rec,input} * cf \qquad (1)$$

Where:

- $m(X)_{rec,output}$ is the mass of recycled material X, produced at the manufacturing plant during an accounting period
- $m(X)_{rec,input}$ is the mass of recycled material X used as an input to the production process(es) at the manufacturing plant during an accounting period. It may

originate from new input arrivals at the manufacturing plant during the accounting periods, and/or from materials stored at the production plant.

- cf = conversion factor, for the target material X at the plant level over the accounting period. The conversion factor shall be estimated by subtracting the losses in the system due to leakage, processing efficiency, conversion efficiencies or any other factors which reduce the total pool of material available for accounting to plant outputs. It may also be calculated based on the product yields and metal contents of the process inputs and outputs. The conversion factor is 1 in case no process losses occur.

2.4.3. Recycled content credits for output fractions destined to the Union market generated during the accounting period

Credits for recycled content are calculated based on the market of destination of the outputs from a specific accounting period:

$$\mathrm{mc}(X_{EU}) = m(X)_{rec,\mathrm{output}} * \frac{\sum m(X_{EU})_{output}}{\sum m(X)_{output}} \quad (2)$$

- $\mathrm{mc}(X_{EU})$ are the credits for the Union market for recycled material X, generated during the accounting period
- $\mathrm{m(X)_{rec,output}}$ is the mass of recycled material X produced over the accounting period as derived via equation (1)
- $\sum m\,(X_{EU})_{output}$ is the total mass of primary and recycled material X in the output(s) of the production processes at production plant in accounting period, that is destined for the Union market.
- $\sum m\,(X)_{output}$ is the total mass of primary and recycled materials X, in all output(s) of the production processes at manufacturing plant in the accounting period.

Credits for recycled content shall be calculated and made available for attribution after all outputs from a specific accounting period have been fully shipped to downstream supply chain actors, even when shipped to the Union market from third countries. Alternatively, credits may be estimated at the finalisation of the accounting period (e.g. considering partial shipments already executed and based on contractual agreements or historic client records).

The accounting period shall not exceed 12 months. Output fractions not shipped prior the finalisation of the subsequent accounting period of their production shall not be considered for the accounting period of its production cycle as per equation (1) and (2).

2.4.4. Recycled content credits attributed to outputs fractions destined for the Union market in an accounting period.

Credits available for attribution during an accounting period are calculated by adding to the credits generated during the accounting period, calculation as per equation (2), the remaining balance of credits available for the Union market not attributed during preceding accounting periods.

The balance of credits available for the Union market for an accounting period is measured by subtracting credits attributed to outputs destined for the Union market in preceding accounting periods to recycled content credits generated during theses preceding accounting periods, calculated

as per equation (2)

The amount of credits attributed to output fractions destined for the Union market during the accounting period, may be equivalent to or lower than the amount of credits available for attribution during the accounting period. Credits not attributed during the accounting period will remain available to be attributed in subsequent accounting periods.

The amount of credits attributed to output fractions destined for the Union market during an accounting period shall not be superior to the amount of credit available for attribution during this accounting period. This means that no negative balance of credit shall be transferred to a subsequent accounting period.

The recycled content attributed to the output fraction shipped to subsequent supply chain actors shall be determined by the supply chain actors, subject to the constraints outlined herein. The attributed recycled content shall be incorporated into the calculations, in accordance with the formula set out in Equation (3).

2.4.5. Recycled content of output fractions produced during the accounting period

The recycled content of outputs shall be calculated by dividing the credits attributed to downstream operators located in the Union or in third countries by the mass of the material:

$$\mathrm{ReCo(X)_o} = \frac{mc(X)_{attributed,o}}{m(X)output,o} * 100 \qquad (3)$$

Where:

- $\mathrm{ReCo(X)_o}$ is the recycled content (expressed as %) of the material X of an output fraction o.
- $mc(X)_{attributed,o}$ is the recycled content attributed to the output fraction shipped to downstream supply chain actors (see section 2.4.4).
- $m(X)output, o$ is the total mass of, primary and recycled, material X of the output fraction shipped to downstream supply chain actors

Λ

2.5. Calculation of the documented recycled content provided by the battery manufacturer

Based on the calculations over the accounting period(s), the battery manufacturer shall calculate the recycled content for each battery model per year and per manufacturing plant, as indicated below.

The battery manufacturer shall determine the year of documentation, it may for example correspond to a calendar year or a bookkeeping year. The calculation of the documented recycled content will be part of the technical documentation referred to in Annex VIII of Regulation (EU) 2023/1542 making it possible to assess compliance with article 8 of the Regulation. The calculation shall be repeated for each subsequent 12 months documentation periods.

The documentation shall be based by considering the calculation results of the accounting periods in which batteries of a specific model produced over the year of documentation are produced and CE marked.

$$documented\ ReCo(X_{EU}) = \left(\frac{\sum_1^A ReCo(X)_o \times mass_{ref}}{total\ mass_{ref}}\right) \quad (4)$$

Where:

- documented $ReCo(X_{EU})$ (%) is the documented recycled content share for a specific material X contained in the battery model per year and per manufacturing plant, placed on the Union market;
- A are the accounting periods contained in the year for documentation;
- $ReCo(X)_o$ is the calculated percentage of recycled content in material X, determined using **[option1:** equations (2a) and (2b**)/][option 2:** equation (4)**/]**, for a specific battery produced at a battery manufacturing plant during a specific accounting period
- $mass_{ref}$ is the mass of material X contained in the battery model produced within a specific accounting period at the manufacturing plant;
- total $mass_{ref}$ is the total mass of material X in the battery models produced during the period of documentation at the manufacturing plant.

[Option 1: It is noted that the approach based on the weighted average of the rolling averages may inherently include data from the prior year for a certain reporting period (e.g., January 2024 uses October–December 2023 in case a 4-month accounting would be applied). A fixed calendar year average would effectively exclude prior-year data, but may create a discrepancy with the weighted average of the output fractions that received an assigned recycled content at their moment of production. This would risk inconsistent metrics or conflicting interpretations of the same data, and is thus not a robust methodology for this traceability option.**/]**

The documentation period may be reduced in the case where the production of a battery model is newly starting and has not been running for a full year.

3. Verification rules

3.1. Documentation for verification

3.1.1 Recycled content study

The study supporting the recycled content share referred to in point 2, second paragraph, point (i), of part B and point 2, point 1, third paragraph, point (i), of Part C of Annex VIII to Regulation (EU) 2023/1542 shall document in a systematic, orderly and comprehensive manner all steps taken for calculating the recycled content and the evidence and information determining the input data for those calculations. Battery manufacturers shall use the format in section 3.1.2 to document input data and calculated data and recycled content rates.

The study shall be updated and established for every documentation year in coherence with the calculation of the documented recycled content as described in section 2.5

3.1.2 Format for the documentation

[Option 1:

The format for documentation includes tables for collecting and presenting the different data necessary to calculate and verify the documented recycled content for each battery model per year and per manufacturing plant.

To this end, tables 2 to 4 shall be reproduced and established for each accounting period composing the 12 months documentation period. Table 5 presents the calculation of the documented recycled content and is based on data from all the accounting periods composing the 12 months documentation period.

Data included in the tables shall be expressed in tonnes when reference is made to the mass and expressed in weight percentages for calculated recycled content.

Table 1

Manufacturer		
Manufacturing plant	Street	
	Postal Code	
	City	
	Country	
	Contact Person	
	Tel	
	Email	

Table 2

Battery model						
Material	*[Note 1]*					
Rolling Accounting Period	from		to		duration	

Table 3

Data on output fractions produced during the rolling accounting period		
Conversion factor	*[Note 2]*	
For output fractions produced under a toll treatment mechanism		
	Mass in input fraction of	Mass in output fraction of

DRAFT

Output fraction identifier	Recycled material	Total material	Recycled material *[Note 3]*	Total material
Total toll-treatment				
For output fractions produced outside of a toll treatment				
	Mass in input fraction of		Mass in output fraction of	
Output fraction identifier	Recycled material	Total material	Recycled material *[Note 4]*	Total material
Total no toll-treatment				

Table 4

Recycled content of output fractions produced during the rolling accounting period						
For output fractions produced under a toll treatment mechanism						
Total mass of recycled material in output fractions produced under a toll treatment mechanism	*[Note 5]*	Total mass of material in output fractions produced under a toll treatment mechanism	*[Note 5]*	Calculated recycled content of the output fractions produced under a toll treatment mechanism	*[Note 6]*	
For output fractions produced outside a toll treatment mechanism						
Total mass of recycled material in output fractions produced outside a toll treatment mechanism	*[Note 5]*	Total mass of material in output fractions produced outside a toll treatment mechanism	*[Note 5]*	Calculated recycled content of the output fractions produced outside a toll treatment mechanism	*[Note 7]*	

Table 5

Document recycled content over a 12 months period						
Documentation	from		to			

period						
	Mass of reference	Recycled content *[Note 8]*				
Accounting period 1				Calculated recycled content	*[Note 9]*	
to						
Accounting period N						
Total mass of reference						

Note 1 : Li, Ni, Co or Pb

Note 2: establishment of the conversion factor shall be explained and documented

Note 3: shall be derived from equation (1b)

Note 4: shall be derived from equation (1a)

Note 5: data shall be consistent with data presented in table 3

Note 6: shall be derived from equation (2b)

Note 7: shall be derived from equation (2a)

Note 8: data shall be consistent with recycled content calculated for each accounting period presented in table 4

Note 9: shall be derived from equation (4)

/]

[Option2:

The format for documentation includes tables for collecting and presenting the different data necessary to calculate and verify the documented recycled content for each battery model per year and per manufacturing plant.

To this end, tables 2 to 6 shall be reproduced and established for each accounting periods composing the 12 months documentation period. Table 6 presents the calculation of the documented recycled content and is based on data from all the accounting periods composing the 12 months documentation period.

Data included in the tables shall be express in tonnes when reference is made to the mass and expressed in weight percentages for calculated recycled content.

Table 1

DRAFT

Manufacturer		
Manufacturing plant	Street	
	Postal Code	
	City	
	Country	
	Contact Person	
	Tel	
	Email	

Table 2

Battery model						
Material	*[Note 1]*					
Accounting Period	from		to		duration	

Table 3

Data on output fractions produced during the accounting period						
Conversion factor	*[Note 2]*					
		Mass in input fraction of		Mass in output fraction of		
Output fraction identifier	Destination (EU market /Third countries markets)	Recycled material	Total material	Recycled material *[Note 3]*	Total material	Mass of recycled content attributed
	Total					
	destined for the Union market					
	destined for Third countries					

DRAFT

	markets					

Table 4

Credits attributed to outputs fractions destined for the Union market during the accounting period						
Credits attributed	*[Note 4]*					
Credits generated during the accounting period	*[Note 5]*	Balance from preceding periods	*[Note 6]*	Credits available for the accounting period		

Table 5

Recycled content attributed during the accounting period						
Total mass of recycled material attributed to output fractions destined for the Union market	*[Note 7]*	Total mass of material in output fractions destined for the EU market	*[Note 7]*	Calculated recycled content of the output fractions produced during the accounting period	*[Note 8]*	

Table 6

Document recycled content over a 12 months period						
Documentation period	from		to			
	Mass of reference	Recycled content *[Note 9]*				
Accounting period 1				Calculated recycled content	*[Note 10]*	
to						
Accounting period N						
Total mass of reference						

Note 1 : Li, Ni, Co or Pb

Note 2: establishment of the conversion factor shall be explained and documented

Note 3: shall be derived from equation (1)

Note 4: data shall not be superior to the amount of credit available for attribution

DRAFT

Note 5: shall be derived from equation (2). Date for calculations should be consistent with data presented in table 3.

Note 6: data should be consistent with data presented for the preceding accounting period

Note 7: data shall be consistent with data presented in table 3

Note 8: shall be derived from equation (3)

Note 9: data shall be consistent with recycled content calculated for each accounting period presented in table 9

Note 10: shall be derived from equation (4)

/1

3.2. Responsibilities of notified bodies

The notified body shall:

- Verify that the battery manufacturer and its identified supply chain partners, based on the information and data required for all transactions described in section 2.3, have duly implemented digital calculation tools and correctly applied the calculation methodology outlined in Section 2.4, as required;

- Review and confirm that the battery manufacturer and its supply chain actors have a time-continuous and contiguous inventory system for recycled metal contents, properly linking recycled content in material supply, materials in storage, and production process output fractions. It shall also be checked that no double-counting of input fractions is applied;

- Check that data linked to specific identifiers corresponds between the databases of consecutive supply chain actors, to guarantee data consistency and integrity;

- Check the accuracy and reliability of data used for the calculation of the recycled content share;

- Review and confirm that the battery manufacturer and its supply chain actors have executed the calculation methodology specified in point 5, with a particular emphasis on the supporting information and calculations on the toll-treatment mechanism and allocation of recycled content credits to materials subject to toll-treatment mechanism and others, if applied.

- Verify that supply chain actors store the data accordingly.

To check the reliability of data used for the calculation of the recycled content, the notified body may request data and information (e.g. spreadsheets for accounting periods covering the production of intermediates for batteries, contracts in relation to materials transactions) for review from upstream supply chain actors, including suppliers of battery modules, cells, (precursor) active materials, refined metals, and raw material, in line with its operational obligations as specified in Article 33 of Regulation (EU) 2023/1542. This may include evidence that inputs originate from eligible waste materials from recyclers that perform the first processing stage of waste materials.

DRAFT

Notified bodies shall not share sensitive data, such as the identity of suppliers, with other supply chain actors with whom the supply chain actor concerned does not have a direct relation, unless consent is being given by that supply chain actor.

DRAFT

Electronically signed on 16/09/2025 13:14 (UTC+02) in accordance with Article 11 of Commission Decision (EU) 2021/2121