


Introduction to calculations

CALCULATIONS IN TABLEAU



Agata Bak-Geerinck
Senior Data Analyst, Telenet

Why do calculations?

Calculations allow you to create new data from data that already exists in your data source and perform computations on your data

Typical use-cases:

- **Measure missing in original dataset:**
 - e.g. `Sales` and `Costs` but no `Profit` measure
- **Transforming existing data:**
 - e.g. extracting `First name` from `First and Last name`
- **Categorizing the data:**
 - e.g. grouping `Age` into "Kids", "Teens", "Adults", based on age thresholds
- ...

Types of calculations in Tableau


There are four main types of calculations:

Basic calculations:

- Row-level calculations
- Aggregate calculations

Advanced calculations:

- Level of Detail expressions
- Table Calculations



Row-level calculations vs. aggregations

- Row-level calculations
 - Performed on each individual row
 - e.g. `End Date` - `Start Date`
- Aggregate calculations e.g. `SUM()` , `AVG()`
 - Performed on set of records defined by dimensions in the view
 - e.g. `Sum of Profit` = `SUM(Sales)` - `SUM(Cost)`
 - Recalculated per dimension in the view

| Start date | End date | Days between |
|------------|------------|--------------|
| 05/03/2022 | 16/01/2022 | 48 |
| 17/03/2022 | 31/01/2022 | 45 |
| 23/02/2022 | 30/11/2021 | 85 |
| 07/03/2022 | 03/01/2022 | 63 |
| 13/02/2022 | 10/02/2022 | 3 |
| 25/02/2022 | 31/01/2022 | 25 |

Sum of Profit
53.950

| Region | Sum of Profit |
|--------------------|---------------|
| Asia | 18.286 |
| Americas | 12.074 |
| Europe | 11.823 |
| Australia | 11.767 |
| Grand Total | 53.950 |

Most common calculation errors

- Tableau has a built-in calculation validity check! The calculation is valid.

- Do **NOT** mix up row-level and aggregate calculations:

`SUM([Sales])/[Customer]` Cannot mix aggregate and non-aggregate arguments with this function.

- Use only row-level or aggregation calculation
- Do **NOT** apply calculations on incompatible data types:

`SUM([Activity Date])` SUM is being called with (date), did you mean (float)?

- Watch out for **syntax errors**:
 - Missing syntax elements, e.g. `ELSEIF` or `END` in an `IF()` statement
 - Missing an identifier, operator, comma, or parenthesis
 - Using incorrect bracket type `{}` , `[]` , `()`

Most common logical errors


Tableau validity check does NOT eliminate all errors!

Typical logical / mathematical errors:

- Applying mathematical operations in the wrong order
- Incorrect or missing brackets in **AND** and **OR** statements
- Wrong application of conditions in **IF** and **CASE** statements
- Summing the non-summable values, e.g. Customer IDs
- Averaging the average
- ...

Final analytical responsibility lies with you!

The dataset - Fitbit usage




Let's practice!

CALCULATIONS IN TABLEAU

Start to calculate in Tableau

CALCULATIONS IN TABLEAU



Agata Bak-Geerinck
Senior Data Analyst, Telenet

Let's practice!

CALCULATIONS IN TABLEAU

String and Logical functions

CALCULATIONS IN TABLEAU



Agata Bak-Geerinck
Senior Data Analyst, Telenet

Overview of data types

Data type - an attribute of a piece of data that tells a computer how to interpret its value.

- String
- Date and Time
- Numeric
- Boolean (True / False)
- ...

Structured data sources: one column = one data type.

| Icon | Data type |
|------|---------------------------------------|
| Abc | Text (string) values |
| 📅 | Date values |
| 🕒 | Date & Time values |
| # | Numerical values |
| T/F | Boolean values (relational only) |
| 🌐 | Geographic values (used with maps) |

String data type

String - a sequence of one or more letters, numbers or other characters.

Examples of string data:

- "Apple"
- "M. L. King"
- "Year 1992"
- "Female, 29 years old"

In calculations, string values are enclosed in " " .

- e.g `IF [Word] = "Apple" THEN "Fruit" END`

String functions in Tableau

- + Concatenation - joining two or more strings end-to end:

| First name | Last name | Concatenation |
|------------|-----------|---------------|
| Adam | Appleton | Adam Appleton |
| | Banks | Adam Banks |
| | Barlow | Adam Barlow |

```
[First name] + " " + [Last name]
```

- `SPLIT()` - extracting parts of a string based on a delimiter:

| Name |
|-------------------------------|
| Abbing, Mr. Anthony |
| Abbott, Master. Eugene Joseph |

| Split |
|--------|
| Abbing |
| Abbott |

```
SPLIT ( [Name] , ", ", 1 )
```

String functions in Tableau

`LEFT()` , `RIGHT()` , `MID()` - extract requested, fixed number of characters, based on the position in the string:

| Fitbit version | LEFT() | RIGHT() | MID() |
|---|--------|---------|-------|
| A11 | A | 11 | 1 |
| B39 | B | 39 | 3 |
| C45 | C | 45 | 4 |
| D35 | D | 35 | 3 |
| <div><div><code>LEFT([Fitbit version],1)</code></div><div><code>RIGHT([Fitbit version],2)</code></div><div><code>MID([Fitbit version],2,1)</code></div></div> | | | |

Logical functions: Boolean (True/False)

Logical functions allow to determine if a certain condition is true or false and returns a requested value based on evaluation.

Boolean (True/False) conditions:

- Top Athlete? : `[Low activity ratio] < 0.1` returns "TRUE" or "FALSE"
- Possible to include several checks in the same condition, adding AND OR statements:
 - `([Gender]="Female" AND [Age] = 30) OR ([Gender]="Male" AND [Age] = 35)`
- Negation:
 - `[Category] = "Busy Mum" AND NOT [Occupation] = "Clerk"`
 - `[Category] = "Busy Mum" AND [Occupation] != "Clerk"`
 - `[Category] = "Busy Mum" AND [Occupation] <> "Clerk"`

Logical functions: IF, IIF, CASE

IF function:

- `IF test1 THEN ____ END`
- `IF test1 THEN ____ ELSE ____ END`
- `IF test1 THEN ____ ELSEIF ____ THEN
____ ELSE ____ END`

IIF function

- `IIF (test, ____, ____)`

CASE function

- `CASE ____ WHEN ____ THEN ____ WHEN ____
THEN ____ ELSE ____ END`

IF allows algebra conditions, e.g :

```
IF [Heart Rate] >=60 THEN "OK" ELSE "NOT OK" END
```

IIF() allows algebra conditions, e.g :

```
IIF ([Heart Rate] >=60, "OK" , "NOT OK")
```

CASE searches for an exact match, e.g :

```
CASE [Fitbit version]  
WHEN "A21" THEN "New" WHEN "B16" THEN "Old" END
```

Other logical functions

ISNULL, ISDATE - checks if a value is "Null" or a date:

- `ISNULL([Steps])` returns "TRUE" or "FALSE"
- `ISDATE([Activity Date])` returns "TRUE"

IFNULL - checks if a value is "Null" and controls the output:

- `IFNULL ([Steps], 0)`
- `IFNULL ([Steps], "No steps")`

ZN - returns a 0 if a value is "Null"


- `ZN([Steps])` returns 0

Let's practice!

CALCULATIONS IN TABLEAU

Practical use of string and logical functions

CALCULATIONS IN TABLEAU



Agata Bak-Geerinck
Senior Data Analyst, Telenet

Let's practice!

CALCULATIONS IN TABLEAU