


# Embeddings of neural field dynamics : simulations and fractal mappings

Lab meeting 2023-04-20

Nicole Vadot

# quick recap : neural field equations


$$\underbrace{\partial_t h(t, \vec{z})}_{\text{neural field (units of voltage)}} = -h(t, \vec{z}) + \int_{\underbrace{\mathbb{R}^p}_{\text{embedding space}}} \underbrace{w(\vec{z}, \vec{y})}_{\text{connectivity kernel}} \underbrace{\phi(h(t, \vec{y}))}_{\text{activation function (gives firing rate, units of Hz)}} \underbrace{\rho(d\vec{y})}_{\text{density of neurons in embedding space}}$$



low-rank RNNs (rate neural networks) converge  
to a neural field equation in  $\mathbb{R}^p$  as  $N \rightarrow \infty$  [1]

- [1] Valentin Schmutz, Johanni Brea, Wulfram Gerstner  
Convergence of redundancy-free spiking neural networks to rate networks


low-rank RNNs (rate neural networks) converge to a neural field equation in  $\mathbb{R}^p$  as  $N \rightarrow \infty$  [1]



$$\dot{h}_i(t) = -h_i(t) + \sum_{j=1}^N J_{ij} \phi(h_j(t))$$

$N$  neurons :  
dynamics in  $\mathbb{R}^N$

low-rank RNNs (rate neural networks) converge to a neural field equation in  $\mathbb{R}^p$  as  $N \rightarrow \infty$  [1]



$$\dot{h}_i(t) = -h_i(t) + \sum_{j=1}^N J_{ij} \phi(h_j(t))$$


N neurons :  
dynamics in  $\mathbb{R}^N$

- ↓
- > if  $J$  is low-rank, neurons span a subspace of  $\mathbb{R}^N$
  - >  $(\xi_{i1}, \dots, \xi_{ip})$  gives the embedding of neuron  $i$


$J$  has rank  $p$  (at most)

$$J_{ij} = \frac{1}{N} \sum_{\mu=1}^p \xi_{\mu,i} \tilde{\phi}(\xi_{\mu,j}), \quad \xi_{\mu,i} \sim \mathcal{N}(0,1), \quad \tilde{\phi}(\xi) = \frac{\phi(\xi) - \mathbb{E}[\phi(\xi)]}{\text{Var}[\phi(\xi)]}$$

low-rank vectors



# low-rank RNNs (rate neural networks) converge to a neural field equation in $\mathbb{R}^p$ as $N \rightarrow \infty$ [1]



$$\dot{h}_i(t) = -h_i(t) + \sum_{j=1}^N J_{ij} \phi(h_j(t))$$


N neurons :  
dynamics in  $\mathbb{R}^N$

- ↓
- > if  $J$  is low-rank, neurons span a subspace of  $\mathbb{R}^N$
  - >  $(\xi_{i1}, \dots, \xi_{ip})$  gives the embedding of neuron  $i$


$J$  has rank  $p$  (at most)

$$J_{ij} = \frac{1}{N} \sum_{\mu=1}^p \xi_{\mu,i} \tilde{\phi}(\xi_{\mu,j}), \quad \xi_{\mu,i} \sim \mathcal{N}(0,1), \quad \tilde{\phi}(\xi) = \frac{\phi(\xi) - \mathbb{E}[\phi(\xi)]}{\text{Var}[\phi(\xi)]}$$

low-rank vectors




- as  $N \rightarrow \infty$
- > neurons sample a gaussian
  - > potential looks smooth




demo : embedding in  $p=1$  dimensions

# demo : embedding in $p=1$ dimensions




→ the dynamics is  
\*structured\* in  
the embedding




^^ simulation  $N=50\_000$ ,  $p=1$ ,  $\phi=\text{sigmoid}$ .  
at fixed point  $\mu=0 \rightarrow$  overlap  $m_0=1$  (only 5000 neurons are shown)



# demo : embedding in $p=1$ dimensions



→ the dynamics is  
\*structured\* in  
the embedding




→ at the fixed point,  
 $h(t; \xi_o) = \xi_o$   
→ the activity follows  
 $\phi(h(t; \xi_o)) = \phi(\xi_o)$   
in the embedding

see animations

^^ simulation  $N=50\_000$ ,  $p=1$ ,  $\phi=\text{sigmoid}$ .  
at fixed point  $\mu=0 \rightarrow$  overlap  $m_o=1$  (only 5000 neurons are shown)


demo : embedding in  $p=2$  dimensions

# demo : embedding in $p=2$ dimensions



^^ simulation  $N=100\_000$ ,  $p=2$ ,  $\phi=\text{sigmoid}$  (only 5000 neurons shown)  
overlap  $m_0=1$ ,  $m_1=0$

# demo : embedding in $p=2$ dimensions



^^ simulation  $N=100\_000$ ,  $p=2$ ,  $\phi=\text{sigmoid}$  (only 5000 neurons shown)  
overlap  $m_0=1, m_1=0$

→ all the variation is along  $\xi_0$ , constant along  $\xi_1$   
→  $h(t; \xi_0, \xi_1) = \xi_0$

demo : embedding in  $p=2$  dimensions  
- cycling RNN version

# demo : embedding in p=2 dimensions

## - cycling RNN version

$$\dot{h}_i(t) = -h_i(t) + \sum_{j=1}^N \frac{1}{N} \sum_{\mu=1}^p \xi_{\mu+1,i} \tilde{\phi}(\xi_{\mu,j}) \phi(h_j(t - \delta))$$


$\delta$  : delay  
 $\mu+1$  : "rolling"  
(p+1=1 by convention)

# demo : embedding in p=2 dimensions

## - cycling RNN version

$$\dot{h}_i(t) = -h_i(t) + \sum_{j=1}^N \frac{1}{N} \sum_{\mu=1}^p \xi_{\mu+1,i} \tilde{\phi}(\xi_{\mu,j}) \phi(h_j(t - \delta))$$

$\delta$  : delay  
 $\mu+1$  : "rolling"  
 (p+1=1 by convention)



initial :  $h(t < 0; \xi_0, \xi_1) = \xi_0$   
 → overlaps are exponentials  
 that get smoothed  
 every cycle  
 → oscillations flatten out  
 over time


see animation

^^ N=20\_000, p=2, delta=10, shift=1, phi=sigmoid


can we go to an even lower dimension ?



# can we go to an even lower dimension ?



# can we go to an even lower dimension ?





mapping a  $[0,1]^2$  square into a  $[0,1]$  segment [2]

[2] Kharazishvili, A. (2017).  
Strange Functions in Real Analysis (3rd ed.)

# mapping a $[0,1]^2$ square into a $[0,1]$ segment [2]

- Peano : surjective and continuous
  - > easy example : linear projections (see animation)
  - > clearly not bijective



linear mappings of a RNN in state  $h = \xi_0 + \xi_1$   
 $N=20\_000$ ,  $p=2$ ,  $\phi = \text{sigmoid}$

>>


[2] Kharazishvili, A. (2017).  
Strange Functions in Real Analysis (3rd ed.)

# mapping a $[0,1]^2$ square into a $[0,1]$ segment [2]

- Peano : surjective and continuous
  - > easy example : linear projections (see animation)
  - > clearly not bijective
- Cantor : bijective (= 1-to-1 mapping)
  - > example : see next slides

linear mappings of a RNN in state  $h = \xi_0 + \xi_1$   
 $N=20\_000$ ,  $p=2$ ,  $\phi = \text{sigmoid}$

[2] Kharazishvili, A. (2017).  
Strange Functions in Real Analysis (3rd ed.)




# mapping a $[0,1]^2$ square into a $[0,1]$ segment [2]

- Peano : surjective and continuous
  - > easy example : linear projections (see animation)
  - > clearly not bijective
- Cantor : bijective (= 1-to-1 mapping)
  - > example : see next slides

Fact : there is no homeomorphism (continuous bijective function) between  $[0,1]^2$  and  $[0,1]$

linear mappings of a RNN in state  $h = \xi_0 + \xi_1$ ,  
 $N=20\_000$ ,  $p=2$ ,  $\phi = \text{sigmoid}$

[2] Kharazishvili, A. (2017).  
Strange Functions in Real Analysis (3rd ed.)




a bijective fractal mapping  $[0,1]^2 \rightarrow [0,1]$  [3]

[3] Cong Dan Pham. (2016)

The existence of a measure-preserving bijection from a unit square to unit segment

# a bijective fractal mapping $[0,1]^2 \rightarrow [0,1] [3]$




1. split into 4 quadrants
2. assign mapping coordinate
3. recurse for every quadrant

[3] Cong Dan Pham. (2016)

The existence of a measure-preserving bijection from a unit square to unit segment



# a bijective fractal mapping $[0,1]^2 \rightarrow [0,1] [3]$






1. split into 4 quadrants
2. assign mapping coordinate
3. recurse for every quadrant

[3] Cong Dan Pham. (2016)

The existence of a measure-preserving bijection from a unit square to unit segment

# a bijective fractal mapping $[0,1]^2 \rightarrow [0,1] [3]$



1. split into 4 quadrants
2. assign mapping coordinate
3. recurse for every quadrant

→ discontinuous, but bijective

see animation

- mean activity in each bin


- there is some "locality"

[3] Cong Dan Pham. (2016)

The existence of a measure-preserving bijection from a unit square to unit segment


can we write a neural field  
in an even lower dimension ?

can we write a neural field  
in an even lower dimension ?



- 
1. simulate neural field in  $R^p$
  2. map  $R^p$  to  $[0,1]$  using  $\varphi$

can we write a neural field  
in an even lower dimension ?



- 
1. simulate neural field in  $R^p$
  2. map  $R^p$  to  $[0,1]$  using  $\varphi$


→ can we do it  
the other way around ?

- 
1. simulate dynamics in  $[0,1]$
  2. assert that the dynamics in  $[0,1]$  are the same as in  $R^p$  (e.g. map  $[0,1]$  to  $R^p$  using  $\varphi^{-1}$ , and plot to compare)

numerical aspects of simulating fractal mappings


# numerical aspects of simulating fractal mappings

smoothness in  $\mathbb{R}^p \Rightarrow$  all neurons inside each bin are similar  
 $\Rightarrow$  take the average potential



# numerical aspects of simulating fractal mappings

smoothness in  $\mathbb{R}^p \Rightarrow$  all neurons inside each bin are similar  
 $\Rightarrow$  take the average potential



$$H_2 = \frac{1}{\text{\#neurons in bin } \alpha=2} \sum_{i \in 2} h_i$$

$$H_\alpha(t) = \frac{1}{|\alpha|} \sum_{i \in \alpha} h_i(t)$$

$\Downarrow$  discretized dynamics, with rescaled J


$$\dot{H}_\alpha(t) = -H_\alpha(t) + \sum_{\beta \in \text{segments of length } 4^{-n}} \tilde{J}_{\alpha,\beta} \phi(H_\beta(t))$$

$$\tilde{J}_{\alpha,\beta} = \frac{1}{|\alpha|} \sum_{i \in \alpha} \sum_{j \in \beta} J_{ij}$$



# numerical aspects of simulating fractal mappings

smoothness in  $\mathbb{R}^p \Rightarrow$  all neurons inside each bin are similar  
 $\Rightarrow$  take the average potential



$$H_2 = \frac{1}{\text{\#neurons in bin } \alpha=2} \sum_{i \in 2} h_i$$

$$H_\alpha(t) = \frac{1}{|\alpha|} \sum_{i \in \alpha} h_i(t)$$

$\Downarrow$  discretized dynamics, with rescaled  $J$

$$\dot{H}_\alpha(t) = -H_\alpha(t) + \sum_{\beta \in \text{segments of length } 4^{-n}} \tilde{J}_{\alpha,\beta} \phi(H_\beta(t))$$

$$\tilde{J}_{\alpha,\beta} = \frac{1}{|\alpha|} \sum_{i \in \alpha} \sum_{j \in \beta} J_{ij}$$


$\rightarrow J_{\alpha\beta}$  converges to a (possibly discontinuous !) connectivity kernel  $w(\alpha,\beta)$  as  $n_{\text{rec}} \rightarrow \infty$

Note : since  $J_{ij}$  is low-rank, (we can prove that)  $J_{\alpha\beta}$  is too !  
 $\rightarrow$  good news, because low-rank RNNs  
 are computationally cheap to simulate

directly computing the connectivity  $J_{\alpha\beta}$  in  $[0,1]$

# directly computing the connectivity $J_{\alpha\beta}$ in $[0,1]$


- steps :
1. discretize the PDF on a grid
  2. apply mapping
  3. generate  $J_{\alpha\beta}$



Note : gaussian wings decay fast  
⇒ approximate PDF by compact support  
⇒ the  $[-4,4]^2$  bounding box approximation is OK


# directly computing the connectivity $J_{\alpha\beta}$ in $[0,1]$

- steps :
1. discretize the PDF on a grid
  2. apply mapping
  3. generate  $J_{\alpha\beta}$



$$\tilde{F}_{\mu,\alpha} = Z_{\mu,\alpha}, \quad \tilde{G}_{\mu,\alpha} = \tilde{\phi}(Z_{\mu,\alpha}), \quad \tilde{J}_{\alpha,\beta} = \tilde{\rho}(Z_{:, \beta}) \sum_{\mu=1}^p \tilde{F}_{\mu,\alpha} \tilde{G}_{\mu,\beta}$$

gaussian PDF



Note : gaussian wings decay fast  
⇒ approximate PDF by compact support  
⇒ the  $[-4,4]^2$  bounding box approximation is OK

^^ connectivity inside the mapping,  $n_{rec}=2$

are dynamics in  $[0,1]$  are the same as in  $\mathbb{R}^p$  ?

are dynamics in  $[0,1]$  are the same as in  $\mathbb{R}^p$  ?


- > for a fair comparison, we \*downsample\* the mapping to  $N=1024$  segments
- > the neural field is the "ground truth"

Note : the neural field drifts due to finite  $N$  effects

are dynamics in  $[0,1]$  are the same as in  $\mathbb{R}^p$  ?

Neural field  
with  $N=1024$  neurons

Fractal mapping  
with  $N=1024$  segments



- > for a fair comparison, we \*downsample\* the mapping to  $N=1024$  segments
- > the neural field is the "ground truth"

→ fractal mapping has oscillations

Note : the neural field drifts due to finite  $N$  effects



# the reshape mapping

the reshape mapping



# the reshape mapping

nrec=1







steps

1. split into  $4^{nrec}$  quadrants
2. enumerate every square column by column

# the reshape mapping

nrec=1

nrec=2





steps



1. split into  $4^{nrec}$  quadrants
2. enumerate every square column by column

# the reshape mapping



nrec=1



nrec=2



nrec=3





steps



1. split into  $4^{nrec}$  quadrants
2. enumerate every square column by column

# the reshape mapping



nrec=1



nrec=2



nrec=3



steps

1. split into  $4^{nrec}$  quadrants
2. enumerate every square column by column

→ in the limit, tends to a projection along the  $\xi_0$  axis


→ "locality" only along  $\xi_0$

→ limit is not bijective


are dynamics in  $[0,1]$  are the same as in  $\mathbb{R}^p$  ?

are dynamics in  $[0,1]$  are the same as in  $\mathbb{R}^p$  ?


Neural field  
with  $N=1024$  neurons






Fractal mapping  
with  $N=1024$  segments



Reshape mapping  
with  $N=1024$  segments



- > for a fair comparison, we \*downsample\* the mappings to  $N=1024$  segments
- > the neural field is the "ground truth"




- fractal mapping has oscillations
- reshape mapping does not

Note : the neural field drifts due to finite  $N$  effects

why doesn't the reshape mapping work ?

# why doesn't the reshape mapping work ?



In  $[0, 1]$  embedding




→ the reshape mapping  
converges to a projection  
along  $\xi_0$ .

> in the state  $\xi_0$ ,  
the projection can  
"encode the variation"



# why doesn't the reshape mapping work ?




In  $[0, 1]$  embedding



→ the reshape mapping  
converges to a projection  
along  $\xi_0$ .

> in the state  $\xi_0$ ,  
the projection can  
"encode the variation"



In  $[0, 1]$  embedding



> but in the state  $\xi_1$ ,  
all the variation  
gets "averaged out"

# summary of mappings so far

Mapping	Bijective in limit	"Locality"	Equivalent dynamics
Recursive Local Reshape	Yes No ( $\rightarrow$ projection)	Yes Only along one axis	Yes No

# summary of mappings so far

Mapping	Bijective in limit	"Locality"	Equivalent dynamics
Recursive Local Reshape	Yes No ( $\rightarrow$ projection)	Yes Only along one axis	Yes No

what's next ?

$\rightarrow$  what conditions on the mapping  
must be met for equivalent dynamics in  $[0,1]$  ?

# summary of mappings so far

Mapping	Bijective in limit	"Locality"	Equivalent dynamics
Recursive Local Reshape	Yes No ( $\rightarrow$ projection)	Yes Only along one axis	Yes No

what's next ?

$\rightarrow$  what conditions on the mapping

must be met for equivalent dynamics in  $[0,1]$  ?

$\rightarrow$  explore tradeoff between dimensionality and "regularity"  
in  $\mathbb{R}^2$  the kernel is continuous -- but high dimension  
in  $[0,1]$  we lose continuity -- but low dimension  
 $\Rightarrow$  here we have presented the first example of such  
equivalent neural fields



extra slides →

rank- $p$  RNNs converge to  
a neural field equation in  $\mathbb{R}^p$  as  $N \rightarrow \infty$

rank-p RNNs converge to  
a neural field equation in  $\mathbb{R}^p$  as  $N \rightarrow \infty$

$$\dot{h}_i(t) = -h_i(t) + \sum_{j=1}^N J_{ij} \phi(h_j(t))$$

$$J_{ij} = \frac{1}{N} \sum_{\mu=1}^p \xi_{\mu,i} \tilde{\phi}(\xi_{\mu,j})$$

**N-dimensional system**

$$\xi_{\mu,i} \sim \mathcal{N}(0, 1), \quad \tilde{\phi}(\xi) = \frac{\phi(\xi) - \mathbb{E}[\phi(\xi)]}{\text{Var}[\phi(\xi)]}$$

-  $h=0$  and  $h=\xi$  are fixed points



rank-p RNNs converge to  
a neural field equation in  $\mathbb{R}^p$  as  $N \rightarrow \infty$

$$\dot{h}_i(t) = -h_i(t) + \sum_{j=1}^N J_{ij} \phi(h_j(t))$$

$$J_{ij} = \frac{1}{N} \sum_{\mu=1}^p \xi_{\mu,i} \tilde{\phi}(\xi_{\mu,j})$$

N-dimensional system

-  $h=0$  and  $h=\xi$  are fixed points

$$\xi_{\mu,i} \sim \mathcal{N}(0, 1), \quad \tilde{\phi}(\xi) = \frac{\phi(\xi) - \mathbb{E}[\phi(\xi)]}{\text{Var}[\phi(\xi)]}$$

sum  $\rightarrow$  int limit,  $h$  spans a p-dim subspace of  $\mathbb{R}^N$

$$\partial_t h(t, \vec{z}) = -h(t, \vec{z}) + \int_{\mathbb{R}^p} \underbrace{w(\vec{z}, \vec{y})}_{J_{ij}} \underbrace{\phi(h(t, \vec{y}))}_{h_i(t)} \underbrace{\rho(d\vec{y})}_{\xi_i \sim p}$$

$$w(\vec{z}, \vec{y}) = \sum_{\mu=1}^p \tilde{\phi}(y_{\mu}) z_{\mu}$$

p-dimensional  
system

# numerical aspects of simulating fractal mappings

low-rank case

# numerical aspects of simulating fractal mappings

## low-rank case

"mean patterns" lead to low-rank dynamics in the mapping  
→ inexpensive to simulate

$$\tilde{F}_{\mu,\alpha} = \frac{1}{|\alpha|} \sum_{i \in \alpha} \underbrace{F_{\mu,i}}_{\zeta_{\mu i}} \quad \tilde{G}_{\mu,\alpha} = \frac{1}{|\alpha|} \sum_{i \in \alpha} \underbrace{G_{\mu,i}}_{\Phi(\zeta_{\mu i})}$$

# numerical aspects of simulating fractal mappings

## low-rank case

"mean patterns" lead to low-rank dynamics in the mapping  
 → inexpensive to simulate

$$\tilde{F}_{\mu,\alpha} = \frac{1}{|\alpha|} \sum_{i \in \alpha} \underbrace{F_{\mu,i}}_{\xi_{\mu i}} \quad \tilde{G}_{\mu,\alpha} = \frac{1}{|\alpha|} \sum_{i \in \alpha} \underbrace{G_{\mu,i}}_{\Phi(\xi_{\mu i})}$$

$$\tilde{J}_{\alpha,\beta} = \underbrace{\frac{|\beta|}{\sum_{\beta'} |\beta'|}}_{\text{weighted binning}} \left( \underbrace{\sum_{\mu=1}^p \tilde{F}_{\mu,\alpha} \tilde{G}_{\mu,\beta}}_{\text{low-rank term}} - \underbrace{\delta_{\alpha,\beta} \sum_{\mu=1}^p \sum_{i \in \alpha} \frac{F_{\mu,i}}{|\alpha|} \frac{G_{\mu,i}}{|\alpha|}}_{\substack{\text{exclude} \\ \text{self-connections} \\ \text{(vanishes at large N)}}} \right)$$

$\underbrace{\sum_{\mu=1}^p \tilde{F}_{\mu,\alpha} \tilde{G}_{\mu,\beta}}_{\text{low-rank term}}$




# numerical aspects of simulating fractal mappings

## low-rank case

"mean patterns" lead to low-rank dynamics in the mapping  
 → inexpensive to simulate

$$\tilde{F}_{\mu,\alpha} = \frac{1}{|\alpha|} \sum_{i \in \alpha} \underbrace{F_{\mu,i}}_{\xi_{\mu i}} \quad \tilde{G}_{\mu,\alpha} = \frac{1}{|\alpha|} \sum_{i \in \alpha} \underbrace{G_{\mu,i}}_{\Phi(\xi_{\mu i})}$$

$$\tilde{J}_{\alpha,\beta} = \underbrace{\frac{|\beta|}{\sum_{\beta'} |\beta'|}}_{\text{weighted binning}} \left( \underbrace{\sum_{\mu=1}^p \tilde{F}_{\mu,\alpha} \tilde{G}_{\mu,\beta}}_{\text{low-rank term}} - \underbrace{\delta_{\alpha,\beta} \sum_{\mu=1}^p \sum_{i \in \alpha} \frac{F_{\mu,i}}{|\alpha|} \frac{G_{\mu,i}}{|\alpha|}}_{\substack{\text{exclude} \\ \text{self-connections} \\ \text{(vanishes at large N)}}} \right)$$



< numerical demo  
 of binning the  
 connectivity  
 N=1024, nrec=4




# numerical aspects of simulating fractal mappings

## low-rank case

"mean patterns" lead to low-rank dynamics in the mapping  
 → inexpensive to simulate

$$\tilde{F}_{\mu,\alpha} = \frac{1}{|\alpha|} \sum_{i \in \alpha} \underbrace{F_{\mu,i}}_{\xi_{\mu i}} \quad \tilde{G}_{\mu,\alpha} = \frac{1}{|\alpha|} \sum_{i \in \alpha} \underbrace{G_{\mu,i}}_{\Phi(\xi_{\mu i})}$$

$$\tilde{J}_{\alpha,\beta} = \underbrace{\frac{|\beta|}{\sum_{\beta'} |\beta'|}}_{\text{weighted binning}} \left( \underbrace{\sum_{\mu=1}^p \tilde{F}_{\mu,\alpha} \tilde{G}_{\mu,\beta}}_{\text{low-rank term}} - \underbrace{\delta_{\alpha,\beta} \sum_{\mu=1}^p \sum_{i \in \alpha} \frac{F_{\mu,i}}{|\alpha|} \frac{G_{\mu,i}}{|\alpha|}}_{\substack{\text{exclude} \\ \text{self-connections} \\ \text{(vanishes at large N)}}} \right)$$






rare neurons  
might not  
show up !

< numerical demo  
of binning the  
connectivity  
N=1024, nrec=4

dynamics inside the fractal mapping converge

# dynamics inside the fractal mapping converge



→ we get the same oscillatory behavior !

Note : this is expected, as we are just doing a mean field, and the mappings are just reorderings of the bins. Connectivity is invariant to permutation of neurons



(if time remains)  
discrete probability spaces  
reduce to population dynamics  
which can easily be embedded in  $[0,1]$