Classification of Algorithms

Distinctive Characteristics



1

Important Definitions



- Correctness: The correctness for an algorithm in a distributed system is defined on two different metrics.
 - Liveness: The right must eventually occur
 - Safety: The wrong must not occur
- An algorithm is correct if and only it ensures both liveness and safety.

16 May 2024

Fairness



- Fairness property generally means that the processes are executed in the order of their arrival in the system
- Each process gets a fair chance to execute the CS.
- Does fairness cause priority inversion?



2

Common Performance Metrics



- Message complexity: The number of control messages required to be exchanged per execution of an algorithm
- Synchronization delay: The time required between two successive executions
 - e.g., it is the time required between a process leaves its CS and the next one enters its CS.



,

Common Performance Metrics



- Response time: The time interval that a request waits before the result is computed
- Throughput: The rate at which the algorithms are executed.
 - Throughput = 1/(SD+E)
 where SD is the synchronization delay and E is the average execution time.




_

Four Major Classes



- Symmetric algorithms
- Diffusion Computation based algorithms
- Token based algorithms
- Edge Chasing algorithms





Symmetric Algorithms


M

A


B


C


16 May 2024





S











Symmetric Algorithms



- Decisions are taken collectively and based on mutual consent
- Simple to understand, design and implement
- Large number of messages are exchanged between the participating processes



16 May 2024

15

Four Major Classes







- Symmetric algorithms
- Diffusion Computation based algorithms
- Token based algorithms
- Edge Chasing algorithms



a

16 May 2024





Diffusion Computation Algorithms



- Engaging queries
 - Engaging replies
- Non-engaging queries
 - Non-engaging replies

16 May 2024

19


Diffusion Computation Algorithms





- Partial results are queued in a node, till all the sub-tasks are done
- Lower message complexity as compared to symmetric algorithms
- Fault tolerant


16 May 2024
































Diffusion Computation Algorithms





- Process that diffuse a query never knows whether the communication will be an engaging or non-engaging query for the recipient
- Recipient decides whether the diffusion is to continue
- A hierarchy evolves dynamically for a particular execution





16 May 2024


33



































Four Major Classes



- Symmetric algorithms
- Diffusion Computation based algorithms
- Token based algorithms
- Edge Chasing algorithms



9

16 May 2024

47

Token-based Algorithms



- There will be a token for each instance of resource
- Algorithm is to be designed to get hold of the token in order to access the resource
- Predominantly used for scheduling, mutual exclusion



9

16 May 2024

Token-based Algorithms - Correctness



- A token-based algorithm is inherently safe as long as a single token exists for each instance of a resource under contention
- Thus, a token-based algorithm is correct if its liveness is ensured.



3

16 May 2024

49

Four Major Classes





- Symmetric algorithms
- Diffusion Computation based algorithms
- Token based algorithms
- Edge Chasing algorithms







16 May 2024

Edge Chasing Algorithms



- Edge-chasing is a technique, often used for deadlock detection in distributed systems.
- When a process, say P, is blocked for some resource held by another process, say Q, a probe message is sent to all processes in the wait for graph with P as the start node



16 May 2024

51

Edge Chasing Algorithms



- Non-blocked processes will discard the probe.
- If the probe returns to process P, a circular wait is detected along with the processes in the cycle.
- Intuitive and limited scope of applications



