


[Courses](#)[Write an Article](#)

Orientation of 3 ordered points

Orientation of an ordered triplet of points in the plane can be

- counterclockwise
- clockwise
- collinear

The following diagram shows different possible orientations of (a,b,c)



If orientation of (p_1, p_2, p_3) is collinear, then orientation of (p_3, p_2, p_1) is also collinear.

If orientation of (p_1, p_2, p_3) is clockwise, then orientation of (p_3, p_2, p_1) is counterclockwise and vice versa is also true.

Given three points p_1 , p_2 and p_3 , find orientation of (p_1, p_2, p_3) .

Example:

Input: $p_1 = \{0, 0\}$, $p_2 = \{4, 4\}$, $p_3 = \{1, 2\}$


Output: CounterClockWise

Input: $p_1 = \{0, 0\}$, $p_2 = \{4, 4\}$, $p_3 = \{1, 1\}$

Output: Collinear

How to compute Orientation?

The idea is to use slope.



Slope of line segment (p1, p2): $\sigma = (y2 - y1)/(x2 - x1)$

Slope of line segment (p2, p3): $\tau = (y3 - y2)/(x3 - x2)$

If $\sigma < \tau$, the orientation is counterclockwise (left turn)

If $\sigma = \tau$, the orientation is collinear

If $\sigma > \tau$, the orientation is clockwise (right turn)

Using above values of σ and τ , we can conclude that, the orientation depends on sign of below expression:

$$(y2 - y1)*(x3 - x2) - (y3 - y2)*(x2 - x1)$$

Above expression is negative when $\sigma < \tau$, i.e., counterclockwise

Above expression is 0 when $\sigma = \tau$, i.e., collinear

Above expression is positive when $\sigma > \tau$, i.e., clockwise

Below is the implementation of above idea.

C++

```
// A C++ program to find orientation of three points
#include <iostream>
using namespace std;

struct Point
{
    int x, y;
};

// To find orientation of ordered triplet (p1, p2, p3).
// The function returns following values
// 0 --> p, q and r are collinear
// 1 --> Clockwise
// 2 --> Counterclockwise
int orientation(Point p1, Point p2, Point p3)
{
    // See 10th slides from following link for derivation
    // of the formula
```

```

int val = (p2.y - p1.y) * (p3.x - p2.x) -
          (p2.x - p1.x) * (p3.y - p2.y);

if (val == 0) return 0; // colinear

return (val > 0)? 1: 2; // clock or counterclock wise
}

// Driver program to test above functions
int main()
{
    Point p1 = {0, 0}, p2 = {4, 4}, p3 = {1, 2};
    int o = orientation(p1, p2, p3);
    if (o==0)      cout << "Linear";
    else if (o == 1) cout << "Clockwise";
    else          cout << "CounterClockwise";
    return 0;
}

```

Java

```

// JAVA Code to find Orientation of 3
// ordered points
class Point
{
    int x, y;
    Point(int x,int y){
        this.x=x;
        this.y=y;
    }
}

class GFG {

    // To find orientation of ordered triplet
    // (p1, p2, p3). The function returns
    // following values
    // 0 --> p, q and r are colinear
    // 1 --> Clockwise
    // 2 --> Counterclockwise
    public static int orientation(Point p1, Point p2,
                                  Point p3)
    {
        // See 10th slides from following link
        // for derivation of the formula
        int val = (p2.y - p1.y) * (p3.x - p2.x) -
                  (p2.x - p1.x) * (p3.y - p2.y);

        if (val == 0) return 0; // colinear

        // clock or counterclock wise
        return (val > 0)? 1: 2;
    }

    /* Driver program to test above function */
    public static void main(String[] args)
    {

```

```
Point p1 = new Point(0, 0);
Point p2 = new Point(4, 4);
Point p3 = new Point(1, 2);

int o = orientation(p1, p2, p3);

if (o==0)
System.out.print("Linear");
else if (o == 1)
System.out.print("Clockwise");
else
System.out.print("CounterClockwise");

}
}
```

//This code is contributed by Arnav Kr. Mandal.

Output:

CounterClockwise

The concept of orientation is used in below articles:

[Find Simple Closed Path for a given set of points](#)

[How to check if two given line segments intersect?](#)

[Convex Hull | Set 1 \(Jarvis's Algorithm or Wrapping\)](#)

[Convex Hull | Set 2 \(Graham Scan\)](#)

Source:

<http://www.dcs.gla.ac.uk/~pat/52233/slides/Geometry1x1.pdf>

This article is contributed by **Rajeev Agrawal**. Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above

Recommended Posts:

[Closest Pair of Points using Divide and Conquer algorithm](#)

[Closest Pair of Points | O\(nlogn\) Implementation](#)

[Find Simple Closed Path for a given set of points](#)

[Count Integral points inside a Triangle](#)

[Number of Integral Points between Two Points](#)

[Area of a polygon with given n ordered vertices](#)

[Non-crossing lines to connect points in a circle](#)

[Count maximum points on same line](#)

[Circle and Lattice Points](#)

Queries on count of points lie inside a circle

Minimum lines to cover all points

How to check if given four points form a square

Dynamic Convex hull | Adding Points to an Existing Convex Hull

Angular Sweep (Maximum points that can be enclosed in a circle of given radius)

Deleting points from Convex Hull

Article Tags : Geometric

Practice Tags : Geometric



1

☐ To-do ☐ Done

2.1

Based on 41 vote(s)

Feedback

Notes

Improve Article

Please write to us at contribute@geeksforgeeks.org to report any issue with the above content.

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

Load Comments

Share this post!

A computer science portal for geeks

710-B, Advant Navis Business Park,
Sector-142, Noida, Uttar Pradesh - 201305
feedback@geeksforgeeks.org

COMPANY

About Us
Careers
Privacy Policy
Contact Us

PRACTICE

Company-wise
Topic-wise
Contests
Subjective Questions

LEARN

Algorithms
Data Structures
Languages
CS Subjects
Video Tutorials

CONTRIBUTE

Write an Article
Write Interview Experience
Internships
Videos

@geeksforgeeks, Some rights reserved