
CSC 5991 Trustworthy AI for LLMs and VLMs

Lecture 10 Agentic AI Safety

Core Agentic Loop

- LLM receives observations from the environment
- Produces intermediate reasoning steps
- Executes actions through tools or APIs
- Updates memory and internal state for the next cycle

At its core, agentic AI runs on a powerful loop:



Bergman, R. (2025). ***Agentic AI: Benefits and Potential Issues.*** **Mediate.com.**
https://www.mediate.com/articles/agentic-ai-benefits-and-potential-issues.cfm

Agent Architecture

- Planner decomposes goals
- LLM reasons and selects actions
- Tools enable external operations
- Memory stores episodic and semantic state
- Safety layer mediates actions

AI Assistant: Personalized Support

Conversational Health Queries


Ask natural language questions about medications or symptoms for immediate, context-aware answers.

Personalized Insights

It leverages your questionnaire data to provide tailored health guidance and priorities.

Voice and History

Use voice input for ease and review past conversations to track recommendations.



Future Vision: Assessment to Action

Assessment Platform

Structured 4Ms framework health data collection.

AI Assistant

Data-driven, personalized recommendations and reminders.

Care Companion

Autonomous agents driving actionable health outcomes.

Agentic Capabilities

Appointments: Automate visit scheduling and management.

Medication: Track adherence and coordinate refills.

Care Coordination: Streamline team communication.

Reminders: Prompt health tasks and next steps.

Community Integration

Expand to location-aware resource matching, recommending local gyms, therapy, and social services tailored to user mobility and goals.

Autonomy Levels and Risk

- Autonomy level: degree to which an AI can initiate actions without real-time human approval

- Example levels:
  - L0: Assistive tools (no actions, text only)
  - L1: Bounded task execution (single-step tools, strong confirmations)
  - L2: Multi-step workflows under monitoring
  - L3+: Self-directed behavior with long-term goals

- Risk grows with:
  - action space (code execution, network access)
  - duration and reversibility of actions
  - access to sensitive data or credentials

Source: Harang, R., & Sablotny, M. (2025). ***Agentic Autonomy Levels and Security.*** NVIDIA Technical Blog.
https://developer.nvidia.com/blog/agentic-autonomy-levels-and-security/

Autonomy Levels and Risk

Autonomy level	Description
0 – Inference API	A single user request results in a single inference call to a single model.
1 – Deterministic system	A single user request triggers more than one inference request, optionally to more than one model, in a predetermined order that does not depend on either user input or inference results.
2 – Weakly autonomous system	A single user request triggers more than one inference request. An AI model can determine if or how to call plugins or perform additional inference at fixed predetermined decision points.
3 – Fully autonomous system	In response to a user request, the AI model can freely decide if, when, or how to call plugins or other AI models, or to revise its own plan freely, including deciding when to return control to the user.

Source: Harang, R., & Sablotny, M. (2025). ***Agentic Autonomy Levels and Security.*** **NVIDIA Technical Blog.**
https://developer.nvidia.com/blog/agentic-autonomy-levels-and-security/


Agentic AI Threat Taxonomy

- Prompt-level attacks: injections, jailbreaks, indirect prompt poisoning
- Autonomous cyber-exploitation & tool abuse: scripted hacking, mass phishing, malware generation
- Multi-agent/protocol threats: collusion, sybil agents, protocol manipulation in marketplaces or swarms
- Interface & environment risks: insecure tool APIs, ambiguous UIs, inconsistent permissions
- Governance & autonomy concerns: goal drift, unapproved self-modification, lack of auditability

Source: Datta, S., Kabir Nahin, S., Chhabra, A., & Mohapatra, P. (2025). Agentic AI Security: Threats, Defenses, Evaluation, and Open Challenges (arXiv:2510.23883v1).
arxiv.org/abs/2510.23883

Direct Prompt Injection


- Malicious text overrides system rules
- No need for external websites
- Very high success across frameworks
- Enables unrestricted tool calls



Datta, S., Kabir Nahin, S., Chhabra, A., & Mohapatra, P. (2025). Agentic AI Security: Threats, Defenses, Evaluation, and Open Challenges. University of South Florida, Bellini College of AI, Cybersecurity, and Computing.

Indirect Prompt Injection

- Hidden instructions inside external content
- Web browsing agents are highly vulnerable
- Attacker does not need to be the user
- Seen in BrowserGym & OSWorld




(b)

Datta, S., Kabir Nahin, S., Chhabra, A., & Mohapatra, P. (2025). Agentic AI Security: Threats, Defenses, Evaluation, and Open Challenges. University of South Florida, Bellini College of AI, Cybersecurity, and Computing.

EchoLeak Case Study

- Attack through email contents
- Copilot accessed internal SharePoint files
- Demonstrates systemic enterprise risk
- Shows tool misuse via agentic LLM



Ravia, I. (2025, May 31). Breaking down 'EchoLeak', the First Zero-Click AI Vulnerability Enabling Data Exfiltration from Microsoft 365 Copilot. Aim Labs blog.
URL: https://www.aim.security/post/echoleak-blogpost

Cyber Exploitation with Tools

- Tools enable remote execution
- LLMs chain multi-step exploits
- Attackers weaponize planning
- High-risk class for enterprise agents

Datta, S., Kabir Nahin, S., Chhabra, A., & Mohapatra, P. (2025). Agentic AI Security: Threats, Defenses, Evaluation, and Open Challenges. University of South Florida, Bellini College of AI, Cybersecurity, and Computing.

Multi-Agent & Protocol-Level Threats

- MCP-induced attacks (Fig. 5a): attacker alters messages flowing through the MCP servers (e.g., contact info, medical advice, poisoned data).
- A2A-induced attacks (Fig. 5b): attacker injects forged discovery responses to mislead agents selecting collaborators.
- Attackers exploit shared protocols instead of user prompts — poisoning the infrastructure layer.
- Malicious agents can register themselves in the ecosystem and respond with misleading or harmful results.
- Compromise spreads across multiple agent hosts, affecting any agent connected via MCP or A2A channels.

Datta, S., Kabir Nahin, S., Chhabra, A., & Mohapatra, P. (2025). Agentic AI Security: Threats, Defenses, Evaluation, and Open Challenges. University of South Florida, Bellini College of AI, Cybersecurity, and Computing.

Multi-Agent & Protocol-Level Threats




Figure 5: Visualizing different protocol-level attacks for multi-agent systems: (a) *MCP-induced*, (b) *A2A-induced*.

Datta, S., Kabir Nahin, S., Chhabra, A., & Mohapatra, P. (2025). Agentic AI Security: Threats, Defenses, Evaluation, and Open Challenges. University of South Florida, Bellini College of AI, Cybersecurity, and Computing.

Environment & UI Failures

- Agents misread dynamic UI states
- Ads & layout shifts cause unsafe actions
- Real-world UIs nondeterministic
- Major cause of silent failure

Datta, S., Kabir Nahin, S., Chhabra, A., & Mohapatra, P. (2025). Agentic AI Security: Threats, Defenses, Evaluation, and Open Challenges. University of South Florida, Bellini College of AI, Cybersecurity, and Computing.

ATFAA Threat Expansion

- Attacker enters through the application layer with malicious input.
- Trust boundaries sit between the app, orchestrator, booking agent, LLM, and payment systems.
- Each T1–T9 label marks a point where the system can be hit: database calls, LLM queries, memory/tools, payment flow.
- Reasoning engine, agent memory, RAG store, and payment agent become exposed once the boundary is crossed.
- A single poisoned step can move across components and trigger downstream damage.

Narajala, V. S., & Narayan, O. (2025). Securing Agentic AI: A Comprehensive Threat Model and Mitigation Framework for Generative AI Agents. Amazon Web Services, Proactive Security.

ATFAA Threat Expansion




Fig. 2. Agentic System Threats, Trust Boundary, Assets.

Narajala, V. S., & Narayan, O. (2025). Securing Agentic AI: A Comprehensive Threat Model and Mitigation Framework for Generative AI Agents. Amazon Web Services, Proactive Security.

SHIELD Defense Architecture

- Defense framework built on ATFAA
- Segmentation of agents, tools, data
- Runtime monitoring of reasoning
- Escalation control for sensitive actions

Narajala, V. S., & Narayan, O. (2025). Securing Agentic AI: A Comprehensive Threat Model and Mitigation Framework for Generative AI Agents. Amazon Web Services, Proactive Security.