Practical 13

Mongosh

```
Use Student;
db.student.insertMany([
  {roll_no: 1, sname: "Aarav", dept: "Computer", marks: 85},
  {roll_no: 2, sname: "Priya", dept: "IT", marks: 75},
  {roll_no: 3, sname: "Rahul", dept: "Computer", marks: 92},
  {roll_no: 4, sname: "Sneha", dept: "IT", marks: 35},
  {roll_no: 5, sname: "Karan", dept: "Mechanical", marks: 60},
  {roll_no: 6, sname: "Neha", dept: "Computer", marks: 38},
  {roll_no: 7, sname: "Amit", dept: "IT", marks: 88},
  {roll_no: 8, sname: "Pooja", dept: "Computer", marks: 70},
  {roll_no: 9, sname: "Vikram", dept: "Mechanical", marks: 45},
  {roll_no: 10, sname: "Payal", dept: "IT", marks: 80}
])
```

1. db.student.find()
2. db.student.find({dept: "Computer"})
3. db.student.find({$or:[{dept:'Computer'},{dept:'IT'}]})
4. db.student.find({marks: {$gt: 70}})
5. db.student.find({$and:[{marks:{$gte:80}},{dept:'Computer'}]})
6. db.student.find({$or:[{marks:{$lt:40}},{dept:'IT'}]})
7. db.student.find({marks:{$gt:40,$lt:80}})
8. db.student.find({dept:"IT"})
9. db.student.aggregate({$group:{_id:"$dept",totalmarks:{$sum:"$marks"}}})
10. db.student.createIndex({sname: 1}) b. db.student.getIndexes() c. db.student.dropIndex("sname_1")