Practical 6

```
sudo docker start oracle-xe
Sudo docker ps –a
Docker start container id/
sudo docker exec -it oracle-xe sqlplus system/system123
```

```
CREATE TABLE employee1 (
    id INT,
    name VARCHAR(30),
    Dept VARCHAR(30),
    salary INT
);

INSERT INTO employee1 VALUES (1, 'Sumit', 'Finance', 30000);
INSERT INTO employee1 VALUES (2, 'Ram', 'Finance', 20000);
INSERT INTO employee1 VALUES (3, 'Abhay', 'HR', 30000);
INSERT INTO employee1 VALUES (4, 'Lakhan', 'HR', 40000);
INSERT INTO employee1 VALUES (5, 'Tejas', 'HR', 45000);
INSERT INTO employee1 VALUES (6, 'Pooja', 'HR', 30000);
INSERT INTO employee1 VALUES (7, 'Meghna', 'HR', 50000);
INSERT INTO employee1 VALUES (8, 'Megha', 'HR', 70000);
INSERT INTO employee1 VALUES (9, 'Adi', 'HR', 70000);

COMMIT;

SET SERVEROUTPUT ON;

DECLARE
    CURSOR cs1 IS
        SELECT *
        FROM employee1
        WHERE salary > 30000;

    info cs1%ROWTYPE;

BEGIN
    OPEN cs1;

    LOOP
        FETCH cs1 INTO info;
        EXIT WHEN cs1%NOTFOUND;

        DBMS_OUTPUT.PUT_LINE(
            'ID: ' || info.id ||
            ' Name: ' || info.name ||
            ' Department: ' || info.dept ||
            ' Salary: ' || info.salary
        );
    END LOOP;

    CLOSE cs1;
END;
/
```