Practical 8

```
sudo apt-get install mysql-server -y
sudo systemctl enable --now mysql
  sudo apt-get install python3-mysql.connector -y
   sudo apt-get install python3 -y
    pip install pymysql
     export CRYPTOGRAPHY_OPENSSL_NO_LEGACY=1


sudo mysql

create database college;

CREATE USER 'Student123'@'localhost' IDENTIFIED BY'Student@123';

GRANT ALL PRIVILEGES ON college.* TO 'Student123'@'localhost';

Use college;

CREATE TABLE IF NOT EXISTS student (
    roll_no INT PRIMARY KEY,
    name VARCHAR(50),
    marks INT
);

Exit mysql;

Nano 8.py

Type code in that:

import pymysql

# Connect to MySQL
mydb = pymysql.connect(
    host="localhost",
    user="Student123",
    password="Student@123",
    database="college"
)

mycursor = mydb.cursor()

print("1. Insert")
print("2. Update")
print("3. Delete")

choice = input("Enter choice (1/2/3): ")

if choice == "1":
    roll_no = input("Type rollno: ")
    name = input("Type a name: ")
```

```
    marks = input("Type marks: ")

    sql = "INSERT INTO student (roll_no, name, marks) VALUES (%s, %s, %s)"
    val = (roll_no, name, marks)

    mycursor.execute(sql, val)
    mydb.commit()

    print(mycursor.rowcount, "record inserted.")

elif choice == "2":
    name = input("Enter the name of the student to update: ")
    new_marks = input("Enter the new marks: ")

    sql = "UPDATE student SET marks = %s WHERE name = %s"
    val = (new_marks, name)

    mycursor.execute(sql, val)
    mydb.commit()

    print(mycursor.rowcount, "record updated.")

elif choice == "3":
    name = input("Enter the name of the student to delete: ")

    sql = "DELETE FROM student WHERE name = %s"
    val = (name,)

    mycursor.execute(sql, val)
    mydb.commit()

    print(mycursor.rowcount, "record deleted.")

else:
    print("Invalid choice. Please enter 1, 2, or 3.")

mycursor.close()
mydb.close()


save
python3 8.py for running
insert vagere kr

then open mysql

use college;
select * from student;
```