Three-Phase Transformer Bank 579559 (8348-40)



LabVolt Series

Datasheet



Table of Contents

General Description	2	<u>)</u>
Specifications	2)

General Description

The Three-Phase Transformer Bank consists of three independent power transformers enclosed in a module. Safety banana jacks on the module front panel provide individual access to the windings of each power transformer, allowing connection in either wye or delta configuration. The transformer windings are polarized and the polarity of each winding is indicated by a small dot on the module front panel. Resettable fuses protect the primary and secondary windings of each transformer against overcurrents. Fuse status lamps on the module front panel turn on when the resettable fuses open.

Specifications

Parameter	Value
Rating (Each Transformer)	
Primary Voltage	208 V
Secondary Voltage	208/120 V
Power	250 VA
Full-Load Current	1.2 A
Physical Characteristics	
Dimensions (H x W x D)	154 x 287 x 410 mm (6.1 x 11.3 x 16.1 in)
Net Weight	13.9 kg (30.6 lb)

2 © Festo Didactic

Reflecting the commitment of Festo Didactic to high quality standards in product, design, development, production, installation, and service, our manufacturing and distribution facility has received the ISO 9001 certification.

Festo Didactic reserves the right to make product improvements at any time and without notice and is not responsible for typographical errors. Festo Didactic recognizes all product names used herein as trademarks or registered trademarks of their respective holders. © Festo Didactic Inc. 2020. All rights reserved.

Festo Didactic SE

Rechbergstrasse 3 73770 Denkendorf Germany

P. +49(0)711/3467-0 F. +49(0)711/347-54-88500

Festo Didactic Inc.

607 Industrial Way West Eatontown, NJ 07724 United States

P. +1-732-938-2000 F. +1-732-774-8573

Festo Didactic Ltée/Ltd

675 rue du Carbone Québec QC G2N 2K7 Canada

P. +1-418-849-1000 F. +1-418-849-1666

www.labvolt.com

www.festo-didactic.com

© Festo Didactic 3