

# Future Radio Access Networks Empowering Mobile Cloud Computing

Niko Kortström

Department of Computer Science

University of Helsinki

Finland

Email: niko.kortstrom@cs.helsinki.fi

**Abstract**—The abstract goes here.

## I. INTRODUCTION

Introduction goes here.

## II. MOBILE CLOUD COMPUTING

Mobile devices lack the computational power residing in personal computers. According to Satyanarayanan et al. this will always be the case because improving size, weight and battery life are higher priorities in designing them[5]. Of course while a design focus, battery life is still an issue when using mobile devices. There are also many other issues like problems with connectivity. Most applications can still be ported to run on mobile devices. Many of them are simple enough that the lack of resources is not an issue at all. Sometimes it can also be a good solution to limit the usability of an application to better fit it into its new environment. This can mean offering only some qualities of the desktop app. This kind of applications can be called companion apps. For example a huge multiplayer games companion app can simply offer a connection to the in-game chat or your characters inventory.

A hot topic called internet of things can benefit a lot from mobile cloud computing. When computational capacity is embedded into things not originally build for it, their resources are most likely close to non-existent. Using them as mere thin clients, providing inputs to applications running on the cloud is a good option until computational resources of these things evolves.

There are numerous problems that can't be solved solely on the limited resources of modern mobile devices. Some of these problems are image processing, natural language processing and multimedia search[1]. This is where mobile cloud computing comes into play. Using a much more powerful device or collection of devices, in other words a cloud, to carry out the brunt of computing solves this issue. In this situation, a mobile device could possibly be used just as a mean to display results of computation. There are several types of clouds that mobile devices can make use of.

1) *Remote Cloud*: This type of mobile cloud computing is mostly similar with traditional cloud computing. A user offloads some computations to a powerful remote cloud. The difference is that in this case the user interacts with the cloud via a mobile device instead of, for example a laptop or a desktop computer. Everyday services that make use of the remote cloud include some of the most widely used applications and web sites in the world, such as Facebook, Google search and Outlook.

2) *Cloudlets*: Cloudlets form a far less known type of mobile cloud computing. Compared to remote clouds, cloudlets can be seen as less powerful but more closely located clouds. Whereas remote clouds can be seen as huge clusters or warehouses full of computational power, cloudlet can be just a single laptop moving with the user or a desktop computer situated at a public location.

3) *Cloud of Mobile Devices*: Mobile devices can also be used to form clouds amongst themselves. For this to be possible, users must be willing to submit their mobile device's computational resources to be used by someone else. Another possibility is that multiple users are interested in the result of same computational task. In this case mobile devices will divide the task into smaller pieces and distribute it between the interested mobile devices. The computational capacity of mobile devices is increasing rapidly. Much of this capacity is often not being used. Having a way to harness this unused power could be a great benefit to both, the users offering and making use of it.

Main benefit of the more closely located clouds is not having to use long range connections. There can be many different reasons that it just isn't a valid option at the time to make use of remote data centers. It might be that it is too battery draining, pricey or time consuming to transmit over long ranges. There are also cases that long range connectivity isn't available as depicted in the disaster scenario of Wang et al.[2].

Bringing cloud computing closer to the user has been envisioned to happen via public cloudlets located as densely as Wi-Fi access points in today's world[5]. This would require numerous different parties to want to establish cloudlets, meaning that they need to gain some sort of benefit out of this. Wi-Fi access points are often deployed in public places to

attract customers and offer them something to do while waiting for example. Similar to this case, if applications making use of cloudlets are interesting enough, people could seek out vicinity of cloudlets. Obviously to gain financial benefits, cloudlet owners could also sell their customers' personal information to third parties or owners of different facilities could allow third parties to set up their own cloudlets a fee.

Probably the most well known peer-to-peer systems are BitTorrent applications used to distribute entertainment. An application making use of a cloud of mobile devices can also be seen as a kind of peer-to-peer system. BitTorrent systems often encourage users to upload their already downloaded files to other users. Offering them higher download data rates in return is one widely used incentive. An example of a possible incentive[3] in case of mobile computation distribution is for service providers to offer discounts for users who distribute computation in cases of congested network bandwidth.

There are also reasons why users should offload some of their computation when possible, even if they aren't paid for it. Usually offloading computation directly helps with an inherent limiting factor of mobility: battery life. This is quite clear as heavy computation consumes battery fast, minimal computation consumes it a lot slower. However, the issue isn't quite as simple since we also have to account for the amount of battery used by network connection. Connections can limit the possibilities of mobile devices cloud usage if not available but they can also consume a lot of power when used. We must make sure that energy cost of offloading computation isn't too high compared to the energy save.

Trade-offs of mobile cloud computing must be considered. For this purpose there are a lot of different models[1] to closely look into the cost-benefit relationship of mobile cloud computing. These models can possibly be used by humans to decide if it would be useful to offload some of the computation of a specific application. Since benefit of offloading computation is often environment dependant, it is also useful for the application itself to be able to determine whether and how to offload.

When discussing moving computation from one entity to another we obviously need to have some kind of method to transfer the data efficiently. Three different methods are considered suitable for this purpose[1]: client-server communication, virtualization and mobile agent. Client-server communication requires the cloud to have some kind of pre-installed interface available for the client to call. When using virtualization, an image of the current memory state of the client is transferred as an image to the server where its execution is resumed. Mobile agent approach includes splitting up the program code from suitable points and sending it ahead to the cloud to be executed. These points can be chosen by the programmer beforehand or the application can for example use an analyzer to find them[2].

Distributing computing to multiple mobile devices also offers other possibilities. One such is also distributing the applications input or sensing capabilities. Distributing a problem to be solved with the help of multiple users is called

crowdsourcing. Users can collectively form larger data sets to be processed. Larger data sets often mean more accurate and reliable results, no matter what data we are talking about. There are many[4] possible applications that could benefit greatly from such an approach.

Modern mobile devices are able to collect enormous amounts of information about our habits, schedules and interests etc. We also use mobile devices to access vital services such as banking. Making applications residing in mobile devices interact with the cloud, directly causes additional security threats to both data about our everyday life and different kinds of personal information. Making sure that no data is disclosed to unwanted parties is a requirement that should absolutely be met before making use of cloud in an application. Additional aspect to consider is that in traditional cloud computing, cloud is usually owned and maintained by some well known corporation that is considered quite trustworthy. In cases of cloudlets and mobile clouds, targets of offloading cannot be always known beforehand. This makes ensuring security and privacy even more difficult.

All these different kinds of clouds, or more precisely combining them, also means rethinking the architecture of applications that we develop. Not only applications might have to be able to choose whether to offload computing, they may also need to pick the best destination for offloading. Having different layers of cloud is a new factor to keep in mind. Programmers need to be able to make applications smart enough for them to get the maximal benefit. This isn't simple as there are many things to compare, like available resources, data rates and network congestion.

Cloudlet and mobile device solutions also contain additional challenges due to mobile devices moving constantly along with their users. Some of the great benefits of these approaches are saving energy and radio access bandwidth by using bluetooth for example. Transmitting the results of offloaded computation while it is still possible, before the device that issued the task moves out of range is essential. How to know make sure this happens is a great challenge for application designers[3]. Losing all the results of offloaded computation right before it's finished can result in much worse processing time, compared to not distributing computing at all. One way to solve this problem is location based offloading[4]. Of course querying users' location adds to the computational needs so it would have to be used sparingly. This is again one problem that could use a powerful artificial intelligence to be solved.

### III. IMPROVING MOBILE NETWORKS

At the moment mobile networks are using the fourth generation technology, LTE. In essence, user equipment (mobile phone etc.) connect to the radio access network. Radio access network is communicating with the mobile core that is connected to the Internet. This is a simplified version of the way our mobile phones get access to the Internet every day.

Fifth generation mobile communication technology is to be released for consumer use in 2020. There are numerous important and really challenging qualities that are required to

be met before the next generation cellular communications technology can be released. 5g standards are yet to be created. Still, many expectations have already been visioned.

Gohil et al. [6] offer their views on what will and should be included in next generation radio access networks. This paper seems like an early review of peoples opinions rather than evidence based research as to what 5g will really be but it offers a good glance at the subject. Some of the technical qualities highlighted in the paper include seamless cooperation of different radio access technologies, combining cellular and ip connectivity and new protocol stack architecture which all sound interesting and powerful concepts. They also list some practical features associated with 5g. Advanced billing interfaces, large data rates, better consistency and reduced latency are some of these.

Andrews et al. [7] offer similar but more recent and in my opinion much more accurate description of the fifth generation of cellular networking. Requirements set for 5g are described pretty accurately in the paper. They include areas of data rate, latency and energy and cost efficiency. It is also stated that while great challenged to be achieved, all of the goals don't necessarily have to work in practise at the same time. Example is given that streaming high-definition video needs the high data rates but can do with a higher latency. Then again the situation is reversed for driverless cars, low latency is crucial but data rates can be lower. Coming of internet of things also suggests a need for supporting huge amounts of connections from really heterogenous device base. Low rate device-to-device connections functioning side by side with high rate mobile user connections require a new approach to mobile core management and control functions.

Three clear requirements are set for the future data rates. noitemsep

- Data rates should be increased by approximately thousand times for each area unit.
- The worst reasonably expectable user data rate should range from 100 Mbps to 1 Gbps. At the moment this value is around 1Mbps so the advance must be at least hundred fold.
- Best possible rate, while mostly a marketing number, should also be increased greatly, to tens of gigabits per second.

Fourth generation radio access networks offer roundtrip latencies of around 15 ms. It is stated that current applications can tolerate this well but some of the applications visioned for the era of 5g networks need faster response times. Roundtrip latency of around 1ms should be delivered.

It would obviously be ideal to reduce energy and financial costs but it is stated that this isn't on the top of requirements of 5g. It is, however, required that the costs wouldn't rise. In practise this means that as data rates are increased by for example a factor of hundred, energy and monetary cost per bit should be reduced to one percent of the current cost to keep the overall cost constant.

Many different approaches can be combined to achieve the maximal gains in energy efficiency. Solutions suggested are:

[7]. noitemsep

- allocating resources in a energy efficient way
- not having unnecessary basestations and running algorithms that turn basestations off when not needed and on again on request
- using renewable energy to power basestations, for example by attaching solar panels to them
- energy efficient hardware solutions

Some ways for operators to deal with financial costs related to moving into 5g are also presented. Needed additional infrastructure could be constructed by some outside parties. Right to use them for offering connections to end users would then be rented to operators. Increased backhaul requirements may be answered because of overall spreading of fiber connections in addition to better wireless backhaul solutions and optimizing the backhaul operations.

The paper lists ultra-densification, mmWave and massive multiple-input multiple-output (massive MIMO) along with virtualization as the defining factors of future radio access networks. The combination of these approaches are seen as the keys to provide ubiquitous, high-rate, low-latency connections to all mobile users.

Densification means simply making cells served by a radio access node smaller. This approach has been used in previous radio access improvements and ultra-densification just means taking it to yet another level. The most important benefit of this approach is that spectrum reserved by a user connection via a basestation accommodates a smaller area. In other words, smaller coverage area per basestation means less users connecting via that particular basestation. Obviously this means that there are more basestation resources available for each user.

The small cell approach doesn't come without downsides. Some of the associated challenges listed are supporting mobility between cells and increased costs of installing and maintaining all the basestations. Keeping the energy and financial costs low enough for the business to be profitable, small cell devices have to be cheaper and more energy-efficient than today's basestations. Smaller areas served by a single unit mean more need to transport computing from one basestation to another while the mobile user is on the move. Efficient algorithms are needed to handle the additional computing caused. Another challenge that cannot be avoided is adding yet another technology into the mix. The fact that the system must be able to support more technologies at the same time increases required complexity.

At the moment wireless communication is mainly propagated via microwave frequencies starting from hundreds of MHz and ranging to few GHz. This isn't too big of a spectrum and it is becoming increasingly congested. Improvements like radio cloud and ultra-densification do help with this issue but don't solve it completely.

The new wave frequencies planned for next generation wireless networking reside at 30 to 300 GHz range. This range is called mmWave because wave length at these frequencies varies from one millimeter to ten. The mmWave frequencies

have not been used before because it has been considered unfit for longer range wireless communication. This is due to it being very susceptible to interference from weather effects and object between the transmitter and the receiver.

Rapport et al. [8] did extensive research on mmWave and its viability and effectibility. They conducted important experiments with mmWave both indoors and outdoors. Different kinds of blockages and interferences were also included. Their tests verified that buildings indeed affect the waves a lot as results from Texas were better than those from New York. However with proper network planning and density the mmWave should work just fine for propagating data. Their tests concluded that 200 meter cell radius is enough to achieve good coverage using mmWave.

Some other challenges related to benefiting from this technology are narrowness of it's beams and initializing the connection between mobile users and the basestation. Building the systems to provide coverage while keeping the cells from interfering with each other is no simple task with beams that can be described to resemble flashlights [7]. The narrowness of the beam also forces the user equipment to possibly scan numerous different directions before locating the the beam.

In practice MIMO means making use of multiple antennas on both, transmitting and receiving ends. More antennas transmitting can be used to reach higher rates. Modern technology also allows multiple basestations to cooperate, even allowing them to turn some of the interference into signals containing data. MIMOs are said to use two to four antennas for transmitting to the mobile device and maximum of eight to transmit within one basestations area.

Envisioned massive MIMOs can consist of hundreds of antennas within one basestation sector. Realizing basestations with these new MIMOs requires a great deal of restructuring the architecture of a basestation. Another thing to consider carefully is how to have MIMOs work together with new small cell and mmWave technologies to achieve maximal benefits.

Virtualization been already somewhat been taken in use with mobile core but there is still a lot of work to be done to extend it farther. There are two important terms related to virtualizing the radio access networks, software devined networking and network function virtualization. Implementations before network function virtualization have always closely paired network functions with the hardware. Now the aim is to move much of these functions to be executed in the cloud, offering improved flexibility and management possibilities. This is the essential meaning of network function virtualization. Software definend networking provides the possibility for external applications to modify the network's capabilities.

Lindholm et al. [9] have studied how to implement the virtualization in practise. In other words, they proposed which parts of the LTE mobile network to virtualize should be virtualized and how to possibly change it's overall architecture. Their approach is based on publish-subscribe model where mobile core subscribes to changes in some functions of radio access network and vice versa. This seems like a well suited and efficient way to handle the communication in a modern

mobile networking system.

On the hardware level virtualization leads to a new design approach, where a traditional radio access point is somewhat divided in two. Remote radio heads handle physically exchanging data with the user equipment. Data centers are user to connect to multiple remote radio heads and handle the processing for them. This is described in more detail for instance by Rost et al. [10].

They view the mobile network divided to seven layers: noitemsep

- Network management
- Admission/congestion control
- Radio resource management
- Medium access control
- Physical layer
- Radio frequency

As much as the first six of the are seen to be possible to be virtualized in future implementations. They also refer to flexible functional splitting, meaning that every layer shouldn't just be automatically virtualized. Virtualization allows creation of more intelligent networks where we can choose which parts would be useful to be virtualized at the time. This is yet another gain from the new architecture, to make the architecture itself better.

As we have discussed, virtualization is a big part of the ongoing mobile network development. Most have heard of system architectures consisting of different services, such as infrastructure as a service, platform as a service and software as a service. Nikaein et al. [11] go as far as to introduce a similar concept related to mobile networks, radio access network as a service. This is a term that to me really shows demonstrates the possible gains from this new approach. The amount of flexibility and manageability gained feels to see new proportions when approached like this.

In addition to the new qualities introduced to improve mobile networks, there are also possibilities to improve the existing ones once the architectural changes have been implemented. One such approach is improving the caching performed by radio access networks [12]. Ao et al. introduce their views on how to increase benefits from caching with the help of small cells.

Multiple radio access points covering an area mean multiple caches available to deliver cached data quickly to the receiving users. They give an example of caching video files based on their popularity (the most popular video being cached to most radio access points). This way some of the ever-increasing data download can be handled even more efficiently in a way that could possibly reduce the stress from core network by a lot.

#### IV. EFFECTS OF IMPROVED RADIO ACCESS NETWORKS

Section text here.

#### V. CONCLUSION

The conclusion goes here.

## REFERENCES

- [1] N. Fernando, S. W. Loke and W. Rahayu, *Mobile cloud computing: A survey*. Future Generation Computer Systems Volume 29 Issue 1, January 2013.
- [2] Y. Wang, I. Chen and D. Wang, *A Survey of Mobile Cloud Computing Applications: Perspectives and Challenges*. Wireless Personal Communications: An International Journal Volume 80 Issue 4, February 2015.
- [3] M. Miluzzo, R. Cceres and Y. Chen, *Vision: mClouds Computing on Clouds of Mobile Devices*. MCS '12 Proceedings of the third ACM workshop on Mobile cloud computing and services, 2012.
- [4] G. Chatzimilioudis, A. Konstantinidis, C. Laoudias and D. Zeinalipour-Yazti, *Crowdsourcing with Smartphones*. IEEE Internet Computing Volume 16 Issue 5, September 2012.
- [5] M. Satyanarayanan, P. Bahl, R. Caceres and N. Davies, *The Case for VM-Based Cloudlets in Mobile Computing*. IEEE Pervasive Computing Volume 8 Issue 4, October 2009
- [6] A. Gohil, H. Modi and S. K. Patel, *5G Technology of Mobile Communication: A Survey*. Intelligent Systems and Signal Processing (ISSP) International Conference, 2013
- [7] J. G. Andrews, S. Buzzi, W. Choi, S. V. Hanly, A. Lozano, A. C. K. Soong and J. C. Zhang, *What Will 5G Be?*. IEEE Journal on Selected Areas in Communications Volume 32 Issue 6, June 2014
- [8] T. S. Rappaport, S. Sun, R. Mayzus, H. Zhao, Y. Azar, K. Wang, G. N. Wong, J. K. Schulz, M. Samimi and F. Gutierrez, *Millimeter Wave Mobile Communications for 5G Cellular: It Will Work!*. IEEE Access Volume 1, May 2013
- [9] H. Lindholm, L. Osmani, H. Flinck, S. Tarkoma and A. Rao, *State Space Analysis to Refactor the Mobile Core*. AllThingsCellular '15 Proceedings of the 5th Workshop on All Things Cellular: Operations, Applications and Challenges, August 2015
- [10] P. Rost, C. J. Bernardos, A. De Domenico, M. Di Girolamo, M. Lalam, A. Maeder, D. Sabella and D. Wbben, *Cloud Technologies for Flexible 5G Radio Access Networks*. IEEE Communications Magazine Volume 52 Issue 5, May 2014
- [11] N. Nikaein, R. Knopp, L. Gauthier, E. Schiller, T. Braun, D. Pichon, C. Bonnet, F. Kaltenberger and D. Nussbaum, *Demo Closer to Cloud-RAN: RAN as a Service*. MobiCom '15 Proceedings of the 21st Annual International Conference on Mobile Computing and Networking, September 2015
- [12] W. Ao and K. Psounis, *Distributed Caching and Small Cell Cooperation for Fast Content Delivery*. MobiHoc '15 Proceedings of the 16th ACM International Symposium on Mobile Ad Hoc Networking and Computing, June 2015