TAD REGISTRO 1.

TAD REGISTRO

```
igualdad observacional

\begin{pmatrix}
(\forall r_1, r_2 : \text{reg}) \ (r_1 =_{\text{obs}} r_2) \Leftrightarrow \left( \text{campos}(r_1) =_{\text{obs}} \text{campos}(r_2) \land_{\text{L}} \left( (\forall \text{c:Campos}) \middle) \right) \\
(c \in \text{campos}(r_1))) \Rightarrow_{\text{L}} \left( (\text{Nat} = \text{tipo}(c) \Rightarrow_{\text{L}} (\text{ValorEn}(r_1, c) =_{\text{obs}} \text{ValorEn}(r_2, c))) \land \right) \\
(\neg \text{Nat} = \text{tipo}(c) \Rightarrow_{\text{L}} (\text{PalabraEn}(r_1, c) =_{\text{obs}} \text{PalabraEn}(r_2, c))) \right) \end{pmatrix}

géneros
exporta
                      reg, generadores, observadores, otras operaciones
                      NAT, STRING, CAMPO, TIPO, CONJUNTO(\alpha)
usa
observadores básicos
   Campos : reg \longrightarrow conj(Campo)
    valor\operatorname{En}:\operatorname{reg} \ \operatorname{r} \times \operatorname{campo} \ \operatorname{c} \ \longrightarrow \operatorname{Nat}
                                                                                                                                   {Nat = tipo(c) \land c \in Campos(r)}
   palabraEn : reg \quad r \times campo \quad c \longrightarrow String
                                                                                                                               \{String = tipo(c) \land c \in Campos(r)\}\
generadores
   NuevoRegistro : \bullet \longrightarrow reg
                                                                                                                                    \{c \notin campos(r) \land Nat = tipo(c)\}
   ag
Valor : reg r \times campo c \times nat n \longrightarrow reg
                                                                                                                                \{c \notin campos(r) \land String = tipo(c)\}\
   agPalabra : reg r \times campo c \times string s \longrightarrow reg
otras operaciones
   \bullet = \bullet : \operatorname{reg} \times \operatorname{reg} \longrightarrow \operatorname{bool}
    \text{Coincide? : conj(reg)} \quad \text{rs} \times \text{reg} \quad \text{r} \times \text{campo} \quad \text{c} \quad \longrightarrow \quad \text{bool} \qquad \quad \{(\forall \ r_1 : \text{reg}) \ r_1 \in rs \Rightarrow (\text{c} \in \text{campos}(r_1))\} 
   Combinar : reg r_1 \times \text{reg} \quad r_2 \longrightarrow \text{reg}
    Combinar
DeAcuerdo<br/>A : reg r_1 \times \text{reg} r_2 \times \text{conj}(\text{campo}) cs \longrightarrow reg
    ConMismoContenido : reg r_1 \times \text{reg} r_2 \times \text{conj(campo)} cs \longrightarrow \text{bool}
   DameCoincidente : conj(reg) rs \times reg \quad r \times campo \quad c \longrightarrow reg
                                                                              \{(\forall r_1 : \text{reg}) \ (r_1 \in rs \Rightarrow c \in \text{campos}(r_1)) \land_{\text{L}} (\text{Coincide}?(rs, r, c))\}
   DameCoincidentesVal : campo \ c \times \text{nat} \ n \times \text{conj(reg)} \ rs \ \longrightarrow \ \text{conj(reg)}
                                                                                               \{(\forall \text{ r:reg})(\text{r} \in \text{rs} \Rightarrow_{\text{L}} c \in \text{campos}(\text{r})) \land_{\text{L}} \text{Nat} = \text{tipo}(c)\}
   DameCoincidentesPal : campo c \times \text{string} s \times \text{conj(reg)} rs \longrightarrow \text{conj(reg)}
                                                                                           \{(\forall \text{ r:reg})(r \in rs \Rightarrow_{L} c \in \text{campos}(r)) \land_{L} \text{String} = \text{tipo}(c)\}
   \text{noRepiten} \ : \ \text{reg} \quad r_1 \times \text{reg} \quad r_2 \times \text{campo} \quad \text{c} \quad \longrightarrow \ \text{bool} \\ \qquad \qquad \{c \in \text{campos}(r_1) \land \text{c} \in \text{campos}(r_2)\}
    AgYCompDefault : reg r_1 \times \text{reg} \ def \times \text{conj(campo)} \ cs \longrightarrow \text{reg}
   Busca : conj(campo) cs \times reg r \times conj(reg) rs \times conj(campo) ci \longrightarrow conj(reg)
                                                                                                                        \{cs \subset campos(r) \land \neg (\emptyset?(cs)) \land ci \subset cs\}
                      \forall r_1, r_2 : \text{reg}, \forall c_1, c_2 : \text{campo}, \forall cs : \text{conj(campo)}, \forall n : \text{nat}, \forall s : \text{string}
   campos(NuevoRegistro) \equiv \emptyset
   campos(agValor(r_1,c_1,n) \equiv Ag(c_1,campos(r_1))
   campos(agPalabra(r_1,c_1,s)) \equiv Ag(c_1,campos(r_1))
    valorEn(agValor(r_1,c_1,n), c_2) \equiv if c_1 = c_2 then n else <math>valorEn(r_1, c_2) fi
    valorEn(agPalabra(r_1,c_1,s),c_2) \equiv valorEn(r_1,c_2)
   palabraEn(agValor(r_1, c_1, n), c_2) \equiv palabraEn(r_1, c_2)
```

palabra $En(agPalabra(r_1,c_1,s), c_2) \equiv if c_1 = c_2 then s else palabra<math>En(r_1,c_2) fi$

 $r_1 = r_2 \equiv \operatorname{campos}(r_1) = \operatorname{campos}(r_2) \wedge_{\scriptscriptstyle{L}} \operatorname{ConMismoContenido}(r_1, r_2, \operatorname{campos}(r_1))$

```
ConMismoContenido(r_1, r_2, cs) \equiv \text{if } \emptyset?(cs) \text{ then}
                                               true
                                           else
                                               \neg \text{noRepiten}(r_1, r_2, \text{DameUno}(cs)) \land \text{ConMismoContenido}(r_1, r_2, \text{SinUno}(cs))
Coincide?(rs, r, c) \equiv if \emptyset?(rs) then
                               false
                               \neg NoRepiten(DameUno(rs), r, c) \lor Coincide?(SinUno(rs), r, c)
DameCoincidente(rs, r, c) \equiv if \text{ noRepiten}(DameUno(rs), r, c) then
                                        DameCoincidente(SinUno(rs), r, c)
                                        DameUno(rs)
Combinar(r_1, r_2) \equiv CombinarDeAcuerdoA(r_1, c_1, campos(c_2))
Combinar
DeAcuerdoA(r_1, r_2, cs) \equiv \mathbf{if} \ \emptyset ? (\mathbf{cs}) \ \mathbf{then}
                                             else
                                                 if DameUno(cs) \in campos(r_1) then
                                                     Combinar De Acuerdo A(r_1, r_2, Sin Uno(cs))
                                                     if Nat = tipo(DameUno(cs)) then
                                                         \operatorname{agValor}(\operatorname{CombinarDeAcuerdoA}(r_1, r_2, \operatorname{SinUno}(\operatorname{cs})), \operatorname{DameUno}(\operatorname{cs}),
                                                         valorEn(r_2,DameUno(cs))
                                                         agPalabra (Combinar De Acuerdo A(r_1, r_2, Sin Uno(cs))),
                                                         DameUno(cs), palabraEn(r_2, DameUno(cs))
                                                 fi
noRepiten(r_1, r_2, c) \equiv Nat = tipo(c) \land_L \neg (valorEn(r_1, c) = valorEn(r_2, c)) \lor
                             (String = tipo(c) \land_L \neg (palabraEn(r_1, c) = palabraEn(r_2, c)))
DameCoincidentesVal(c, n, rs) \equiv \text{if } \emptyset ? (rs) \text{ then}
                                          else
                                              if ValorEn(DameUno(rs),c)=n then
                                                  Ag(DameUno(rs),DameCoincidentesVal(c,n,SinUno(rs)))
                                              else
                                                  DameCoincidentesVal(c, n, SinUno(rs))
                                              fi
                                          fi
DameCoincidentesPal(c, s, rs) \equiv \text{if } \emptyset ? (rs) \text{ then}
                                          else
                                             if PalabraEn(DameUno(rs),c)=s then
                                                 Ag(DameUno(rs),DameCoincidentesPal(c,s,SinUno(rs)))
                                             else
                                                 DameCoincidentesPal(c,s,SinUno(rs))
                                             fi
                                         fi
```

```
AgYCompDefault(r, def, cs) \equiv if \emptyset?(cs) then
                                   NuevoRegistro
                               else
                                   if DameUno(cs) \in campos(r) then
                                     if Nat = tipo(DameUno(cs)) then
                                         AgValor (AgYCompDefault (r, def, SinUno(cs)), DameUno(cs),
                                         ValorEn(r,DameUno(cs))
                                      else
                                         AgPalabra (AgYCompDefault (r, def, SinUno(cs)), DameUno(cs),
                                         PalabraEn(r,DameUno(cs))
                                     fi
                                   else
                                      if Nat = tipo(DameUno(cs)) then
                                         AgValor (AgYCompDefault (r, def, SinUno(cs)), DameUno(cs),
                                         ValorEn(def, DameUno(cs))
                                      else
                                         AgPalabra (AgYCompDefault (r, def, SinUno(cs)), DameUno(cs),
                                         PalabraEn(def, DameUno(cs))
                                     fi
                                  fi
                               fi
DameCamposCoinci(r,ci) \equiv if \emptyset?(ci) then
                                Ag(RearmarCoinci(DameUno(cs),ci),DameCamposCoinci(SinUno(rs),ci)
                            fi
RearmarCoinci(r,ci) \equiv if \emptyset?(ci) then
                           NuevoRegistro
                       else
                           if tipo(DameUno(ci))= Nat then
                              AgValor(RearmarCoinci(r,SinUno(ci)),DameUno(ci),valorEn(r,DameUno(ci)))
                           else
                              AgPalabra(RearmarCoinci(r,SinUno(ci)),DameUno(ci),palabraEn(r,DameUno(ci)))
                           fi
Busca(cs,r,rs,ci) \equiv if \emptyset?(SinUno(cs)) then
                       if tipo(DameUno(cs)) = Nat then
                          DameCoincidentesVal(DameUno(cs),valorEn(r,DameUno(cs)),rs)
                       else
                          DameCoincidentesPal(DameUno(cs),valorEn(r,DameUno(cs)),rs)
                   else
                       if tipo(DameUno(cs)) = Nat then
                          DameCoincidentesVal(DameUno(cs), valorEn(r, DameUno(cs)), Busca(SinUno(cs), r, rs))
                          DameCoincidentesPal(DameUno(cs),valorEn(r,DameUno(cs)),Busca(SinUno(cs),r,rs))
                       fi
                   fi
```

Fin TAD