

Data Collection and Labeling

CS 203: Software Tools and Techniques for AI

Prof. Nipun Batra

Table of contents

1	Module Overview	4
1.1	Four Core Components	4
2	Part 1: Data Collection	4
2.1	Why Data Collection Matters	4
2.2	Common Data Sources	5
2.2.1	Digital Sources	5
2.2.2	Physical Sources	5
2.3	Instrumentation: The Foundation	5
2.3.1	Key Principles	5
2.4	Basic Instrumentation Example	5
2.5	Web Analytics Tools	6
2.5.1	Google Analytics 4	6
2.5.2	Mixpanel	6
2.6	Self-Hosted Analytics	6
2.6.1	Why Self-Host?	6
2.7	Plausible & Umami Examples	7
2.8	Application Performance Monitoring	7
2.8.1	Sentry	7
2.8.2	Datadog	7
2.9	Database Event Logging	8
2.10	Change Data Capture (CDC)	8
2.10.1	Debezium Example	8
2.11	OpenTelemetry: Industry Standard	9
2.12	Web Scraping with Scrapy	9
2.13	Ethical Web Scraping	10
2.14	Streaming Data with Kafka	10
2.15	Data Collection Best Practices	11
2.15.1	Schema Design with Pydantic	11

2.16	Sampling Strategies	11
2.17	Privacy and Compliance	11
3	Part 2: Data Validation	12
3.1	Why Data Validation Matters	12
3.1.1	The Cost of Bad Data	12
3.1.2	Real-World Impact	12
3.2	Types of Data Quality Issues	12
3.3	Data Validation with Pydantic	13
3.4	Using Pydantic	13
3.5	Great Expectations Framework	14
3.6	Pandera: Statistical Validation	14
3.7	Custom Validation Pipelines	15
3.8	Statistical Distribution Validation	15
3.9	Data Quality Monitoring	16
4	Part 3: Data Labeling	17
4.1	What is Data Labeling?	17
4.1.1	Why It's Critical	17
4.2	Types of Labeling Tasks	17
4.2.1	Classification	17
4.2.2	Object Detection	17
4.2.3	Sequence Labeling	17
4.2.4	Structured Prediction	18
4.3	Label Studio	18
4.3.1	Key Features	18
4.3.2	Installation	18
4.4	Label Studio: Image Classification	18
4.5	Label Studio: Object Detection	19
4.6	Label Studio: NER	19
4.7	Alternative Labeling Tools	19
4.7.1	Labelbox	19
4.7.2	CVAT	19
4.7.3	Prodigy	20
4.7.4	Scale AI / SageMaker	20
4.8	Inter-Annotator Agreement	20
4.8.1	Cohen's Kappa ()	20
4.9	Cohen's Kappa Implementation	20
4.10	Fleiss' Kappa: Multiple Annotators	21
4.11	Improving Agreement	21
4.11.1	1. Clear Guidelines	21
4.11.2	2. Training Phase	22
4.11.3	3. Regular Consensus Meetings	22

4.12	Sampling Strategies	22
4.12.1	Random Sampling	22
4.12.2	Stratified Sampling	22
4.13	Snowball Sampling	22
4.14	Active Learning	23
4.14.1	Process	23
4.15	Uncertainty Sampling	23
4.16	Active Learning Loop	24
4.17	Active Learning Benefits	24
4.17.1	Cost Reduction	24
4.17.2	Real-world Savings	25
4.18	Weak Supervision with Snorkel	25
4.19	Combining Weak Labels	25
4.20	Pre-labeling with Models	26
5	Part 4: Data Augmentation	26
5.1	Why Data Augmentation?	27
5.1.1	The Problem	27
5.1.2	The Solution	27
5.2	Image Data Augmentation	27
5.3	Advanced: Albumentations	28
5.4	Cutout, Mixup, CutMix	28
5.4.1	Cutout	28
5.4.2	Mixup	29
5.4.3	CutMix	29
5.5	Text Data Augmentation	29
5.5.1	Synonym Replacement	29
5.6	EDA: Easy Data Augmentation	30
5.7	Back-Translation	30
5.8	Contextual Augmentation with BERT	31
5.9	Audio Augmentation	31
5.10	Time Series Augmentation	32
5.11	SMOTE for Tabular Data	32
5.12	SMOTE Variants	33
5.12.1	ADASYN	33
5.12.2	BorderlineSMOTE	33
5.13	Generative Models	33
5.14	Best Practices	34
5.14.1	1. Domain-Appropriate	34
5.14.2	2. Preserve Semantics	34
5.14.3	3. Validation Split First	34
5.15	Monitor Augmentation Impact	34
5.16	Class-Specific Augmentation	35

6	Summary	36
6.1	Key Takeaways	36
6.1.1	Data Collection	36
6.1.2	Data Validation	36
6.2	Key Takeaways (cont.)	36
6.2.1	Data Labeling	36
6.2.2	Data Augmentation	36
6.3	Hands-On Lab	37
6.3.1	Complete Data Pipeline	37
6.4	Additional Resources	37
6.4.1	Documentation	37
6.4.2	Key Papers	37
7	Questions?	37
7.1	Thank You!	37

1 Module Overview

1.1 Four Core Components

1. **Data Collection** - Tools and techniques for gathering data from diverse sources
2. **Data Validation** - Ensuring data quality and reliability
3. **Data Labeling** - Annotating datasets with ground truth
4. **Data Augmentation** - Expanding datasets strategically

Key Insight

Quality data is the foundation of successful AI systems. Garbage in, garbage out!

2 Part 1: Data Collection

Instrumenting and Logging Data Sources

2.1 Why Data Collection Matters

- **Real-world AI systems** depend on continuous data flow
- **User behavior** changes over time → models need fresh data
- **Production systems** require automated collection pipelines
- **Debugging** often requires understanding what data was seen

2.2 Common Data Sources

2.2.1 Digital Sources

- Web applications
- Mobile apps
- IoT devices
- APIs and databases

2.2.2 Physical Sources

- Sensors
- Cameras
- Microphones
- Manual entry

2.3 Instrumentation: The Foundation

Instrumentation = Adding code to collect data about system behavior

2.3.1 Key Principles

1. **Minimal Performance Impact** - Don't slow down production systems
2. **Comprehensive Coverage** - Capture all relevant events
3. **Privacy-Aware** - Respect user privacy and regulations (GDPR, CCPA)
4. **Structured Logging** - Consistent formats for easy parsing

2.4 Basic Instrumentation Example

```
import logging
import json
from datetime import datetime

def log_user_action(user_id, action, metadata):
    event = {
        "timestamp": datetime.utcnow().isoformat(),
        "user_id": user_id,
        "action": action,
        "metadata": metadata
```

```
}  
logging.info(json.dumps(event))
```

2.5 Web Analytics Tools

2.5.1 Google Analytics 4

```
// Track custom events  
gtag('event', 'search', {  
  'search_term': query,  
  'results_count': results.length  
});
```

Pros: Free, Rich ecosystem, Real-time dashboards **Cons:** Privacy concerns, Limited customization

2.5.2 Mixpanel

```
// Track with properties  
mixpanel.track('Video Played', {  
  'video_id': video.id,  
  'duration': video.length,  
  'quality': '1080p'  
});
```

Pros: Detailed analytics, Cohort analysis **Cons:** Costly at scale

2.6 Self-Hosted Analytics

2.6.1 Why Self-Host?

- **Data ownership** - Complete control over your data
- **Privacy compliance** - GDPR-friendly by design
- **No tracking cookies** - Lightweight and fast
- **Cost-effective** - Predictable infrastructure costs

2.7 Plausible & Umami Examples

```
// Plausible: Simple, privacy-focused
<script defer data-domain="yourdomain.com"
    src="https://plausible.io/js/script.js"></script>

plausible('signup', {props: {plan: 'premium'}});
```

```
// Umami: Open-source alternative
<script async src="https://analytics.yourdomain.com/umami.js"
    data-website-id="your-website-id"></script>

umami.track('button-click', {button: 'subscribe'});
```

2.8 Application Performance Monitoring

2.8.1 Sentry

```
import sentry_sdk

sentry_sdk.init(
    dsn="your-dsn",
    traces_sample_rate=1.0
)

try:
    process_data()
except Exception as e:
    sentry_sdk.capture_exception(e)
```

2.8.2 Datadog

```
from datadog import initialize, statsd

initialize(
    api_key='your-key',
    app_key='your-app-key'
```

```
)

statsd.increment('api.requests')
statsd.histogram('api.latency', 245)
```

2.9 Database Event Logging

```
-- PostgreSQL: Track all changes to users table
CREATE TABLE user_audit (
    audit_id SERIAL PRIMARY KEY,
    user_id INT,
    action VARCHAR(10),
    old_data JSONB,
    new_data JSONB,
    changed_at TIMESTAMP DEFAULT NOW()
);

CREATE OR REPLACE FUNCTION audit_user_changes()
RETURNS TRIGGER AS $$
BEGIN
    IF (TG_OP = 'UPDATE') THEN
        INSERT INTO user_audit(user_id, action, old_data, new_data)
        VALUES (NEW.id, 'UPDATE', row_to_json(OLD), row_to_json(NEW));
    END IF;
    RETURN NEW;
END;
$$ LANGUAGE plpgsql;
```

2.10 Change Data Capture (CDC)

CDC = Capturing and streaming database changes in real-time

2.10.1 Debezium Example

```
{
  "name": "inventory-connector",
  "config": {
```



```

"connector.class": "io.debezium.connector.postgresql.PostgresConnector",
"database.hostname": "postgres",
"database.port": "5432",
"table.include.list": "public.orders,public.customers",
"topic.prefix": "dbserver1"
}
}

```

Benefits: Real-time streaming, No app changes, Complete history

2.11 OpenTelemetry: Industry Standard

```

from opentelemetry import trace
from opentelemetry.sdk.trace import TracerProvider

trace.set_tracer_provider(TracerProvider())
tracer = trace.get_tracer(__name__)

@tracer.start_as_current_span("process_request")
def process_request(user_id):
    span = trace.get_current_span()
    span.set_attribute("user.id", user_id)
    # Your logic here

```

2.12 Web Scraping with Scrapy

```

import scrapy

class ProductSpider(scrapy.Spider):
    name = 'products'
    start_urls = ['https://example.com/products']

    custom_settings = {
        'DOWNLOAD_DELAY': 2, # Respectful scraping
        'CONCURRENT_REQUESTS': 1
    }

    def parse(self, response):

```

```

for product in response.css('div.product'):
    yield {
        'name': product.css('h2::text').get(),
        'price': product.css('span.price::text').get(),
        'rating': product.css('div.rating::attr(data-rating)').get()
    }

```

2.13 Ethical Web Scraping

1. **Check robots.txt** - Respect website's scraping policy
2. **Rate Limiting** - Don't overwhelm servers
3. **User-Agent** - Identify yourself honestly
4. **Terms of Service** - Read and comply with ToS
5. **Personal Data** - Respect privacy laws (GDPR, CCPA)

Warning

Scraping can violate ToS or copyright. Always consult legal counsel for commercial use.

2.14 Streaming Data with Kafka

```

from kafka import KafkaProducer, KafkaConsumer
import json

# Producer: Collect data
producer = KafkaProducer(
    bootstrap_servers=['localhost:9092'],
    value_serializer=lambda v: json.dumps(v).encode('utf-8')
)

event = {
    'user_id': '12345',
    'event_type': 'page_view',
    'page': '/products'
}
producer.send('user-events', event)

# Consumer: Process data
consumer = KafkaConsumer('user-events')

```

```
for message in consumer:
    process_event(message.value)
```

2.15 Data Collection Best Practices

2.15.1 Schema Design with Pydantic

```
from pydantic import BaseModel, Field
from datetime import datetime

class UserEvent(BaseModel):
    user_id: str
    event_type: str
    timestamp: datetime = Field(default_factory=datetime.utcnow)
    properties: dict
    session_id: Optional[str] = None
```

2.16 Sampling Strategies

```
import random

class SamplingCollector:
    def __init__(self, sample_rate=0.1):
        self.sample_rate = sample_rate

    def should_collect(self, event):
        if random.random() < self.sample_rate:
            return True
        if event.get('priority') == 'high':
            return True
        return False
```

When to use: High-traffic systems where full collection is expensive

2.17 Privacy and Compliance

```

import hashlib

class PrivacyAwareCollector:
    def __init__(self, pii_fields=['email', 'phone']):
        self.pii_fields = pii_fields

    def anonymize(self, data):
        anonymized = data.copy()
        for field in self.pii_fields:
            if field in anonymized:
                value = str(anonymized[field])
                hashed = hashlib.sha256(value.encode()).hexdigest()
                anonymized[field] = hashed
        return anonymized

```

3 Part 2: Data Validation

Ensuring Data Quality and Reliability

3.1 Why Data Validation Matters

3.1.1 The Cost of Bad Data

- Garbage In, Garbage Out
- Silent Failures
- Expensive Debugging
- Lost Trust

3.1.2 Real-World Impact

E-commerce: Missing IDs → 30% drop in CTR **Medical:** Wrong units → Misdiagnoses

Fraud Detection: Duplicates → 45% false positives

3.2 Types of Data Quality Issues

1. **Completeness** - Missing or null values
2. **Accuracy** - Incorrect or outdated values
3. **Consistency** - Contradictory data

4. **Timeliness** - Stale or outdated data
5. **Uniqueness** - Duplicate records
6. **Validity** - Violates business rules

3.3 Data Validation with Pydantic

```
from pydantic import BaseModel, Field, validator, EmailStr

class UserEvent(BaseModel):
    user_id: str = Field(..., min_length=1, max_length=100)
    email: EmailStr
    age: int = Field(..., ge=0, le=150)
    event_type: str

    @validator('event_type')
    def validate_event_type(cls, v):
        allowed = ['click', 'view', 'purchase', 'signup']
        if v not in allowed:
            raise ValueError(f'event_type must be one of {allowed}')
        return v

    @validator('timestamp')
    def timestamp_not_future(cls, v):
        if v > datetime.utcnow():
            raise ValueError('timestamp cannot be in the future')
        return v
```

3.4 Using Pydantic

```
try:
    event = UserEvent(
        user_id="user_123",
        email="user@example.com",
        age=25,
        event_type="click",
        timestamp=datetime.utcnow()
    )
    print(" Valid event")
```

```
except ValueError as e:
    print(" Validation errors:", e.json())
```

3.5 Great Expectations Framework

```
import great_expectations as gx
from great_expectations.dataset import PandasDataset

df = pd.read_csv('user_events.csv')
dataset = PandasDataset(df)

# Define expectations
dataset.expect_column_values_to_not_be_null('user_id')
dataset.expect_column_values_to_be_unique('event_id')
dataset.expect_column_values_to_be_in_set(
    'event_type',
    ['click', 'view', 'purchase']
)
dataset.expect_column_values_to_be_between('age', 0, 150)

# Validate
results = dataset.validate()
```

3.6 Pandera: Statistical Validation

```
import pandera as pa
from pandera import Column, Check

schema = pa.DataFrameSchema({
    "user_id": Column(str, checks=[
        Check.str_length(min_value=1, max_value=100)
    ]),
    "age": Column(int, checks=[
        Check.in_range(min_value=0, max_value=150),
        Check(lambda s: s.mean() > 18)
    ]),
    "purchase_amount": Column(float, checks=[
        Check.greater_than_or_equal_to(0)
    ])
})
```

```

    ], nullable=True)
})

validated_df = schema.validate(df)

```

3.7 Custom Validation Pipelines

```

from dataclasses import dataclass
from typing import List

@dataclass
class ValidationResult:
    passed: bool
    errors: List[str]
    warnings: List[str]

class DataValidationPipeline:
    def __init__(self):
        self.validators = []

    def add_validator(self, validator):
        self.validators.append(validator)
        return self

    def validate(self, df):
        all_errors = []
        for validator in self.validators:
            result = validator.validate(df)
            all_errors.extend(result.errors)
        return ValidationResult(
            passed=len(all_errors) == 0,
            errors=all_errors,
            warnings=[]
        )

```

3.8 Statistical Distribution Validation

```

class DistributionValidator:
    def __init__(self, reference_df, columns):
        self.reference_stats = {
            col: {
                'mean': reference_df[col].mean(),
                'std': reference_df[col].std()
            }
            for col in columns
        }

    def validate(self, df):
        errors = []
        for col, ref_stats in self.reference_stats.items():
            current_mean = df[col].mean()
            mean_shift = abs(current_mean - ref_stats['mean']) / ref_stats['std']

            if mean_shift > 2:
                errors.append(
                    f"{col}: Mean shifted by {mean_shift:.2f} std deviations"
                )
        return ValidationResult(passed=len(errors) == 0, errors=errors, warnings=[])

```

3.9 Data Quality Monitoring

```

import sentry_sdk
from datadog import statsd

class DataQualityMonitor:
    def monitor(self, df, dataset_name):
        result = self.pipeline.validate(df)

        # Send metrics
        statsd.gauge(f'{dataset_name}.row_count', len(df))
        statsd.gauge(f'{dataset_name}.validation.errors', len(result.errors))

        # Alert on failures
        if not result.passed:
            sentry_sdk.capture_message(
                f"Data validation failed for {dataset_name}",

```



```
        extras={"errors": result.errors}  
    )
```

4 Part 3: Data Labeling

Annotating Datasets with Ground Truth

4.1 What is Data Labeling?

Data Labeling: Adding meaningful tags or annotations to raw data

4.1.1 Why It's Critical

- **Supervised Learning** requires labeled examples
- **Quality labels** → Better models
- **Consistent labels** → Reliable evaluation
- **Cost:** Often 60-80% of ML project time and budget

4.2 Types of Labeling Tasks

4.2.1 Classification

- Image: “cat” vs “dog”
- Text: “spam” vs “not spam”
- Audio: speaker identification

4.2.2 Object Detection

- Bounding boxes
- Keypoint annotation
- Polygon segmentation

4.2.3 Sequence Labeling

- Named Entity Recognition
- Part-of-speech tagging
- Time series anomalies

4.2.4 Structured Prediction

- Semantic segmentation
- Dependency parsing
- Relationship extraction

4.3 Label Studio

Label Studio: Open-source, multi-modal annotation platform

4.3.1 Key Features

- Multi-modal: Images, text, audio, video, time series
- Custom interfaces with XML config
- ML-assisted labeling and active learning
- Collaboration features
- Export: JSON, CSV, COCO, Pascal VOC, YOLO

4.3.2 Installation

```
pip install label-studio
label-studio start
```

4.4 Label Studio: Image Classification

```
<View>
  <Image name="image" value="$image_url"/>
  <Choices name="choice" toName="image">
    <Choice value="Cat"/>
    <Choice value="Dog"/>
    <Choice value="Other"/>
  </Choices>
</View>
```

4.5 Label Studio: Object Detection

```
<View>
  <Image name="image" value="$image_url"
    zoom="true" zoomControl="true"/>
  <RectangleLabels name="label" toName="image">
    <Label value="Person" background="red"/>
    <Label value="Car" background="blue"/>
    <Label value="Bicycle" background="green"/>
  </RectangleLabels>
</View>
```

4.6 Label Studio: NER

```
<View>
  <Text name="text" value="$text"/>
  <Labels name="label" toName="text">
    <Label value="Person" background="red"/>
    <Label value="Organization" background="blue"/>
    <Label value="Location" background="green"/>
    <Label value="Date" background="orange"/>
  </Labels>
</View>
```

Example: “Apple Inc. CEO Tim Cook announced the new iPhone in Cupertino”

4.7 Alternative Labeling Tools

4.7.1 Labelbox

- Enterprise features
- Model-assisted labeling
- **Cons:** Expensive, vendor lock-in

4.7.2 CVAT

- Open-source by Intel
- Video annotation
- **Cons:** Setup complexity

4.7.3 Prodigy

- By spaCy creators
- Active learning built-in
- **Cons:** License cost

4.7.4 Scale AI / SageMaker

- Managed services
- Human workforce included
- **Cons:** Very expensive

4.8 Inter-Annotator Agreement

Problem: Different annotators may label differently

Solution: Measure agreement to ensure quality

4.8.1 Cohen's Kappa ()

Measures agreement between **two annotators** accounting for chance

$$\kappa = \frac{p_o - p_e}{1 - p_e}$$

Interpretation:

- 0.0-0.20: Slight
- 0.21-0.40: Fair
- 0.41-0.60: Moderate
- 0.61-0.80: Substantial
- 0.81-1.00: Almost perfect

4.9 Cohen's Kappa Implementation

```

from sklearn.metrics import cohen_kappa_score

annotator1 = ['spam', 'ham', 'spam', 'ham', ...]
annotator2 = ['spam', 'ham', 'ham', 'ham', ...]

kappa = cohen_kappa_score(annotator1, annotator2)
print(f"Cohen's Kappa: {kappa:.3f}")

```

Example Output:

Cohen's Kappa: 0.745
→ Substantial agreement

4.10 Fleiss' Kappa: Multiple Annotators

```

from statsmodels.stats.inter_rater import fleiss_kappa
import numpy as np

# Matrix: rows = items, columns = category counts
data = np.array([
    [3, 0], # Item 1: all 3 annotators said "ham"
    [2, 1], # Item 2: 2 said "ham", 1 said "spam"
    [0, 3], # Item 3: all 3 said "spam"
])

kappa = fleiss_kappa(data, method='fleiss')
print(f"Fleiss' Kappa: {kappa:.3f}")

```

4.11 Improving Agreement

4.11.1 1. Clear Guidelines

- Define each label precisely
- Provide examples and counter-examples
- Document edge cases
- Create decision trees for ambiguous cases

4.11.2 2. Training Phase

- Use gold standard datasets
- Review disagreements together
- Iterative calibration sessions

4.11.3 3. Regular Consensus Meetings

- Discuss disputed items
- Update guidelines based on patterns
- Track improvement over time

4.12 Sampling Strategies

4.12.1 Random Sampling

```
import random
random.sample(dataset, n=100)
```

Pros: Unbiased **Cons:** May miss rare classes

4.12.2 Stratified Sampling

```
from sklearn.model_selection import train_test_split
_, sampled, _, _ = train_test_split(
    dataset, labels,
    train_size=len(dataset)-100,
    stratify=labels
)
```

Pros: Ensures class representation

4.13 Snowball Sampling

```

from sklearn.neighbors import NearestNeighbors

class SnowballSampler:
    def sample(self, labeled_data, unlabeled_data, n=100):
        # Vectorize
        labeled_vectors = self.vectorizer.fit_transform(labeled_data)
        unlabeled_vectors = self.vectorizer.transform(unlabeled_data)

        # Find nearest neighbors
        nn = NearestNeighbors(n_neighbors=5)
        nn.fit(unlabeled_vectors)
        distances, indices = nn.kneighbors(labeled_vectors)

        return [unlabeled_data[i] for i in indices.flatten()[:n]]

```

Use case: Finding more examples of a rare class

4.14 Active Learning

Active Learning: Intelligently select which examples to label next

4.14.1 Process

1. Train model on small labeled set
2. Find **most informative** unlabeled examples
3. Label those examples
4. Retrain model
5. Repeat

Goal: Achieve good performance with minimal labeling

4.15 Uncertainty Sampling

```

class UncertaintySampler:
    def sample(self, X_unlabeled, n=10):
        probs = self.model.predict_proba(X_unlabeled)

        # Higher entropy = more uncertain
        uncertainties = -np.sum(probs * np.log(probs + 1e-10), axis=1)

```

```
# Select top-n most uncertain
uncertain_indices = np.argsort(uncertainties)[-n:]
return uncertain_indices
```

4.16 Active Learning Loop

```
def active_learning_loop(X_labeled, y_labeled, X_unlabeled, budget=100):
    model = MultinomialNB()
    sampler = UncertaintySampler(model)

    for iteration in range(budget // 10):
        # Train model
        model.fit(X_labeled, y_labeled)

        # Select informative examples
        indices = sampler.sample(X_unlabeled, n=10)

        # Get human labels
        new_X = [X_unlabeled[i] for i in indices]
        new_y = get_human_labels(new_X)

        # Update datasets
        X_labeled.extend(new_X)
        y_labeled.extend(new_y)

        # Evaluate
        accuracy = evaluate_model(model)
        print(f"Iteration {iteration}: Accuracy = {accuracy:.3f}")
```

4.17 Active Learning Benefits

4.17.1 Cost Reduction

Random Sampling: 10,000 labels → 85% accuracy

Active Learning: 2,000 labels → 85% accuracy

Savings: 80% fewer labels!

4.17.2 Real-world Savings

- 10k labels \times \$0.50 = \$5,000
- 2k labels \times \$0.50 = \$1,000
- **Saved: \$4,000**

Key Insight: Active learning reaches target accuracy with 5-10 \times fewer labels

4.18 Weak Supervision with Snorkel

Weak Supervision: Use noisy/heuristic labels instead of manual annotation

```
from snorkel.labeling import labeling_function

SPAM = 1
HAM = 0
ABSTAIN = -1

@labeling_function()
def lf_contains_money(x):
    money_keywords = ['$ ', 'money', 'cash', 'prize']
    return SPAM if any(kw in x.text.lower() for kw in money_keywords) else ABSTAIN

@labeling_function()
def lf_short_message(x):
    return SPAM if len(x.text.split()) < 10 else ABSTAIN

@labeling_function()
def lf_known_sender(x):
    trusted_domains = ['company.com', 'university.edu']
    return HAM if any(d in x.sender for d in trusted_domains) else ABSTAIN
```

4.19 Combining Weak Labels

```
from snorkel.labeling.model import LabelModel

# Apply labeling functions
lfs = [lf_contains_money, lf_short_message, lf_known_sender]
L_train = applier.apply(df=df)
```

```
# Combine noisy labels
label_model = LabelModel(cardinality=2)
label_model.fit(L_train=L_train, n_epochs=500)

# Get predictions
predicted_labels = label_model.predict(L=L_train)
```

Advantages: Fast, Flexible, No manual labeling needed

4.20 Pre-labeling with Models

```
class PreLabelingPipeline:
    def pre_label(self, unlabeled_data, confidence_threshold=0.9):
        predictions = self.model.predict_proba(unlabeled_data)

        auto_labeled = []
        needs_review = []

        for i, probs in enumerate(predictions):
            max_prob = max(probs)

            if max_prob >= confidence_threshold:
                auto_labeled.append({
                    'data': unlabeled_data[i],
                    'label': np.argmax(probs),
                    'source': 'model'
                })
            else:
                needs_review.append(unlabeled_data[i])

        return auto_labeled, needs_review
```

5 Part 4: Data Augmentation

Expanding Training Datasets Strategically

5.1 Why Data Augmentation?

5.1.1 The Problem

- Limited labeled data is expensive
- Class imbalance leads to biased models
- Overfitting on small datasets
- Rare events underrepresented

5.1.2 The Solution

Data Augmentation: Creating new training examples by applying transformations

Benefits: Increase dataset size, Improve generalization, Reduce overfitting, Balance classes

5.2 Image Data Augmentation

```
from torchvision import transforms

transform = transforms.Compose([
    # Geometric
    transforms.RandomHorizontalFlip(p=0.5),
    transforms.RandomRotation(degrees=15),
    transforms.RandomResizedCrop(size=224, scale=(0.8, 1.0)),

    # Color
    transforms.ColorJitter(
        brightness=0.2, contrast=0.2,
        saturation=0.2, hue=0.1
    ),

    # Blurring
    transforms.GaussianBlur(kernel_size=3),

    # Normalization
    transforms.ToTensor(),
    transforms.Normalize(mean=[0.485, 0.456, 0.406],
                          std=[0.229, 0.224, 0.225])
])
```

5.3 Advanced: Albumentations

```
import albumentations as A

transform = A.Compose([
    A.RandomResizedCrop(height=224, width=224),
    A.HorizontalFlip(p=0.5),
    A.ShiftScaleRotate(shift_limit=0.0625, scale_limit=0.1, rotate_limit=15),
    A.ElasticTransform(p=0.3),

    # Color
    A.RandomBrightnessContrast(p=0.5),
    A.HueSaturationValue(p=0.5),

    # Blur and noise
    A.OneOf([
        A.MotionBlur(p=0.5),
        A.GaussianBlur(p=0.5),
    ], p=0.3),
    A.GaussNoise(p=0.3),

    # Weather
    A.RandomRain(p=0.2),
    A.RandomFog(p=0.2),
])
```

5.4 Cutout, Mixup, CutMix

5.4.1 Cutout

Random rectangular masks

```
A.CoarseDropout(
    max_holes=8,
    max_height=32,
    p=0.5
)
```

5.4.2 Mixup

Blend two images

```
def mixup(x1, y1, x2, y2):
    lam = np.random.beta(0.2, 0.2)
    x = lam * x1 + (1 - lam) * x2
    y = lam * y1 + (1 - lam) * y2
    return x, y
```

5.4.3 CutMix

Paste regions

```
def cutmix(x1, y1, x2, y2):
    # Cut and paste
    # region from x2 to x1
    ...
```

5.5 Text Data Augmentation

5.5.1 Synonym Replacement

```
from nltk.corpus import wordnet

def get_synonyms(word):
    synonyms = set()
    for syn in wordnet.synsets(word):
        for lemma in syn.lemmas():
            synonyms.add(lemma.name())
    return list(synonyms)

def synonym_replacement(text, n=2):
    words = text.split()
    random_indices = random.sample(range(len(words)), n)

    for idx in random_indices:
        synonyms = get_synonyms(words[idx])
        if synonyms:
            words[idx] = random.choice(synonyms)
```

```
return ' '.join(words)
```

5.6 EDA: Easy Data Augmentation

```
class EDA:
    @staticmethod
    def random_insertion(words, n=1):
        """Insert n random synonyms"""
        ...

    @staticmethod
    def random_swap(words, n=1):
        """Swap n pairs of words"""
        ...

    @staticmethod
    def random_deletion(words, p=0.1):
        """Delete each word with probability p"""
        return [w for w in words if random.random() > p]
```

5.7 Back-Translation

```
from transformers import MarianMTModel, MarianTokenizer

class BackTranslator:
    def __init__(self, intermediate_lang='fr'):
        # English → French
        self.forward_model = MarianMTModel.from_pretrained(
            f'Helsinki-NLP/opus-mt-en-{intermediate_lang}'
        )
        # French → English
        self.backward_model = MarianMTModel.from_pretrained(
            f'Helsinki-NLP/opus-mt-{intermediate_lang}-en'
        )

    def augment(self, text):
        # Translate to French and back
```

```
intermediate = self.forward_model.translate(text)
return self.backward_model.translate(intermediate)
```

Result: “The weather is beautiful” → “The weather is nice”

5.8 Contextual Augmentation with BERT

```
from transformers import pipeline

class ContextualAugmentor:
    def __init__(self):
        self.unmasker = pipeline('fill-mask', model='bert-base-uncased')

    def augment(self, text):
        words = text.split()
        mask_idx = random.randint(0, len(words) - 1)

        masked_words = words.copy()
        masked_words[mask_idx] = '[MASK]'

        predictions = self.unmasker(' '.join(masked_words))

        return [pred['sequence'] for pred in predictions[:3]]
```

5.9 Audio Augmentation

```
import librosa

class AudioAugmentor:
    @staticmethod
    def add_noise(audio, noise_factor=0.005):
        noise = np.random.randn(len(audio))
        return audio + noise_factor * noise

    @staticmethod
    def time_stretch(audio, rate=1.0):
        return librosa.effects.time_stretch(audio, rate=rate)
```

```

@staticmethod
def pitch_shift(audio, sr=22050, n_steps=2):
    return librosa.effects.pitch_shift(audio, sr=sr, n_steps=n_steps)

```

5.10 Time Series Augmentation

```

class TimeSeriesAugmentor:
    @staticmethod
    def jittering(x, sigma=0.03):
        """Add Gaussian noise"""
        return x + np.random.normal(0, sigma, x.shape)

    @staticmethod
    def scaling(x, sigma=0.1):
        """Multiply by random factor"""
        factor = np.random.normal(1, sigma, size=(x.shape[0], 1))
        return x * factor

    @staticmethod
    def time_warping(x, sigma=0.2):
        """Warp time dimension"""
        # Use cubic spline interpolation
        ...

```

5.11 SMOTE for Tabular Data

SMOTE: Synthetic Minority Over-sampling Technique

```

from imblearn.over_sampling import SMOTE

# Imbalanced dataset: {0: 900, 1: 100}
smote = SMOTE(sampling_strategy='auto', random_state=42)
X_resampled, y_resampled = smote.fit_resample(X_train, y_train)

# Now balanced: {0: 900, 1: 900}

```

How it works:

1. For each minority sample, find k nearest neighbors

2. Randomly select one neighbor
3. Create synthetic sample along line segment

5.12 SMOTE Variants

5.12.1 ADASYN

Adaptive Synthetic Sampling

```
from imblearn.over_sampling import ADASYN

adasyn = ADASYN(random_state=42)
X_res, y_res = adasyn.fit_resample(X, y)
```

Advantage: Generates more samples in harder-to-learn regions

5.12.2 BorderlineSMOTE

Focus on decision boundary

```
from imblearn.over_sampling import BorderlineSMOTE

bsmote = BorderlineSMOTE(random_state=42)
X_res, y_res = bsmote.fit_resample(X, y)
```

Advantage: More conservative, focuses on boundary

5.13 Generative Models

```
from diffusers import StableDiffusionPipeline

pipe = StableDiffusionPipeline.from_pretrained(
    "stabilityai/stable-diffusion-2-1"
)

def generate_augmented_images(prompt, n=10):
    images = []
    for i in range(n):
        image = pipe(prompt, num_inference_steps=50).images[0]
```

```

        images.append(image)
    return images

# Generate synthetic training data
synthetic = generate_augmented_images(
    "A high-quality photo of a defective product",
    n=100
)

```

Use cases: Rare defects, medical imaging, artistic styles

5.14 Best Practices

5.14.1 1. Domain-Appropriate

Good: Horizontal flip for general images **Bad:** Horizontal flip for text/digits (changes meaning)

5.14.2 2. Preserve Semantics

Bad: Extreme rotation for digits ($6 \rightarrow 9$) **Good:** Slight rotation ($\pm 15^\circ$)

5.14.3 3. Validation Split First

```

# Correct
train, val = train_test_split(data)
aug_train = augment(train) # Only augment training

# Wrong (data leakage!)
aug_data = augment(data)
train, val = train_test_split(aug_data)

```

5.15 Monitor Augmentation Impact

```

def evaluate_augmentation(model, train_data, val_data, aug_levels):
    results = []

    for strength in aug_levels:
        aug_train = augment(train_data, strength=strength)
        model.fit(aug_train)
        val_acc = model.evaluate(val_data)
        results.append({'strength': strength, 'accuracy': val_acc})

    # Plot results to find optimal augmentation
    plt.plot([r['strength'] for r in results],
             [r['accuracy'] for r in results])
    plt.xlabel('Augmentation Strength')
    plt.ylabel('Validation Accuracy')

```

5.16 Class-Specific Augmentation

```

class ClassBalancedAugmentor:
    def __init__(self, target_samples_per_class=1000):
        self.target = target_samples_per_class

    def augment(self, X, y):
        X_aug, y_aug = [], []

        for cls in np.unique(y):
            X_cls = X[y == cls]
            current_count = len(X_cls)

            if current_count < self.target:
                n_to_generate = self.target - current_count
                augmented = self.generate_samples(X_cls, n_to_generate)
                X_aug.extend(augmented)
                y_aug.extend([cls] * len(augmented))

        return np.array(X_aug), np.array(y_aug)

```

6 Summary

6.1 Key Takeaways

6.1.1 Data Collection

- Instrument systems for automatic capture
- Use appropriate tools (analytics, APM, CDC)
- Implement buffering, batching, error handling
- Respect privacy and comply with regulations

6.1.2 Data Validation

- Validate early and often
- Use schema validation (Pydantic, Pandera)
- Monitor data quality metrics
- Set up alerts for anomalies

6.2 Key Takeaways (cont.)

6.2.1 Data Labeling

- Use appropriate tools (Label Studio, CVAT)
- Measure inter-annotator agreement (Cohen's Kappa)
- Apply smart sampling (active learning)
- Leverage weak supervision when possible

6.2.2 Data Augmentation

- Choose domain-appropriate transformations
- Preserve label semantics
- Augment only training data
- Monitor impact on performance

! Important

High-quality data is the foundation of successful AI systems. Invest time in getting it right!

6.3 Hands-On Lab

6.3.1 Complete Data Pipeline

Tasks:

1. Data Collection (30 min) - Scrape reviews, set up logging
2. Data Validation (30 min) - Create schemas, build validation pipeline
3. Data Labeling (45 min) - Label Studio, calculate agreement, active learning
4. Data Augmentation (30 min) - Apply EDA, back-translation, measure impact

Deliverable: Jupyter notebook with complete pipeline

6.4 Additional Resources

6.4.1 Documentation

- Label Studio: <https://labelstud.io/guide/>
- Great Expectations: <https://docs.greatexpectations.io/>
- Alumentations: <https://alumentations.ai/docs/>
- Snorkel: <https://www.snorkel.org/>

6.4.2 Key Papers

- “SMOTE: Synthetic Minority Over-sampling Technique” (2002)
- “Snorkel: Rapid Training Data Creation with Weak Supervision” (2017)
- “Active Learning Literature Survey” (2009)

7 Questions?

7.1 Thank You!

Next: Reproducibility & Versioning

Contact: nipun.batra@iitgn.ac.in