

CSE 331: Microprocessor Interfacing and Embedded Systems

Lecture 6: Procedures

C functions

**What information must
compiler/programmer
keep track of?**

```
main() {  
    int a,b,c;  
    ...  
    c = sum(a,b); /* a,b,c:r0,r1,r2*/  
    ...  
}
```

```
/* really dumb sum function  
*/ int sum(int x, int y) {  
    return x+y;  
}
```

**What instructions can
accomplish this?**

Function Call Bookkeeping

- ❖ Registers play a major role in keeping track of information for function calls

- ❖ **Register conventions:**

❖ Return address	1 r
❖ Arguments	r0, r1, r2, r3
❖ Return value	r0, r1, r2, r3
❖ Local variables	r4, r5, ... , r12

- ❖ The stack is also used; more later

Register Usage

Arguments into function
Result(s) from function
otherwise corruptible
(Additional parameters
passed on stack)

Register

r0
r1
r2
r3

The compiler has a set of rules known as a Procedure Call Standard that determine how to pass parameters to a function (see **AAPCS**)

CPSR flags may be corrupted by function call.
Assembler code which links with compiled code must follow the AAPCS at external interfaces

Register
variables Must
be preserved

r4
r5
r6
r7
r8
r9/sb
r10/s1
r11

The AAPCS is part of the new ABI for the ARM Architecture

-Stack base

-Stack limit if software stack checking selected

Scratch register
(corruptible)

r12

Stack Pointer Link
Register Program
Counter

r13/sp
r14/lr
r15/pc

-SP should always be 8-byte (2 word) aligned
-R14 can be used as a temporary once value stacked


Instruction Support for Functions

```
... sum(a,b); ... /* a,b:$r3,$r4 */  
  
C      }  
      int sum(int x, int y) {return x+y; }  
      }
```

ARM

Address

1000
1004
1008
1012
1016



In ARM, all instructions are stored in memory just like data. So here we show the addresses of where the programs are stored.

Instruction Support for Functions

```
... sum(a,b);... /* a,b:r4,r5 */  
}  
int sum(int x, int y) {  
    return x+y;  
}
```

C

address

```
1000 MOV    r0, r4  
1004 MOV    r1, r5  
1008 MOV    lr, 1016  
1012 B      sum  
1016 ...
```

```
; x = a  
; y = b  
; lr = 1016  
; branch to  
sum
```

**A
R
M**


```
2000 sum: ADD r0, r0, r1  
2004 BX lr // MOV pc, lr i.e., return
```

Instruction Support for Functions

```
... sum(a,b);... /* a,b:$s0,$s1 */  
}  
  
C      int sum(int x, int y)  
      { return x+y;  
      }
```

-
- ❖ Question: Why use **BX** here? Why not simply use **B**?
 - ❖ Answer: **sum** might be called by many functions, so we can't return to a fixed place. The calling proc to **sum** must be able to say “return here” somehow.

A R M



```
2000 sum: ADD r0,r0,r1  
2004 BX lr ; new instruction
```

Instruction Support for Functions

- ❖ Single instruction to jump and save return address:
jump and link (BL)

- ❖ **Before:**

```
1008 MOV lr, 1016 ; lr=1016  
1012 B sum ; goto sum
```

- ❖ **After:**

```
1008 BL sum # lr=1012, goto sum
```

- ❖ Why have a BL? Make the common case fast:
function calls are very common. Also, you don't have to know where the code is loaded into memory with BL.

Instruction Support for Functions

- ❖ Syntax for BL (branch and link) is same as for B (branc):
BLlabel
- ❖ BL functionality:
 - ❖ Step 1 (link): Save address of *next* instruction into `lr` (Why next instruction? Why not current one?)
 - ❖ Step 2 (branch): Branch to the given label

Instruction Support for Functions

- ❖ Syntax for BX (branch and exchange):
 - BX register
- ❖ Instead of providing a label to jump to, the BX instruction provides a register which contains an address to jump to
- ❖ Only useful if we know exact address to jump
- ❖ Very useful for function calls:
 - ❖ BL stores return address in register (lr)
 - ❖ BX lr jumps back to that address

Nested Procedures


```
int sumSquare(int x, int y) {  
    return mult(x, x) + y;  
}
```

- ❖ Something called `sumSquare`, now `sumSquare` is calling `mult`.
- ❖ So there's a value in `lr` that `sumSquare` wants to jump back to, but this will be overwritten by the call to `mult`.
- ❖ Need to save `sumSquare` return address before call to `mult`.

Nested Procedures

- ❖ In general, may need to save some other info in addition to `lr`.
- ❖ When a C program is run, there are 3 important memory areas allocated:
 - ❖ **Static**: Variables declared once per program, cease to exist only after execution completes. E.g., C globals
 - ❖ **Heap**: Variables declared dynamically
 - ❖ **Stack**: Space to be used by procedure during execution; this is where we can save register values

C Memory Allocation



Using the Stack

- ❖ So we have a register `sp` which always points to the last used space in the stack.
- ❖ To use stack, we decrement this pointer by the amount of space we need and then fill it with info.

- ❖ So, how do we compile this?

```
int sumSquare(int x, int y)
{
    return mult(x, x) + y;
}
```

Using the Stack

❖ Hand-compile

```
int sumSquare(int x, int y)
{ return mult(x,x)+ y; }
```

“push”

```
ADD sp, sp, #-8      ; space on stack
STR lr, [sp, #4]     ; save ret addr

STR r1, [sp]          ; save y
BL mult              ; call mult

LDR r1, [sp]          ; restore y
ADD r0, r0, r1        ; mult()+y
LDR lr, [sp, #4]      ; get ret addr
```

“pop”

```
ADD sp, sp, #8        ; restore stack
BX lr                 ; return original location

mult: mul r0, r0, r0   ; mult x,x
BX lr
```

Steps for Making a Procedure Call

- 1) Save necessary values onto stack
- 2) Assign argument(s), if any
- 3) BL call
- 4) Restore values from stack

Rules for Procedures

- ❖ Called with a BL instruction, returns with a BX lr (or MOV pc, lr)
- ❖ Accepts up to 4 arguments in r0, r1, r2 and r3
- ❖ Return value is always in r0 (and if necessary in r1, r2, r3)
- ❖ Must follow **register conventions** (even in functions that only you will call)! So what are they?

ARM Registers

Register	Synonym	Role in Procedure Call Standard
r0-r1	a1-a2	Argument/Result/Scratch Register
r2-r3	a3-a4	Argument/Scratch Register
r4-r8	v1-v5	Variable Register
r9	v6/sb/tr	Platform Register
r10-r11	v7-v8	Variable Register
r12	ip	Intra-Procedure Call Scratch Register
r13	sp	Stack Pointer
r14	lr	Link Register
r15	pc	Program Counter

Register Conventions

- ❖ **Callee**R: the calling function
- ❖ **Calle**E: the function being called
- ❖ When callee returns from executing, the caller needs to know which registers may have changed and which are guaranteed to be unchanged.
- ❖ **Register Conventions**: A set of generally accepted rules as to which registers will be unchanged after a procedure call (BL) and which may be changed.

Saved Register Conventions

- ❖ r4-r11 (v1-v8): **Restore if you change**. Very important. If the callee changes these in any way, it must restore the original values before returning.
- ❖ sp: **Restore if you change**. The stack pointer must point to the same place before and after the **BL** call, or else the caller won't be able to restore values from the stack.

Volatile Register Conventions

- ❖ **lr: Can Change.** The BX call itself will change this register. Caller needs to save on stack if nested call.
- ❖ **r0-r3 (a1-a4): Can change.** These are volatile argument registers. Caller needs to save if they'll need them after the call. E.g., r0 will change if there is a return value
- ❖ **r12 (ip)** may be used by a linker as a scratch register between a routine and any subroutine it calls. It can also be used within a routine to hold intermediate values *between* subroutine calls.


Register Conventions

- ❖ What do these conventions mean?
 - ❖ If function R calls function E, then function R must save any temporary registers that it may be using onto the stack before making a BL call.
 - ❖ Function E must save any saved registers it intends to use before garbling up their values
 - ❖ Remember: Caller/callee need to save only volatile/saved registers **they are using**, not all registers.

Basic Structure of a Function

Prologue

```
entry_label:  
ADD sp, sp, -framesize  
STR lr, [sp, #framesize-4] ; save lr  
save other regs if need be  
...
```



Body (call other functions...)

```
LDR lr, [$sp, framesize-4] ; restore lr  
ADD sp, sp, #framesize  
BX lr
```

Epilogue

restore other regs if need be

Example

```
main() {  
    int i,j,k,m; /* i-m:v0-v3 */  
    ...  
    i = mult(j,k); ...  
    m = mult(i,i); ... }  
  
int mult (int mcand, int mlrier) {  
    int product;  
    product = 0;  
    while (mlrier > 0) {  
        product += mcand;  
        mlrier -= 1; }  
    return product;}
```


Example

```
main() {int i,j,k,m; /* i-m:v0-v3 */
```

```
  i = mult(j,k); ...
```

```
  m = mult(i,i); ... }
```

—start:

MOV a1,v1

MOV a2,v2

BL mult

MOV v0,r0

...

MOV a1,v0

MOV a2,v0

BL mult

MOV v3,r0

...

done

```
  ; arg1 = j
  ; arg2 = k
  ; call mult
  ; i = mult()
```

```
  ; arg1 = i
  ; arg2 = i
  ; call mult
  ; m = mult()
```

Example

❖ Notes:

- ❖ `main` function ends with `done`, not `BX lr`, so there's no need to save `lr` onto stack
- ❖ All variables used in `main` function are saved registers, so there's no need to save these onto stack

Example

```
int mult (int mcand, int mlier){  
    int product = 0;  
    while (mlier > 0) {  
        product += mcand;  
        mlier -= 1; } return  
    product;}  

```

```
mult: MOV a3, #0; prod=0
```

```
Loop: CMP a2, #0      ; mlier == 0?  
      BLE Fin        ; if mlier <= 0 goto Fin  
      ADD a3,a3,a1    ; product += mcand  
      ADD a2,a2,#-1   ; mlier -= 1  
      B Loop ; goto Loop
```

```
Fin:  MOV a1,a3 ; setup return value  
      BX lr    ; return
```

Example

❖ Notes:

- ❖ No BL calls are made from `mult` and we don't use any saved registers, so we don't need to save anything onto stack
- ❖ Temp registers are used for intermediate calculations (could have used saved registers, but would have to save the caller's on the stack.)
- ❖ `a2` is modified directly (instead of copying into a temp register) since we are free to change it
- ❖ Result is put into `a1` (`r0`) before returning

Conclusion

- ❖ Functions are called with BL, and return with BX 1r.
- ❖ The stack is your friend: Use it to save anything you need. Just be sure to leave it the way you found it.
- ❖ **Register Conventions:** Each register has a purpose and limits to its usage. Learn these and follow them, even if you're writing all the code yourself.

Conclusion

- ❖ Instructions so far:

- ❖ Previously:

ADD, SUB, MUL, MULA, [U|S]MULL, [U|S]MLAL, RSB
AND, ORR, EOR, BIC
MOV, MVN
LSL, LSR, ASR, ROR
CMP, B{EQ, NE, LT, LE, GT, GE}
LDR, LDR, STR, LDRB, STRB, LDRH, STRH

- ❖ New:

BL, BX

- ❖ Registers we know so far

- ❖ All of them!