

Some
interesting
facts about
static member
functions in
C++

Friend class
and function
in C++

Local Classes
in C++

Nested
Classes in C++

Simulating
final class in
C++

Constructors
in C++

Copy
Constructor in
C++

Destructors in
C++

Does C++
compiler
create default
constructor
when we write
our own?

When should
we write our
own copy

constructor?

When is copy
constructor
called?

Initialization of
data members

Use of explicit
keyword in
C++

When do we
use Initializer
List in C++?

C++ Internals |
Default
Constructors |
Set 1

Private
Destructor

Playing with
Destructors in
C++

→ Copy elision in
C++

C++ default
constructor |
Built-in types

When does
compiler
create default
and copy
constructors
in C++?

Why copy

constructor
argument
should be
const in C++?

time.h header
file in C with
Examples

scanf("%
[^\n]s", str) Vs
gets(str) in C
with Examples

C program to
Insert an
element in an
Array

Types of
Literals in
C/C++ with
Examples

Conditional or
Ternary
Operator (?:) in
C/C++

→ Difference
between C and
C#

time.h
localtime()
function in C
with Examples

asctime() and
asctime_s()
functions in C
with Examples

return
statement in

C/C++ with
Examples



Ad \

From Student to a World-Class Coder

2 Year Program for Full Stack
Women Engineering Students

KNOW MORE



When do we use Initializer List in C++?

Initializer List is used in initializing the data members of a class. The list of members to be initialized is indicated with constructor as a comma-separated list followed by a colon. Following is an example that uses the initializer list to initialize x and y of Point class.








```
#include<iostream>
using namespace std;

class Point {
private:
    int x;
    int y;
public:
    Point(int i = 0, int j = 0):x(i), y(j) {}
    /* The above use of Initializer list is optional as the
       constructor can also be written as:
       Point(int i = 0, int j = 0) {
           x = i;
           y = j;
       }
    */

    int getX() const {return x;}
    int getY() const {return y;}
};

int main() {
    Point t1(10, 15);
    cout<<"x = "<<t1.getX()<<" , ";
    cout<<"y = "<<t1.getY();
    return 0;
}





/* OUTPUT:
   x = 10, y = 15
*/
```

The above code is just an example for syntax of the Initializer list. In the above code, x and y can also be easily initialed inside the constructor. But there are situations where initialization of data members inside constructor doesn't work and Initializer List must be used. Following are such cases:

1) For initialization of non-static const data members:

const data members must be initialized using Initializer List. In the following example, "t" is a const data member of Test class and is initialized using Initializer List. Reason for initializing the const data member in initializer list is because no memory is allocated separately for const data member, it is folded in the symbol table due to which we need to initialize it in the initializer list.

Also, it is a copy constructor and we don't need to call the assignment operator which means we are avoiding one extra operation.

```
#include<iostream>
using namespace std;





class Test {
    const int t;
public:
    Test(int t):t(t) {} //Initializer list must be used
    int getT() { return t; }
};

int main() {
    Test t1(10);
    cout<<t1.getT();
    return 0;
}

/* OUTPUT:
10
*/
```

2) For initialization of reference members:

Reference members must be initialized using Initializer List. In the following example, "t" is a reference member of Test class and is initialized using Initializer List.

```
// Initialization of reference data members
#include<iostream>
using namespace std;





class Test {
    int &t;
public:
    Test(int &t):t(t) {} //Initializer list must be used
    int getT() { return t; }
};

int main() {
    int x = 20;
    Test t1(x);
    cout<<t1.getT()<<endl;
    x = 30;
    cout<<t1.getT()<<endl;
    return 0;
}

/* OUTPUT:
20
30
*/
```

3) For initialization of member objects which do not have default constructor:

In the following example, an object "a" of class "A" is data member of class "B", and "A" doesn't have default constructor. Initializer List must be used to initialize "a".

```
#include <iostream>
using namespace std;

class A {
    int i;
public:
    A(int );
};

A::A(int arg) {
    i = arg;
    cout << "A's Constructor called: Value of i: " << i << endl;
}

// Class B contains object of A
class B {
    A a;
public:
    B(int );
};





B::B(int x):a(x) { //Initializer list must be used
    cout << "B's Constructor called";
}

int main() {
    B obj(10);
    return 0;
}

/* OUTPUT:
    A's Constructor called: Value of i: 10
    B's Constructor called
*/
```

If class A had both default and parameterized constructors, then Initializer List is not must if we want to initialize "a" using default constructor, but it is must to initialize "a" using parameterized constructor.

4) For initialization of base class members : Like point 3, the parameterized constructor of the base class can only be called using Initializer List.



```
#include <iostream>
using namespace std;

class A {
    int i;
public:
    A(int );
};

A::A(int arg) {
    i = arg;
    cout << "A's Constructor called: Value of i: " << i << endl;
}

// Class B is derived from A
class B: A {
public:
    B(int );
};





B::B(int x):A(x) { //Initializer list must be used
    cout << "B's Constructor called";
}

int main() {
    B obj(10);
    return 0;
}
```

5) When constructor's parameter name is same as data member

If constructor's parameter name is same as data member name then the data member must be initialized either using **this pointer** or Initializer List. In the following example, both member name and parameter name for A() is "i".



```
#include <iostream>
using namespace std;





class A {
    int i;
public:
    A(int );
    int getI() const { return i; }
};

A::A(int i):i(i) { } // Either Initializer list or this pointer must
/* The above constructor can also be written as
A::A(int i) {
    this->i = i;
}
*/

int main() {
    A a(10);
    cout<<a.getI();
    return 0;
}
/* OUTPUT:
10
*/
```

6) For Performance reasons:

It is better to initialize all class variables in Initializer List instead of assigning values inside body. Consider the following example:

```
// Without Initializer List
class MyClass {
    Type variable;
public:
    MyClass(Type a) { // Assume that Type is an already
                     // declared class and it has appropriate
                     // constructors and operators
        variable = a;
    }
};
```


Here compiler follows following steps to create an object of type MyClass

1. Type's constructor is called first for "a".
2. The assignment operator of "Type" is called inside body of MyClass() constructor to assign

```
variable = a;
```

3. And then finally destructor of "Type" is called for "a" since it goes out of scope.

Now consider the same code with MyClass() constructor with Initializer List



```
// With Initializer List
class MyClass {
    Type variable;
public:
    MyClass(Type a):variable(a) {    // Assume that Type is an already
                                    // declared class and it has appropriate
                                    // constructors and operators
    }
};
```

With the Initializer List, the following steps are followed by compiler:


1. Copy constructor of "Type" class is called to initialize: variable(a). The arguments in the initializer list are used to copy construct "variable" directly.
2. The destructor of "Type" is called for "a" since it goes out of scope.

As we can see from this example if we use assignment inside constructor body there are three function calls: constructor + destructor + one addition assignment operator call. And if we use Initializer List there are only two function calls: copy constructor + destructor call. See [this](#) post for a running example on this point.

This assignment penalty will be much more in "real" applications where there will be many such variables. Thanks to *ptr* for adding this point.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

Recommended Posts:

- 
- [list::remove\(\) and list::remove_if\(\) in C++ STL](#)
 - [list::empty\(\) and list::size\(\) in C++ STL](#)
 - [list::push_front\(\) and list::push_back\(\) in C++ STL](#)
 - [list::emplace_front\(\) and list::emplace_back\(\) in C++ STL](#)
 - [list::front\(\) and list::back\(\) in C++ STL](#)
 - [list::pop_front\(\) and list::pop_back\(\) in C++ STL](#)
 - [list::begin\(\) and list::end\(\) in C++ STL](#)
 - [list get_allocator in C++ STL](#)
 - [list end\(\) function in C++ STL](#)
 - [list::clear\(\) in C++ STL](#)
 - [Nested list in C++ STL](#)
 - [list::operator= in C++ STL](#)
 - [list insert\(\) in C++ STL](#)
 - [list::swap\(\) in C++ STL](#)

List in C++ | Set 2 (Some Useful Functions)

Improved By : [RajendraStalekar](#)Article Tags : [C](#) [C++](#)Practice Tags : [C](#) [CPP](#)

35

3.4

☐ To-do ☐ DoneBased on **89** vote(s)

Feedback/ Suggest Improvement

Add Notes

Improve Article

Please write to us at contribute@geeksforgeeks.org to report any issue with the above content.Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

Load Comments



GeeksforGeeks
A computer science portal for geeks

5th Floor, A-118,
Sector-136, Noida, Uttar Pradesh - 201305
feedback@geeksforgeeks.org

COMPANY

About Us
Careers
Privacy Policy
Contact Us

LEARN

Algorithms
Data Structures
Languages
CS Subjects
Video Tutorials

PRACTICE

Courses
Company-wise
Topic-wise
How to begin?

CONTRIBUTE

Write an Article
Write Interview Experience
Internships
Videos

@geeksforgeeks, Some rights reserved