

**Order #****9639**

Date: **23/07/2019**
 Attention: **Orders
Filix Lighting**
 Project: **Taronga Western Plains Zoo, African Waterhole & Overlook
Cafe**

Deliver To:

LiTEsource and Controls
Unit 8, 69-73 O'Riordan Street
Alexandria NSW 2015
Australia

Qty	Cat. #	Type	Description	Price	Total
2	NO-620-H-27-GR-2 4-HCL-IO	L1b - 2 x 1900mm	Filix Lighting NO-620-H-27-GR-24-HCL Surface mounted adjustable (IP67) NOOR L620mm GR-Graze (14D x 40D) 2700K 24Vdc 39W/m 304 stainless steel standard cable 1m with 4mm tempered glass lens and honeycomb louver driver not included. IO - in/out cabling	219.00 €	438.00 €
2	NO-1220-H-27-GR- 24-HCL-IO	L1b - 2 x 1900mm	Filix Lighting NO-1220-H-27-GR-24-HCL Surface mounted adjustable (IP67) NOOR L1220mm GR-Graze (14D x 40D) 2700K 24Vdc 39W/m 304 stainless steel standard cable 1m with 4mm tempered glass lens and honeycomb louver driver not included. IO - in/out cabling	242.00 €	484.00 €
2	C9	L1b - 2 x 1900mm	Filix Lighting C9 Leader Cable L = 9000mm, double insulated, rubber flex.	45.00 €	90.00 €
2	SDB-324-H-27-GR- 24-LL-IO	L1a 2 x 2200mm	Filix Lighting SDB-324-H-27-GR-24-LL Step UP Deco in-grade linear line of light with high performance Optics GR-Graze (14D x 40D) L324mm (IP67) 2700K 24Vdc 39W/m standard cable 1m 304 Stainless steel housing with 10mm tempered glass lens for seamless integration into grade and anti glare louver, Installation housing & driver not included. LL = supplied with ETER Glass IO - in/out cabling	134.00 €	268.00 €
2	SDB-624-H-27-GR- 24-LL-IO	L1a 2 x 2200mm	Filix Lighting SDB-624-H-27-GR-24-LL Step UP Deco in-grade linear line of light with high performance Optics GR-Graze (14D x 40D) L624mm (IP67) 2700K 24Vdc 39W/m standard cable 1m 304 Stainless steel housing with 10mm tempered glass lens for seamless integration into grade and anti glare louver, Installation housing & driver not included. LL = supplied with ETER Glass IO - in/out cabling	180.00 €	360.00 €
2	SDB-1224-H-27-GR -24-LL-IO	L1a 2 x 2200mm	Filix Lighting SD-1224-H-27-GR-24-LL Step UP Deco in-grade linear line of light with high performance Optics GR-Graze (14D x 40D) L1224mm (IP67) 2700K 24Vdc 39W/m standard cable 1m 304 Stainless steel housing with 10mm tempered glass lens for seamless integration into grade and anti glare louver, Installation housing & driver not included. LL = supplied with ETER Glass IO - in/out cabling	290.00 €	580.00 €
2	C9	L1a 2 x 2200mm	Filix Lighting C9 Leader Cable L = 9000mm, double insulated, rubber flex.	45.00 €	90.00 €
Total (EUR)				2,310.00 €	