

## Contents

---

- Initialize variables
- Loop through the input
- Draw data samples
- Calculate the estimate of lambda using MLE
- Calculate the estimate of lambda using Posterior
- Update errors in the matrices
- Plot the data!

## Initialize variables

---

```
clear; clc; close all;
rng(1);
N_list = [5, 10, 20, 40, 60, 80, 100, 500, 1000, 10000];
M = 100;

alpha = 5.5;
beta = 1;
true_lambda = 5;

err_MLE = zeros(M,length(N_list));
err_Post = zeros(M,length(N_list));
```

## Loop through the input

---

```
for iter = 1:length(N_list)
    N = N_list(iter);
    for i = 1:M
```

## Draw data samples

---

```
X = -(log(rand(N, 1)) * 0.2);
```

## Calculate the estimate of lambda using MLE

---

For lambda, the MLE is derived in the report

```
ml_estimate = N / sum(X);
```

## Calculate the estimate of lambda using Posterior

---

For a Gamma prior, the posterior mean is derived in the report.

```
posterior_estimate = (alpha + N)/(beta + sum(X));
```

## Update errors in the matrices

---



```
err1 = abs(ml_estimate - true_lambda)/true_lambda;  
err2 = abs(posterior_estimate - true_lambda)/true_lambda;  
err_MLE(i, iter) = err1;  
err_Post(i, iter) = err2;
```


```
    end  
end
```

## Plot the data!

---

```
figure(1);  
boxplot(err_MLE, 'COLOR', 'r', 'Symbol', 'r+');  
hold on;  
boxplot(err_Post, 'COLOR', 'b', 'Symbol', 'b+');  
hold on;  
xlabel('Size of data');  
ylabel('Relative error');  
title('Comparison between relative errors');  
hold off;  
  
figure(2);  
boxplot(err_MLE, 'COLOR', 'r', 'Symbol', 'r+');  
hold on;  
xlabel('Size of data');  
ylabel('Relative error');  
title('Relative errors for MLE');  
hold off;  
  
figure(3);  
boxplot(err_Post, 'COLOR', 'b', 'Symbol', 'b+');  
hold on;  
xlabel('Size of data');  
ylabel('Relative error');  
title('Relative errors for Posterior');  
hold off;
```





---

Published with MATLAB® R2015b