Flight Route Finder

Finding connecting flights between any two airports with Dijkstra's algorithm and A* search


BCA, CHRIST (Deemed to be University), Bengaluru
October 2026

1. The routing problem

Big cities have direct flights to each other. Small airports do not. In my data Mysuru has flights only to Bengaluru, and Shillong only to Kolkata. Somebody going from Mysuru to Shillong has to change planes, and has to **work out where to change**.

Problem: given a starting airport and a destination, find the chain of flights that is best for the passenger. "Best" can mean reaching quickest, taking the fewest flights or flying the shortest distance. If an airport is closed (fog, a cyclone) or the passenger cannot pass through it (no transit visa), the route must go round it.

As a graph: every airport is a **node**, every flight is a **directed edge** with a cost, and I need the cheapest path from one node to another (single-pair shortest path).




Mysuru to Shillong in my prototype: 3 flights, changing at Bengaluru and Kolkata.

2. Inputs and outputs

Input	• From and To airport (type a city, airport name or 3-letter code, or click a dot on the map). • What matters most: quickest, fewest flights or shortest distance. • Hours wanted between two flights (1 to 4), and airports to avoid. • The network: 3,257 airports with latitude and longitude, 37,042 routes.
Output	• The flights to take in order, with km and time of each, and the total. • Where to change planes, and up to 3 other routes to choose from. • The route on a world map and a link to check each flight on Google Flights. • How many airports the search looked at.

Data: OpenFlights open database. I cleaned it with a Python script: removed airports without a code, kept every route once (67,663 rows became 37,042) and corrected 20 Indian city names (Madras to Chennai, Patina to Patna). 225 countries, 71 airports in India. 820 routes have no flight back, so the graph is directed.

3. The prototype



Hubballi to Leh: the answer with 3 other routes on the left, the map on the right.

A web page in HTML and plain JavaScript with Bootstrap and Leaflet. Nothing to install, works on a phone. It draws the world map itself from land outline data, so it works without internet.

- Next to every change of planes there is "avoid this airport". One click and it finds a way round.
- A "How was this found?" box draws the airports that Dijkstra and A* looked at.

Files: index.html, js/app.js (the page), js/routing.js (all the algorithms, 400 lines), tools/build_data.py (cleans the data), tests.html, benchmark.html.

4. The algorithm

The cost of one flight

Every flight costs **a × km + b**, where km is the great circle distance (haversine formula). Only a and b change, so one search function does all three kinds of "best". No cost is negative.

Best means	a	b	The total is in
Shortest distance	1	0	km
Quickest	1/800	0.5 + wait	hours (800 km/h + 0.5 h a flight)
Fewest flights	0.000001	1	flights (km only breaks ties)


Dijkstra's algorithm

1. The start gets cost 0, every other airport infinity. Put the start in a **min-heap**.
2. Take the airport with the smallest cost out of the heap. Its cost is now final ("finished").
3. For every flight out of it: if this way is cheaper than what the next airport has now, write the new cost, note where it came from and put it in the heap.
4. Repeat 2 and 3 until the destination is finished. Walk back through the notes to get the route.


A*: the same thing with a guess

In A* the heap is ordered by **cost so far + a guess of the cost still to go**. My guess is the cost of one direct flight to the destination. No real route can be cheaper than that, so the guess is never too high and the answer stays the best one. Airports in the wrong direction get a big guess and sink in the heap.

Worked example: Mangaluru (IXE) to Guwahati (GAU), real km



Shortest distance: via BLR, HYD, CCU **2,470 km**, 4 flights, 11 h 05 min



Quickest, fewest flights: via BOM, CCU
2,880 km, 3 flights, **9 h 06 min** (2 h waits)

Dijkstra, shortest distance. Best km known after each step (yellow = changed, CCU improves in step 4):

Step	Finished	BLR	BOM	HYD	CCU	GAU
1	IXE (0)	**307**	**715**	-	-	-
2	BLR (307)	307	715	**763**	-	-
3	BOM (715)	307	715	763	**2381**	-
4	HYD (763)	307	715	763	**1971**	-
5	CCU (1971)	307	715	763	1971	**2470**
6	GAU (2470)	destination finished, stop				

A* on the same example. Straight line km to Guwahati: BLR 2039, BOM 2071, HYD 1678, CCU 498. Heap values: BLR 307 + 2039 = 2346, HYD 763 + 1678 = 2441, CCU 1971 + 498 = 2469, GAU 2470, BOM 715 + 2071 = **2786**. Guwahati comes out before Mumbai, so **A* finishes 5 airports and never Mumbai**. Dijkstra finishes all 6.

Pseudocode

```
best[start] = 0, best[all others] = infinity
heap.push(start, guess(start))
while heap is not empty
    u = heap.pop()                  // smallest cost + guess
    if u is finished, skip it       // old copy
    mark u finished
    if u is the destination, stop
    for every flight u -> v, v not finished or closed
        c = best[u] + a * km(u, v) + b
        if c < best[v]
            best[v] = c;  cameFrom[v] = u
            heap.push(v, c + guess(v))
guess(v) = a * straightLineKm(v, destination) + b
          (guess = 0 gives plain Dijkstra)
```


5. Why this algorithm?

I wrote five methods and timed them on the same 100 random trips ("quickest" cost, full network). ms = milliseconds for one search.

Method	Best route?	Time	ms	What I found
Breadth first search	Fewest flights only	O(V + E)	0.14	Does not look at km or hours. Not the quickest in 72 of 100 trips.
Dijkstra without a heap	Yes	O(V²)	13.15	Looks through all airports to find the next one.
Bellman-Ford	Yes	O(V · E)	1.09	Made for negative costs, which I do not have. Cannot stop early.
Floyd-Warshall	Yes, all pairs	O(V³)	not tried	3.5×10^{10} steps and a table of 10.6 million numbers to answer one question.
Dijkstra with a min-heap	Yes	O((V + E) log V)	0.63	21 times faster than without the heap.
A* (chosen)	**Yes**	**same, worst case**	**0.28**	**Same answers. Finishes about 1 airport in 6.**

Why it fits this problem: costs are never negative. I need one start and one destination, not all pairs. The network is sparse (11 routes per airport on average, 0.35% of all possible pairs), so a heap pays off. Every airport has a position, so the straight line guess is free. And the answer must come while the user waits.

Dijkstra: 1,853 airports finished | **A*: 12 airports finished**



Kochi to Toronto, same answer from both (change at Dubai). Dijkstra spreads in every direction, A* goes towards the destination. This trip is a good case, the average is in section 8.

6. Test cases

27 test cases run on the same code that the page uses (tests.html). Some of them:

Test	Expected	Got	
Distance, quarter of the equator	10,007.54 km	10,007.54 km	Pass
Distance London to New York	about 5,540 km	5,539.6 km	Pass
Heap: push 5, 3, 8, 1, 9, 2, 7, 1	1, 1, 2, 3, 5, 7, 8, 9	same	Pass
Example, shortest distance	via BLR, HYD, CCU, 2470 km	same	Pass
Example, quickest (2 h waits)	via BOM, CCU, 9.10 hours	same	Pass
From and To the same airport	0 km, no flight	0 km, 0 flights	Pass
Example, Hyderabad closed	goes round, 2880 km	2880 km	Pass
Example, Kolkata closed	no route (only way in)	no route	Pass
Real: Bengaluru to Delhi	direct, 1710 km, 2 h 38	same	Pass
Real: Mysuru to Shillong	MYQ-BLR-CCU-SHL	same	Pass
A* against Dijkstra, 900 searches	same cost every time	900 of 900	Pass
Fewest flights against BFS	same count	300 of 300	Pass
Every route can really be flown	all valid	876 of 876	Pass
Closing an airport never helps	never quicker	199 of 199	Pass
Slowest of 1800 searches	under 50 ms	about 3 ms	Pass

Result: 27 of 27 test cases passed. In the worked example I know the answers by hand. On the real network the methods are checked against each other.

7. Time and space complexity


Part	Time	Space
Network as adjacency lists	O(V + E) to build	O(V + E)
Dijkstra with a min-heap	O((V + E) log V)	O(V) lists + O(E) heap
A*	**same in the worst case**	**same**
Dijkstra without a heap	O(V²)	O(V)
Bellman-Ford	O(V · E)	O(V)
Breadth first search	O(V + E)	O(V)

V = 3,257 airports, E = 37,042 routes. A V × V table would need 10.6 million cells, the lists need 37,042. The heap can grow to E in the worst case (I push a new copy instead of changing the old one). Measured: biggest heap 1,028 items on average for Dijkstra, 862 for A*.


8. Experimental results

Random pairs of airports that have a route, same pairs for every method. Chrome 154, MacBook Air (M4).

Time for one search when the network grows (log scale)



Airports finished before the answer (1000 trips, longer trips are harder)



Kind of cost	Airports finished			ms for one search	
	Dijkstra	A*	A* / Dijkstra	Dijkstra	A*
Shortest distance	1,643	190	12%	0.70	0.24
Quickest	1,647	284	17%	0.63	0.28
Fewest flights	1,656	443	27%	0.64	0.38

- **The heap matters most.** At 3,257 airports Dijkstra takes 11.8 ms without it and 0.65 ms with it. From 200 to 3,257 airports the first got 98 times slower, the second 8 times.
- **A* finishes 12 to 27% of the airports** Dijkstra does. It helps least for fewest flights, where the guess is almost the same (1 flight) for every airport.
- **But it is only about 2 times faster**, not 6, because every guess needs the distance formula (sin, cos).
- **Bellman-Ford** needed about 6 passes, not 3,256, but looked at 213,010 flights. Dijkstra looked at 12,971.

9. Who can use it, and limits

- People in small towns who need to know where to change (Hubballi to Leh).
- A hub is shut by fog or a cyclone: click "avoid" and see the next best way.
- People who cannot pass through a country without a transit visa.

Different from a booking site: not tied to one airline, lets you rule out airports, shows how the answer was found.

Limits: the routes are from 2014, so some flights do not run now and new ones are missing. No timetable and no ticket price, the wait is the same at every airport. **Next:** real schedules, so that the cost becomes the real arrival time, and price as a fourth kind of cost.

References: E. W. Dijkstra, "A note on two problems in connexion with graphs", Numerische Mathematik, 1959. Hart, Nilsson, Raphael, "A formal basis for the heuristic determination of minimum cost paths", IEEE Trans. SSC, 1968 (A*). Cormen et al., Introduction to Algorithms. OpenFlights (openflights.org/data). Natural Earth. Leaflet.

Prototype: open index.html in a browser | Test cases: tests.html | Experiments: benchmark.html

Land outline: Natural Earth | Airports and routes: OpenFlights