

# Activity Recognition using Text Mining and Object Recognition

Niranjan A. Viladkar  
Under the guidance from

Dr. Subhashis Banerjee and Dr. Parag Singla  
Department of Computer Science  
IIT Delhi

M.Tech Minor Project Presentation – May 13, 2013

# Problem Statement

- What is Video Activity Recognition?

# Problem Statement

- What is Video Activity Recognition?



Dance

# Problem Statement

- What is Video Activity Recognition?



Play

# Approach

*Improving Video Activity Recognition using  
Object Recognition and Text Mining*


by Tanvi Motwani and Raymond J. Mooney,  
ECAI-2012

# Approach – Only Text Mining

- **Extract Labels** - Use Natural Language descriptions of video clips.
- **Extract STIP features** – Represent a clip in HoG and HoF features.
- **Train** a model


# Approach – Only Text Mining

- Natural Language Description of a **video**



# Approach – Only Text Mining

- Natural Language Description of a **video**




- Batsman is **playing** cricket



# Approach – Only Text Mining



- Natural Language Description of a **video**



- Batsman is **playing** cricket
- Mansoor Ali Khan Pataudi is **playing** cricket.

# Approach – Only Text Mining



- Natural Language Description of a **video**



- Batsman is **playing** cricket
- Mansoor Ali Khan Pataudi is **playing** cricket.
- Players are **playing** cricket.

# Approach – Only Text Mining


- **Extracting Verbs** from Description



- Batsman is playing cricket : **PLAY**
- Mansoor Ali Khan Pataudi is playing cricket. : **PLAY**
- Players are playing cricket. : **PLAY**

# Approach – Only Text Mining

- Extracting STIP features



STIP HoG and HoF feature vector :

0.627496	0.0892087	0.0293946	0.253901	0.668772
0.160494	0.000758835	0.169975	0.414533	0.508073 ...

.....

.....


# Approach – Only Text Mining

- Take random samples of STIP feature descriptors
- Clustering K-Means
- Describe a video clip in terms of these clusters

# Activity Recognizer using Video Features



Training Video



STIP features

- A woman is **riding** horse in a beach.
- A woman is **riding** on a horse.
- A woman is **riding** on a horse.

NL description

ride, walk,  
run, move,  
race

Discovered  
Activity Label

Classifier Trained on  
input features as  
STIP features and  
classes as activity  
cluster labels

# Object Detection

- Using Discriminatively Trained Deformable Part Models
  - Pre-trained object detector for 19 objects



# Object Detection





# Object Detection



# Relation between Activity and Objects

- English Gigaword Corpus – 15 GB of raw text
- **Occurrence counts:**
  - of an activity  $A_i$ : occurrence of the verbs
  - of an object  $O_j$ : occurrence of object noun  $O_j$  or its synonym.
- **Co-occurrence of an Activity and an Object:**
  - *POS Tagging*
    - Using Stanford tagger.
    - Occurrence of the object ( tagged as noun ) within a window of  $w$  or fewer words of an occurrence of the activity ( tagged as verb ).

# Relation between Activity and Objects

Probability of each activity given each object

$$P(A_i|O_j) = (\text{Count}(A_i, O_j) + 1) / (\text{Count}(O_j) + |A|)$$

# Integrated Activity Recogniser

- $P(A_i | F_v)$  – Calculated in 1st part.

# Integrated Activity Recogniser

- $P(A_i | F_v)$  – Calculated in 1st part.
- $P(A_i | F_o)$  -

$$P(A_i | F_o) = \sum_{j=1}^{|O|} \underbrace{P(A_i | O_j)}_{\text{Gigaword Corpus}} * \underbrace{P(O_j | F_o)}_{\text{Object Detector}}$$

Gigaword  
Corpus

Object  
Detector

# Integrated Activity Recogniser

- $P(A_i | F_v)$  – Calculated in 1st part.
- $P(A_i | F_o)$  -

$$P(A_i | F_o) = \sum_{j=1}^{|O|} P(A_i | O_j) * P(O_j | F_o)$$

- Consider only  $P(A_i | F_v)$  when no object is detected and  $P(A_i | F_o, F_v)$  when objects are recognized

# Work Done

- **Verbs Extraction** from Natural language description of clips done.

Clip Name	Natural Language Description
_0nX-El-ySo_83_93	A man is cutting a piece of paper.
_0nX-El-ySo_83_93	A man is cutting a paper by scissor.
_0nX-El-ySo_83_93	A man is cutting paper.
_0nX-El-ySo_83_93	A man is cutting a piece of paper.

# Work Done

- **Verbs Extraction** from Natural language description of clips done.

Clip Name	Most frequent verb identified
_0nX-El-ySo_83_93	cut
_1vy2HIN60A_32_40	jump
_6OTzzK7t9Y_158_170	play
_6OTzzK7t9Y_73_78	crash




# Work Done

- **Classes Extraction** from Natural language description of clips done.

Clip Name	Most frequent verb identified
_0nX-El-ySo_83_93	cut, slice
_O9kWD8nuRU_70_76	peel, remove
_JVxurtGIhI_32_42	sing, talk, bark
_WRC7HXBJpU_414_425	pour, stir, put

# Work Done

- **Classes Extraction** from Natural language description of clips done.
- **STIP features extraction** done.



# Work Done

- **Classes Extraction** from Natural language description of clips done.
- **STIP features extraction** done.
- **Clustering** done.

# Work Done

- **Classes Extraction** from Natural language description of clips done.
- **STIP features extraction** done.
- **Clustering** done.

# Work To be Done

- Representation of each clip
- Learning a model

# Work Done

- **Classes Extraction** from Natural language description of clips done.
- **STIP features extraction** done.
- **Clustering** done.

# Work To be Done

- Representation of each clip
- Learning a model
- Object Detection
- Learning Gigaword Corpus

# Novel Idea

- Approach by Motwani et al. is only in forward direction.
- We plan to introduce notion of **feedback**
  - To improve accuracy of weak object detector and activity recogniser

# References

- *Improving Video Activity Recognition using Object Recognition and Text Mining* by Tanvi Motwani and Raymond J. Mooney, [ECAI-2012](#)
- WordNet – 3.0 from Princeton University
- MIT Java Wordnet Interface from MIT
- WordNet Similarity from Sussex university