

Practical 7: Parameterized Cursors

1. *Write a PL/SQL block to display employees of a given Department ID.*

```

DECLARE
    CURSOR emp_cursor (p_dept_id NUMBER) IS
        SELECT Emp_ID, Emp_Name, Salary FROM Employee
        WHERE Department_ID = p_dept_id;
        v_id Employee.Emp_ID%TYPE;
        v_name Employee.Emp_Name%TYPE;
        v_salary Employee.Salary%TYPE;
BEGIN
    OPEN emp_cursor(10);
    LOOP
        FETCH emp_cursor INTO v_id, v_name, v_salary;
        EXIT WHEN emp_cursor%NOTFOUND;
        DBMS_OUTPUT.PUT_LINE( 'ID: ' || v_id || ', Name: ' || v_name || ', Salary: ' ||
            v_salary );
    END LOOP;
    CLOSE emp_cursor;
END;
/

```

OUTPUT :

ID: 101, Name: John, Salary: 60500

ID: 103, Name: Arjun, Salary: 54450

2. *Write a PL/SQL block to list orders for a given Customer ID.*

```

DECLARE
    CURSOR order_cursor (p_customer_id NUMBER) IS
        SELECT Order_ID, Amount
        FROM Orders
        WHERE Customer_ID = p_customer_id;
        v_order_id Orders.Order_ID%TYPE;
        v_amount Orders.Amount%TYPE;
BEGIN
    OPEN order_cursor(1);
    LOOP
        FETCH order_cursor INTO
            v_order_id, v_amount;
        EXIT WHEN order_cursor%NOTFOUND;
        DBMS_OUTPUT.PUT_LINE( 'Order ID: ' || v_order_id || ', Amount: ' || v_amount );
    END LOOP;
    CLOSE order_cursor;
END;

```

/OUTPUT :

Order ID: 1001, Amount: 2500

Order ID: 1003, Amount: 3000

3. Write a PL/SQL block to calculate total marks for a given Student ID.

```
DECLARE
    CURSOR student_cursor (p_student_id NUMBER) IS
        SELECT Student_ID, Name, Marks
        FROM Student
        WHERE Student_ID = p_student_id;
        v_id Student.Student_ID%TYPE;
        v_name Student.Name%TYPE;
        v_marks Student.Marks%TYPE;
        v_total NUMBER := 0;
BEGIN
    OPEN student_cursor(1);
    LOOP
        FETCH student_cursor INTO
            v_id, v_name, v_marks;
        EXIT WHEN student_cursor%NOTFOUND;
        v_total := v_total + v_marks;
        DBMS_OUTPUT.PUT_LINE( 'Student ID: ' || v_id );

        DBMS_OUTPUT.PUT_LINE( 'Name: ' || v_name );

        DBMS_OUTPUT.PUT_LINE( 'Total Marks: ' || v_total);
    END LOOP;
    CLOSE student_cursor;
END;
```

OUTPUT :

Student ID: 1

Name: Amit

Total Marks: 85