

<b>Document Title</b>	Requirements on Module XCP
<b>Document Owner</b>	AUTOSAR
<b>Document Responsibility</b>	AUTOSAR
<b>Document Identification No</b>	429
<b>Document Classification</b>	Auxiliary

<b>Document Version</b>	1.1.0
<b>Document Status</b>	Final
<b>Part of Release</b>	4.0
<b>Revision</b>	3

<b>Document Change History</b>			
<b>Date</b>	<b>Version</b>	<b>Changed by</b>	<b>Change Description</b>
12.12.2011	1.1.0	AUTOSAR Administration	Added support for deactivation of transmission capabilities
30.11.2009	1.0.0	AUTOSAR Administration	Initial Release

**Disclaimer**

This specification and the material contained in it, as released by AUTOSAR, is for the purpose of information only. AUTOSAR and the companies that have contributed to it shall not be liable for any use of the specification.

The material contained in this specification is protected by copyright and other types of Intellectual Property Rights. The commercial exploitation of the material contained in this specification requires a license to such Intellectual Property Rights.

This specification may be utilized or reproduced without any modification, in any form or by any means, for informational purposes only.

For any other purpose, no part of the specification may be utilized or reproduced, in any form or by any means, without permission in writing from the publisher.

The AUTOSAR specifications have been developed for automotive applications only. They have neither been developed, nor tested for non-automotive applications.

The word AUTOSAR and the AUTOSAR logo are registered trademarks.

**Advice for users**

AUTOSAR specifications may contain exemplary items (exemplary reference models, "use cases", and/or references to exemplary technical solutions, devices, processes or software).

Any such exemplary items are contained in the specifications for illustration purposes only, and they themselves are not part of the AUTOSAR Standard. Neither their presence in such specifications, nor any later documentation of AUTOSAR conformance of products actually implementing such exemplary items, imply that intellectual property rights covering such exemplary items are licensed under the same rules as applicable to the AUTOSAR Standard.

## Table of Contents

1	Scope of Document .....	4
2	Conventions to be used .....	5
3	Functional Overview .....	6
4	Requirements Specification .....	8
4.1	Functional Requirements .....	8
4.1.1	General .....	8
4.1.1.1	[BSW429001] Location of XCP within the architecture .....	8
4.1.1.2	[BSW429002] API usage .....	8
4.1.1.3	[BSW429003] Unique PDU-ID .....	8
4.1.1.4	[BSW429004] XCP Specification Version 1.1 .....	9
4.1.1.5	[BSW429005] XCP on CAN .....	9
4.1.1.6	[BSW429006] XCP on FlexRay .....	9
4.1.1.7	[BSW429007] XCP on Ethernet .....	10
4.1.2	Features .....	10
4.1.2.1	[BSW429008] A2L IF_DATA Section Support .....	10
4.1.2.2	[BSW429009] Synchronous data acquisition .....	10
4.1.2.3	[BSW429010] Synchronous data stimulation .....	11
4.1.2.4	[BSW429011] Block communication mode .....	11
4.1.2.5	[BSW429012] Interleaved communication mode .....	11
4.1.2.6	[BSW429013] Dynamic data transfer configuration .....	12
4.1.2.7	[BSW429014] Timestamped Data transfer .....	12
4.1.2.8	[BSW429015] Bypassing .....	12
4.1.2.9	[BSW429016] Seed & Key .....	12
4.1.2.10	[BSW429018] Calibration Data Page Switching .....	13
4.1.2.11	[BSW429019] DAQ configuration storing with power-up data transfer (RESUME mode) .....	13
4.1.2.12	[BSW420020] Suppress TX Capabilities .....	13
4.1.3	Initialisation .....	14
4.1.3.1	[BSW429017] XCP Initialization .....	14
4.1.4	Normal Operation .....	14
4.1.5	Shutdown Operation .....	14
4.1.6	Fault Operation .....	14
5	References .....	15

## 1 Scope of Document

This document defines general rules and formats for requirements specification within AUTOSAR. It shall be used as a basis for each requirements document.

The AUTOSAR Requirements on XCP specifies the XCP feature-set, which shall be supported by the AUTOSAR XCP Software Specification document.

A detailed list can be found on Chapter 4.2 “Functional Requirements”.

## 2 Conventions to be used

- In requirements, the following specific semantics shall be used (based on the Internet Engineering Task Force IETF).

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as:

- **SHALL:** This word means that the definition is an absolute requirement of the specification.
- **SHALL NOT:** This phrase means that the definition is an absolute prohibition of the specification.
- **MUST:** This word means that the definition is an absolute requirement of the specification due to legal issues.
- **MUST NOT:** This phrase means that the definition is an absolute prohibition of the specification due to legal constraints.
- **SHOULD:** This word, or the adjective "RECOMMENDED", mean that there may exist valid reasons in particular circumstances to ignore a particular item, but the full implications must be understood and carefully weighed before choosing a different course.
- **SHOULD NOT:** This phrase, or the phrase "NOT RECOMMENDED" mean that there may exist valid reasons in particular circumstances when the particular behavior is acceptable or even useful, but the full implications should be understood and the case carefully weighed before implementing any behavior described with this label.
- **MAY:** This word, or the adjective „OPTIONAL“, means that an item is truly optional. One vendor may choose to include the item because a particular marketplace requires it or because the vendor feels that it enhances the product while another vendor may omit the same item. An implementation, which does not include a particular option, **MUST** be prepared to interoperate with another implementation, which does include the option, though perhaps with reduced functionality. In the same vein an implementation, which does include a particular option, **MUST** be prepared to interoperate with another implementation, which does not include the option (except, of course, for the feature the option provides.)

### 3 Functional Overview

XCP is an ASAM standard for calibration purpose of an ECU. This protocol provides the following functionality:

**XCP provides the following basic features:**

- Synchronous data acquisition
- Synchronous data stimulation
- Online memory calibration (read / write access)
- Calibration data page initialization and switching
- Flash Programming for ECU development purposes
- Various transportation layers (CAN, Ethernet (TCP/IP, UDP), USB,...)
- Block communication mode
- Interleaved communication mode
- Dynamic data transfer configuration
- Timestamped data transfer
- Synchronization of data transfer
- Priorization of data transfer
- Atomic bit modification
- Bitwise data stimulation

**XCP improves the following features compared to CCP 2.1:**

- compatibility and specification
- efficiency and throughput
- power-up data transfer
- data page freezing
- auto configuration
- flash programming.

**XCP was designed according to the following principles:**

- Minimal Slave resource consumption (RAM, ROM, runtime)
- Efficient communication
- Simple Slave implementation



## 4 Requirements Specification

### 4.1 Functional Requirements

#### 4.1.1 General

##### 4.1.1.1 [BSW429001] Location of XCP within the architecture

<b>ID:</b>	BSW429001
<b>Initiator:</b>	BMW
<b>Date:</b>	21.07.2008
<b>Short Description:</b>	The AUTOSAR XCP module shall be located above the bus interfaces / Socket Adaptor
<b>Type:</b>	new
<b>Importance:</b>	high
<b>Description:</b>	Within the AUTOSAR layered architecture, the AUTOSAR XCP module shall be located above the bus specific interfaces (CAN, FlexRay) and for Ethernet on top of the Socket Adaptor.
<b>Rationale:</b>	Due to performance reason, the AUTOSAR XCP is located as low as possible within the layered architecture.
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Conflicts:</b>	--
<b>Supporting Material:</b>	BSW Layered Software Architecture
<b>Contributes to:</b>	BRF00280

##### 4.1.1.2 [BSW429002] API usage

<b>ID:</b>	BSW429002
<b>Initiator:</b>	BMW
<b>Date:</b>	21.07.2008
<b>Short Description:</b>	The AUTOSAR XCP shall make use of the data transmit- and receive APIs of the Bus Interfaces
<b>Type:</b>	new
<b>Importance:</b>	high
<b>Description:</b>	For sending and transmission of XCP Messages, the corresponding APIs provided by the bus specific interfaces shall be used
<b>Rationale:</b>	Usage of available APIs
<b>Use Case:</b>	Transmit and receive XCP Messages
<b>Dependencies:</b>	FlexRay Interface, CAN Interface, Socket Adaptor
<b>Conflicts:</b>	--
<b>Supporting Material:</b>	SWS FlexRay Interface, SWS CAN Interface, SWS Socket Adaptor
<b>Contributes to:</b>	--

##### 4.1.1.3 [BSW429003] Unique PDU-ID

<b>ID:</b>	BSW429003
<b>Initiator:</b>	BMW
<b>Date:</b>	21.07.2008
<b>Short Description:</b>	The AUTOSAR XCP messages shall be identified by unique PDU-IDs
<b>Type:</b>	new
<b>Importance:</b>	high
<b>Description:</b>	Unique PDU-IDs have to be assigned to the the XCP messages by configuration



<b>Rationale:</b>	PDU-IDs are used by the Bus Interfaces to route the PDUs to the assigned target AUTOSAR modules (PDUR, NM, TP, XCP, CDD)
<b>Use Case:</b>	Routing / Scheduling
<b>Dependencies:</b>	--
<b>Conflicts:</b>	--
<b>Supporting Material:</b>	BSW Layered Software Architecture
<b>Contributes to:</b>	--

#### 4.1.1.4 [BSW429004] XCP Specification Version 1.1

<b>ID:</b>	BSW429004
<b>Initiator:</b>	BMW
<b>Date:</b>	21.07.2008
<b>Short Description:</b>	The XCP Specification Version 1.1 shall be used
<b>Type:</b>	new
<b>Importance:</b>	high
<b>Description:</b>	The XCP Specification Version 1.1 shall be used for implementation
<b>Rationale:</b>	XCP Specification Version 1.1 is the latest Version available for AUTOSAR at this time
<b>Use Case:</b>	Calibration purpose
<b>Dependencies:</b>	--
<b>Conflicts:</b>	--
<b>Supporting Material:</b>	<a href="http://www.asam.net/doc_int/getfile/getfile.php?id=238&amp;memberlogin=">http://www.asam.net/doc_int/getfile/getfile.php?id=238&amp;memberlogin=</a>
<b>Contributes to:</b>	--

#### 4.1.1.5 [BSW429005] XCP on CAN

<b>ID:</b>	BSW429005
<b>Initiator:</b>	BMW
<b>Date:</b>	21.07.2008
<b>Short Description:</b>	Support of the CAN communications bus
<b>Type:</b>	new
<b>Importance:</b>	high
<b>Description:</b>	XCP on CAN shall be supported as described within the ASAM "XCP Transport Layer on CAN" specification
<b>Rationale:</b>	It shall be possible to exchange XCP data using the CAN communications bus
<b>Use Case:</b>	Calibration/Stimulation purpose
<b>Dependencies:</b>	CAN Interface
<b>Conflicts:</b>	--
<b>Supporting Material:</b>	<a href="http://www.asam.net/doc_int/getfile/getfile.php?id=239&amp;memberlogin=">http://www.asam.net/doc_int/getfile/getfile.php?id=239&amp;memberlogin=</a>
<b>Contributes to:</b>	--

#### 4.1.1.6 [BSW429006] XCP on FlexRay

<b>ID:</b>	BSW429006
<b>Initiator:</b>	BMW
<b>Date:</b>	21.07.2008
<b>Short Description:</b>	Support of the FlexRay communications bus
<b>Type:</b>	new
<b>Importance:</b>	high
<b>Description:</b>	XCP on FlexRay shall be supported as described within the ASAM "XCP Transport Layer on FlexRay" specification
<b>Rationale:</b>	It shall be possible to exchange XCP data using the FlexRay communications bus
<b>Use Case:</b>	Calibration/Stimulation purpose
<b>Dependencies:</b>	FlexRay Interface

<b>Conflicts:</b>	--
<b>Supporting Material:</b>	<a href="http://www.asam.net/doc_int/getfile/getfile.php?id=376&amp;memberlogin=">http://www.asam.net/doc_int/getfile/getfile.php?id=376&amp;memberlogin=</a>
<b>Contributes to:</b>	--

#### 4.1.1.7 [BSW429007] XCP on Ethernet

<b>ID:</b>	BSW429007
<b>Initiator:</b>	BMW
<b>Date:</b>	21.07.2008
<b>Short Description:</b>	Support of the Ethernet communications bus
<b>Type:</b>	new
<b>Importance:</b>	high
<b>Description:</b>	XCP on Ethernet shall be supported as described within the ASAM "XCP Transport Layer on Ethernet" specification, using TCP/IP and/or UDP
<b>Rationale:</b>	It shall be possible to exchange XCP data using the Ethernet communications bus
<b>Use Case:</b>	Calibration/Stimulation purpose
<b>Dependencies:</b>	Socket Adaptor
<b>Conflicts:</b>	--
<b>Supporting Material:</b>	<a href="http://www.asam.net/doc_int/getfile/getfile.php?id=240&amp;memberlogin=">http://www.asam.net/doc_int/getfile/getfile.php?id=240&amp;memberlogin=</a>
<b>Contributes to:</b>	--

#### 4.1.2 Features

##### 4.1.2.1 [BSW429008] A2L IF\_DATA Section Support

<b>ID:</b>	BSW429008
<b>Initiator:</b>	ASAM-AUTOSAR joint meeting
<b>Date:</b>	21.07.2008
<b>Short Description:</b>	Support of A2L description files
<b>Type:</b>	new
<b>Importance:</b>	high
<b>Description:</b>	The code generator of the XCP Module shall generate the A2L IF_DATA section, based on the configuration of XCP.
<b>Rationale:</b>	The configuration information of the XCP Slave (AUTOSAR XCP Module) should also be used for the configuration of the XCP Master.
<b>Use Case:</b>	Ensure consistency of XCP Master and XCP Slave configuration.
<b>Dependencies:</b>	--
<b>Conflicts:</b>	--
<b>Supporting Material:</b>	<a href="http://www.asam.net/doc_int/getfile/getfile.php?id=240&amp;memberlogin=">http://www.asam.net/doc_int/getfile/getfile.php?id=240&amp;memberlogin=</a>
<b>Contributes to:</b>	--

##### 4.1.2.2 [BSW429009] Synchronous data acquisition

<b>ID:</b>	BSW429009
<b>Initiator:</b>	BMW
<b>Date:</b>	21.07.2008
<b>Short Description:</b>	Support of the XCP feature "Synchronous data acquisition"
<b>Type:</b>	new
<b>Importance:</b>	high
<b>Description:</b>	The slave has to transfer the contents of the elements defined in each ODT of the DAQ-list to the master.
<b>Rationale:</b>	-
<b>Use Case:</b>	Calibration purpose
<b>Dependencies:</b>	--
<b>Conflicts:</b>	--

<b>Supporting Material:</b>	<a href="http://www.asam.net/doc_int/getfile/getfile.php?id=238&amp;memberlogin=">http://www.asam.net/doc_int/getfile/getfile.php?id=238&amp;memberlogin=</a>
<b>Contributes to:</b>	--

#### 4.1.2.3 [BSW429010] Synchronous data stimulation

<b>ID:</b>	BSW429010
<b>Initiator:</b>	BMW
<b>Date:</b>	21.07.2008
<b>Short Description:</b>	Support of the XCP feature "Synchronous data stimulation"
<b>Type:</b>	new
<b>Importance:</b>	high
<b>Description:</b>	Synchronous Data Stimulation is the inverse mode of Synchronous Data Acquisition. The master has to transfer the contents of the elements defined in each ODT of the DAQ-list to the slave.
<b>Rationale:</b>	-
<b>Use Case:</b>	Stimulation purpose
<b>Dependencies:</b>	--
<b>Conflicts:</b>	--
<b>Supporting Material:</b>	<a href="http://www.asam.net/doc_int/getfile/getfile.php?id=238&amp;memberlogin=">http://www.asam.net/doc_int/getfile/getfile.php?id=238&amp;memberlogin=</a>
<b>Contributes to:</b>	--

#### 4.1.2.4 [BSW429011] Block communication mode

<b>ID:</b>	BSW429011
<b>Initiator:</b>	BMW
<b>Date:</b>	21.07.2008
<b>Short Description:</b>	Support of the XCP feature "Block communication mode"
<b>Type:</b>	new
<b>Importance:</b>	high
<b>Description:</b>	Multiple direct successive packets without acknowledge can be sent / received
<b>Rationale:</b>	Speed up memory uploads and downloads
<b>Use Case:</b>	Stimulation/Calibration purpose
<b>Dependencies:</b>	--
<b>Conflicts:</b>	--
<b>Supporting Material:</b>	<a href="http://www.asam.net/doc_int/getfile/getfile.php?id=238&amp;memberlogin=">http://www.asam.net/doc_int/getfile/getfile.php?id=238&amp;memberlogin=</a>
<b>Contributes to:</b>	--

#### 4.1.2.5 [BSW429012] Interleaved communication mode

<b>ID:</b>	BSW429012
<b>Initiator:</b>	BMW
<b>Date:</b>	21.07.2008
<b>Short Description:</b>	Support of the XCP feature "Interleaved communication mode"
<b>Type:</b>	new
<b>Importance:</b>	high
<b>Description:</b>	The XCP master may already send the next request before having received the response on the previous request.
<b>Rationale:</b>	Speed up data transfer
<b>Use Case:</b>	Stimulation/Calibration purpose
<b>Dependencies:</b>	--
<b>Conflicts:</b>	--
<b>Supporting Material:</b>	<a href="http://www.asam.net/doc_int/getfile/getfile.php?id=238&amp;memberlogin=">http://www.asam.net/doc_int/getfile/getfile.php?id=238&amp;memberlogin=</a>
<b>Contributes to:</b>	--

#### 4.1.2.6 [BSW429013] Dynamic data transfer configuration

<b>ID:</b>	BSW429013
<b>Initiator:</b>	BMW
<b>Date:</b>	21.07.2008
<b>Short Description:</b>	Support of the XCP feature "Dynamic data transfer configuration"
<b>Type:</b>	new
<b>Importance:</b>	high
<b>Description:</b>	It shall be possible to configure the DAQ Lists dynamically
<b>Rationale:</b>	Allow flexibility for selection of different data/signal values to be transmitted
<b>Use Case:</b>	Stimulation/Calibration purpose
<b>Dependencies:</b>	--
<b>Conflicts:</b>	--
<b>Supporting Material:</b>	<a href="http://www.asam.net/doc_int/getfile/getfile.php?id=238&amp;memberlogin=">http://www.asam.net/doc_int/getfile/getfile.php?id=238&amp;memberlogin=</a>
<b>Contributes to:</b>	--

#### 4.1.2.7 [BSW429014] Timestamped Data transfer

<b>ID:</b>	BSW429014
<b>Initiator:</b>	BMW
<b>Date:</b>	21.07.2008
<b>Short Description:</b>	Support of the XCP feature "Timestamped Data transfer"
<b>Type:</b>	new
<b>Importance:</b>	high
<b>Description:</b>	It shall be possible to transmit a timestamp within the XCP packet
<b>Rationale:</b>	Timing information of the XCP packets are important for the XCP master to be able to reorder the received XCP packets if necessary
<b>Use Case:</b>	Reordering received XCP packets
<b>Dependencies:</b>	--
<b>Conflicts:</b>	--
<b>Supporting Material:</b>	<a href="http://www.asam.net/doc_int/getfile/getfile.php?id=238&amp;memberlogin=">http://www.asam.net/doc_int/getfile/getfile.php?id=238&amp;memberlogin=</a>
<b>Contributes to:</b>	--

#### 4.1.2.8 [BSW429015] Bypassing

<b>ID:</b>	BSW429015
<b>Initiator:</b>	BMW
<b>Date:</b>	21.07.2008
<b>Short Description:</b>	Support of the XCP feature "Bypassing"
<b>Type:</b>	new
<b>Importance:</b>	high
<b>Description:</b>	It shall be possible to bypass data by making use of Synchronous Data Acquisition and Synchronous Data Stimulation simultaneously.
<b>Rationale:</b>	Including additional calculation / manipulation of data
<b>Use Case:</b>	Calibration / Stimulation purpose
<b>Dependencies:</b>	Support of Synchronous Data Acquisition and Synchronous Data Stimulation, interaction with AUTOSAR RTE required
<b>Conflicts:</b>	--
<b>Supporting Material:</b>	<a href="http://www.asam.net/doc_int/getfile/getfile.php?id=238&amp;memberlogin=">http://www.asam.net/doc_int/getfile/getfile.php?id=238&amp;memberlogin=</a> SWS RTE
<b>Contributes to:</b>	--

#### 4.1.2.9 [BSW429016] Seed & Key

<b>ID:</b>	BSW429016
<b>Initiator:</b>	BMW
<b>Date:</b>	21.07.2008

<b>Short Description:</b>	Support of the XCP feature "Seed&Key"
<b>Type:</b>	new
<b>Importance:</b>	high
<b>Description:</b>	The feature "Seed&Key" is used for protection handling purpose.
<b>Rationale:</b>	Secure access to the XCP slave's memory
<b>Use Case:</b>	The need for information hiding is different, depending on the project phase
<b>Dependencies:</b>	--
<b>Conflicts:</b>	--
<b>Supporting Material:</b>	<a href="http://www.asam.net/doc_int/getfile/getfile.php?id=238&amp;memberlogin=">http://www.asam.net/doc_int/getfile/getfile.php?id=238&amp;memberlogin=</a>
<b>Contributes to:</b>	--

#### 4.1.2.10 [BSW429018] Calibration Data Page Switching

<b>ID:</b>	BSW429018
<b>Initiator:</b>	BMW
<b>Date:</b>	12.11.2008
<b>Short Description:</b>	Support of the XCP feature "Online Calibration Data Page Switching". If the slave supports the optional commands GET_CAL_PAGE and SET_CAL_PAGE, page switching shall be supported.
<b>Type:</b>	new
<b>Importance:</b>	high
<b>Description:</b>	The master can request the slave to answer the current active PAGE. The XCP slave shall be able to switch to another page if this is requested by the XCP master at any point in time.
<b>Rationale:</b>	
<b>Use Case:</b>	Data Page switching is required for high end ECUs because of the huge amount of different data/variables to be transmitted via XCP
<b>Dependencies:</b>	--
<b>Conflicts:</b>	--
<b>Supporting Material:</b>	<a href="http://www.asam.net/doc_int/getfile/getfile.php?id=238&amp;memberlogin=">http://www.asam.net/doc_int/getfile/getfile.php?id=238&amp;memberlogin=</a>
<b>Contributes to:</b>	--

#### 4.1.2.11 [BSW429019] DAQ configuration storing with power-up data transfer (RESUME mode)

<b>ID:</b>	BSW429019
<b>Initiator:</b>	BOSCH
<b>Date:</b>	24.09.2008
<b>Short Description:</b>	Support of the ASAM XCP RESUME mode
<b>Type:</b>	new
<b>Importance:</b>	high
<b>Description:</b>	The XCP master requests the XCP slave to set the RESUME bit of selected DAQ lists. After power-up, the slave has to restore the DAQ lists and indicate the RESUME mode to the XCP master autonomously.
<b>Rationale:</b>	The purpose of the resume mode is to enable automatic data transfer (DAQ, STIM) directly after the power up of the XCP slave
<b>Use Case:</b>	Calibration data are immediately needed after power-up of an ECU for optimization purpose (e.g. optimization of engine start behaviour).
<b>Dependencies:</b>	--
<b>Conflicts:</b>	--
<b>Supporting Material:</b>	<a href="http://www.asam.net/doc_int/getfile/getfile.php?id=238&amp;memberlogin=">http://www.asam.net/doc_int/getfile/getfile.php?id=238&amp;memberlogin=</a>
<b>Contributes to:</b>	BRF00280

#### 4.1.2.12 [BSW420020] Suppress TX Capabilities

<b>ID:</b>	BSW420020
<b>Initiator:</b>	BOSCH

<b>Date:</b>	26.08.2011
<b>Short Description:</b>	Communication Enabling and Disabling
<b>Type:</b>	new
<b>Importance:</b>	high
<b>Description:</b>	The XCP shall provide a feature to enable and disable communication on specific channel (TX capabilities)
<b>Rationale:</b>	
<b>Use Case:</b>	Allowing only requested channel communication in order to use bandwidth effectively
<b>Dependencies:</b>	--
<b>Conflicts:</b>	--
<b>Supporting Material:</b>	--
<b>Contributes to:</b>	--

### 4.1.3 Initialisation

#### 4.1.3.1 [BSW429017] XCP Initialization

<b>ID:</b>	BSW429017
<b>Initiator:</b>	BMW
<b>Date:</b>	21.07.2008
<b>Short Description:</b>	The AUTOSAR XCP module shall implement an interface for initialization.
<b>Type:</b>	new
<b>Importance:</b>	high
<b>Description:</b>	The AUTOSAR XCP module implements an interface for initialization. This service shall initialize all global variables of the module.
<b>Rationale:</b>	Basic functionality.
<b>Use Case:</b>	Set the AUTOSAR XCP module into a defined state
<b>Dependencies:</b>	--
<b>Conflicts:</b>	--
<b>Supporting Material:</b>	--
<b>Contributes to:</b>	--

### 4.1.4 Normal Operation

The AUTOSAR XCP module shall operate as described within the ASAM XCP Specification Version 1.1. Please refer to [http://www.asam.net/doc\\_int/getfile/getfile.php?id=238&memberlogin=](http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin=)

### 4.1.5 Shutdown Operation

The AUTOSAR XCP module shall operate as described within the ASAM XCP Specification Version 1.1. Please refer to [http://www.asam.net/doc\\_int/getfile/getfile.php?id=238&memberlogin=](http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin=)

### 4.1.6 Fault Operation

The AUTOSAR XCP module shall operate as described within the ASAM XCP Specification Version 1.1. Please refer to [http://www.asam.net/doc\\_int/getfile/getfile.php?id=238&memberlogin=](http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin=)

## 5 References

There are no references for this document.