

MACHINE LEARNING

Q1 to Q11 have only one correct answer. Choose the correct option to answer your question.

1. Movie Recommendation systems are an example of:

- i) Classification
- ii) Clustering
- iii) Regression

Options:

- a) 2 Only
- b) 1 and 2
- c) 1 and 3
- d) 2 and 3

ANS: - (A) 2 Only

2. Sentiment Analysis is an example of:

- i) Regression
- ii) Classification
- iii) Clustering
- iv) Reinforcement

Options:

- a) 1 Only
- b) 1 and 2
- c) 1 and 3
- d) 1, 2 and 4

ANS: - (D) 1, 2 and 4

3. Can decision trees be used for performing clustering?

- a) True
- b) False

ANS: - (A) True

4. Which of the following is the most appropriate strategy for data cleaning before performing clustering analysis, given less than desirable number of data points:

- i) Capping and flooring of variables
- ii) Removal of outliers

Options:

- a) 1 only
- b) 2 only
- c) 1 and 2
- d) None of the above

ANS: - (A) 1 only

5. What is the minimum no. of variables/ features required to perform clustering?

- a) 0
- b) 1
- c) 2
- d) 3

ANS: - (B) 1

MACHINE LEARNING

6. For two runs of K-Mean clustering is it expected to get same clustering results?
- a) Yes
 - b) No

ANS: - (B) No

7. Is it possible that Assignment of observations to clusters does not change between successive iterations in K-Means?
- a) Yes
 - b) No
 - c) Can't say
 - d) None of these

ANS: - (A) Yes

MACHINE LEARNING

8. Which of the following can act as possible termination conditions in K-Means?
- i) For a fixed number of iterations.
 - ii) Assignment of observations to clusters does not change between iterations. Except for cases with a bad local minimum.
 - iii) Centroids do not change between successive iterations.
 - iv) Terminate when RSS falls below a threshold.

Options:

- a) 1, 3 and 4
- b) 1, 2 and 3
- c) 1, 2 and 4
- d) All of the above

ANS: - (D) All of the above

9. Which of the following algorithms is most sensitive to outliers?

- a) K-means clustering algorithm
- b) K-medians clustering algorithm
- c) K-modes clustering algorithm
- d) K-medoids clustering algorithm

ANS: - (A) K-means clustering algorithm

10. How can Clustering (Unsupervised Learning) be used to improve the accuracy of Linear Regression model (Supervised Learning):

- i) Creating different models for different cluster groups.
- ii) Creating an input feature for cluster ids as an ordinal variable.
- iii) Creating an input feature for cluster centroids as a continuous variable.
- iv) Creating an input feature for cluster size as a continuous variable.

Options:

- a) 1 only
- b) 2 only
- c) 3 and 4
- d) All of the above

ANS: - (D) All of the above

11. What could be the possible reason(s) for producing two different dendrograms using agglomerative clustering algorithms for the same dataset?

- a) Proximity function used
- b) of data points used
- c) of variables used
- d) All of the above

ANS: - (D) All of the above

Q12 to Q14 are subjective answers type questions, Answers them in their own words briefly

12. Is K sensitive to outliers?

ANS: - The algorithm aims to minimize the squared Euclidean distances between observation and the centroid of cluster to which it belongs. But sometimes K-means algorithm does not give best

MACHINE LEARNING

result. It is sensitive to outliers. An outlier is a point which is different from the rest of data points.

13. Why is K means better?

ANS: - K means better because It is relatively simple to implement, scales to large data sets. It is guarantees convergence. It can warm start the positions of centroids. It is generalizes to clusters of different shapes and sizes, such as elliptical clusters.

14. Is K means a deterministic algorithm?

ANS: - The basic k-means clustering is based on a non-deterministic algorithm. This means that running the algorithm several times on the same data, could give different results, however to ensure consistent results, FCS Express performs k-means clustering using a deterministic method.
