RAJALAKSHMI ENGINEERING COLLEGE

Nirmal S 251001167-2025-IT

N2

Started on	Friday, 28 August 2026, 3:49 PM
State	Finished
Completed on	Friday, 28 August 2026, 3:58 PM
Time taken	9 mins 29 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main()
{
    int n, i, j, temp;
    long long sum = 0;
    scanf("%d", &n);

    int A[n], B[n];
    for (i = 0; i < n; i++)
    {
        scanf("%d", &A[i]);
    }
    for (i = 0; i < n; i++)
    {
        scanf("%d", &B[i]);
    }
    for (i = 0; i < n - 1; i++)
    {
        for (j = i + 1; j < n; j++)
        {
            if (A[i] > A[j])
            {
                temp = A[i];
                A[i] = A[j];
                A[j] = temp;
            }
        }
    }
    for (i = 0; i < n - 1; i++)
    {
        for (j = i + 1; j < n; j++)
        {
            if (B[i] < B[j])
            {
                temp = B[i];
                B[i] = B[j];
                B[j] = temp;
            }
        }
    }
    for (i = 0; i < n; i++)
    {
        sum = sum + (long long)A[i] * B[i];
    }
    printf("%lld",sum);
    return 0;
}
```

```
49
```

	Input	Expected	Got	
✔	3 1 2 3 4 5 6	28	28	✔
✔	4 7 5 1 2 1 3 4 1	22	22	✔
✔	5 20 10 30 10 40 8 9 4 3 10	590	590	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course