Large-scale peer-to-peer network for mobile platforms: Challenges and Experiences

Nirmit Desai, Wendy Chong, Heather Achilles, Shahrokh Daijavad
IBM T. J. Watson Research Center
Yorktown Heights, NY, USA
{nirmit.desai, wendych, hachilles, shahrokh}@us.ibm.com

Thomas La Porta
Dept. of Computer Science and Engineering
Penn State University
University Park, PA, USA
tlp@cse.psu.edu

Abstract—Peer-to-peer (p2p) networks and Mobile ad hoc networks (MANET) have been widely studied. However, a real-world deployment for the masses has remained elusive. Ever-increasing density of mobile devices, especially in urban areas, has given rise to new applications of p2p communication. However, the modern smartphone platforms have limited support for such communications. Further, the issues of battery life, range, and security remain unaddressed. A key question then is, what kinds of applications can the modern mobile platforms support and what challenges remain? This paper identifies a class of applications and presents a novel p2p architecture called Mesh Network Alerts (MNA) to support them. We describe our experiences in deploying MNA as a real-world peer-to-peer network to millions of users for relaying severe weather information along with the challenges faced, and the approaches for addressing them.

Index Terms—peer-to-peer systems, mobile ad hoc network, delay-tolerant network

I. Introduction

Mobile devices with programmable platforms such as android and iOS have steadily grown over the last decade, surpassing the 2 billion mark [1]. MANETs have been greatly studied given their decentralized nature and potential for new applications [5], [10]. Most of the prior work on p2p networks has focused on valuable analytical and simulation-based study of MANET behavior [6], [7], [11]. Given the outstanding practical challenges of physical nodes, real-world implementations have been limited and have not reached mass scale [4]. However, with the growth of smartphones, large-scale real-world implementations may become feasible. This paper describes a real-world implementation of a p2p delay-tolerant network, called Mesh Network Alerts (MNA), for relaying severe weather information to millions of mobile device users as part of the Weather Channel app[2] on both android and iOS platforms.

Before describing MNA, it is critical to identify applications that need p2p communication, given pervasive Internet connectivity. Doing so enables us to define key characteristics of such applications and focus on the challenges in meeting them. This paper focuses on two separate classes of applications: communication in (a) disaster-affected or remote areas and (b) congested networks in densely populated areas, e.g., sports arenas. The following are the key characteristics in these scenarios:

CH_0. No secondary communication infrastructure such as WiFi access points to fall back on

CH_1. Network nodes are mobile, pattern of mobility is not predictable

CH_2. New information may arrive at any time

CH_3. Trustworthy information is scarce, misinformation and rumours are common place

CH_4. Small payloads suffice in many cases and information stays relevant for a few minutes

CH_5. Device battery is a scarce resource, power supply for recharging may not be available

CH_6. Devices are owned by citizens, deployment of special-purpose devices is cost prohibitive

The above needs are well-recognized in the industry with several ambitious attempts to address them, e.g., Google Loon project[3] and Facebook Aquilla[4], though with limited impact. Leveraging user mobile devices as peer nodes for a large-scale deployment has been another theme in the prior works, e.g., the Serval project [3]. Serval mesh enables p2p communication over on-device WiFi radio, but requires root access to the device via jailbreaking. Although significant leassons have been learned through these attempts, a mass-scale p2p network for such applications remains elusive.

A vast majority of the literature has focused on a traditional model of stateful and reliable networking. Specifically, the nodes maintain connectivity with peers, routing is optimized with techniques based on link state or distance vectors [2], [9] focusing on optimizing the network utilization. Given the application characteristics above, this paper identifies main practical challenges associated with modern device platforms and finds novel ways to overcome them. This leads to MNA — a new paradigm in p2p networking that employs connection-less, delay-tolerant, and zero-routing overhead protocols. MNA is implemented on both Android and iOS as an SDK and integrated with the Weather Channel mobile apps. With extensive experiments and experience of deploying to

---

[1] https://www.statista.com/statistics/330695/number-of-smartphone-users-worldwide/
[2] https://weather.com/apps/ibm/meshnetworkalerts

[3] https://loon.co
[4] https://en.wikipedia.org/wiki/Facebook_Aquila

almost 10 million users, MNA represents a way forward for large-scale p2p networks.

In summary, this paper makes the following key contributions:

- Identification of a class of applications for p2p and their key characteristics
- A deeper investigation of the practical challenges in supporting the above class of applications
- A novel p2p networking SDK using multiple radio channels for modern mobile platforms (Android and iOS)
- Experimental evaluation and deployment statistics

In the following, Section II describes the practical challenges. Section III outlines the architectural details of MNA along with platform-specific implementation issues for Android and iOS in addressing the challenges. Experimental evaluation and deployment statistics are presented in Section IV. A deeper look at the literature and contrast to MNA is summarized in Section V with conclusions in Section VI.

II. Practical Challenges

We present the main challenges for modern mobile device platforms in meeting the classes of applications described above. These have been uncovered via extensive experiments and in some cases include direct feedback from the makers of Android and iOS.

A. Operating system constraints

Due to CH_2, even when a user is not interacting with the weather app, or worse yet, when the device is not being used at all, the devices must discover peer devices to receive and forward potentially life-saving weather information. Although modern mobile operating systems such as Android and iOS offer APIs to discover and advertise information to peer devices over WiFi and Bluetooth interfaces, peer-to-peer connections do not work when the same APIs are accessed while the app is in the background. Prior works, widely document these challenges and take the approach of having special access on the devices, e.g., jail-breaking or rooting [3]. Clearly, such an approach does not scale to mass adoption.

B. Power constraints

Since devices may be offline when new weather information arrives, MNA processes on each peer must remain active at all times to be able to discover new information as soon as it arrives. Further, as there is no back up infrastructure (CH_0) and a set of peers in range can change at any time (CH_1), each peer is responsible for constantly forwarding available information to other peers via advertisements. However, due to CH_5, the MNA activity must keep the device battery consumption to a minimum. This is a challenge because advertising and discovery are power-hungry operations over the radio channels.

C. Testing p2p networks

Given the heterogeneity of devices and operating system distributions owned by users (CH_6), it is challenging to test whether or not MNA functions as expected on a single device. Further, running test scenarios on a p2p network at large-scale is non-trivial given that a large number of devices need to take specific coordinated action followed by coordinated observations to determine whether a test passes or fails. Further, since range and mobility affect p2p communications and they are unpredictable (CH_1), it is important to run test cases under various mobility patterns across all nodes in the network. Emulated mobility frameworks such as CORE [1] and EMANE [8] fall short as the connection latencies and wireless transmission are specific to device model and radio. This is not a challenge in traditional mobile application development as the application functionality is confined within a single connected device.

D. Trust in information

As user devices with MNA advertise on a continuous basis over well-known radio protocols, it may be possible for a malicious attacker to listen for such advertisements and reverse-engineer the message formats and protocols used. Then, the attackers may generate fake messages and advertise them, e.g., a fake tornado alert. Given a lack of trusted information in such scenarios (CH_3), misinformation campaigns can have disastrous consequences. In open decentralized systems, such false messages cannot be distinguished from the real ones, and MNA will end up propagating them to as many devices as possible, "poisoning" the network. In general, veracity of such information cannot be independently verified in open decentralized distributed systems and previous work on peer-to-peer networks do not address this challenge.

III. System Architecture

We overcame these challenges via innovative techniques, without resorting to hacks that may violate user security or Appstore guidelines. With our technique, exchange of information happens without making network connections. As we describe later, this is achieved by splitting the messages into small enough chunks so that they can be stuffed into service advertisements themselves and broadcast over multiple advertisements in a quick succession.

Our approach here is two-pronged. Firstly, via extensive experiments on a large number of devices, we fine-tune the algorithms governing the intervals at which discovery and advertisements occur. In a nutshell, receiving new information during a period causes MNA to be more aggressive in discovery and advertisement. Similarly, lack of new information for a period makes the device less aggressive. Secondly, we allow "wake up" messages to be broadcast in the network ahead of an anticipated severe weather event. When devices receive such messages, they schedule themselves to remain aggressive during the specified window of time. Outside of this window, the device can afford to have long sleep cycles and conserve

power. With these techniques, our testing shows less than 1% battery consumption per hour on most device models.

We developed test automation tools and processes such that multiple devices can be controlled from a single test station and follow prescribed steps to generate, send, and receives messages to play out a test scenario. Finally, the framework allows automated analysis of the observations to determine the test result. This capability was instrumental in uncovering bugs at a fast pace to meet the aggressive timeline and avoid the cost of acquisition. Further, the automation framework is general and can be expressly applied to test other apps in this fashion.

In our approach, since the origin of weather information is the Weather Channel service, digital signatures can be attached to all weather alerts broadcast from the service. The mobile application is distributed with the corresponding public key so that digital signatures from the service can be verified. If a message fails such a verification, it is discarded and not forwarded any further.

IV. Experimental Results

Fig. 1. End-to-end latency



Fig. 2. Duplicity due to flooding

Fig. 3. Average hop count

V. Related Work

VI. Conclusions and Future Work

Acknowledgment

References

[1] J. Ahrenholz, C. Danilov, T. R. Henderson, and J. H. Kim. Core: A real-time network emulator. In *MILCOM 2008 - 2008 IEEE Military Communications Conference*, pages 1–7, Nov 2008.

[2] T. Clausen and P. Jacquet. Optimized link state routing protocol (olsr). *RFC 3626*, October 2003.

[3] P. Gardner-Stephen and S. Palaniswamy. Serval mesh software-wifi multi model management. In *Proceedings of the 1st International Conference on Wireless Technologies for Humanitarian Relief*, ACWR '11, pages 71–77, New York, NY, USA, 2011. ACM.

[4] W. Kiess and M. Mauve. A survey on real-world implementations of mobile ad-hoc networks. *Ad Hoc Networks*, 5(3):324 – 339, 2007.

[5] J. Loo, J. L. Mauri, and J. H. Ortiz. *Mobile Ad Hoc Networks: Current Status and Future Trends*. CRC Press, Inc., Boca Raton, FL, USA, 1st edition, 2011.

[6] S. Marti, T. J. Giuli, K. Lai, and M. Baker. Mitigating routing misbehavior in mobile ad hoc networks. In *Proceedings of the 6th Annual International Conference on Mobile Computing and Networking*, MobiCom '00, pages 255–265, New York, NY, USA, 2000. ACM.

[7] M. Mauve, J. Widmer, and H. Hartenstein. A survey on position-based routing in mobile ad hoc networks. *IEEE Network*, 15(6):30–39, Nov 2001.

[8] Naval Research Laboratory. Extendable mobile ad-hoc network emulator (emane). Available at http://cs.itd.nrl.navy.mil/work/emane/.

[9] C. Perkins, E. Belding-Royer, and S. Das. Ad hoc on-demand distance vector (aodv) routing. *RFC 3561*, July 2003.

[10] C. E. Perkins. In *Ad Hoc Networking*, chapter Ad Hoc Networking: An Introduction, pages 1–28. Addison-Wesley Longman Publishing Co., Inc., Boston, MA, USA, 2001.

[11] X. M. Zhang, Y. Zhang, F. Yan, and A. V. Vasilakos. Interference-based topology control algorithm for delay-constrained mobile ad hoc networks. *IEEE Transactions on Mobile Computing*, 14(4):742–754, April 2015.