

Technical Specification and Validation Report: MVP Pile Load Testing Report Generator (IS 2911 Part 4 Compliance)

1. Architectural Overview and Domain Context

1.1 Introduction to the Digital Transformation of Geotechnical Reporting

The construction and infrastructure sector in India stands at a critical juncture where the scale of development necessitates a rigorous adherence to safety standards and engineering precision. Foundation testing, specifically the Pile Load Test (PLT), serves as the definitive method for validating the structural integrity and load-bearing capacity of deep foundations. Historically, the documentation and reporting of these tests have been plagued by manual inconsistencies, calculation errors, and a lack of standardized formatting, often leading to delays in project approvals and potential safety risks. This report specifies the functional and technical requirements for a Minimum Viable Product (MVP) Pile Load Testing Report Generator, designed exclusively for the Indian market. The system is engineered to enforce strict compliance with the **Bureau of Indian Standards (BIS) code IS 2911 (Part 4): 2013** (Reaffirmed 2018), ensuring that every report generated carries the weight of engineering authority and legal validity.

The operational constraint for this MVP is the absence of Optical Character Recognition (OCR) technology. This design choice is not merely a technical limitation but a strategic decision to prioritize data integrity. By requiring engineers to manually enter field data into a structured digital environment, the system incorporates a layer of human verification that automated OCR processes often lack when dealing with handwritten field logs. The focus, therefore, shifts from image processing to robust data validation, algorithmic precision, and the automated generation of compliance-ready documentation. The system must seamlessly handle the three primary modes of testing—Vertical (Compression), Lateral, and Uplift (Pull-out)—while distinguishing between Initial (Preliminary) and Routine (Working) tests, as each category demands distinct safety factors and acceptance criteria under IS 2911.

1.2 The Imperative of IS 2911 (Part 4) Compliance

The Indian Standard IS 2911 (Part 4) provides the overarching methodology for determining the safe load capacity of piles. It is not merely a guideline but a mandatory code of practice that dictates loading sequences, measurement intervals, and, most critically, the mathematical definitions of failure and safety. Any software solution aiming to serve this domain must treat the clauses of IS 2911 not as flexible parameters but as immutable logic

gates. For instance, the distinction between a safe load based on a 12 mm settlement versus one based on 2% of the pile diameter is a calculated engineering decision defined by the code. Automating this decision-making process requires a deep programmatic understanding of the standard's nuances, ensuring that the software acts as a rigid compliance officer rather than a simple text editor.

The proposed system addresses the specific pain points identified in the analysis of current manual workflows. Engineers currently grapple with complex interpolations to find loads at specific settlements (e.g., 12 mm or 18 mm), a process prone to human error when performed on non-standardized spreadsheets. Furthermore, the formatting of reports often varies between testing agencies, creating friction during regulatory audits. By standardizing the output to match the provided sample reports (IVPLT, RVPLT, Lateral, Uplift), the system ensures interoperability and immediate acceptance by clients, consultants, and government bodies.¹ The architecture proposed herein is modular, allowing for the distinct logic paths required for Vertical Compression, Lateral Deflection, and Uplift Tension tests to coexist within a unified user interface.

1.3 Scope of the MVP

The scope of this MVP is tightly defined to deliver maximum value with high reliability. It encompasses the end-to-end workflow from project definition to final PDF generation. The system handles the calculation of test loads based on design parameters, verifies the sufficiency of reaction systems (jack capacity), records time-stamped settlement readings, and executes the complex "Least of" logic required to determine safe loads. It covers Initial Vertical Pile Load Tests (IVPLT) and Routine Vertical Pile Load Tests (RVPLT), recognizing the divergent safety factors (2.5x vs. 1.5x) and settlement limits (12 mm vs. 18 mm) associated with each. Similarly, it integrates the logic for Lateral Load Tests, focusing on the 5 mm deflection limit, and Uplift Tests, dealing with the identification of yield points and 12 mm upward movement limits. The exclusion of OCR mandates a user experience (UX) design that facilitates rapid, error-checked data entry, effectively mimicking the tabular nature of field logbooks while enforcing real-time logical constraints.¹

2. Comprehensive Regulatory Analysis: IS 2911 (Part 4) Logic

The foundation of the Report Generator is the algorithmic implementation of IS 2911 (Part 4): 2013. This section deconstructs the standard into programmable logic blocks, identifying the inputs, constants, and decision trees required for each test type.

2.1 Vertical Load Tests (Compression)

Vertical compression tests are the most common form of pile testing and are subdivided into

Initial and Routine categories. The software must enforce this distinction at the project setup level, as it dictates the entire downstream validation logic.

2.1.1 Initial Vertical Pile Load Test (IVPLT)

The Initial test is conducted on a test pile to determine the ultimate load capacity and verify the design assumptions. The IS 2911 standard imposes a rigorous testing regime for these piles.

Test Load Determination:

The system must enforce that the Test Load is at least 2.5 times the Estimated Safe Load (Design Load). During the "Scope of Work" input phase, the software will validate the user-entered Test Load against the Design Load. If the ratio is less than 2.5, the system will trigger a critical warning, requiring a specific override justification, as this constitutes a deviation from Clause 5.1.2 of IS 2911.1

Acceptance Criteria and Safe Load Calculation (Clause 7.1.5):

The determination of the Safe Vertical Load is a multi-step calculation. The software must compute two distinct values and select the lower of the two as the final Safe Load.

1. **Settlement Criterion:** The system must identify the load corresponding to a total settlement of **12 mm**. The safe load is defined as two-thirds ($\frac{2}{3}$) of this load. This requires the software to perform linear interpolation between the recorded load-settlement data points to find the exact load at 12 mm settlement.
2. **Ultimate Capacity Criterion:** The system must calculate the load corresponding to a total settlement of **10% of the pile diameter** (ϕ). For a standard 600 mm pile, this threshold is 60 mm. The safe load is defined as 50% (0.5ϕ) of this ultimate load.
 - o *Logic Check:* If the test was terminated before reaching 10% diameter settlement (which is common), the software must extrapolate or note that this criterion was not the governing factor, defaulting to the 12 mm criterion or the maximum applied load logic.¹

Report Narrative Generation:

The system must automatically generate the conclusion text based on these calculations. For example, if the safe load calculated is greater than the design load, the report will state: "The test pile has shown greater load-carrying capacity than the design load of T. Therefore, T is adopted as the safe vertical load for the working piles."¹

2.1.2 Routine Vertical Pile Load Test (RVPLT)

The Routine test is performed on a working pile to ensure it can support the design load without excessive settlement. The logic here is simpler but strictly bounded by settlement limits.

Test Load Determination:

The system must default the Test Load to 1.5 times the Working Load (Design Load). This is a critical validation step for Routine tests under Clause 5.2 of IS 2911. Any deviation (e.g., testing

to only 1.0x or 1.25x) must be flagged.¹

Acceptance Criteria (Clause 7.1.5.1):

The definition of "safe" varies based on pile size. The software must implement a conditional logic branch based on the Pile Diameter (D) input:

- **Case A ($D \leq 600$ mm):** The maximum settlement at the full test load ($1.5 \times$ Design Load) must not exceed **12 mm**.
- **Case B ($D > 600$ mm):** The maximum settlement must not exceed **18 mm OR 2% of the pile diameter**, whichever is **less**. For example, for a 1200 mm diameter pile, 2% is 24 mm. Since 18 mm is less than 24 mm, the 18 mm limit governs. The software must dynamically calculate this comparison for every test.¹

Result Interpretation:

The system must compare the Net Settlement (Total Settlement minus Rebound) against these limits. If the observed settlement is within limits, the report generates a "Satisfactory" conclusion. If it exceeds the limits, the report must generate a "Failure" or "Non-Compliant" warning, highlighting exactly which threshold was breached.¹

2.2 Lateral Load Tests

Lateral tests assess the pile's horizontal deflection. The reporting requirements for these tests are distinct because the failure mode is typically governed by serviceability (deflection limits) rather than structural rupture.

Test Load Logic:

- **Initial Test:** Typically conducted to **2.5 times** the design lateral load.
- **Routine Test:** Conducted to **1.0 times** the Working Load (Design Lateral Load). Note that while vertical routine tests are 1.5x, IS 2911 Clause 8.4.1 explicitly states routine lateral tests check deflection at the *working load*. However, some project specifications may request 1.5x. The software should default to 1.0x but allow an override with an audit note.¹

Safe Load Calculation (Clause 8.4):

The software must calculate the safe lateral load as the least of the following:

1. 50% of the final load at which the total displacement is **12 mm**.
2. The final load at which the total displacement corresponds to **5 mm**.
3. The load corresponding to any other project-specific displacement limit (e.g., 10 mm) entered by the user.

Operational Requirement:

The standard dictates that load increments should be maintained until the rate of displacement is less than 0.1 mm per 30 minutes. The software's data entry grid should ideally allow users to input the start and end time of each increment to verify this hold duration.¹

2.3 Uplift (Pull-out) Tests

Uplift tests evaluate the pile's resistance to tension. The logic here mirrors the vertical

compression test but with different failure mechanisms (skin friction/anchorage failure).

Test Load:

For Initial tests, the load is 2.5 times the estimated safe uplift load.

Safe Load Calculation (Clause 9.4):

The software must compute the safe load based on two primary criteria:

1. **Displacement Limit:** Two-thirds ($\frac{2}{3}$) of the load at which the total displacement (uplift) is **12 mm**. Alternatively, some amendments suggest using the load at 12 mm uplift or 2% of the diameter. The MVP will standardize on the 12 mm limit as per the provided sample reports.¹
2. **Yield Point:** Half ($\frac{1}{2}$) of the load at which the load-displacement curve shows a clear break (yield point).
 - *Implementation Note:* Detecting a "clear break" programmatically is complex without advanced ML. For this MVP, the software will plot the Load-Uplift curve and require the engineer to **manually identify** the yield load if it occurs. The system will then use this user-provided value to calculate the safety factor. If no yield is observed (the curve is linear), the displacement criterion governs.¹

Summary of Safety Factors and Limits

Test Type	Category	Test Load Factor	Governing Limit (Acceptance)	Reference Clause
Vertical	Initial	$2.5 \times \text{Design}$	Min($\frac{2}{3}$ Load @ 12mm, $0.5 \times$ Load @ 10% Dia)	7.1.5
Vertical	Routine	$1.5 \times \text{Design}$	Max Settlement $\leq 12\text{mm}$ (Dia ≤ 600) OR $\leq 18\text{mm}$ (Dia > 600)	7.1.5.1
Lateral	Initial	$2.5 \times \text{Design}$	Min($0.5 \times$ Load @ 12mm, Load @ 5mm)	8.4
Lateral	Routine	$1.0 \times \text{Design}$	Max Deflection	8.4.1

		Design	≤ 5mm	
Uplift	Initial	2.5 × Design	Min(2/3 Load @ 12mm, 0.5 Load @ Yield)	9.4

3. Computational Logic and Algorithms

The core value of the Report Generator lies in its ability to transform raw pressure and dial gauge readings into precise engineering conclusions. This section details the mathematical models and algorithms required.

3.1 Load Calculation from Hydraulic Pressure

Field data is typically recorded as hydraulic pressure (kg/cm²) and dial gauge readings (mm). The software must convert this pressure into an applied load (Metric Tonnes - MT) using the specific hydraulic jack's calibration data.

Formula:

$$\text{Applied Load (MT)} = \frac{\text{Pressure (kg/cm}^2\text{)} \times \text{Ram Area (cm}^2\text{)}}{1000}$$

The system must store the **Ram Area** as a precise floating-point number (e.g., 2551.0 cm²). The conversion factor of 1000 (kg to Tonnes) is standard. The software must allow for multiple jacks (parallel connection), in which case the effective Ram Area is the sum of all individual ram areas.

Validation: The calculated load must be compared against the target test load. If the pressure reading suggests a load significantly deviating from the planned increment (e.g., > 5% variance), the system should flag this entry for review, as holding exact pressure in the field is difficult and slight variances are expected but large errors indicate equipment fault.¹

3.2 Settlement Averaging and Net Settlement

Most tests use 2 to 4 dial gauges. The system must compute the arithmetic mean of these gauges for every reading interval.

Average Settlement (S_{avg}):

$$S_{\text{avg}} = \frac{\sum_{i=1}^n DG_i}{n}$$

Where DG_i is the reading of the i -th dial gauge and n is the number of active gauges.

Handling Faulty Sensors: The UI must allow users to "disable" a specific gauge for a specific reading row if it malfunctioned (e.g., stuck dial), re-calculating the average based on the remaining $n-1$ gauges.

Net Settlement (S_{net}):

Crucial for determining elastic rebound.

$$S_{\text{net}} = S_{\text{max}} - S_{\text{rebound}}$$

Where S_{max} is the settlement at the maximum applied load, and S_{rebound} (or recovery) is the movement recorded after the load is fully released to zero. The software must automatically identify the row with Max Load and the final row (Zero Load) to perform this subtraction.

3.3 Interpolation Algorithms for Safe Load Determination

To find the load corresponding to exactly 12 mm or 5 mm settlement, the software cannot rely on the discrete data points entered, as the pile rarely settles exactly 12.00 mm at a recorded interval. Linear interpolation between the two nearest data points is the standard engineering approach.

Algorithm:

1. Identify the two data points (L_1, S_1) and (L_2, S_2) such that $S_1 < 12 \text{ mm} < S_2$.
2. Apply Linear Interpolation:

$$L_{12} = L_1 + (L_2 - L_1) \times \frac{(12 - S_1)}{(S_2 - S_1)}$$

3. This calculated L_{12} is then used in the safety factor equations (e.g., $\text{Safe Load} = \frac{2}{3} \times L_{12}$).

This logic applies to all "Load at X displacement" criteria, including the 5 mm lateral limit and 10% diameter vertical limit.

3.4 Data Integrity Checks

- **Monotonicity:** During the loading phase, settlement should generally increase. If a subsequent reading shows a decrease in settlement while load is constant or increasing, the system must trigger a "Potential Data Entry Error" warning.
- **Rebound Logic:** During unloading, settlement must decrease. Any increase is physically impossible (unless dealing with swelling soils, which is rare/specialized) and should be flagged.

- **Gauge Consistency:** If one gauge reads 5 mm and another reads 15 mm, the pile is tilting severely or a gauge is broken. The system should flag readings where the standard deviation between gauges exceeds a set threshold (e.g., 20% of the mean).
-

4. User Experience (UX) and Data Acquisition

The "No OCR" constraint demands a highly efficient, grid-based manual entry interface. The UX design must minimize keystrokes and maximize data entry speed while preventing transcription errors.

4.1 The Data Entry Grid

The central component of the application is the "Readings Grid," designed to function like a spreadsheet (e.g., Excel or Google Sheets).

Grid Columns:

- **Stage:** Dropdown (Loading, Hold, Unloading).
- **Target Load (%):** Auto-populated based on the test plan (e.g., 0, 20, 40,... 100,... 0).
- **Time (HH:MM):** User input.
- **Pressure (\$kg/cm²):** User input. *Crucial:* Upon entry, the "Load (MT)" column auto-calculates immediately.
- **Load (MT):** Read-only, calculated field.
- **DG1 (mm), DG2 (mm), DG3 (mm), DG4 (mm):** User inputs.
- **Average (mm):** Read-only, auto-updated.

Productivity Features:

- **Batch Fill Time:** An option to "Fill Intervals" (e.g., every 15 mins) to pre-populate the Time column.
- **Tab Navigation:** Users must be able to navigate cells using the Tab key, facilitating rapid 10-key data entry.
- **Live Graphing:** A "mini-chart" sidebar that plots Load vs. Settlement in real-time as data is entered. This is the single most effective validation tool; if a user types "50" instead of "5.0", the spike in the graph will be immediately visible, prompting instant correction.¹

4.2 Project Setup Wizard

To ensure the correct IS 2911 logic is applied, the "Scope of Work" entry must be a guided wizard rather than a simple form.

Step 1: Project Metadata: Client, Contractor, Site Name.

Step 2: Pile Details:

- Pile ID.

- **Diameter (mm):** This is a "logic driver." Entering 600 vs 1200 changes the RVPLT acceptance criteria.
- Design Load (MT): This sets the baseline for Test Load validation.
Step 3: Test Selection:
- Select Type: Vertical / Lateral / Uplift.
- Select Category: Initial / Routine.
- *Validation:* The system calculates the Required Test Load (e.g., $\$2.5 \times \text{Design}$). The user enters the Actual Planned Test Load. If Actual < Required, a warning blocks progress unless an "Engineering Override" with a justification note is provided.

4.3 Calibration Management

The system must maintain a database of hydraulic jacks and gauges. Users should be able to select "Jack J-01" from a dropdown, and the system automatically pulls the Ram Area (e.g., 706.9 cm²) and calibration expiry date. If the test date is after the calibration expiry, the system appends a warning note to the final report.¹

5. Report Generation and Output Logic

The final deliverable is a PDF report that is indistinguishable from a manually typed report by a premier consultant. The generation logic involves dynamic text synthesis and precise layout control.

5.1 Dynamic Narrative Generation

Instead of static templates, the system uses logic-driven text assembly for the "Results" and "Conclusion" sections.

Logic for Conclusion (RVPLT):

- *Input:* Calculated Net Settlement ($\$S_{\text{net}}\$$), Calculated Limit ($\$L_{\text{limit}}\$$).
- *Condition:* IF $\$S_{\text{net}} \leq L_{\text{limit}}\$$:
 - *Output Text:* "Based on the field observations, the maximum settlement at the test load was [Max] mm with a net settlement of [Net] mm. This is within the permissible limit of [Limit] mm as per IS 2911 (Part 4). Therefore, the pile is deemed satisfactory for the design load of MT."
- *Condition:* IF $\$S_{\text{net}} > L_{\text{limit}}\$$:
 - *Output Text:* "The pile observed a net settlement of [Net] mm, which exceeds the permissible limit of [Limit] mm. The pile does not meet the criteria for the specified design load."

Logic for Conclusion (IVPLT):

- *Input:* Safe Load derived from 12mm criterion ($\$P_{12}\$$), Safe Load derived from Ultimate

criterion (P_{ult}), Design Load (P_{design}).

- **Output Text:** "The safe load capacity is calculated as MT, based on the lesser of the settlement criterion (P_{12} MT) and the ultimate capacity criterion (P_{ult} MT). Since the calculated safe capacity is greater than the design load of P_{design} MT, the design is validated."

5.2 Visual Data Presentation (Graphs)

The report must include high-resolution charts generated from the data grid.

- **Load vs. Settlement Curve:**
 - X-Axis: Settlement (mm) (inverted for vertical tests to mimic physical settlement).
 - Y-Axis: Load (MT).
 - **Annotations:** The graph must automatically draw a **Green Line** at the Design Load and a **Red Dashed Line** at the Safe/Test Load. For Routine tests, a line indicating the 12 mm or 18 mm limit is mandatory for visual compliance verification.
- **Time vs. Settlement Curve:** (Optional but recommended for Initial tests to show creep behavior).

5.3 PDF Structure and Formatting

The PDF generator (e.g., utilizing Puppeteer or WeasyPrint) must strictly follow the layout of the sample reports:

- **Header:** Logos of Client, Consultant, and Contractor on every page.
- **Footer:** Page numbers and document control IDs.
- **Tables:** High-contrast borders, alternating row shading for readability.
- **Sections:** 1.0 General, 2.0 Scope, 3.0 Methodology, 4.0 Results, 5.0 Data & Graphs. This mapping ensures that the digital output fits seamlessly into existing physical archives.¹

6. System Architecture and Implementation Strategy

To deliver this solution as a robust, scalable web application, a modern tech stack is required.

6.1 Technology Stack

- **Frontend: React.js.** The complexity of the "Readings Grid" (editable cells, real-time calculation, keyboard navigation) demands a reactive framework. Libraries like Ag-Grid or Handsontable can provide Excel-like performance.
- **Backend: Node.js or Python (FastAPI/Django).** Python is preferable for the heavy mathematical interpolations and scientific plotting (using Matplotlib or Plotly for server-side graph generation), while Node.js offers excellent JSON handling and PDF generation libraries.
- **Database: PostgreSQL.** The relational nature of Projects -> Piles -> Readings fits perfectly with SQL. Storing readings as JSONB within a relational table offers flexibility

for varying numbers of dial gauges.

- **PDF Engine: Puppeteer** (headless Chrome). This allows the report to be designed using standard HTML/CSS and then "printed" to PDF, ensuring pixel-perfect control over page breaks and layout, which is notoriously difficult with standard PDF libraries.

6.2 Data Schema (Relational Model)

Table: Projects

- id (UUID), name, client_name, contractor_name, site_location, created_at.

Table: Test_Piles

- id (UUID), project_id (FK), pile_id (String), test_type (Enum: IVPLT, RVPLT, Lateral, Uplift), diameter_mm (Float), depth_m (Float), design_load_mt (Float), test_load_mt (Float), concrete_grade (String).

Table: Readings

- id (UUID), pile_id (FK), cycle_type (Enum: Load, Unload), step_number (Int), time_stamp (Time), pressure_bar (Float), load_mt (Float), dial_1 (Float), dial_2 (Float), dial_3 (Float), dial_4 (Float), avg_settlement (Float).

Table: Calibration_Data

- id (UUID), pile_id (FK), jack_ram_area (Float), pressure_gauge_id (String), calibration_date (Date).

6.3 Security and Audit

Given the legal nature of these reports, **Data Immutability** is a key feature. Once a report is "Finalized" and generated, the underlying data should be locked. Any subsequent changes must create a new version of the report, preserving the audit trail. This prevents post-test manipulation of data to "pass" failing piles.

7. Development Roadmap (User Stories)

Phase 1: Core Logic & Input (Weeks 1-4)

- **Story 1.1:** As an engineer, I can define a project and pile parameters so that the system knows which IS 2911 limits to apply (e.g., 600mm diameter check).
- **Story 1.2:** I can enter jack calibration details (Ram Area) so that pressure inputs automatically convert to Load (MT).
- **Story 1.3:** I can enter readings into a grid where Average Settlement is calculated instantly.

Phase 2: Validation & Calculation Engine (Weeks 5-6)

- **Story 2.1:** The system interpolates the load-settlement curve to find the exact load at 12 mm settlement for IVPLT.
- **Story 2.2:** The system flags any routine test where settlement exceeds the IS 2911 limits (12mm/18mm).
- **Story 2.3:** The system calculates Net Settlement by subtracting the final rebound reading from the max load reading.

Phase 3: Reporting & Output (Weeks 7-8)

- **Story 3.1:** I can generate a PDF that includes the Load-Settlement graph with limit lines drawn automatically.
- **Story 3.2:** The "Conclusion" text is auto-generated based on the Pass/Fail logic, referencing specific observed values.

Phase 4: Lateral & Uplift Logic (Weeks 9-10)

- **Story 4.1:** For Lateral tests, the system checks the 5 mm deflection limit.
- **Story 4.2:** For Uplift tests, I can visually identify a "yield point" on a graph if present, or let the system default to the 12 mm uplift limit.

8. Conclusion

This specification outlines a robust, compliance-driven software solution for generating Pile Load Test reports. By anchoring every feature in the clauses of **IS 2911 (Part 4)**, the system transcends simple data entry to become an active participant in the quality assurance process. It eliminates the ambiguity of manual interpretation, ensures rigorous adherence to safety factors (2.5x/1.5x), and standardizes the reporting format across the industry. The constraint of manual data entry is leveraged here as a strength, ensuring that engineering oversight remains central to the process while the software handles the computational heavy lifting and regulatory validation. Implementation of this specification will result in a tool that significantly reduces reporting time, eliminates calculation errors, and provides a legally defensible record of foundation testing.

Works cited

1. Developer Guidelines for Automated Pile Load Test Report Generation.pdf
2. QUALITY POP UP, accessed December 11, 2025, <https://ehsapi.mclindia.com/Attachments/mclindia/NewsMaster/4fcfc3da-861b-45d7-9f89-a95d8f5451f6.pdf>
3. IS 2911-4 (1985): Code of practice for design and construction of pile foundations, Part 4, accessed December 11, 2025, <https://archive.org/download/gov.in.is.2911.4.1985/is.2911.4.1985.pdf>