

ExecutiveLink

Phase 1 Project Plan — CEO / Managing Director and Prime Assistant

Prepared: 5 October 2026 | Status: Proposed build-ready plan

PHASE 1: One CEO/MD + one Prime Assistant

PHASE 2: Scalable organizational expansion

1. Executive summary

ExecutiveLink is a mobile-first communication and coordination app designed to reduce delays and missed updates between a CEO/Managing Director (CEO/MD) and their designated Prime Assistant. Phase 1 delivers a focused MVP for one executive and one Prime Assistant. The data model and authorization approach should support later expansion to additional assistants, department heads, staff reporting lines and multiple executives.

Phase 1 focuses on two-way communication, shared appointment coordination, actionable notifications, acknowledgement tracking, basic approvals, follow-ups and a daily briefing. Phase 2 features remain out of the initial interface until the first release is stable.

2. Goals and success measures

- Reduce missed or delayed messages and meeting changes.
- Show sent, provider-accepted where measurable, read, acknowledged and actioned states separately.
- Synchronize the CEO agenda and Prime Assistant view.
- Preserve messages, meetings and decisions across server restarts and device changes.
- Protect executive information through authentication, least-privilege access and audit records.
- Validate with one CEO/MD and one Prime Assistant before expansion.

Measure	Proposed acceptance target
Online synchronization	95th percentile under 3 seconds in agreed test conditions.
Notification processing	99% of eligible jobs accepted by the push provider within 60 seconds under normal conditions; this is not proof of human receipt.
Meeting changes	Every authorized change is persisted and creates a traceable notification event.
Persistence	Records survive application/server restart.
Access control	Automated tests confirm users cannot access another workspace.
Pilot usability	Both users complete core workflows without developer assistance.

3. Phase 1 scope

Included in MVP

- Secure sign-in, account recovery and invitation-based pairing for one CEO and one Prime Assistant.
- Role-based workspace authorization; one executive and one designated Prime Assistant configured for the first release.
- Two-way message inbox with urgent/important/routine categories, timestamps, read and acknowledgement states, and history.
- Quick replies and actions such as acknowledge, approve, reject, request clarification or defer where applicable.
- Shared calendar: create, update, reschedule and cancel appointments with time, timezone, location/link, purpose and notes.
- Meeting confirmations, change notifications and configurable reminders (e.g. 24 hours and 15 minutes before).
- In-app and push notifications where supported; deadline-based follow-up for unacknowledged urgent items.
- Basic approval requests with decision, comment, actor and timestamp.
- Daily briefing and end-of-day handover covering meetings, urgent messages, pending decisions and overdue follow-ups.
- Basic tasks, audit events, backups, error logging and production monitoring.

Excluded from Phase 1

- Multiple supporting assistants or multiple executives in the active UI.
- Department-head/staff reporting workflows and cross-department routing.
- AI summaries, voice notes or automatic decision-making.
- Full Google Calendar / Outlook integration unless essential and separately estimated.
- WhatsApp/SMS automation unless a supported, authorized integration is separately scoped.
- Complex enterprise approval chains, billing and public self-registration.

4. Users and permissions

Role	Phase 1 permissions
CEO / Managing Director	Access own workspace; message; view agenda; confirm/decline/request meeting changes; respond to approvals; manage own notification preferences.
Prime Assistant	Manage CEO calendar; send messages and briefings; create follow-ups and approval requests; track acknowledgements; coordinate assigned items.
Platform administrator	Operate service with tightly controlled, audited privileged access; no routine access to message content.
Future Phase 2 roles	Supporting Assistant, Department Head, Staff Member and Organization Administrator; reserved for later implementation.

Coordination priority is not the same as approval authority. The Prime Assistant does not automatically gain unrestricted access to confidential material or the power to approve every decision. Define permissions by action and data scope.

5. Core user workflows

A. Send and acknowledge a message

1. Assistant composes a message, selects category and optional response deadline.
2. Backend checks authorization and persists the message before attempting notification.
3. Notification worker queues push/in-app notification and records processing status.
4. CEO opens the message; read state is recorded. CEO explicitly acknowledges or responds when action is required.
5. Assistant sees the status and response. Unacknowledged urgent items trigger configured follow-up after the deadline.

B. Schedule or change a meeting

1. Assistant creates or edits an event with timezone, purpose, location/link and notes.
2. Backend persists the event and a notification outbox record.
3. CEO confirms, declines or requests a change.
4. Both users see the current event state; changes and cancellations remain auditable.
5. Old reminders are cancelled or recalculated after a time change.

C. Request a decision

1. Assistant submits a request with context and due date.
2. CEO approves, rejects, defers or requests clarification.
3. Backend checks permission and records actor, timestamp and comment.
4. Assistant is notified and linked follow-up status is updated.

D. Daily briefing

1. System gathers authorized upcoming meetings, urgent messages, pending approvals and overdue actions.
2. Prime Assistant reviews and edits the briefing.
3. CEO marks items for follow-up; unresolved items carry forward.

6. Recommended technical architecture

Reuse the existing Daymark React/TypeScript/Vite codebase where useful, after a repository audit confirms current dependencies, tests, build status and security gaps.

Layer	Recommendation
Client	React + TypeScript + Vite responsive Progressive Web App (PWA). Validate iOS/Android browser push and installation early.
Backend	Node.js API using the existing server framework where appropriate; authenticated endpoints, server-side authorization and input validation.
Authentication	Managed identity provider such as Supabase Auth or equivalent; invitation-based pairing and account recovery.
Database	PostgreSQL (managed Supabase is an option); organization/workspace scoping and RLS if using Supabase.
Live updates	Supabase Realtime or WebSockets; database remains the source of truth.
Notifications	Durable outbox/queue with retries; Web Push initially, platform-specific push if native apps are introduced.
Files	Private object storage for optional attachments with access checks and expiring links.

Layer	Recommendation
Operations	Separate dev/staging/production environments, managed secrets, backups, monitoring, error tracking and recovery documentation.

Avoid in-memory-only storage and full-state overwrite synchronization. Use durable records, scoped updates, concurrency/version checks and idempotent processing. Push delivery cannot guarantee a person has seen a notification.

7. Initial data model

Entity	Purpose / key fields
organizations	id, name, status, created_at; future workspace boundary.
users / profiles	auth user id, display_name, status, created_at.
organization_memberships	organization_id, user_id, role, status, joined_at.
executive_assistant_assignments	organization_id, executive_user_id, assistant_user_id, assignment_type, active dates; supports PRIME and future SUPPORT.
conversations / members	Workspace-scoped conversations and authorized participants.
messages	sender, conversation, body, category, timestamps, linked entity, response deadline.
message_receipts	message_id, user_id, read_at, acknowledged_at, response_state; delivery time only if measurable.
calendar_events	owner, title, description, start/end, timezone, location/link, status, version, audit timestamps.
event_participants	event_id, user_id, response status and timestamp.
approval_requests	requester, approver, details, due date, status, decision comment/time.
tasks	owner, creator, due date, status and optional linked entity.
notification_jobs	recipient, event type, schedule, attempts, status, provider id and last error.
audit_events	actor, action, entity, timestamp and minimized metadata.

Use UUID primary keys, foreign keys, timestamps and indexes for workspace membership, recipient status, event dates and due dates. Define retention, deletion and backup policies before production.

8. Initial API surface

Method / endpoint (proposed)	Purpose
POST /api/invitations	Create short-lived invitation.
POST /api/invitations/accept	Accept invitation after authentication.
GET /api/me/workspace	Return authorized workspace and role.
GET /api/conversations	List visible conversations.
POST /api/conversations/:id/messages	Persist a message and enqueue notification.
POST /api/messages/:id/receipt	Record read or acknowledgement action.
GET /api/calendar/events	List authorized events by date range.
POST /api/calendar/events	Create event and notification record.
PATCH /api/calendar/events/:id	Update event with conflict checks and notify participants.
POST /api/calendar/events/:id/respond	Confirm, decline or request change.
POST /api/approvals	Create approval request.
POST /api/approvals/:id/decision	Record authorized decision.
GET /api/briefing/today	Return authorized daily briefing.
GET /api/notifications	List visible notification status.

Endpoint names are proposed, not claims about existing endpoints. Derive actor identity from the authenticated session; verify membership and resource-level permissions server-side; validate input, rate-limit sensitive actions and return safe errors.

9. Security, privacy and reliability

- Authenticate every non-public endpoint; never trust client-supplied user_id, role or organization_id without server-side validation.
- Enforce least privilege and workspace isolation; test cross-workspace access explicitly.

- Use TLS, managed secrets, secure sessions, rate limits and protection against invitation replay/brute force.
- Use expiring single-use invitations; allow session revocation and device removal.
- Audit role changes, invitation acceptance, approval decisions and meeting changes; avoid unnecessary logging of message bodies/secrets.
- Use idempotency and a transactional outbox or equivalent so committed updates do not silently lose notification jobs.
- Retry failed notifications with backoff; expose errors for review and avoid duplicate alerts.
- Encrypt backups where supported and test restore procedures.
- Define retention, export/deletion, account deactivation and incident response.
- Separate provider acceptance, device display, read status and human acknowledgement.

10. Delivery plan and milestones

Timing (indicative)	Workstream	Exit criteria
Week 1	Repository audit, requirements, user journeys and UX prototype	Scope approved; risks and reuse opportunities documented.
Weeks 2–3	Authentication, workspace model, database, authorization and environments	Two users securely access only their workspace; persistence and migrations work.
Weeks 4–5	Messages, receipts, calendar, event responses and approvals	End-to-end workflows pass integration tests.
Week 6	Push, reminder jobs, acknowledgement follow-up and briefing	Retry, cancellation and failure paths tested on target devices.
Weeks 7–8	Security, accessibility, offline/reconnect, device testing and pilot fixes	No open critical defects; acceptance checklist passed.
Weeks 9–10 contingency	Production hardening, restore drill, monitoring, onboarding and release	Release approved after pilot and readiness review.

Planning estimate: 8–10 weeks for a production-minded initial release with an experienced developer and design/testing support. Confirm after repository audit; integrations, native app packaging, enterprise reviews or limited team capacity may extend the schedule.

11. Testing and acceptance checklist

- CEO and Prime Assistant can sign in, sign out and recover access.
- Invitation is time-limited, single-use and validated server-side.
- Messages persist and sync; read and acknowledgement states are distinct.
- Urgent messages follow configured reminders without unlimited duplicates.
- Meeting creation, edits, rescheduling and cancellation update both views and leave an audit trail.
- Meeting time changes cancel or recalculate old reminders.
- Approval decisions require the authorized actor and preserve comments/timestamps.
- Server restart does not erase messages, meetings or decisions.
- Offline/reconnect does not silently overwrite newer server data or duplicate actions.
- Cross-workspace access tests fail safely; secrets and message content do not leak into logs.
- Push is tested on actual target devices, including denied permissions and unavailable devices.
- Backup restoration, monitoring alerts and rollback are rehearsed.

12. Phase 2 readiness by design

- Include organization_id and ownership/relationship fields in business records from the start.
- Make roles and permissions data-driven; do not hardcode one assistant into authorization logic.
- Use executive_assistant_assignments with assignment_type PRIME or SUPPORT; enforce one active PRIME assignment per executive.
- Support resource-level permissions and explicit direct-reporting exceptions later.
- Keep notification preferences, routing and escalation rules configurable.
- Maintain schema migrations and API versioning.
- Do not build Phase 2 screens or complex workflows until the pilot proves Phase 1 is stable.

Phase 2 candidates: supporting assistants, department heads and staff reporting; multiple executives; configurable approval chains; Google Calendar/Outlook integration; document management; optional AI-assisted summaries with privacy controls.

13. Risks and mitigations

Risk	Mitigation
Push not shown or not seen	Track provider status separately from read/acknowledgement; use pending queue and deadline-based follow-up.
Confidential data exposure	Authenticated APIs, least privilege, workspace isolation, secure invitations, audit logs and security testing.
Lost or duplicate updates	Persistent database, transactional outbox, idempotency and retries.
Conflicting calendar edits	Versioning, optimistic concurrency and conflict prompts.
Scope creep	Limit Phase 1 to one CEO and one Prime Assistant; change-control advanced integrations.
Mobile browser differences	Prototype push early; test supported OS/browser combinations; consider native client if required.
Phase 2 redesign	Use organization-scoped data, extensible assignments and permission policies from the beginning.

14. Governance and next actions

1. Audit the Daymark repository: reusable UI, sync endpoints, dependency health, tests and security gaps.
2. Confirm target devices, identity provider, notification requirements and whether calendar integration is mandatory for launch.
3. Approve Phase 1 requirements and screen wireframes.
4. Create migrations, environment configuration and automated authorization tests before feature expansion.
5. Implement message and meeting workflows end-to-end from UI through database to notifications.
6. Pilot with one CEO/MD and one Prime Assistant; measure notification processing, acknowledgement and meeting-change reliability.
7. Release only after acceptance checks, backup/restore and support readiness.

The uploaded Daymark project is a starting codebase, not yet a verified production-ready foundation. Audit it before estimating refactoring effort or declaring features complete.

Appendix A. Suggested initial backlog

ID	Priority	Task	Acceptance summary
AUTH-01	P0	Sign-in and account recovery	Authenticated identity; no shared demo credentials.
AUTH-02	P0	Invitation and pair CEO with Prime Assistant	Expiring single-use invitation; workspace/role checked server-side.
DATA-01	P0	PostgreSQL schema and migrations	Workspace-scoped records; backup strategy documented.
SEC-01	P0	Authorization and workspace isolation	Unauthorized requests denied; negative tests included.
MSG-01	P0	Send/list messages	Persisted, paginated inbox with sender and timestamps.
MSG-02	P0	Read and acknowledgement receipts	States are distinct and synchronized.
NTF-01	P0	Notification outbox/worker	Retryable jobs, idempotency and error visibility.
NTF-02	P0	Push and in-app notifications	Permission-aware alerts link to relevant record.
CAL-01	P0	Create/update shared events	Timezone-aware records and conflict checks.
CAL-02	P0	Confirm, decline, reschedule, cancel	Traceable updates reach participants.
CAL-03	P0	Scheduled reminders	Old reminders recalculated after changes.
APR-01	P1	Approval request and decision history	Authorized decisions with comments/timestamps.
BRF-01	P1	Daily briefing	Shows authorized meetings, urgent messages and actions.
TASK-01	P1	Follow-up tasks and deadlines	Tasks link to messages/events and appear in overdue view.
OPS-01	P0	Monitoring and backup/restore	Alerts and recovery procedure documented.
QA-01	P0	Device, security and workflow tests	Pilot passes agreed acceptance checklist.