Urban Land Cover Analysis Pipeline – Phase 2 Progress Report

Group H: Nisarg Shah, Ansar Ur Rahman Mohammed

October 23, 2026

Digital Image Processing – Course Project, Phase 2 (progress checkpoint), October 2026

Repository: https://github.com/nisarg-007/dip-urban-land-cover-pipeline

1. Project Objective

We are building a classical (non-machine-learning) image-processing pipeline that makes an urban aerial scene easier to interpret for land-cover discrimination, so that roads, buildings, vegetation and water can be told apart and measured. The pipeline corrects illumination and contrast so that shadowed regions are usable, enhances local contrast, denoises and sharpens structural detail, separates coarse regions from fine detail in the frequency domain, and extracts edges and corners (building outlines, road intersections) that a later segmentation step can build on.

[1]:
```
import os
import cv2
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt

plt.rcParams.update({"figure.dpi": 100, "font.size": 9, "axes.titlesize": 9})
pd.set_option("display.precision", 3)
pd.set_option("display.width", 120)
# Tables render as real LaTeX tables in the PDF export
pd.set_option("styler.render.repr", "latex")
pd.set_option("styler.format.precision", 3)
pd.set_option("styler.latex.hrules", True)
pd.set_option("styler.format.escape", "latex")

DATA_PATH = os.path.join("data", "naip_raw.png")
color = cv2.imread(DATA_PATH, cv2.IMREAD_COLOR)
assert color is not None, f"could not read {DATA_PATH}"
gray = cv2.cvtColor(color, cv2.COLOR_BGR2GRAY)

# Zoom window used for close-up comparisons (tall-building shadows, I-45 ramps,␣
 ↪parking lots)
CROP = (slice(380, 764), slice(300, 684))

# Tone bands used by several metrics below
shadow_mask = gray <= np.percentile(gray, 25)
```

```
bright_mask = gray >= np.percentile(gray, 75)


def rgb(im):
    return cv2.cvtColor(im, cv2.COLOR_BGR2RGB) if im.ndim == 3 else im


def show(images, titles, suptitle=None, cols=None, size=3.4, crop=False):
    cols = cols or len(images)
    rows = int(np.ceil(len(images) / cols))
    height = (size + 0.55) * rows + 0.4
    fig, axes = plt.subplots(rows, cols, figsize=(size * cols, height),␣
 ↪squeeze=False)
    for ax in axes.ravel():
        ax.axis("off")
    for ax, im, t in zip(axes.ravel(), images, titles):
        im = im[CROP] if crop else im
        ax.imshow(rgb(im), cmap="gray" if im.ndim == 2 else None, vmin=0,␣
 ↪vmax=255)
        ax.set_title(t)
    if suptitle:
        fig.suptitle(suptitle, fontsize=11, fontweight="bold")
    fig.tight_layout(rect=(0, 0, 1, 1 - 0.35 / height))
    plt.show()


def local_std_map(img, k=16):
    f = img.astype(np.float32)
    m = cv2.blur(f, (k, k))
    return np.sqrt(np.clip(cv2.blur(f * f, (k, k)) - m * m, 0, None))


def psnr(ref, img):
    mse = np.mean((ref.astype(np.float64) - img.astype(np.float64)) ** 2)
    return float("inf") if mse == 0 else 10 * np.log10(255.0 ** 2 / mse)


print("image size:", gray.shape[::-1], "| gray min/mean/max:", gray.min(),␣
 ↪round(gray.mean(), 1), gray.max())
```

```
image size: (1024, 1024) | gray min/mean/max: 45 161.6 253
```

2. Dataset / Image Sample

Source: USDA **NAIP** (National Agriculture Imagery Program) 1 m/pixel true-color aerial orthoimagery, retrieved from the USGS National Map NAIP ImageServer (the same NAIP holdings indexed by USGS EarthExplorer). NAIP is U.S. Government public-domain data (credit: USDA Farm Production and Conservation Business Center / USGS).


Scene: a 1024 x 1024 px crop of downtown Houston, TX, at the I-45 (Pierce Elevated) / US-59 interchange, near the George R. Brown Convention Center and Discovery Green. One frame contains high-rise buildings with long shadows, a multi-level highway interchange, a street grid, parking lots, trees and lawns. It contains **no open water**: Buffalo Bayou, named in our proposal, runs just north of this crop. The water class is therefore not tested in Phase 2 (see Next Steps). Export request used:


```
https://imagery.nationalmap.gov/arcgis/rest/services/
    USGSNAIPImagery/ImageServer/exportImage
    ?bbox=-95.377495,29.748295,-95.366905,29.757515
    &bboxSR=4326&imageSR=4326&size=1024,1024&format=png&f=image
```

The image is saved in the repository as `data/naip_raw.png`. Because a 1024 px frame is small in print, most parameter comparisons below are also shown on a 384 x 384 px zoom window (yellow box), which covers building shadows, the highway ramps and parking lots.

[2]:
```
boxed = color.copy()
cv2.rectangle(boxed, (CROP[1].start, CROP[0].start), (CROP[1].stop, CROP[0].
 ↪stop), (0, 255, 255), 4)
show([boxed, gray], ["Original NAIP true-color (1024x1024, 1 m/px)\nyellow box␣
 ↪= zoom window used below",
                     "Grayscale input to the pipeline"],
     suptitle="Representative dataset image: downtown Houston, I-45 / US-59␣
 ↪interchange", size=5)

fig, ax = plt.subplots(figsize=(6, 2.4))
ax.hist(gray.ravel(), bins=256, range=(0, 255), color="gray")
ax.axvline(np.percentile(gray, 25), color="navy", ls="--", label="25th pct␣
 ↪(shadow band)")
ax.axvline(np.percentile(gray, 75), color="darkorange", ls="--", label="75th␣
 ↪pct (bright band)")
ax.set_title("Grayscale histogram of the original image"); ax.
 ↪set_xlabel("intensity"); ax.legend()
fig.tight_layout(); plt.show()
```





3. Implemented Processing Stages

We implemented techniques from all five project categories: point processing, histogram processing, spatial filtering, frequency-domain filtering, and edge & corner detection. Each stage shows the input, the output, a parameter experiment, and a short analysis.

Where the baselines come from. Two kinds of earlier settings are compared against below:

- *Proposal (Phase 1 document):* the smoke-test values gamma = 1.4, median k = 5, FFT low-pass radius 60 px, CLAHE clip 2.5 / 8 x 8 tiles, Harris k = 0.04.
- *Repo baseline:* our first full script run after the proposal (`scripts/dip_pipeline.py`), which set the Canny thresholds and the Harris threshold (0.01 x max). The proposal called the

Canny rule a "median-intensity heuristic"; the code actually uses the median of the *gradient magnitude*, which is the version tested here.

3.1 Point Processing – Gamma Correction and Linear Contrast Stretch

Gamma correction uses $s = 255\,(r/255)^{1/\gamma}$, so $\gamma > 1$ brightens. Instead of picking γ by eye, we define "shadow" pixels as the darkest 25% of the scene and solve for the γ that moves their mean to a mid-gray target of 110: $\gamma = \ln(\bar{r}_{shadow}/255)/\ln(110/255)$. We compare it against no correction and two stronger values.

The local-contrast gain columns divide the mean local standard deviation (16 x 16 window) after correction by the value before correction, separately for the darkest and brightest quartiles. A value below 1 means texture in that band was flattened.

[3]:
```
def gamma_correct(img, g):
    return np.clip(255.0 * np.power(img / 255.0, 1.0 / g), 0, 255).astype(np.
 ↪uint8)

shadow_mean = float(gray[shadow_mask].mean())
TARGET = 110.0
gamma_auto = float(np.log(shadow_mean / 255.0) / np.log(TARGET / 255.0))


base_std = local_std_map(gray)
rows, gamma_imgs = [], {}
for g in [1.0, gamma_auto, 1.6, 2.2]:
    out = gamma_correct(gray, g)
    s = local_std_map(out)
    gamma_imgs[g] = out
    rows.append({"gamma": g,
                 "shadow mean": out[shadow_mask].mean(),
                 "bright mean": out[bright_mask].mean(),
                 "shadow local-contrast gain": s[shadow_mask].mean() /␣
 ↪base_std[shadow_mask].mean(),
                 "bright local-contrast gain": s[bright_mask].mean() /␣
 ↪base_std[bright_mask].mean()})
gamma_table = pd.DataFrame(rows)
print(f"shadow-quartile mean before correction = {shadow_mean:.1f}; solved␣
 ↪gamma = {gamma_auto:.3f}")
gamma_table
```


```
shadow-quartile mean before correction = 89.5; solved gamma = 1.245
```

[3]:

	gamma	shadow mean	bright mean	shadow local-contrast gain	bright local-contrast gain
0	1.000	89.495	207.126	1.000	1.000
1	1.245	109.106	215.269	0.919	0.884
2	1.600	131.221	223.416	0.811	0.753
3	2.200	156.918	231.323	0.667	0.596

[4]:
```
gamma_img = gamma_imgs[gamma_auto]
show([gray, gamma_img], ["Input: original grayscale", f"Output: gamma corrected␣
 ↪(gamma = {gamma_auto:.3f})"],
     suptitle="Gamma correction: before / after", size=5)
show([gamma_imgs[g] for g in gamma_imgs],
     [f"gamma = {g:.3f}" + (" (none)" if g == 1.0 else " (solved)" if g ==␣
 ↪gamma_auto else "") for g in gamma_imgs],
     cols=2, size=4, suptitle="Gamma parameter experiment (zoom window)",␣
 ↪crop=True)
```





Parameter result. The solved value $\gamma = 1.245$ moves the shadow mean from 89.5 to 109.1, within 1% of the target of 110. $\gamma = 1.6$ and 2.2 overshoot (131 and 157) and lighten the image visibly. They also flatten texture: bright-band contrast gain drops to 0.75 and 0.60, so light roofs and pavement start to wash out. The solved γ worked best because it is the smallest correction that reaches the target, so it costs the least highlight contrast.

Analysis.

- *What changed:* the whole image got brighter. The biggest change is in shadowed building faces and tree canopy, which move from near-black into the mid-tones.
- *Did it help:* partly. Shadowed areas are now in a usable intensity range, but gamma alone did **not** increase local contrast in the shadows (gain 0.92). It shifts brightness; it does not add detail. The stretch and CLAHE stages below supply the contrast.
- *Unwanted effects:* highlights are compressed (bright-band gain 0.88), so bright rooftops lose some texture.
- *Decision:* **keep**, using the solved γ rather than a fixed value. Its main job is to move shadows into a range where the following contrast steps can work.

[5]:
```
rows = [{"percentile clip": "none (input)", "input low": gamma_img.min(),␣
 ↪"input high": gamma_img.max(),
```


```
        "% pixels saturated (0 or 255)": 100 * np.mean((gamma_img == 0) |␣
 ↪(gamma_img == 255)),
        "global std": gamma_img.std(), "mean local std":␣
 ↪local_std_map(gamma_img).mean()}]
stretch_imgs = {}
for lo, hi in [(0, 100), (2, 98), (5, 95)]:
    a, b = np.percentile(gamma_img, [lo, hi])
    out = np.clip((gamma_img.astype(np.float64) - a) * 255.0 / max(b - a,␣
 ↪1e-6), 0, 255).astype(np.uint8)
    stretch_imgs[(lo, hi)] = out
    rows.append({"percentile clip": f"{lo}/{hi}", "input low": a, "input high":␣
 ↪b,
                 "% pixels saturated (0 or 255)": 100 * np.mean((out == 0) |␣
 ↪(out == 255)),
                 "global std": out.std(),
                 "mean local std": local_std_map(out).mean()})
stretch_table = pd.DataFrame(rows)
stretched = stretch_imgs[(2, 98)]
stretch_table
```

[5]:


	percentile clip	input low	input high	% pixels saturated (0 or 255)	global std	mean local std
0	none (input)	63.000	253.000	0.000	43.236	26.665
1	0/100	63.000	253.000	0.006	58.010	35.775
2	2/98	80.000	233.000	4.518	71.385	44.157
3	5/95	89.000	224.000	10.133	79.009	49.191

[6]:
```
show([gamma_img, stretched], ["Input: gamma corrected", "Output: linear stretch␣
 ↪(2nd/98th percentile)"],
     suptitle="Linear contrast stretch: before / after", size=5)
show([gamma_img] + list(stretch_imgs.values()),
     ["Input (gamma corrected)"] + [f"stretch {k[0]}/{k[1]} pct" for k in␣
 ↪stretch_imgs],
     cols=2, size=4, suptitle="Contrast-stretch parameter experiment (zoom␣
 ↪window)", crop=True)
```

Linear contrast stretch: before / after



Contrast-stretch parameter experiment (zoom window)



Parameter result. We compared min/max stretching (0/100 percentile), a 2/98 percentile clip, and a 5/95 percentile clip, starting from a mean local std of 26.7. Min/max raises it to 35.8 (+34%) but is limited by a few extreme pixels at 63 and 253. The 2/98 clip ignores those outliers and raises local std to 44.2 (+66%) while saturating only 4.5% of pixels. The 5/95 clip gives more contrast (49.2) but saturates 10% of the image, which turns the brightest roofs and deepest shadows pure white and black. **2/98 worked best**: most of the gain, with a small, controlled amount of clipping.

Analysis.

- *What changed:* the 80-233 intensity band that holds 96% of the pixels now covers the full 0-255 range, so pavement, roofs and lawns are spread further apart in tone.
- *Did it help:* yes. Global contrast (std 43.2 to 71.4) and local contrast (26.7 to 44.2) both increase.
- *Unwanted effects:* 4.5% of pixels are clipped, mostly specular roofs and the darkest shadow cores.
- *Decision:* **keep** with the 2/98 clip.

3.2 Histogram Processing – CLAHE vs. Global Histogram Equalization

We vary the CLAHE clip limit (1.5, 2.5, 4.0) and tile grid (4 x 4, 8 x 8, 16 x 16), and compare against global histogram equalization (HE). Three measures are reported, each relative to the stretched input:

- **gain dark / gain bright:** local-contrast gain in the darkest and brightest quartiles.
- **balance (dark/bright):** the ratio of those two gains. A value of 1.0 means both bands improved equally.
- **gain in flat regions:** local-contrast gain in the 20% smoothest neighborhoods (bare roofs and pavement). Gain there is mostly amplified noise and texture, so lower is better.

[7]:
```
pre_std = local_std_map(stretched)
# "Flat" pixels = the 20% smoothest neighbourhoods (bare roofs, pavement).␣
 ↪Contrast gain
# there is mostly amplified noise/texture, so it is tracked as an␣
 ↪unwanted-effect metric.
flat_mask = pre_std <= np.percentile(pre_std, 20)

def he_metrics(name, out):
    s = local_std_map(out)
    gd = s[shadow_mask].mean() / pre_std[shadow_mask].mean()
    gb = s[bright_mask].mean() / pre_std[bright_mask].mean()
    return {"method": name, "mean local std": s.mean(), "gain dark": gd, "gain␣
 ↪bright": gb,
            "balance (dark/bright)": gd / gb, "gain in flat regions":␣
 ↪s[flat_mask].mean() / pre_std[flat_mask].mean()}


he_imgs = {"global HE": cv2.equalizeHist(stretched)}
for clip, tile in [(1.5, 8), (2.5, 8), (4.0, 8), (2.5, 4), (2.5, 16)]:
```


```
    he_imgs[f"CLAHE clip={clip}, tile={tile}"] = cv2.
 ↪createCLAHE(clipLimit=clip, tileGridSize=(tile, tile)).apply(stretched)
clahe_table = pd.DataFrame([he_metrics(k, v) for k, v in he_imgs.items()])
clahe_img = he_imgs["CLAHE clip=2.5, tile=8"]
clahe_table
```

[7]:

	method	mean local std	gain dark	gain bright	balance (dark/bright)	gain in flat regions
0	global HE	50.091	0.909	1.370	0.663	1.800
1	CLAHE clip=1.5, tile=8	46.605	1.016	1.081	0.940	1.188
2	CLAHE clip=2.5, tile=8	47.660	0.999	1.145	0.873	1.370
3	CLAHE clip=4.0, tile=8	48.913	0.978	1.223	0.799	1.589
4	CLAHE clip=2.5, tile=4	46.879	0.977	1.138	0.859	1.324
5	CLAHE clip=2.5, tile=16	48.881	1.032	1.155	0.894	1.432

[8]:
```
show([stretched, he_imgs["global HE"], clahe_img],
     ["Input: contrast stretched", "Global histogram equalization", "Output:␣
 ↪CLAHE (clip 2.5, tile 8x8)"],
     suptitle="Histogram processing: before / after", size=4.2)
keys = ["CLAHE clip=1.5, tile=8", "CLAHE clip=2.5, tile=8", "CLAHE clip=4.0,␣
 ↪tile=8",
        "CLAHE clip=2.5, tile=4", "CLAHE clip=2.5, tile=16", "global HE"]
show([he_imgs[k] for k in keys], keys, cols=3, suptitle="CLAHE parameter␣
 ↪experiment (zoom window)", crop=True)
```





Parameter result. Global HE has the highest overall local contrast (50.1), but it is the most unbalanced method (0.66). It *reduces* contrast in shadows (gain 0.91) while boosting bright areas by 1.37x, and it amplifies flat regions the most (1.80x), which shows up as grainy roofs in the zoom window. All CLAHE settings are more balanced. Raising the clip limit from 1.5 to 4.0 trades balance (0.94 down to 0.80) and noise (1.19x up to 1.59x) for a little more contrast (46.6 up to 48.9). Tile size matters less: 4 x 4 gives slightly less contrast (46.9), and 16 x 16 gives more contrast (48.9) but amplifies flat regions more (1.43x).

Which setting worked better: on this table alone, clip 1.5 is best: the most balanced (0.94) and the least noise amplification in flat regions (1.19x). Clip 2.5 (the proposal value) gives a little more contrast. Because the real purpose of CLAHE here is to feed edge detection, we re-ran the full downstream chain (sharpen, blur, Canny) with clip 1.5, 2.0 and 2.5 in Section 3.5. The edge maps came out almost the same, with 2.5 slightly ahead, so we keep **clip 2.5, tile 8 x 8**.

Analysis.

- *What changed:* texture on mid-gray pavement and bright roofs became more visible, and building outlines stand out more from their surroundings.
- *Did it help:* partly. CLAHE raises bright-band local contrast by 1.14x and leaves shadow contrast unchanged (0.999x). It does **not** add contrast in the shadows, but unlike global HE it does not take any away (global HE drops shadow contrast to 0.91x). That is the advantage over global HE on this mixed scene.

- *Unwanted effects:* flat roofs and lots get grainier (1.37x local-contrast gain in flat regions).
- *Decision:* **keep** at clip 2.5. Lowering the clip limit improves the balance metric but did not improve the downstream edges.

3.3 Spatial Filtering – Median Filtering and Laplacian Sharpening

Median filtering. The NAIP crop has almost no impulse noise, so to test the filter properly we add 2% synthetic salt-and-pepper noise (fixed random seed) to the CLAHE output. We then compare median kernels k = 3, 5, 7 and a 3 x 3 mean filter against the clean image. We measure PSNR and the correlation between Laplacian edge maps (how much fine edge structure survives). We also apply k = 3 to the *real, un-noised* image to see what the filter costs when no noise is present.

[9]:
```
rng = np.random.default_rng(0)
noisy = clahe_img.copy()
n = int(0.02 * noisy.size)
ys, xs = rng.integers(0, noisy.shape[0], n), rng.integers(0, noisy.shape[1], n)
noisy[ys[: n // 2], xs[: n // 2]] = 255
noisy[ys[n // 2:], xs[n // 2:]] = 0

lap_clean = cv2.Laplacian(clahe_img, cv2.CV_32F)
def edge_corr(img):
    return float(np.corrcoef(lap_clean.ravel(), cv2.Laplacian(img, cv2.CV_32F).
 ↪ravel())[0, 1])

den_imgs = {"noisy input": noisy,
            "median k=3": cv2.medianBlur(noisy, 3),
            "median k=5": cv2.medianBlur(noisy, 5),
            "median k=7": cv2.medianBlur(noisy, 7),
            "mean (box) k=3": cv2.blur(noisy, (3, 3))}
median_table = pd.DataFrame([{"filter": k, "PSNR vs clean (dB)":␣
 ↪psnr(clahe_img, v),
                              "edge correlation vs clean": edge_corr(v)} for k,␣
 ↪v in den_imgs.items()])


# Cost of the median filter on the real (un-noised) image
med_real = cv2.medianBlur(clahe_img, 3)
print(f"median k=3 on the REAL clean image: PSNR vs unfiltered =␣
 ↪{psnr(clahe_img, med_real):.1f} dB, "
      f"edge correlation = {edge_corr(med_real):.3f}")
median_table
```


```
median k=3 on the REAL clean image: PSNR vs unfiltered = 26.5 dB, edge
correlation = 0.613
```

[9]:

	filter	PSNR vs clean (dB)	edge correlation vs clean
0	noisy input	21.768	0.505
1	median k=3	26.193	0.593
2	median k=5	22.235	0.381
3	median k=7	20.190	0.274
4	mean (box) k=3	23.804	0.358

[10]:
```
show([noisy, den_imgs["median k=3"]], ["Input: CLAHE + 2% synthetic␣
 ↪salt-and-pepper noise", "Output: median filter k=3"],
     suptitle="Median filtering: before / after", size=5)
show(list(den_imgs.values()), list(den_imgs.keys()), cols=3, size=3.4,
     suptitle="Median kernel-size experiment, with a mean filter for comparison␣
 ↪(zoom window)", crop=True)
```





Parameter result. k = 3 worked best: PSNR rises from 21.8 to 26.2 dB and edge correlation from 0.51 to 0.59. Larger kernels remove the noise too, but they blur away real detail. k = 5 is barely better than the noisy input on PSNR (22.2 vs. 21.8 dB), and k = 7 is worse (20.2 dB). On edge correlation, both are worse than the noisy input (0.38 and 0.27 vs. 0.51). In the zoom window, cars, lot striping and thin ramps disappear at k = 7. The 3 x 3 mean filter scores lower on both measures (23.8 dB and 0.36) because it smears the impulses into gray blotches instead of removing them. This confirms that the median filter suits this kind of noise.

Analysis.

- *What changed:* the impulse noise is removed almost completely at k = 3.
- *Did it help:* yes for impulse noise. However, on the **real** image (which has no impulse noise), the k = 3 output measures only 26.5 dB PSNR against the unfiltered image and keeps only 0.61 edge correlation. It removes real detail such as cars and lot markings without removing any noise.
- *Unwanted effects:* loss of small, real structures, which gets worse quickly at larger kernel sizes.
- *Decision:* **modify**. We will use the median filter only when a scene actually has impulse noise or speckle, and **remove** it from the default chain for this clean NAIP scene. Smoothing before edge detection is handled better by a Gaussian blur (Section 3.5).

Laplacian sharpening computes $g = f - w\,\nabla^2 f$ on the CLAHE output. We tested weights from

0.03 to 0.6 and measured the fraction of hard-clipped (0 or 255) pixels, which indicates overshoot and ringing. We also report the mean absolute Laplacian as a "detail energy" check. That figure uses the same Laplacian operator as the sharpening step, so it rises by construction as w increases; the clipping budget is the actual selection rule.

[11]:
```
lap = cv2.Laplacian(clahe_img, cv2.CV_64F, ksize=3)
rows, sharp_imgs = [], {}
for w in [0.03, 0.05, 0.1, 0.2, 0.6]:
    out = np.clip(clahe_img.astype(np.float64) - w * lap, 0, 255).astype(np.
 ↪uint8)
    sharp_imgs[w] = out
    rows.append({"weight": w, "% pixels clipped (0/255)": 100 * np.mean((out ==␣
 ↪0) | (out == 255)),
                 "mean |Laplacian| (detail energy)": np.mean(np.abs(cv2.
 ↪Laplacian(out, cv2.CV_64F, ksize=3)))})
sharpen_table = pd.DataFrame(rows)
print(f"unsharpened CLAHE: {100 * np.mean((clahe_img == 0) | (clahe_img ==␣
 ↪255)):.1f}% clipped, "
      f"detail energy {np.mean(np.abs(lap)):.1f}")
sharp = sharp_imgs[0.05]
sharpen_table
```


```
unsharpened CLAHE: 2.3% clipped, detail energy 105.3
```

[11]:


	weight	% pixels clipped (0/255)	mean |Laplacian| (detail energy)
0	0.030	3.450	131.618
1	0.050	4.586	149.023
2	0.100	7.848	190.934
3	0.200	14.727	263.669
4	0.600	35.766	444.294

[12]:
```
show([clahe_img, sharp], ["Input: CLAHE output", "Output: Laplacian sharpened␣
 ↪(weight 0.05)"],
     suptitle="Laplacian sharpening: before / after", size=5)
show([clahe_img] + [sharp_imgs[w] for w in [0.05, 0.2, 0.6]],
     ["unsharpened"] + [f"weight = {w}" for w in [0.05, 0.2, 0.6]],
     cols=2, size=4, suptitle="Sharpening-weight experiment (zoom window)",␣
 ↪crop=True)
```

Laplacian sharpening: before / after



Sharpening-weight experiment (zoom window)



Parameter result. Detail energy rises steadily with w, and so does clipping: 3.5% at 0.03, 4.6% at 0.05, 7.8% at 0.1, 14.7% at 0.2 and 35.8% at 0.6. With a 5% clipping budget, $w = 0.05$ **is the strongest setting we can use**. It raises the Laplacian energy from 105 to 149 (+42%), as expected from using the same operator that does the sharpening. At $w = 0.2$ and above, the zoom window shows bright and dark halos around every roof edge and car, and pavement turns noisy.

Analysis.

- *What changed:* roof edges, curbs and ramp boundaries look crisper.
- *Did it help:* yes for visual interpretation. For edge detection the effect is mixed, because sharpening also amplifies texture and contributes to the overly dense repo-baseline Canny result (Section 3.5).
- *Unwanted effects:* halos and noise amplification at higher weights; even at 0.05, about 2.3 percentage points of extra pixels are clipped.
- *Decision:* **keep at w = 0.05** for the enhanced visual output, but always follow it with a Gaussian blur before edge and corner detection.

3.4 Frequency-Domain Filtering – FFT Low-Pass / High-Pass

We take the 2-D FFT of the CLAHE output. Our first cut-off rule came from the image's own radial power spectrum: the smallest radius that contains 90% of the AC power, excluding the DC term (the image mean, which would otherwise satisfy any threshold at r = 0). We compare ideal (hard-cutoff) low-pass filters at r = 60 (the proposal value) and at that 90% radius, with **Gaussian** low-pass filters $H = e^{-D^2/2D_0^2}$ at $D_0 = 15$, 30, 60 and the 90% radius.

Each filter is scored three ways:

- **% AC power kept.**
- **PSNR against the input.** This rewards weak filtering, so on its own it would always pick the largest cut-off.
- **% local contrast removed** (mean 16 x 16 local std, before vs. after). This measures how uniform the regions become, which is what a region map for segmentation needs.

[13]:
```
F = np.fft.fftshift(np.fft.fft2(clahe_img.astype(np.float64)))
h, w = clahe_img.shape
cy, cx = h // 2, w // 2
Y, X = np.ogrid[:h, :w]
D = np.sqrt((X - cx) ** 2 + (Y - cy) ** 2)

power = np.abs(F) ** 2
radial = np.bincount(D.astype(int).ravel(), weights=power.ravel())
radial[0] = 0.0                          # exclude DC (image mean), otherwise r=0␣
 ↪already holds most power
cum = np.cumsum(radial) / radial.sum()
r90 = int(np.searchsorted(cum, 0.90))

def inv(spec):
    return np.real(np.fft.ifft2(np.fft.ifftshift(spec)))
```


```
def gaussian_lp(d0):
    return np.exp(-(D ** 2) / (2.0 * d0 ** 2))


def percentile_stretch(x, lo=1, hi=99):
    a, b = np.percentile(x, [lo, hi])
    return np.clip((x - a) * 255.0 / (b - a), 0, 255).astype(np.uint8)

# Region uniformity: how much of the input's local contrast (16x16 std) the␣
 ↪low-pass removes.
# PSNR alone favours the weakest filter, so both are reported.
input_local_std = local_std_map(clahe_img).mean()
lp_imgs, rows = {}, []
for name, H in [("ideal r=60", (D <= 60).astype(float)),
                (f"ideal r={r90}", (D <= r90).astype(float)),
                ("Gaussian D0=15", gaussian_lp(15)),
                ("Gaussian D0=30", gaussian_lp(30)),
                ("Gaussian D0=60", gaussian_lp(60)),
                (f"Gaussian D0={r90}", gaussian_lp(r90))]:
    out = np.clip(inv(F * H), 0, 255).astype(np.uint8)
    lp_imgs[name] = out
    ac = (power * H ** 2).copy(); ac[cy, cx] = 0
    rows.append({"low-pass filter": name, "% AC power kept": 100 * ac.sum() /␣
 ↪(power.sum() - power[cy, cx]),
                 "PSNR vs input (dB)": psnr(clahe_img, out),
                 "% local contrast removed": 100 * (1 - local_std_map(out).
 ↪mean() / input_local_std)})
fft_table = pd.DataFrame(rows)

D0 = 30
lp_img = lp_imgs[f"Gaussian D0={D0}"]
hp_img = percentile_stretch(inv(F * (1 - gaussian_lp(D0))))
hp_img_r90 = percentile_stretch(inv(F * (1 - gaussian_lp(r90))))

fig, axes = plt.subplots(1, 2, figsize=(10, 3.6))
axes[0].imshow(np.log1p(np.abs(F)), cmap="gray"); axes[0].
 ↪set_title("Log-magnitude spectrum (centred)"); axes[0].axis("off")
axes[1].plot(cum); axes[1].axvline(r90, color="r", ls="--", label=f"r = {r90}␣
 ↪(90% of AC power)")
axes[1].set_xlabel("radius (cycles / image)"); axes[1].set_ylabel("cumulative␣
 ↪AC power"); axes[1].legend()
axes[1].set_title("Radial power spectrum (cut-off selection)")
fig.tight_layout(); plt.show()
fft_table
```







[13]:

	low-pass filter	% AC power kept	PSNR vs input (dB)	% local contrast removed
0	ideal r=60	73.574	16.755	32.298
1	ideal r=138	89.905	20.945	12.423
2	Gaussian D0=15	25.217	13.465	81.354
3	Gaussian D0=30	44.449	15.443	63.207
4	Gaussian D0=60	64.154	18.306	40.819
5	Gaussian D0=138	82.910	23.074	19.217

[14]:
```
show([clahe_img, lp_img, hp_img],
     ["Input: CLAHE output", f"Output: Gaussian low-pass (D0={D0})\nregion map",
      f"Output: Gaussian high-pass (D0={D0})\nstructure map, 1-99% stretch"],
     suptitle="Frequency-domain filtering: before / after", size=4.2)
show(list(lp_imgs.values()), list(lp_imgs.keys()), suptitle="Low-pass cut-off␣
 ↪and filter-shape experiment (zoom window)",
     crop=True, cols=3, size=3.4)
show([hp_img, hp_img_r90], [f"high-pass D0={D0}", f"high-pass D0={r90}␣
 ↪(90%-power radius)"],
     suptitle="High-pass cut-off comparison (zoom window, 1-99% stretch)",␣
 ↪crop=True, size=4)
```





Low-pass cut-off and filter-shape experiment (zoom window)
ideal r=60
ideal r=138
Gaussian D0=15
Gaussian D0=30
Gaussian D0=60
Gaussian D0=138



[15]:
```
# Ringing check: one image row crossing building / shadow edges, ideal vs. Gaussian at the same cut-off
row, cols_ = 560, slice(380, 640)
x = np.arange(cols_.start, cols_.stop)
fig, ax = plt.subplots(figsize=(10, 3.2))
ax.plot(x, clahe_img[row, cols_], color="lightgray", lw=2.5, label="input (CLAHE)")
ax.plot(x, lp_imgs["ideal r=60"][row, cols_], color="tab:red", lw=1.2, label="ideal low-pass r=60")
ax.plot(x, lp_imgs["Gaussian D0=60"][row, cols_], color="tab:blue", lw=1.2, label="Gaussian low-pass D0=60")
ax.set_xlabel(f"column (row {row})"); ax.set_ylabel("intensity"); ax.legend(loc="upper right", fontsize=8)
ax.set_title("Intensity profile across edges: ringing check at the same cut-off")
fig.tight_layout(); plt.show()

ft = fft_table.set_index("low-pass filter")
print("At cut-off 60: ideal removes {:.0f}% of local contrast at {:.1f} dB; Gaussian removes {:.0f}% at {:.1f} dB".format(
    ft.loc["ideal r=60", "% local contrast removed"], ft.loc["ideal r=60", "PSNR vs input (dB)"],
    ft.loc["Gaussian D0=60", "% local contrast removed"], ft.loc["Gaussian D0=60", "PSNR vs input (dB)"]))
```




```
At cut-off 60: ideal removes 32% of local contrast at 16.8 dB; Gaussian removes
41% at 18.3 dB
```

Parameter result. The 90%-power radius (r = 138) turned out to be the wrong criterion for a region map. The Gaussian filter at $D_0 = 138$ removes only 19% of local contrast, and the output looks almost the same as the input. Its high PSNR (23.1 dB) only means it changed little. Lowering the cut-off trades PSNR for uniformity: $D_0 = 60$ removes 41%, $D_0 = 30$ removes 63%, and $D_0 = 15$ removes 81%. The uniformity metric alone would pick $D_0 = 15$. We reject that setting because neighboring building blocks merge into blobs. The rule we use is therefore **the largest local-contrast removal before blocks merge**, which selects **Gaussian $D_0 = 30$**. In the zoom window the result is a *soft* region map: cars, striping and roof texture are gone, and building blocks, the highway corridor and the lawn remain as separate (but not perfectly flat) regions.

Ideal vs. Gaussian (ringing). At the same cut-off of 60, the Gaussian filter removes *more* local contrast than the ideal filter (41% vs. 32%) yet stays *closer* to the input (18.3 vs. 16.8 dB). The ideal filter's extra error is therefore not useful smoothing. The intensity profile shows what it is: at columns 383 and 458, where the input is already at a flat roof top, the ideal filter (red) overshoots by +27 and +25 intensity units and oscillates beside the edge. That is Gibbs ringing. The Gaussian (blue) is -6 and +5 at those same columns: it overshoots less. (Column 628 is not used as evidence: both filters overshoot there.) In the zoom window, the ideal r = 60 panel shows the same ringing as stripes parallel to building edges.

Analysis.

- *What changed:* the $D_0 = 30$ low-pass output keeps coarse regions (building blocks, lawns, the highway corridor) and removes small detail. Its complementary high-pass output, shown with a 1-99% percentile stretch, keeps the street grid, building outlines and ramp edges. The high-pass at $D_0 = 138$ shows only fine texture, not the grid.
- *Did it help:* yes. Low-pass and high-pass now actually separate "where the regions are" from "where the boundaries are".
- *Unwanted effects:* region boundaries in the low-pass image are soft, about 5 px of blur, so it cannot locate edges precisely. Edges come from Canny. Tall buildings' shadows remain as dark regions that could be mistaken for a separate class.
- *Decision:* **modify**. Use a Gaussian instead of an ideal mask, and set $D_0 = 30$ by the rule "largest local-contrast removal before blocks merge" (not the 90%-power rule). The low-pass output becomes the input for region segmentation in Phase 3, and the high-pass output becomes a structure map.

3.5 Edge & Corner Detection – Canny and Harris

Canny. In our repo baseline we ran Canny on the sharpened image, with thresholds set by the median-gradient rule (low = 0.66 x median, high = 1.33 x median of the Sobel gradient magnitude). We compare four settings:

- A: the repo baseline.
- B: the same rule without sharpening.
- C: Gaussian blur (5 x 5, $\sigma = 1.4$) before Canny.
- D: Gaussian blur plus stricter thresholds (1.0 x / 2.0 x median).

Without ground-truth edges we use objective structure metrics: edge-pixel density, number of connected edge segments, mean segment length (longer means more continuous outlines), and the share of tiny segments under 10 px, which are mostly texture speckle rather than real boundaries. **Caveat:** these metrics favor fewer edges by construction. A setting that drops real but weak edges also scores "better", so they are proxies until we can score precision and recall against reference outlines (Next Steps).

[16]:
```
def median_rule(img, lo=0.66, hi=1.33):
    gx = cv2.Sobel(img, cv2.CV_64F, 1, 0, ksize=3)
    gy = cv2.Sobel(img, cv2.CV_64F, 0, 1, ksize=3)
    m = float(np.median(np.hypot(gx, gy)))
    return lo * m, min(255.0, hi * m)

def edge_stats(name, img, lo, hi):
    e = cv2.Canny(img, int(lo), int(hi))
    n, _, stats, _ = cv2.connectedComponentsWithStats((e > 0).astype(np.uint8),␣
 ↪connectivity=8)
    sizes = stats[1:, cv2.CC_STAT_AREA]
    return e, {"setting": name.split(":")[0], "low": lo, "high": hi, "edge px␣
 ↪%": 100 * np.mean(e > 0),
               "segments": n - 1, "mean length (px)": sizes.mean(),
               "speckle % (<10 px)": 100 * np.mean(sizes < 10)}


smooth = cv2.GaussianBlur(sharp, (5, 5), 1.4)
settings = [("A: sharpened, median rule (repo baseline)", sharp,␣
 ↪*median_rule(sharp)),
            ("B: CLAHE (no sharpening), median rule", clahe_img,␣
 ↪*median_rule(clahe_img)),
            ("C: sharpened + Gaussian blur, median rule", smooth,␣
 ↪*median_rule(smooth)),
            ("D: sharpened + Gaussian blur, 1.0x / 2.0x median", smooth,␣
 ↪*median_rule(smooth, 1.0, 2.0))]
canny_imgs, rows = {}, []
for name, img, lo, hi in settings:
    e, r = edge_stats(name, img, lo, hi)
    canny_imgs[name] = e
    rows.append(r)
```


```
canny_table = pd.DataFrame(rows)
canny_table
```

[16]:

	setting	low	high	edge px %	segments	mean length (px)	speckle % (<10 px)
0	A	65.716	132.427	27.580	11999	24.101	69.156
1	B	56.073	112.995	26.140	10582	25.902	65.451
2	C	44.899	90.479	18.630	5546	35.224	44.176
3	D	68.029	136.059	16.104	3703	45.601	31.704

[17]:
```
best_canny = canny_imgs["D: sharpened + Gaussian blur, 1.0x / 2.0x median"]
show([smooth, best_canny], ["Input: sharpened + Gaussian blur (what Canny␣
 ↪receives)", "Output: Canny edges (setting D)"],
     suptitle="Canny edge detection: before / after", size=5)
show(list(canny_imgs.values()), [k.split(",")[0] + ",\n" + k.split(",", 1)[1].
 ↪strip() for k in canny_imgs], cols=2,
     size=4, suptitle="Canny threshold / pre-processing experiment (zoom␣
 ↪window)", crop=True)
```





Parameter result. The repo baseline (A) marks 27.6% of all pixels as edges. 69% of its segments are shorter than 10 px, and the zoom window looks like dense texture rather than outlines. Removing sharpening (B) barely helps (26.1%). Most of the clutter comes from fine texture, not the sharpening weight. Blurring first (C) cuts the density to 18.6% and speckle to 44%. **Setting D worked best**: 16.1% edge pixels, 3,703 segments instead of 11,999, mean segment length 45.6 px instead of 24.1 px, and only 32% speckle. Building footprints, the highway edges and the ramp curves now form continuous lines.

Analysis.

- *What changed:* the edge map went from a texture map to an outline map.
- *Did it help:* yes. Long, connected building and road boundaries are what a later segmentation step needs.
- *Unwanted effects:* stricter thresholds drop some weak edges, such as low-contrast roof edges and lane lines inside shadows. Trees still produce small closed contours.
- *Decision:* **modify**. Use a Gaussian blur followed by Canny with 1.0 x / 2.0 x median thresholds.

CLAHE clip limit, re-checked downstream. Section 3.2 found clip 1.5 more balanced than our chosen 2.5. To see whether that matters for the actual goal, we re-ran the whole chosen chain (CLAHE, sharpen w = 0.05, Gaussian blur, Canny setting D) with clip 1.5, 2.0 and 2.5.

[18]:
```
rows = []
for clip in [1.5, 2.0, 2.5]:
    ch = cv2.createCLAHE(clipLimit=clip, tileGridSize=(8, 8)).apply(stretched)
    sh = np.clip(ch.astype(np.float64) - 0.05 * cv2.Laplacian(ch, cv2.CV_64F,␣
 ↪ksize=3), 0, 255).astype(np.uint8)
    sm = cv2.GaussianBlur(sh, (5, 5), 1.4)
    _, r = edge_stats(f"clip {clip}", sm, *median_rule(sm, 1.0, 2.0))
    rows.append(r)
clahe_recheck = pd.DataFrame(rows).drop(columns=["low", "high"])
clahe_recheck
```

[18]:

	setting	edge px %	segments	mean length (px)	speckle % (<10 px)
0	clip 1.5	15.646	3827	42.870	33.185
1	clip 2.0	15.969	3843	43.573	32.787
2	clip 2.5	16.104	3703	45.601	31.704

Result. The edge maps are almost identical: 15.6-16.1% edge pixels and 32-33% speckle for all three clip values. Clip 2.5 has slightly longer segments (45.6 px vs. 42.9 px at clip 1.5) and the least speckle. The better balance of clip 1.5 does not carry through to edge quality, so we **keep clip 2.5**.

Harris corners. We vary the response threshold (0.01, 0.05 and 0.10 of the maximum response), the sensitivity k (0.04 vs. 0.06), and the input (sharpened vs. sharpened + blurred). Because each corner covers several pixels, we count "corner clusters" (connected groups of corner pixels) as an approximate keypoint count.


[19]:
```
def harris_overlay(img, k, frac):
    R = cv2.cornerHarris(np.float32(img), blockSize=2, ksize=3, k=k)
    mask = R > frac * R.max()
    n_blobs = cv2.connectedComponents(cv2.dilate(mask.astype(np.uint8), None),␣
 ↪connectivity=8)[0] - 1
    ov = color.copy()
    ov[cv2.dilate(mask.astype(np.uint8), None) == 1] = (0, 0, 255)
    return ov, {"input": "sharpened" if img is sharp else "sharpened + Gaussian␣
 ↪blur", "k": k, "threshold (x max R)": frac,
                "corner pixels": int(mask.sum()), "corner clusters␣
 ↪(~keypoints)": n_blobs}


harris_imgs, rows = {}, []
for img, k, frac in [(sharp, 0.04, 0.01), (sharp, 0.04, 0.05), (sharp, 0.04, 0.
 ↪10), (sharp, 0.06, 0.05), (smooth, 0.04, 0.05)]:
    ov, r = harris_overlay(img, k, frac)
    harris_imgs[f"{r['input']}\nk={k}, thr={frac} x max"] = ov
    rows.append(r)
harris_table = pd.DataFrame(rows)
harris_table
```

[19]:

	input	k	threshold (x max R)	corner pixels	corner clusters (~keypoints)
0	sharpened	0.040	0.010	61967	4075
1	sharpened	0.040	0.050	15884	3466
2	sharpened	0.040	0.100	6143	2215
3	sharpened	0.060	0.050	13250	3281
4	sharpened + Gaussian blur	0.040	0.050	9151	1959

[20]:
```
show([color, harris_imgs["sharpened + Gaussian blur\nk=0.04, thr=0.05 x max"]],
     ["Input: original colour image", "Output: Harris corners (blurred input,␣
 ↪k=0.04, thr=0.05)"],
     suptitle="Harris corner detection: before / after", size=5)
show(list(harris_imgs.values()), list(harris_imgs.keys()), cols=3, size=3.4,
     suptitle="Harris threshold / k experiment (zoom window, red = corner)",␣
 ↪crop=True)
```





Parameter result. The repo-baseline threshold (0.01 x max) flags 62k pixels in 4,075 clusters. The zoom window is covered in red, including tree canopy and pavement texture. Raising the threshold to 0.05 cuts this to 15.9k pixels and 3,466 clusters, and 0.10 cuts it to 2,215 clusters but starts missing real building corners. Changing k from 0.04 to 0.06 has a smaller effect (3,466 to 3,281 clusters). **Blurred input with threshold 0.05 worked best**: 1,959 clusters, concentrated on building corners, roof structures and road junctions, with far fewer hits in tree canopy.

Analysis.

- *What changed:* corners are now sparse, interpretable keypoints instead of a texture response.
- *Did it help:* yes. The remaining corners match real structure, which is what we wanted as a proxy for structural complexity.
- *Unwanted effects:* tree crowns and cars still produce some corners, and a few corners on low-contrast roofs are lost.
- *Decision:* **modify**. Run Harris on the blurred image with threshold 0.05 x max and $k = 0.04$. Add non-maximum suppression in Phase 3 to get exactly one point per corner.

4. Preliminary Evaluation

We do not have pixel-level ground truth for this scene yet, so each stage is scored with a metric that matches its purpose: reaching a target mean intensity, balanced contrast gain, PSNR against


a clean reference, clipped-pixel fraction, region uniformity, and edge continuity and speckle. The table compares a baseline with the current choice. The "baseline (source)" column says whether each baseline comes from the proposal, our repo run, or is simply the unprocessed or worst-tested case. The figure shows the intermediate result of each stage on the full frame.

[21]:
```
g = gamma_table.set_index("gamma")
c = clahe_table.set_index("method")
m = median_table.set_index("filter")
s = sharpen_table.set_index("weight")
f = fft_table.set_index("low-pass filter")
e = canny_table.set_index("setting")
hr = harris_table
summary = pd.DataFrame([
    ["Gamma", "shadow-quartile mean (target 110)", f"{g.iloc[0]['shadow mean']:.
 ↪1f} (no gamma)", f"{g.loc[gamma_auto, 'shadow mean']:.1f} (gamma={gamma_auto:
 ↪.3f})"],
    ["CLAHE", "dark/bright gain balance (1.0 = even)", f"{c.loc['global HE',␣
 ↪'balance (dark/bright)']:.2f} (global HE)", f"{c.loc['CLAHE clip=2.5,␣
 ↪tile=8', 'balance (dark/bright)']:.2f} (clip 2.5, tile 8)"],
    ["Median", "PSNR vs clean reference (dB)", f"{m.loc['noisy input', 'PSNR vs␣
 ↪clean (dB)']:.1f} (noisy)", f"{m.loc['median k=3', 'PSNR vs clean (dB)']:.
 ↪1f} (k=3)"],
    ["Sharpening", "% clipped pixels (budget 5%)", f"{s.loc[0.6, '% pixels␣
 ↪clipped (0/255)']:.1f} (w=0.6)", f"{s.loc[0.05, '% pixels clipped (0/255)']:.
 ↪1f} (w=0.05)"],
    ["FFT low-pass", "% local contrast removed (region uniformity)", f"{f.
 ↪loc['ideal r=60', '% local contrast removed']:.0f} (ideal r=60, proposal)",␣
 ↪f"{f.loc[f'Gaussian D0={D0}', '% local contrast removed']:.0f} (Gaussian␣
 ↪D0={D0})"],
    ["Canny", "edge px % / speckle %",
     f"{e.iloc[0]['edge px %']:.1f} / {e.iloc[0]['speckle % (<10 px)']:.0f}␣
 ↪(setting A, repo)",
     f"{e.iloc[3]['edge px %']:.1f} / {e.iloc[3]['speckle % (<10 px)']:.0f}␣
 ↪(setting D)"],
    ["Harris", "corner clusters", f"{hr.iloc[0]['corner clusters␣
 ↪(~keypoints)']} (thr 0.01, repo)", f"{hr.iloc[4]['corner clusters␣
 ↪(~keypoints)']} (blurred, thr 0.05)"],
], columns=["stage", "metric", "baseline (source)", "current choice"])
summary
```

[21]:

	stage	metric	baseline (source)	current choice
0	Gamma	shadow-quartile mean (target 110)	89.5 (no gamma)	109.1 (gamma=1.245)
1	CLAHE	dark/bright gain balance (1.0 = even)	0.66 (global HE)	0.87 (clip 2.5, tile 8)
2	Median	PSNR vs clean reference (dB)	21.8 (noisy)	26.2 (k=3)
3	Sharpening	% clipped pixels (budget 5%)	35.8 (w=0.6)	4.6 (w=0.05)
4	FFT low-pass	% local contrast removed (region uniformity)	32 (ideal r=60, proposal)	63 (Gaussian D0=30)
5	Canny	edge px % / speckle %	27.6 / 69 (setting A, repo)	16.1 / 32 (setting D)
6	Harris	corner clusters	4075 (thr 0.01, repo)	1959 (blurred, thr 0.05)

[22]:
```
show([gray, clahe_img, sharp, smooth, best_canny, harris_imgs["sharpened +␣
↪Gaussian blur\nk=0.04, thr=0.05 x max"], lp_img, hp_img],
    ["1. Original grayscale", "2. Gamma + stretch + CLAHE", "3. Laplacian␣
↪sharpened (w=0.05)", "4. Gaussian blur",
     "5. Canny edges (setting D)", "6. Harris corners", f"7. FFT low-pass␣
↪D0={D0} (regions)", f"8. FFT high-pass D0={D0} (structure)"],
    cols=4, size=3.2, suptitle="Current pipeline: intermediate results, full␣
↪frame")
```



Summary. Every stage now has a measurable reason for its parameters:

- Gamma reaches its shadow target within 1%.
- CLAHE is measurably more balanced than global HE (0.87 vs. 0.66), and its clip limit was confirmed downstream.
- The median filter recovers 4.4 dB on impulse noise but is not needed on this clean image.
- Sharpening stays within the 5% clipping budget.
- The Gaussian low-pass at $D_0 = 30$ removes 63% of local contrast, a real region map, without the ringing of the ideal filter.

The largest improvements over our earlier settings are in edge detection (edge density 27.6% to 16.1%, speckle 69% to 32%) and in the FFT stage, which now actually separates regions from structure. The main limitation is that these are *proxy* metrics. In particular, the edge metrics favor fewer edges. In Phase 3 we plan to score edges against reference building and road outlines (see Next Steps).


5. Updated Pipeline

Current planned sequence. Changes from the proposal or the repo baseline are in **bold**.

1. Load the NAIP 1 m RGB crop and convert it to grayscale.
2. Gamma correction with γ **solved from the shadow-quartile mean** (1.245 for this scene; the proposal used a fixed 1.4).
3. Linear contrast stretch, 2nd/98th percentile clip.
4. CLAHE, clip 2.5 and 8 x 8 tiles (unchanged; clip 1.5 and 2.0 tested downstream with no gain).
5. **Median filter, k = 3, only when impulse noise or speckle is present** (the proposal used k = 5; removed from the default chain for this clean scene).
6. Laplacian sharpening, **weight 0.05** (largest weight within the 5% clipping budget), for the enhanced visual output.
7. **Gaussian blur (5 x 5, σ = 1.4) before feature extraction** (new step).
8. Canny edges with **1.0 x / 2.0 x median-gradient thresholds** (repo baseline: 0.66 x / 1.33 x on the unblurred image).
9. Harris corners **on the blurred image, threshold 0.05 x max response**, k = 0.04 (repo baseline: 0.01 x max).

Frequency-domain branch, taken from the CLAHE output after step 4:

- **Gaussian low-pass, D_0 = 30** (the proposal used an ideal r = 60). This gives the region map for land-cover segmentation.
- **Gaussian high-pass at the same D_0**, percentile-stretched for display. This gives the structure map (street grid, building outlines).



6. Next Steps

What still needs to be completed

- A land-cover separation step that combines the outputs: thresholding or region growing on the low-pass image, plus simple color indices from the RGB bands, such as excess green ($2G - R - B$) for vegetation. This would produce approximate road, building and vegetation maps; at the moment the pipeline only works in grayscale.
- The **water class**. This crop has no open water, so water separation is untested. We will add a second NAIP crop that includes Buffalo Bayou (just north of the current scene). This NAIP product is RGB only (no NIR), and the bayou water in that strip is brown, so a simple RGB water index may fail. If it does, we will fall back on the low-pass region map plus hue/saturation or a hand-labeled mask rather than assuming an index will work.

- An objective accuracy check against reference data. We plan to compare Canny edges with OpenStreetMap building and road outlines for the same bounding box, reporting edge precision and recall, or to hand-label a small patch. This will also replace our proxy edge metrics, which favor fewer edges by construction.
- Test whether blurring the CLAHE output directly, without sharpening, gives equally clean Canny edges.
- Non-maximum suppression for Harris, so each corner is a single keypoint.
- (Optional) Deep-learning extension. A COCO-pretrained YOLOv8n returned no detections on this 1 m scene in our repo run, because cars are only about 4 to 5 px wide. We plan to try an aerial-trained model (YOLOv8-OBB trained on DOTA) on tiled, upsampled patches.

Problems and challenges encountered

- The real NAIP crop has almost no impulse noise, so the median filter could only be tested with synthetic noise. It turned out to be unnecessary for this scene.
- Without ground truth, we had to design proxy metrics for each stage.
- Our first edge detector setting was far too dense (27.6% of pixels). We traced this to texture amplification by the enhancement stages and fixed it with blurring and stricter thresholds.
- Our first FFT cut-off rule (90% of AC power) produced a "low-pass" image that barely differed from the input, and PSNR made it look good. We added a region-uniformity metric to choose the cut-off.
- Gamma brightens shadows but compresses highlights, so it must be paired with stretching or CLAHE.
- During development we fixed an inverted gamma formula and an FFT cut-off search that always returned r = 0 because the DC term was included.

Planned improvements before Phase 3

- Test the pipeline on a second NAIP scene (the Buffalo Bayou crop above, and possibly a residential area) to check that the self-tuning parameters and the $D_0 = 30$ cut-off generalize.
- Try an FFT band-pass filter, as mentioned in the proposal, to isolate the street-grid frequency band.
- Combine the edge, corner and region outputs into one land-cover overlay for the final report.